Group by

Description | Editorial | Solutions | Submissions

586. Customer Placing the Largest Number of Orders

Solved

Easy | Topics | Companies | Hint

SQL Schema > Pandas Schema >

Table: `Orders`

```
+-----------------+-----------+
| Column Name     | Type      |
+-----------------+-----------+
| order_number    | int       |
| customer_number | int       |
+-----------------+-----------+
order_number is the primary key (column with unique values) for this table.
This table contains information about the order ID and the customer ID.
```

Write a solution to find the `customer_number` for the customer who has placed **the largest number of orders**.

The test cases are generated so that **exactly one customer** will have placed more orders than any other customer.

The result format is in the following example.

Example 1:

```
Input:
Orders table:
```

Code

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT customer_number FROM Orders
GROUP BY customer_number
ORDER BY COUNT(customer_number ) DESC LIMIT 1;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 19 / 19 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:35

Solution

Runtime

472 ms | Beats 32.77%

10%

Description | Editorial | Solutions | Submissions

511. Game Play Analysis I

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Activity`

```
+--------------+---------+
| Column Name  | Type    |
+--------------+---------+
| player_id    | int     |
| device_id    | int     |
| event_date   | date    |
| games_played | int     |
+--------------+---------+
(player_id, event_date) is the primary key (combination of columns with unique
values) of this table.
This table shows the activity of players of some games.
Each row is a record of a player who logged in and played a number of games
(possibly 0) before logging out on someday using some device.
```

Write a solution to find the **first login date** for each player.

Return the result table in **any order**.

The result format is in the following example.

Code

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT   player_id,min(event_date ) AS first_login   FROM Activity GROUP BY player_id ;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 12 / 12 testcases passed Time taken: 9hrs 28m 4s

Bhagyesh12396 submitted at Mar 18, 2026 21:37

Solution

Runtime

516 ms | Beats 30.69%

10%

Problem List

Description | Editorial | Solutions | Submissions

1693. Daily Leads and Partners

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `DailySales`

```
+-----------+---------+
| Column Name | Type    |
+-----------+---------+
| date_id     | date    |
| make_name   | varchar |
| lead_id     | int     |
| partner_id  | int     |
+-----------+---------+
There is no primary key (column with unique values) for this table. It may contain
duplicates.
This table contains the date and the name of the product sold and the IDs of the
lead and partner it was sold to.
The name consists of only lowercase English letters.
```

For each `date_id` and `make_name`, find the number of **distinct** `lead_id`'s and **distinct** `partner_id`'s.

Return the result table in **any order**.

The result format is in the following example.

Code

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT date_id ,make_name , count(DISTINCT(lead_id)) AS unique_leads ,count(DISTINCT
(partner_id )) AS unique_partners FROM DailySales  GROUP BY date_id,make_name;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 22 / 22 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:39

Solution

Runtime

608 ms | Beats 17.12%

10%

Group by

1741. Find Total Time Spent by Each Employee

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Employees`

Column Name	Type
emp_id	int
event_day	date
in_time	int
out_time	int

(emp_id, event_day, in_time) is the primary key (combinations of columns with unique values) of this table.
The table shows the employees' entries and exits in an office.
event_day is the day at which this event happened, in_time is the minute at which the employee entered the office, and out_time is the minute at which they left the office.
in_time and out_time are between 1 and 1440.
It is guaranteed that no two events on the same day intersect in time, and in_time < out_time.

Write a solution to calculate the total time **in minutes** spent by each employee on each day at the office. Note that

MySQL | Auto

```
# Write your MySQL query statement below
SELECT event_day AS day,emp_id ,SUM(out_time - in_time ) AS total_time FROM Employees GROUP BY emp_id ,event_day ;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 22 / 22 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:40

Solution

Runtime

498 ms | Beats 67.44%

10%

1050. Actors and Directors Who Cooperated At Least Three Times

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `ActorDirector`

Column Name	Type
actor_id	int
director_id	int
timestamp	int

timestamp is the primary key (column with unique values) for this table.

Write a solution to find all the pairs `(actor_id, director_id)` where the actor has cooperated with the director at least three times.

Return the result table in **any order**.

The result format is in the following example.

MySQL | Auto

```
# Write your MySQL query statement below
SELECT actor_id , director_id FROM ActorDirector GROUP BY actor_id ,director_id HAVING COUNT (actor_id)>=3;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 12 / 12 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:41

Solution

Runtime

340 ms | Beats 78.97%

10%

1050. Actors and Directors Who Cooperated At Least Three Times

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `ActorDirector`

Column Name	Type
actor_id	int
director_id	int
timestamp	int

timestamp is the primary key (column with unique values) for this table.

Write a solution to find all the pairs `(actor_id, director_id)` where the actor has cooperated with the director at least three times.

Return the result table in **any order**.

The result format is in the following example.

Example 1:

MySQL | Auto

```
# Write your MySQL query statement below
SELECT actor_id , director_id FROM ActorDirector GROUP BY actor_id ,director_id HAVING COUN
(actor_id)>=3;
```

Ln 1, Col 1 | Saved

Run | Submi

Accepted

All Submissions

Accepted 12 / 12 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:42

Solution

Runtime

413 ms | Beats 14.83%

10%

Group by

1141. User Activity for the Past 30 Days I

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Activity`

```
+---------------+---------+
| Column Name   | Type    |
+---------------+---------+
| user_id       | int     |
| session_id    | int     |
| activity_date | date    |
| activity_type | enum    |
+---------------+---------+
This table may have duplicate rows.
The activity_type column is an ENUM (category) of type ('open_session',
'end_session', 'scroll_down', 'send_message').
The table shows the user activities for a social media website.
Note that each session belongs to exactly one user.
```

Write a solution to find the daily active user count for a period of `30` days ending `2019-07-27` inclusively. A user was active on someday if they made at least one activity on that day.

Return the result table in **any order**.

The result format is in the following example.

```
# Write your MySQL query statement below
SELECT activity_date AS day ,COUNT(DISTINCT user_id) AS active_users  FROM  Activity WHERE
'2019-07-27' >= activity_date AND activity_date > '2019-06-27' GROUP BY activity_date
;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 16 / 16 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:44

Solution

Runtime

523 ms | Beats 24.47%

8%

6%

596. Classes With at Least 5 Students

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Courses`

```
+-------------+---------+
| Column Name | Type    |
+-------------+---------+
| student     | varchar |
| class       | varchar |
+-------------+---------+
(student, class) is the primary key (combination of columns with unique values) for
this table.
Each row of this table indicates the name of a student and the class in which they
are enrolled.
```

Write a solution to find all the classes that have **at least five students**.

Return the result table in **any order**.

The result format is in the following example.

MySQL | Auto

```
# Write your MySQL query statement below
-- SELECT class FROM Courses WHERE COUNT(class) >5 GROUP BY class;
SELECT DISTINCT class FROM Courses  GROUP BY class HAVING COUNT(class)>=5;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 11 / 11 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:45

Solution

Runtime

303 ms | Beats 78.66%

10%