378. Replace Employee ID With The Unique Identifier

Solved

Easy | Topics | Companies

QL Schema > Pandas Schema >

able: `Employees`

Column Name	Type
id	int
name	varchar

id is the primary key (column with unique values) for this table.
Each row of this table contains the id and the name of an employee in a company.

able: `EmployeeUNI`

Column Name	Type
id	int
unique_id	int

(id, unique_id) is the primary key (combination of columns with unique values) for this table.
Each row of this table contains the id and the corresponding unique id of an

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT eu.unique_id , e.name As name  from EmployeeUNI eu right join Employees e ON eu.id =e.id;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 25 / 25 testcases passed Time taken: 9hrs 30m 6s

Bhagyesh12396 submitted at Mar 18, 2026 21:49

Solution

Runtime

1964 ms | Beats 5.01%

6%

4%

Description | Editorial | Solutions | Submissions

577. Employee Bonus

Solved

Easy | Topics | Companies | Hint

SQL Schema > Pandas Schema >

Table: `Employee`

Column Name	Type
empId	int
name	varchar
supervisor	int
salary	int

empId is the column with unique values for this table.
Each row of this table indicates the name and the ID of an employee in addition to their salary and the id of their manager.

Code

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT e.name as name, b.bonus as bonus
FROM Employee e LEFT JOIN Bonus b
ON e.empId = b.empId
WHERE b.bonus < 1000 OR b.bonus IS NULL;
```

Description | Editorial | Solutions | Submissions

1280. Students and Examinations

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Students`

Column Name	Type
student_id	int
student_name	varchar

student_id is the primary key (column with unique values) for this table.
Each row of this table contains the ID and the name of one student in the school.

Table: `Subjects`

Column Name	Type
subject_name	varchar

subject_name is the primary key (column with unique values) for this table.
Each row of this table contains the name of one subject in the school.

Code

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT
    s.student_id,
    s.student_name,
    sub.subject_name,
    COUNT(e.subject_name) AS attended_exams
FROM Students s
CROSS JOIN Subjects sub
LEFT JOIN Examinations e
    ON s.student_id = e.student_id
    AND sub.subject_name = e.subject_name
GROUP BY
    s.student_id,
    s.student_name,
    sub.subject_name
ORDER BY
    s.student_id,
    sub.subject_name;
```

1068. Product Sales Analysis I

Solved

Easy | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Sales`

Column Name	Type
sale_id	int
product_id	int
year	int
quantity	int
price	int

(sale_id, year) is the primary key (combination of columns with unique values) of this table.
product_id is a foreign key (reference column) to `Product` table.
Each row of this table shows a sale on the product product_id in a certain year.
Note that the price is per unit.

Table: `Product`

Column Name	Type

```mysql
# Write your MySQL query statement below
select p.product_name , s.year , s.price from Product p inner join Sales s on p.product_id=s
product_id;
```

Ln 1, Col 1 | Restored from local | Upgrade to Cloud Saving

Run | Submit

Description | Editorial | Solutions | Submissions

570. Managers with at Least 5 Direct Reports

Solved

Medium | Topics | Companies | Hint

SQL Schema > Pandas Schema >

Table: `Employee`

Column Name	Type
id	int
name	varchar
department	varchar
managerId	int

id is the primary key (column with unique values) for this table.
Each row of this table indicates the name of an employee, their department, and the id of their manager.
If managerId is null, then the employee does not have a manager.
No employee will be the manager of themself.

Write a solution to find managers with at least **five direct reports**.

Return the result table in **any order**.

The result format is in the following example.

Code

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT e2.name
FROM Employee e1
JOIN Employee e2
    ON e1.managerId = e2.id
GROUP BY e2.id, e2.name
HAVING COUNT(e1.id) >= 5;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 11 / 11 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 21:59

Solution

Runtime

368 ms | Beats 25.36%

15%

10%

1204. Last Person to Fit in the Bus

Solved

Medium | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Queue`

Column Name	Type
person_id	int
person_name	varchar
weight	int
turn	int

person_id column contains unique values.
This table has the information about all people waiting for a bus.
The person_id and turn columns will contain all numbers from 1 to n, where n is the number of rows in the table.
turn determines the order of which the people will board the bus, where turn=1 denotes the first person to board and turn=n denotes the last person to board.
weight is the weight of the person in kilograms.

There is a queue of people waiting to board a bus. However, the bus has a weight limit of `1000` **kilograms**, so there may be some people who cannot board.

MySQL | Auto

```mysql
# Write your MySQL query statement below
SELECT q1.person_name
FROM Queue q1
WHERE (
    SELECT SUM(q2.weight)
    FROM Queue q2
    WHERE q2.turn <= q1.turn
) <= 1000
ORDER BY q1.turn DESC
LIMIT 1;
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 29 / 29 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 22:00

Solution

Runtime

1745 ms | Beats 10.84%

10%

Description | Editorial | Solutions | Submissions

1164. Product Price at a Given Date

Solved

Medium | Topics | Companies

SQL Schema > Pandas Schema >

Table: `Products`

```
+----------------+-----------+
| Column Name    | Type      |
+----------------+-----------+
| product_id     | int       |
| new_price      | int       |
| change_date    | date      |
+----------------+-----------+
(product_id, change_date) is the primary key (combination of columns with unique
values) of this table.
Each row of this table indicates that the price of some product was changed to a
new price at some date.
```

Initially, all products have price 10.

Write a solution to find the prices of all products on the date `2019-08-16`.

Return the result table in **any order**.

The result format is in the following example.

Code

MySQL | Auto

```sql
# Write your MySQL query statement below
SELECT
    p.product_id,
    COALESCE(pr.new_price, 10) AS price
FROM
    (SELECT DISTINCT product_id FROM Products) p
LEFT JOIN (
    SELECT product_id, new_price
    FROM Products
    WHERE (product_id, change_date) IN (
```

Ln 1, Col 1 | Saved

Run | Submit

Accepted

All Submissions

Accepted 15 / 15 testcases passed

Bhagyesh12396 submitted at Mar 18, 2026 22:01

Solution

Runtime

462 ms | Beats 61.41%

15%