1) Create a view that shows all of the customers who have the highest ratings.

```
D6_96715_bhagyesh>CREATE VIEW HighestSalaryEmployees AS
    -> SELECT *
    -> FROM employees
    -> WHERE salary = (SELECT MAX(salary) FROM employees);
Query OK, 0 rows affected (0.03 sec)

D6_96715_bhagyesh>select * from HighestSalaryEmployees;
+-------------+------------+-----------+-------+----------------+------------+---------+----------+----------------+----
--------+---------------+
| EMPLOYEE_ID | FIRST_NAME | LAST_NAME | EMAIL | PHONE_NUMBER   | HIRE_DATE  | JOB_ID  | SALARY   | COMMISSION_PCT | MAN
AGER_ID | DEPARTMENT_ID |
+-------------+------------+-----------+-------+----------------+------------+---------+----------+----------------+----
--------+---------------+
|         100 | Steven     | King      | SKING | 1.515.555.0100 | 2013-06-17 | AD_PRES | 24000.00 |           NULL |
   NULL |            90 |
+-------------+------------+-----------+-------+----------------+------------+---------+----------+----------------+----
```

2) Create a view that shows the number of salespeople in each city.

```
D6_96715_bhagyesh>CREATE VIEW EmployeesPerCity AS
    -> SELECT l.city, COUNT(e.employee_id) AS total_employees
    -> FROM employees e
    -> JOIN departments d ON e.department_id = d.department_id
    -> JOIN locations l ON d.location_id = l.location_id
    -> GROUP BY l.city;
Query OK, 0 rows affected (0.01 sec)
D6_96715_bhagyesh>select * from EmployeesPerCity;
+----------------------+-----------------+
| city                 | total_employees |
+----------------------+-----------------+
| Seattle              |              18 |
| Toronto              |               5 |
| London               |               1 |
| South San Francisco  |              42 |
| Southlake            |               2 |
| Munich               |               1 |
| Oxford               |              34 |
```

3) Create a view that shows the average and total orders for each salesperson after his or her
name. Assume all names are unique.

```
   -> ON e.manager_id = m.employee_id
   -> GROUP BY m.employee_id, m.first_name;
uery OK, 0 rows affected (0.01 sec)

6_96715_bhagyesh>select * from ManagerSalaryStats;
+------------+------------+--------------+--------------+
| manager_id | first_name | avg_salary   | total_salary |
+------------+------------+--------------+--------------+
        100 | Steven     | 11100.000000 |    155400.00 |
        102 | Lex        |  9000.000000 |      9000.00 |
        103 | Alexander  |  4950.000000 |     19800.00 |
        101 | Neena      |  8983.200000 |     44916.00 |
        108 | Nancy      |  7920.000000 |     39600.00 |
        114 | Den        |  2780.000000 |     13900.00 |
        120 | Matthew    |  2762.500000 |     22100.00 |
        121 | Adam       |  3175.000000 |     25400.00 |
        122 | Payam      |  2950.000000 |     23600.00 |
        123 | Shanta     |  3237.500000 |     25900.00 |
        124 | Kevin      |  2875.000000 |     23000.00 |
        145 | John       |  8500.000000 |     51000.00 |
        146 | Karen      |  8500.000000 |     51000.00 |
        147 | Alberto    |  7766.666667 |     46600.00 |
        148 | Gerald     |  8650.000000 |     51900.00 |
        149 | Eleni      |  8333.333333 |     50000.00 |
        201 | Michael    |  6000.000000 |      6000.00 |
        205 | Shelley    |  8300.000000 |      8300.00 |
```

4) Create a view that shows each salesperson with multiple customers.
Changing Values through Views.

```
D6_96715_bhagyesh>CREATE VIEW ManagersWithMultipleEmployees AS
    -> SELECT manager_id, COUNT(*) AS total_employees
    -> FROM employees
    -> WHERE manager_id IS NOT NULL
    -> GROUP BY manager_id
    -> HAVING COUNT(*) > 1;
Query OK, 0 rows affected (0.01 sec)

D6_96715_bhagyesh>select * from ManagersWithMultipleEmployees;
+------------+-----------------+
| manager_id | total_employees |
+------------+-----------------+
|        100 |              14 |
|        101 |               5 |
|        103 |               4 |
|        108 |               5 |
|        114 |               5 |
|        120 |               8 |
|        121 |               8 |
|        122 |               8 |
|        123 |               8 |
|        124 |               8 |
|        145 |               6 |
|        146 |               6 |
|        147 |               6 |
|        148 |               6 |
|        149 |               6 |
+------------+-----------------+
15 rows in set (0.01 sec)
```

5) Which of these views are updateable (will allow DML operations)?

```
D6_96715_bhagyesh>CREATE VIEW Commissions AS
    -> SELECT employee_id, commission_pct
    -> FROM employees
    -> WHERE commission_pct BETWEEN 0.10 AND 0.2
    -> WITH CHECK OPTION;
Query OK, 0 rows affected (0.01 sec)
```

6) Create a view of the Salespeople table called Commissions. This view will include only
the snum and comm fields. Through this view, someone could enter or change commissions, but only to values between .10 and .20.

```
D6_96715_bhagyesh>select * from Commissions;
+-------------+----------------+
| employee_id | commission_pct |
+-------------+----------------+
|         149 |           0.20 |
|         153 |           0.20 |
|         154 |           0.20 |
|         155 |           0.15 |
|         163 |           0.15 |
|         164 |           0.10 |
|         165 |           0.10 |
|         166 |           0.10 |
|         167 |           0.10 |
|         169 |           0.20 |
|         170 |           0.20 |
|         171 |           0.15 |
|         172 |           0.15 |
|         173 |           0.10 |
|         176 |           0.20 |
|         177 |           0.20 |
|         178 |           0.15 |
|         179 |           0.10 |
+-------------+----------------+
18 rows in set (0.00 sec)
```