Poker Zero Lightning Presentation

Problem Statement and Motivation

Objective

Develop a reasoning model optimized for **no-limit hold'em poker**. Success in poker extends beyond monetary gain—it signifies advancements in:

- Reasoning under incomplete information
- Adversarial decision-making
- Strategic adaptation

Applications

Poker AI has significant implications in:

- Game Theory
- Economic Modeling
- Negotiation

Prior Work

Several notable Al-driven poker models include:

- Poker Bench Trained LLMs to become professional poker players
- PokerGPT Lightweight solver leveraging a large language model
- Pluribus Demonstrated multiplayer, near-GTO strategies

Data

Instruction	Output
You are a specialist in playing 6-handed No Limit Texas Hold'em. The following will be a game scenario, and you need to make the optimal decision.	Bet 18
Game Summary:	
- Small Blind: 0.5 chips	
- Big Blind: 1 chip	
- Everyone started with 100 chips	
- Player positions: UTG, HJ, CO, BTN, SB, BB	
- Your Position: HJ	
- Your Hand: [King of Diamond, Jack of Spade]	

Technical Approach

Unsloth

Unsloth is an open-source Python framework that speeds up the process of fine-tuning and using LLMs.

- Optimized PyTorch code
- Handwriting GPU kernels to speed up inference
- Better memory utilization via typecasting
- Allows us to fine-tune 8B parameter models on just a Colab T4 GPU

GRPO

GRPO (Group Relative Policy Optimization) is a reinforcement learning algorithm developed by DeepSeek.

- Trains a model to optimize a reward function instead of training a model solely on next-token prediction (which simply teaches it to mimic data)
- Uses group-based comparisons to improve performance instead of after every trial
- Calculates advantage and updates policy to increase likelihood of better actions
- Uses KL Divergence constraint to prevent drastic changes in policy
- Overall objective maximizes cumulative reward with stable policy updates

LoRA

Low Rank Adaptation (LoRA) is a method for fine-tuning large models efficiently.

- It works by introducing low-rank matrices into pretrained model layers.
- This approach allows significant performance gains with a minimal number of additional parameters.

Mathematical Formulation of LoRA

- ullet Pretrained Weight Matrix: Let $W \in \mathbb{R}^{d imes k}$ be a pretrained weight matrix.
- ullet Low-Rank Decomposition: LoRA approximates the weight update ΔW as:

$$\Delta W = BA$$

where:

- ullet $B \in \mathbb{R}^{d imes r}$
- ullet $A \in \mathbb{R}^{r imes k}$
- $r \ll \min(d, k)$
- Adapted Weights: The updated weight matrix becomes: $W^\prime = W + BA$

Initial Results

- Successfully fine tuned our model in Colab, showing Unsloth's capabilities in speeding up fine-tuning
- PyPokerEngine: A library for simulating poker games with Al bots
 - Used PyPokerEngine to make our model play against itself
- Initial testing through sanity check on output

Next Steps

PyPokerEngine

 More Players Poker environment is only heads up (2 players). Our goal is to play 6 handed, which would have more interesting applications because heads-up Texas Hold'em is a solved game

Additional Training

- Self-Play Model competes against previous versions, gradual improvement and adaptation to exploitative strategies
- Training Pipeline Feed data back into our model for reinforcement learning training.
 Eliminates need for a premade dataset and allows the model to learn optimal strategies by itself

Thank You!

Questions?