

Category	Fortran	python	Notes
Put and Get (2.2.7)		<code>field=pyoasis.asarray(field[, dtype])</code>	Make sure that field is a numpy asfortran array of the required dtype (optional argument defaulting to <code>numpy.float64</code>) The call can be skipped if field is already so
	<code>CALL oasis_put (var_id, date, fld1, info, fld2, fld3, fld4, fld5, write_restart, fracwgt)</code>	<code>var.put(time, field[, write_restart][, fracwgt])</code>	var is a previously defined object of the Var class field, and possibly fracwgt, have been checked by <code>pyoasis.asarray</code> Bundle are supported (bundle index is the last index) Bicubic and conservative 2nd extra fields not supported. write_restart boolean optional argument for triggering a NetCDF dump of the sent field. fracwgt is an optional dynamic fraction field. Returned value is to be compared against the Oasis Parameters enumeration (in long or short syntax)
	<code>CALL oasis_get (var_id, date, fld, info)</code>	<code>var.get(time, field)</code>	field has to be preallocated and checked by <code>pyoasis.asarray</code> Returned value is to be compared against the Oasis Parameters enumeration (in long or short syntax)
Termination (2.2.8)	<code>CALL oasis_terminate (ierror)</code>	<code>del comp / nothing</code>	oasis terminates at the comp object destruction, either explicitly by <code>del comp</code> or automatically at garbage collection on exit
Auxiliary routines (2.2.9)	<code>CALL oasis_get_debug(debug_value)</code>	<code>comp.debug_level</code> <code>pyoasis.get_debug()</code>	Coded as a property of a Component object or as a standalone function
	<code>CALL oasis_set_debug(debug_value)</code>	<code>comp.debug_level = debug_value</code> <code>pyoasis.set_debug(debug_value)</code>	Coded as a setter for a Component object property or as a standalone function
	<code>CALL oasis_put_inquire(var_id, date, kinfo)</code>	<code>var.put_inquire(time)</code>	var is a Var object. Returned value is to be compared against the Oasis Parameters enumeration (in long or short syntax)
	<code>CALL oasis_get_ncpl(var_id, ncpl, kinfo)</code> <code>CALL oasis_get_freqs(var_id, mop, ncpl, cpl_freqs, kinfo)</code>	<code>var.cpl_freqs</code>	Coded as a property of a Var object. Returns an iterable list
	<code>CALL oasis_get_intercomm(new_comm, cdnam, kinfo)</code>	<code>comp.get_intercomm(comp_name)</code>	Coded as a method of a Component object.
	<code>CALL oasis_get_intracomm(new_comm, cdnam, kinfo)</code>	<code>comp.get_intracomm(comp_name)</code>	Coded as a method of a Component object.
	<code>CALL oasis_get_multi_intracomm(new_comm, cdnam, root_ranks, kinfo)</code>	<code>comp.get_multi_intracomm(complist)</code>	Coded as a method of a Component object. Returns a pair of values: the new comm and a dictionary associating root ranks (values) to component names (keys)
	<code>CALL oasis_abort (compid, routine_name, abort_message, file, line, rcode)</code>	<code>raise PyOasisException(text)</code> <code>raise OasisException(text, error)</code>	Preferred use of exceptions over an abort function