
pyOASIS

Philippe Gambron, Rupert Ford, Andrea Piacentini

Jan 13, 2021

CONTENTS:

1	Introduction	1
2	Using pyOASIS	3
2.1	Code structure	3
2.2	Creating a component using MPI	3
2.3	Creating a partition	4
2.4	Declaring the coupling data	7
2.5	Ending the definition phase	8
2.6	Sending and receiving data	8
2.7	Termination	8
2.8	Exceptions and aborting	9
3	Examples	11
3.1	Serial partitions	11
3.2	Apple and orange partitions	12
3.3	Fortran and Python interoperability	12
4	API reference	15
5	Correspondence with the OASIS3-MCT Fortran API	21
5.1	Component	21
5.2	Partition	21
5.3	Var	22
5.4	Grid	22
5.5	Utilities	23
6	Installation	25
6.1	Under GNU/Linux	25
6.2	Under macOS	26
6.3	Virtual Python environment	26
6.4	Documentation	27
7	Acknowledgments	29
8	Index and search	31
	Index	33

INTRODUCTION

pyOASIS is a Python wrapper for OASIS written using ctypes and ISO C bindings to Fortran. It provides an object-oriented interface to OASIS3-MCT. This allows users to write and couple models written in Python or to couple models written in Python with models written in Fortran.

It is part of the distribution of OASIS3-MCT. See <https://portal.enes.org/oasis/download> for more information about obtaining it.

pyOASIS and OASIS3-MCT are distributed under the GNU Lesser General Public License. For more details, see the file lgpl-3.0.txt or <https://www.gnu.org/licenses/lgpl-3.0.en.html>.

USING PYOASIS

2.1 Code structure

The source code of pyOASIS is in the directory `pyoasis/src`. First, the OASIS3-MCT Fortran code is wrapped in Fortran using ISO-C bindings. The corresponding source files are in the subdirectory `lib/cbindings/fortran_isoc`. The file names are the same as the corresponding ones in the original source code but ending in `_iso.F90`. Subsequently, the Fortran with ISO-C bindings is wrapped in C, see the source code is in `lib/cbindings/c_src`. The names of the files are the same as the corresponding Fortran ones, but ending in `_c.c`. Finally, the C is wrapped in Python in the directory `pyoasis/src`. A low-level wrapper is made using the same filenames as the Fortran ones but ending in `.py`. To access the python interface, one must write a `import pyoasis` in his/her python code.

These functions are all tested, at the level of the Python wrapper, in `/pyoasis` with “make wrappertest”. To run all tests including python, C and fortran examples from `pyoasis/examples`, use “make test”.

2.2 Creating a component using MPI

In pyOASIS, components are instances of the **Component** class. To initialise a component, its name has to be supplied

```
import pyoasis
component_name = "component"
comp = pyoasis.Component(component_name)
```

It is also possible to provide an optional `coupling_flag` argument which defaults to “True”, which means the component is coupled through OASIS3-MCT:

```
import pyoasis
component_name = "component"
coupling_flag = True
comp = pyoasis.Component(component_name, coupling_flag)
```

OASIS3-MCT couples models which communicate using MPI. By default, the **Component** class will set up MPI internally and provides methods to get access to information such as rank and number of processes in the local communicator gathering only the component processes

```
import pyoasis

comp = pyoasis.Component("component")

print("Hello world from process " + str(comp.localcomm.rank)
      + " of " + str(comp.localcomm.size))
```

If the user needs to specify that the global communicator gathering at start all components of the coupled model is different from the default MPI COMM WORLD, this can be passed to the **Component** class through the communicator optional argument. This should be created with `mpi4py`.

```
import pyoasis
from mpi4py import MPI
[...]
comm = my_global_comm

component_name = "component"
coupling_flag = True
comp = pyoasis.Component(component_name, coupling_flag, comm)
```

Sophie:

To create a coupling communicator for a subset of processes, one can use the method `create_couplcomm`, with a flag being `True` for all these processes:

```
coupled = True
if local_comm_size > 3:
    if local_comm_rank >= local_comm_size - 2:
        coupled = False
comp.create_couplcomm(coupled)
```

If such a communicator already exists in the code, it should simply be provided to OASIS3-MCT with the method `set_couplcomm`:

```
couplcomm = comp.localcomm.Split(icpl, local_comm_rank)
if icpl == 0:
    couplcomm = MPI.COMM_NULL
comp.set_couplcomm(couplcomm)
```

To set up an MPI intra-communicator or inter-communicator between the local component and another component, e.g. the component receiver in the example below, one can use `get_intracomm` or `get_intercomm`:

```
intracomm = comp.get_intracomm("receiver")
intercomm = comp.get_intercomm("receiver")
```

The current OASIS3-MCT internal debug level (\$NLOGPRT value in the `namcouple`), is provided by, and can be changed by modifying, the `debug_level` property of the component:

```
comp.debug_level = 2
```

End Sophie

2.3 Creating a partition

The data can be partitioned in various ways. These correspond to the **SerialPartition**, **ApplePartition**, **BoxPartition**, **OrangePartition** and **PointsPartition** classes which are inherited from the **Partition** abstract class. For details on the different ways to describe the partitions, see OASIS3-MCT User Guide, section 2.2.3 and examples 1-serial, 2-apple, 3-box, 4-orange, 5-points in `pyoasis/examples`.

The simplest situation is the serial partitioning where all the data is held by a single process and only the number of points has to be specified (see example 1-serial)


```
n_points = 1600
serial_partition = pyoasis.SerialPartition(n_points)
```

In the case of the apple partitioning, each process contains a segment of a linear domain. To initialise such a partitioning, an offset has to be supplied for each rank as well as the number of data points that will be stored locally. The following example, close to example 2-apple, if run with 4 processes, will produce 4 consecutive local segments containing 400 data points

```
component_name = "component"
comp = pyoasis.Component(component_name)
rank = comp.localcomm.rank
size = comp.localcomm.size
n_points = 1600
local_size = int(n_points/size)
offset = rank * local_size
partition = pyoasis.ApplePartition(offset, local_size)
```

When we use the box partitioning, a 2-dimensional domain is split into several rectangles. The global offset, local extents in the x and y directions and the global extent in the x direction have to be supplied to the constructor. The global offset is the index of the corner of the local rectangle. For example, we can split a 4x4 square domain into 4 2x2 parts with the following code that will have to be executed using 4 processes. The offset is computed from the global and local domain sizes as well as the rank. Another example of a box partition is available in example 3-box

```
rank = comp.localcomm.rank
n_global_points_per_side = 4
n_partitions_per_side = 2
local_extent = n_global_points_per_side / n_partitions_per_side
i_partition_x = rank / n_partitions_per_side
i_partition_y = rank % n_partitions_per_side
global_offset = i_partition_x * n_global_points_per_side * local_extent
               + i_partition_y * local_extent
global_extent_x = n_global_points_per_side
partition = pyoasis.BoxPartition(global_offset, local_extent, local_extent,
                                global_extent_x)
```

The orange partitioning consists of several segments of a linear domain. As a consequence, a list of offsets and local sizes have to be provided. In this example, each process contains 2 consecutive segments of 2 points. (Another example with only one segment per process is available in example 4-orange.)

```
rank = comp.localcomm.rank
n_segments_per_rank = 2
n_points_per_segment = 2
offset_beginning = rank * n_segments_per_rank * n_points_per_segment
offset = [offset_beginning, offset_beginning + n_points_per_segment]
extents = [n_points_per_segment, n_points_per_segment]
partition = pyoasis.OrangePartition(offsets, extents)
```

The last type of partitioning is points, where we have to specify, in a list, the global indices of the points stored by the process. (Another example with only one segment per process is available in example 5-points.)

```
global_indices=[0, 1, 2, 3]
partition = pyoasis.PointsPartition(global_indices)
```

Sophie

Defining the coupling grids

The grid data files, containing the definition of the grids onto which the coupling data is defined, can be created by the user before the run or can be written directly at run time by the components, either by one component process to write the whole grid or by each process holding a part of a grid. Details about the grid definition can be found in section 2.2.4 of OASIS3-MCT User Guide. A full example of writing a grid in sequential and parallel models can be found in `examples/10-grid`.

To initialise a grid and write the grid longitudes and latitudes, one has to use the `Grid` method:

```
[...]
lon = np.array([-180. + comm_rank*nx_loc*dx + float(i)*dx +
               dx/2.0 for i in range(nx_loc)], dtype=np.float64)
lon = np.tile(lon, (ny_loc, 1)).T

lat = np.array([-90.0 + float(j)*dy + dy/2.0 for j in range(ny_loc)],
               dtype=np.float64)
lat = np.tile(lat, (nx_loc, 1))
grid = pyoasis.Grid('pyoa', nx_global, ny_global, lon, lat, partition)
```

To write the grid cell corner longitudes and latitudes, the `set_corners` method can be used

```
[...]
ncrn = 4
clo = pyoasis.asarray(np.zeros((nx_loc, ny_loc, ncrn), dtype=np.float64))
clo[:, :, 0] = lon[:, :] - dx/2.0
clo[:, :, 1] = lon[:, :] + dx/2.0
clo[:, :, 2] = clo[:, :, 1]
clo[:, :, 3] = clo[:, :, 0]
cla = pyoasis.asarray(np.zeros((nx_loc, ny_loc, ncrn), dtype=np.float64))
cla[:, :, 0] = lat[:, :] - dy/2.0
cla[:, :, 1] = cla[:, :, 0]
cla[:, :, 2] = lat[:, :] + dy/2.0
cla[:, :, 3] = cla[:, :, 2]

grid.set_corners(clo, cla)
```

To write the grid cell areas, the

set_area method can be used `[::] [...]` `area = np.zeros((nx_loc, ny_loc), dtype=np.float64)` `area[:, :] = dp_conv * np.abs(np.sin(cla[:, :, 2] * dp_conv) - np.sin(cla[:, :, 0] * dp_conv)) * np.abs(clo[:, :, 1] - clo[:, :, 0])`

```
grid.set_area(area)
```

To define the mask of the grid, the `set_mask` method can be used (here a mask where all points have zera value i.e. are valid) :

```
msk = np.zeros((nx_loc, ny_loc), dtype=np.int32)
grid.set_mask(msk, companion=None)
```

To define the grid cell fraction, the `set_frac` method can be used: ::

```
frc = np.ones((nx_loc, ny_loc), dtype=np.float64) frc = np.where(msk == 1, 0.0, 1.0)
grid.set_frac(frc, companion=None)
```

To define the grid cell angles, the `set_angle` method can be used: :: `angle = np.zeros((nx_loc, ny_loc), dtype=np.float64)` `grid.set_angle(angle)`

end Sophie

2.4 Declaring the coupling data

The coupling data is handled by the class **Var**. Its constructor requires its symbolic name, as it appears in the `namcouple` file, the partition and a flag indicating whether the data is incoming or outgoing. The latter is an enumerated type and can have the values `pyoasis.OasisParameters.OASIS_OUT` or `pyoasis.OasisParameters.OASIS_IN`. In the following example, we wish to send data to a process having the rank 1 and we use a partition that was previously created.:

```
data_name = "name"
variable = pyoasis.Var(data_name, partition,
                       pyoasis.OasisParameters.OASIS_OUT)
```

In the case of the receiving model, the code is:

```
data_name = "name"
variable = pyoasis.Var(data_name, partition,
                       pyoasis.OasisParameters.OASIS_IN)
```

Sophie

The property `is_active` can be tested to check if the variable is activated in the `namcouple` configuring file:

```
variable2 = pyoasis.Var("NOTANAME", partition, OASIS.OUT)
if variable2.is_active:
    print("{} is active".format(variable2))
else:
    print("{} is not active".format(variable2))
```

The coupling period(s) of the data, as defined in the `namcouple`, can be accessed with the property `cpl_freqs` and the number of coupling exchanges in which the data is involved by `len(cpl_freqs)`:

```
var_1 = pyoasis.Var("FRECVATM_1", partition, OASIS.IN)
print("Recv_one: coupling frequencies for {} = ".format(var_1.name),
      var_1.cpl_freqs)
```

The property `put_inquire` of the variable tells what would happen to the corresponding data at that date below the corresponding send action. This maybe useful if, for example, the calculation of a coupling field is costly and if one wants to compute it only when it is really sent out. The different possible return codes are listed in section 2.2.9 of OASIS3-MCT User Guide.

```
for date in range(43200):
    if var_1.put_inquire(date) == OASIS.SENT:
        var_1.put(date, pyoasis.asarray([date], dtype=np.float64))
[...]
```

end Sophie

2.5 Ending the definition phase

We must end the definition of the component by calling the `enddef()` method.

```
comp.enddef()
```

However this must be done only once the partitioning and the variable data have been initialised.

2.6 Sending and receiving data

pyOASIS expects data to be provided as a **pyoasis.asarray** object:

```
field = pyoasis.asarray(range(n_points))
```

This is a Numpy array but ordered in the Fortran way. In C, multidimensional arrays store data in row-major order where contiguous elements are accessed by incrementing the rightmost index while varying the other indices will correspond to increasing strides in memory as we use indices further towards the left. By default, Numpy arrays use that ordering as well. Fortran, on the other hand, uses column-major order. In that case, contiguous elements are accessed by incrementing the leftmost index. **pyoasis.asarray** objects use the same ordering as Fortran. As a consequence, it is not necessary to transform data in order to use it in the OASIS3-MCT Fortran library.

The sending and receiving actions may be called by the component at each timestep. The date argument is automatically analysed and actions are actually performed only if date corresponds to a time for which it should be activated, given the period indicated by the user in the namcouple. See OASIS3-MCT User Guide section 2.2.7 for details.

The data is sent with the following function.

```
date = int(0)
variable.put(date, field)
```

Conversely, it is received with the function

```
variable.get(date, field)
```

This will fill the **pyoasis.asarray** object.

2.7 Termination

Finally, the coupling is terminated in the destructor of the component:

```
del comp
```

2.8 Exceptions and aborting

Sophie

When an error occurs in OASIS3-MCT, the code coupler returns an error code and an **OasisException** is raised. In practice, OASIS3-MCT will internally handle the error, write an error message in its debug log files and to the screen, and abort before the exception is raised. It may also happen that the code aborts before the error message appears on the screen.

When an error is caught by the pyOASIS wrapper, such as an incorrect parameter or a wrong argument type, a **PyOasisException** is raised.

In the following example, where we attempt to initialise a component, a **PyOasisException** will be raised as the user supplies an empty name :

```
try:
    comp = pyoasis.Component("")
except (pyoasis.PyOasisException) as exception:
    pyoasis.pyoasis_abort(exception)
```

The function `pyoasis.pyoasis_abort` takes an exception as argument. It stops the execution of all the processes after having displayed an error message and written information in the log files about the error and the context in which it took place.

Another function is available, `pyoasis.oasis_abort`, for the cases where a voluntary abort is needed in the code where or not an exception has been raised. Its interface mimics the corresponding OASIS3-MCT function `oasis_abort`.

end Sophie

EXAMPLES

3.1 Serial partitions

The example in examples/1-serial/python, containing the full source code as well as the namcouple file and a script to run this example, consists in two models, one sending data to another. The sender and receiver start in the same way.

-Import pyOASIS and initialise the MPI communicator

```
import pyoasis
from mpi4py import MPI
comm = MPI.COMM_WORLD
```

-Initialisation of the component

```
comp = pyoasis.Component(component_name)
```

-Initialisation of the serial partition

```
partition = pyoasis.SerialPartition(n_points)
```

-From this point, the sender and the receiver start to differ. In the sender, the variable data is initialised by

```
variable = pyoasis.Var("FSENDON", partition,
                       pyoasis.OasisParameters.OASIS_OUT)
```

whereas, in the receiver, we have

```
variable = pyoasis.Var("FRECVATM", partition,
                       pyoasis.OasisParameters.OASIS_IN)
```

where the last flag is instead `pyoasis.OasisParameters.OASIS_IN` to indicate that, in this case, the data will be incoming.

In both scripts, the initialisation of the component ends by

```
comp.enddef()
```

In the sender, the data is subsequently transmitted by

```
time_in_the_model = int(0)
field = pyoasis.asarray(range(n_points))
variable.put(date, field)
```

while, in the receiver, it is recovered by

```
time_in_the_model = int(0)
field = pyoasis.asarray(numpy.zeros(n_points))
variable.get(date, field)
```

3.2 Apple and orange partitions

In the example in `examples/6-apple_and_orange/python`, both models run as several processes. The beginning of the code is identical to the previous example. We will highlight only the differences. In the sender, the data is split according to the apple partitioning

```
partition = pyoasis.ApplePartition(offset, local_size)
```

whereas the receiver uses the orange partitioning.

```
partition = pyoasis.OrangePartition(offsets, extents)
```

In both cases, the offsets and sizes of the local part of the data have to be specified. Each process subsequently transmits and receives its share of the data as previously. In the sender, we have

```
date = int(0)
field = pyoasis.asarray(numpy.zeros(local_size))
for i in range(local_size):
    field[i] = offset + i
variable.put(date, field)
```

while, in the receiver,

```
date = int(0)
field = pyoasis.asarray(numpy.zeros(extent))
variable.get(date, field)
```

3.3 Fortran and Python interoperability

In order to illustrate the possibility to couple models written in Python and in Fortran, the previous example is repeated in `pyoasis/examples/8-interoperability/fortran_and_python` but this time, the sender has been written in Fortran. The receiver is the same as above.

The sender consists in an analogous sequence using the OASIS3-MCT Fortran API

-Initialisation of the component

```
call oasis_init_comp(comp_id, comp_name, kinfo)
```

-Initialisation of the apple partition with the relevant offset and local size

```
part_params=[1, offset, local_size]
call oasis_def_partition(part_id, part_params, kinfo)
```

-Creation of the variable data, a bundle with two fields

```
var_nodims=[1, 2]
call oasis_def_var(var_id, var_name, part_id, var_nodims, OASIS_OUT,
                  [1], OASIS_REAL, kinfo)
```


-End of the definition of the component

```
call oasis_enddef(kinfo)
```

-Transmission of the local part of the data to the other component

```
call oasis_put(var_id, date, bundle, kinfo)
```

-End of the coupling

```
call oasis_terminate(kinfo)
```


API REFERENCE

class `pyoasis.Component` (*name, coupled=True, communicator=None*)

Component that will be coupled by OASIS3-MCT

Parameters

- **name** (*str*) – name of the component
- **coupled** (*bool*) – whether the component will be coupled (default: True)
- **communicator** (*mpi4py.MPI.Intracomm*) – global MPI communicator (default: MPI.COMM_WORLD)

Raises

- *OasisException* – if OASIS is unable to initialise the component
- *PyOasisException* – if an incorrect parameter is supplied

create_couplcomm (*coupled*)

Creates a coupling communicator toto

Parameters **coupled** (*bool*) – coupling flag

Returns error code

Return type int

Raises

- *OasisException* – if OASIS is unable to create the coupling communicator
- *PyOasisException* – if an incorrect parameter is supplied

property **debug_level**

Returns the currently set debug level

Returns debug level

Return type int

Raises *OasisException* – if OASIS is unable to get the debug level

static **enddef** ()

Ends the initialisation of the component.

Raises *OasisException* – if OASIS is unable to end the initialisation

get_intercomm (*compname*)

Parameters **compname** (*string*) – name of the other component in the intercommunicator

Returns the intercommunicator

Return type MPI.communicator

Raises *OasisException* – if OASIS is unable to create

the intercommunicator :raises PyOasisException: if an incorrect parameter is supplied

get_intracomm(*compname*)

Parameters **compname** (*string*) – name of the other component in the intracommunicator

Returns the intracommunicator

Return type MPI.communicator

Raises

- *OasisException* – if OASIS is unable to create the intracommunicator
- *PyOasisException* – if an incorrect parameter is supplied

get_multi_intracomm(*complist*)

Parameters **complist** (*string*) – list of names of the other component in the intracommunicator

Returns the intracommunicator and a dictionary of the ranks of the component roots in the intracommunicator

Return type MPI.communicator, dict

Raises

- *OasisException* – if OASIS is unable to create the intracommunicator
- *PyOasisException* – if an incorrect parameter is supplied

property name

Returns the name of the component

Return type string

set_couplcomm(*couplcomm*)

Sets the coupling communicator :param MPI.communicator couplcomm: coupling communicator

Returns error code

Return type int

Raises

- *OasisException* – if OASIS is unable to set the coupling communicator
- *PyOasisException* – if an incorrect parameter is supplied

class pyoasis.**SerialPartition**(*size, global_size=-1, name=""*)

Serial partition

Parameters

- **size** (*int*) – number of points in the partition
- **global_size** (*int*) – global size of the grid (optional)
- **name** (*str*) – name of the partition (optional)

Raises

- *OasisException* – if OASIS is unable to initialise the partition

- **PyOasisException** – if an incorrect parameter is supplied

class pyoasis.**ApplePartition** (*offset, size, global_size=- 1, name=""*)
Apple partition

Parameters

- **offset** (*int*) – offset according to the global index
- **size** (*int*) – number of points in the partition
- **global_size** (*int*) – global size of the grid (optional)
- **name** (*str*) – name of the partition (optional)

Raises **OasisException** – if OASIS is unable to initialise the
partition :raises PyOasisException: if an incorrect parameter is supplied

class pyoasis.**BoxPartition** (*global_offset, local_extent_x, local_extent_y, global_extent_x,*
global_size=- 1, name="")

Box partition

Parameters

- **global_offset** (*int*) – offset according to the global index
- **local_extent_x** (*int*) – extent in the x direction of the local partition
- **local_extent_y** (*int*) – extent in the y direction of the local partition
- **global_extent_x** (*int*) – global extent in the x direction
- **global_size** (*int*) – global size of the grid (optional)
- **name** (*str*) – name of the partition (optional)

Raises

- **OasisException** – if OASIS is unable to initialise the partition
- **PyOasisException** – if an incorrect parameter is supplied

class pyoasis.**OrangePartition** (*offsets, extents, global_size=- 1, name=""*)
Orange partition

Parameters

- **offsets** (*list of integers*) – list of offsets according to the global index
- **extents** (*list of integers*) – list of the partition extents
- **global_size** (*int*) – global size of the grid (optional)
- **name** (*str*) – name of the partition (optional)

Raises

- **OasisException** – if OASIS is unable to initialise the partition
- **PyOasisException** – if an incorrect parameter is supplied

class pyoasis.**PointsPartition** (*global_indices, global_size=- 1, name=""*)
Points partition

Parameters

- **global_indices** (*list of integers*) – list containing the global indices of the points in the partition

- **global_size** (*int*) – global size of the grid (optional)
- **name** (*str*) – name of the partition (optional)

Raises

- *OasisException* – if OASIS is unable to initialise the partition
- *PyOasisException* – if an incorrect parameter is supplied

`pyoasis.OasisParameters()`

Enumeration of parameters used by OASIS (values: OASIS_OUT, OASIS_IN)

`pyoasis.asarray(data, dtype=<class 'numpy.float64'>)`

Numpy array of double precision floating point numbers in Fortran ordering

Parameters

- **data** – any object that can be used to initialise a numpy array
- **dtype** – the numpy datatype of the returned array

Raises *PyOasisException* – if a Numpy array cannot be initialised

`class pyoasis.Var(name, partition, inout, bundle_size=1)`

Variable data

Parameters

- **name** (*string*) – name of the variable data
- **inout** (*pyoasis.OasisParameter*) – flag indicating whether the data is outgoing or ingoing
- **bundle_size** (*int*) – size of a bundle of fields

Raises

- *OasisException* – if OASIS is unable to initialise the variable data
- *PyOasisException* – if an incorrect parameter is supplied

`property cpl_freqs`

Returns the coupling periods

Return type array of integers

Raises *OasisException* – if OASIS is unable to obtain the coupling periods

`get(time, field)`

Gets data from another model.

Parameters

- **time** (*int*) – model time (in seconds) [kstep in OASIS]
- **field** (*pyoasis.asarray*) – data

Raises

- *OasisException* – if OASIS is unable to receive data from the other component
- *PyOasisException* – if an incorrect parameter is supplied

`property is_active`

Returns flag indicating if the variable is activated in the namcouple

Return type bool

property name**Returns** name of variable data**Return type** string**put** (*time, field, write_restart=False*)

Sends data to another model.

Parameters

- **time** (*int*) – model time (in seconds) [kstep in OASIS]
- **field** (*pyoasis.asarray*) – data
- **write_restart** (*bool*) – optional flag for writing a restart file

Raises

- **OasisException** – if OASIS is unable to send data to the other component
- **PyOasisException** – if an incorrect parameter is supplied

put_inquire (*time*)**Parameters** **time** (*int*) – model time (in seconds) [msec in OASIS]**Returns** return value expected at a specified time

for a given variable

Return type pyoasis.OasisParameters**Raises** **OasisException** – if OASIS is unable to obtain

the return code

Raises **PyOasisException** – if an incorrect parameter is supplied**class** pyoasis.**Grid** (*cgrid, nx_global, ny_global, lon, lat, partition=None*)

Grid declared via pyoasis API and written to netcdf files grids.nc masks.nc areas.nc

Parameters

- **cgrid** (*string*) – grid name (should be shorter than 64 char)
- **nx_global** (*int*) – global (non distributed) x size of the grid
- **ny_global** (*int*) – global (non distributed) y size of the grid
- **lon** (*numpy.array*) – longitudes of the cell centres (2D array)
- **lat** (*numpy.array*) – latitudes of the cell centres (2D array)
- **partition** (*type*) – optional partition object for distributed grids

Raises **PyOasisException** – if the name is empty**set_angle** (*angle*)

Set angle values

Parameters **angle** (*array of double precision floating numbers*) – mask array**set_area** (*area*)

Set area values

Parameters **area** (*array of double precision floating numbers*) – mask array

set_corners (*clo, cla*)

Sets corner latitudes and longitudes

Parameters

- **clo** (*array of double-precision floating numbers*) – array longitudes
- **cla** (*array of double-precision floating numbers*) – array longitudes

set_mask (*mask, companion=None*)

Sets integer mask values

Parameters

- **mask** (*array of integer numbers*) – mask array
- **companion** (*str*) – companion

write ()

Writes the grid

class `pyoasis.OasisException` (*text, error*)

class `pyoasis.PyOasisException` (*text*)

`pyoasis.pyoasis_abort` (*exception*)

Stops the execution of all the processes corresponding to the components after having displayed an error message and written to the log files information about the error and the context in which it took place.

Parameters **exception** (*Exception*) – exception to be handled

Raises `PyOasisException` – if the argument is not an exception

`pyoasis.oasis_abort` (*component_id, routine, message, filename, line, error*)

Stops the execution of all the processes corresponding to the components after having displayed an error message and written to the log files information about the error and the context in which it took place.

Parameters

- **component_id** (*int*) – Identifier of the component
- **routine** (*str*) – Name of the routine
- **message** (*str*) – Error message
- **line** (*int*) – Line
- **error** (*int*) – Error code

CORRESPONDENCE WITH THE OASIS3-MCT FORTRAN API

These tables show the correspondence between the functions described in the OASIS3-MCT user guide and their analogue in pyoasis. All the functions have been implemented with their full interface except `put` which, in the case of pyoasis, accepts only a single field.

5.1 Component

OASIS3-MCT	pyoasis.Component.
<code>oasis_init_comp(comp_id, comp_name, ierror, coupled, comm_world)</code>	<code>__init__(name, coupled=True, communicator=None)</code>
<code>oasis_terminate(ierror)</code>	<code>__del__()</code>
<code>oasis_create_couplcomm(icpl, localcomm, couplcomm, kinfo)</code>	<code>create_couplcomm(coupled)</code>
<code>oasis_set_couplcomm(couplcomm, kinfo)</code>	<code>set_couplcomm(couplcomm)</code>
<code>oasis_get_multi_intracomm(newcomm, cdnam, root_ranks, kinfo)</code>	<code>get_multi_intracomm(complist)</code>
<code>oasis_get_intracomm(newcomm, cdnam, kinfo)</code>	<code>get_intracomm(compname)</code>
<code>oasis_get_intercomm(newcomm, cdnam, kinfo)</code>	<code>get_intercomm(compname)</code>
<code>oasis_enddef(ierror)</code>	<code>enddef()</code>
<code>oasis_get_local_comm(local_comm, ierror)</code>	<code>localcomm</code>
<code>oasis_get_debug(debugvalue)</code>	<code>debug_level</code>
<code>oasis_set_debug(debugvalue)</code>	<code>debug_level</code>

5.2 Partition

OASIS3-MCT	pyoasis.
<code>oasis_def_partition(ilpart_id, igparal, ierror, isize, name)</code>	SerialPartition (size, global_size=-1, name='') ApplePartition (offset, size, global_size=-1, name='') BoxPartition (global_offset, local_extent_x, local_extent_y, global_extent_x, global_size=-1, name='') OrangePartition (offsets, extents, global_size=-1, name='') PointsPartition (global_indices, global_size=-1, name='')

5.3 Var

OASIS3-MCT	pyoasis.var.
oasis_def_var (var_id, name, il_part_id, var_nodims, kinout, var_actual_shape, vartype, ierror)	__init__ (name, partition, inout, bundle_size=1)
oasis_put(varid, date, fld1, info, fld2, fld3, fld4, fld5, write_restart)	put (date, field, write_restart=False)
oasis_get(varid, date, fld, info)	get(date, field)
oasis_put_inquire (varid, date, kinfo)	put_inquire(date)
oasis_get_ncpl(varid, ncpl, kinfo)	len(cpl_freqs)
oasis_get_freqs (varid, mop, ncpl, cplfreqs, kinfo)	cpl_freqs

5.4 Grid

OASIS3-MCT	pyoasis.grid.
oasis_start_grids_writing(flag) oasis_write_grid(cgrid, nx_global, ny_global, lon, lat, il_partid)	__init__ (cgrid, nx_global, ny_global, lon, lat, partition=None)
oasis_write_corner (cgrid, nx_global, ny_global, nc, clon, clat, il_partid)	set_corners(clo, cla)
oasis_write_area (cgrid, nx_global, ny_global, area, il_partid)	set_area(area)
oasis_write_mask (cgrid, nx_glo, ny_glo, mask, part_id, companion)	set_mask (mask, companion=None)
oasis_write_frac (cgrid, nx_glo, ny_glo, frac, part_id, companion)	set_frac (frac, companion=None)
oasis_write_angle (cgrid, nx_global, ny_global, angle, il_partid)	set_angle(angle)
oasis_terminate_grids_writing()	write()

5.5 Utilities

OASIS3-MCT	pyoasis.
oasis_abort(compid, routinename, abortmessage, rcode)	oasis_abort(component_id, routine, message, file- name, line, error) pyoasis_abort(exception)

INSTALLATION

The sections between brackets are necessary only when Cartopy plots are required, for the examples 11 and 12.

6.1 Under GNU/Linux

6.1.1 Prerequisites

- A Fortran and C compiler suite (tested with version 18 of the Intel compilers as well as versions 7.3, 8.3 and 9 of the GNU compilers).
- An MPI library (tested with version 18 of the Intel MPI Library and versions 4.0.1 and 4.0.5 of OpenMPI)
- NetCDF 4
- Python 3 with mpi4py and NumPy
- Sphinx and Tex Live (for the documentation)
- [Matplotlib]
- [GEOS (Geometry Engine, Open Source): package libgeos-dev under Debian or Ubuntu]
- [proj: package libproj-dev under Debian or Ubuntu]

6.1.2 Installation

- Obtain OASIS3-MCT (refer to OASIS3-MCT User Guide for details).
- Change directory to `${OASIS_ROOT}/util/make_dir`.
- Create your own `make.inc` file based on `make.intel_davinci`, `make.gfortran_openmpi_linux` or `make.bindings`.
- Build and install OASIS3-MCT and pyOASIS:

```
make -f TopMakefile realclean
make -f TopMakefile pyoasis
```

- Append the lines displayed at the end of the compilation to your `.bashrc` file or, alternatively, before using pyOASIS, source the script mentioned there.

6.1.3 [Extra software]

- Create a virtual environment:

```
export VENVDIR=~/.INSTALL/PY_ENV/PyO    directory containing the virtual environment
python3 -m venv ${VENVDIR}
source ${VENVDIR}/bin/activate
```

- Install software:

```
pip install --upgrade pip
pip uninstall shapely
pip install shapely --no-binary shapely
pip install cartopy
pip install pykdtree
```

The uninstall steps are needed only if a previous version of the software was already there. The last package is not necessary. It is only used for optimisation.

6.2 Under macOS

6.2.1 Prerequisites

```
brew install gcc
brew install openblas
brew install openmpi
[brew install geos]
[brew install proj]
```

(This has been tested with gcc 10.2.0.)

6.2.2 Installation

Same as under GNU/Linux. See previous section.

6.3 Virtual Python environment

- Create a virtual environment:

Same as under GNU/Linux, see previous section.

- Install packages:

```
pip install mpi4py
pip uninstall numpy
pip cache remove numpy
OPENBLAS="$(brew --prefix openblas)" pip install --global-option=build-ext numpy
pip install netcdf4
[pip uninstall scipy]
[pip cache remove scipy]
[pip install --global-option=build-ext scipy]
[pip uninstall shapely]
```

(continues on next page)

(continued from previous page)

```
[pip install shapely --no-binary shapely]
[pip install matplotlib]
[pip install cartopy]
[pip install pykdtree]
```

The uninstall steps are needed only if a previous version of the software was already there. The last package is not necessary. It is only used for optimisation.

6.3.1 Set up the environment

At the end of your `.bashrc`,

```
export TMPDIR=/tmp
export OMPI_MCA_mca_base_env_list=LD_LIBRARY_PATH=${PYOASIS_ROOT}/lib
```

6.4 Documentation

If pyOASIS is modified, this document can be regenerated, using Sphinx, by typing the following command in the directory `${OASIS_ROOT}/pyoasis`:

```
make doc
```


ACKNOWLEDGMENTS

This work has been financed by the IS-ENES3 project which has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 824084.



INDEX AND SEARCH

- `genindex`
- `search`

A

ApplePartition (*class in pyoasis*), 17
 asarray () (*in module pyoasis*), 18

B

BoxPartition (*class in pyoasis*), 17

C

Component (*class in pyoasis*), 15
 cpl_freqs () (*pyoasis.Var property*), 18
 create_couplcomm () (*pyoasis.Component method*), 15

D

debug_level () (*pyoasis.Component property*), 15

E

enddef () (*pyoasis.Component static method*), 15

G

get () (*pyoasis.Var method*), 18
 get_intercomm () (*pyoasis.Component method*), 15
 get_intracomm () (*pyoasis.Component method*), 16
 get_multi_intracomm () (*pyoasis.Component method*), 16
 Grid (*class in pyoasis*), 19

I

is_active () (*pyoasis.Var property*), 18

N

name () (*pyoasis.Component property*), 16
 name () (*pyoasis.Var property*), 18

O

oasis_abort () (*in module pyoasis*), 20
 OasisException (*class in pyoasis*), 20
 OasisParameters () (*in module pyoasis*), 18
 OrangePartition (*class in pyoasis*), 17

P

PointsPartition (*class in pyoasis*), 17
 put () (*pyoasis.Var method*), 19
 put_inquire () (*pyoasis.Var method*), 19
 pyoasis_abort () (*in module pyoasis*), 20
 PyOasisException (*class in pyoasis*), 20

S

SerialPartition (*class in pyoasis*), 16
 set_angle () (*pyoasis.Grid method*), 19
 set_area () (*pyoasis.Grid method*), 19
 set_corners () (*pyoasis.Grid method*), 20
 set_couplcomm () (*pyoasis.Component method*), 16
 set_mask () (*pyoasis.Grid method*), 20

V

Var (*class in pyoasis*), 18

W

write () (*pyoasis.Grid method*), 20