

XSIM

VO.10a 2017/10/04

EXERCISE SHEETS IMPROVED
the official successor of the **EXSHEETS** package

Clemens NIEDERBERGER

<https://github.com/cgnieder/xsim>

contact@mychemistry.eu

Table of Contents

1. Licence, Requirements and README	2	8.3. (Re-) Inserting a Certain Ex- ercise	19
2. Motivation and Background	3	9. Collecting Exercises	19
3. How to Read the Manual	3	9.1. Background	19
3.1. Nomenclature	3	9.2. Usage	20
3.2. Package Options	4	10. Printing Random Exercises From a Collection	23
3.3. Setting Options	4	11. Printing Solutions	24
3.4. Command descriptions	5	12. Grading Tables	26
4. Exercises and Solutions	5	13. Styling the Exercises – Templates	28
5. How the Exercise Environ- ments Work	6	13.1. Background	28
6. New Exercise Types	8	13.2. Templates Provided by the Package	29
7. Exercise Properties	10	13.3. Commands for Usage in Template Definitions	29
7.1. Predefined Properties	10	13.3.1. Goals	29
7.2. Declaring Own Properties . .	12	13.3.2. Properties	30
7.3. Exercise Goals	13	13.3.3. Parameters	32
7.4. Exercise Tags	16	13.3.4. Tags	32
8. Using and Printing an Exercise	17	13.3.5. Further Commands for Usage in Tem- plate Definitions	32
8.1. What the Environments do . .	17		
8.2. Environment Options & Hooks	17		

1. Licence, Requirements and README

13.4. Declaring Templates	35	B.2. ...Resolve Getting Repeatedly Wrong Exercise Properties or Wrong Exercise Lists? .	47
13.4.1. Environment Templates	35	B.3. ...Resolve Strange Errors After Updating?	47
13.4.2. Heading Templates	35	B.4. ! TeX capacity exceeded, sorry [text input levels=15]. Why?	47
13.4.3. Grading Table Templates	35	B.5. Runaway argument? !File ended while scanning use of ^M. Why?	47
13.5. Examples	35	B.6. ...Put a Star (or Another Symbol) in Headings of Exercises That Are Special?	48
13.5.1. The default Exercise Template	35	B.7. ...Create and Use xsim Style Files?	49
13.5.2. A New Exercise Type Using tcolorbox	36	B.8. ...Print All Solutions Grouped by Section?	50
13.5.3. Mimicking exsheets' runin Template	37	C. The xsimverb package	51
13.5.4. Mimicking exsheets' margin Template	38	D. All Exercise Examples	52
13.5.5. The Headings Templates	39	E. All Solution Examples	54
13.5.6. The default Table Template	39	F. Example Documents Coming With This Package	55
13.5.7. The default* Table Template	40	G. References	66
14. Exercise Translations	42	H. Index	68
15. Cloze Tests and Blank Lines	44		
A. Future Plans	46		
B. FAQ & How to...	46		
B.1. ...Know if xsim Needs Another Compilation?	47		

1. Licence, Requirements and README

Permission is granted to copy, distribute and/or modify this software under the terms of the L^AT_EX Project Public License (LPPL), version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The software has the status “maintained.”

xsim loads the packages expl3 [L3Pa], xparse [L3Pb], etoolbox [Leh15], array [MCo8] booktabs [Fea05] and translations [Nie15]. All of these packages are present on a modern and up to date T_EX distribution such as T_EX Live or MiK_TE_X so no further action should be needed. When you are using **xsim** you should be using an up to date T_EX distribution, anyway.



Newer versions of **xSIM** may depend on newer versions of the support packages. Remember: it is always dangerous to update single packages. Always update your T_EX distribution if you want an up to date version of a package. Be careful: if you're in the middle of an important project it might be better to wait with the update until you've finished the project. Every update might be breaking some things.

2. Motivation and Background

It has been quite a while since I first published exsheets [Nie17] in June 2012. Since then it has gained a user base and a little bit of popularity as the number of questions on tex.sx shows (103 at the time of writing) [var]. User questions, bug reports and feature requests improved it over the time. It still has a version number starting with a zero, though, which in my versioning system means I still consider it experimental.

This is due to several facts. It lacks a few features which I consider essential for a full version 1. For one thing it is not possible to have several kinds of exercises numbered independently. Using verbatim material such as listings inside exercises and solutions is not possible and the current workaround isn't that ideal either. One request which dates back quite a while now was to have different types of points to exercises...

All of those aren't easy to add due to the way exsheets is implemented right now. As a consequence I wanted to re-implement exsheets for a long time. This is what lead to **xSIM**. Internally the package works completely different.



xSIM will be the official successor of exsheets which is now considered obsolete but will stay alive and will still receive bugfix releases. However, new features will not be added to exsheets any more.

3. How to Read the Manual

3.1. Nomenclature

Throughout this manual certain terms are used. This section explains their meaning in this manual.

collection A *collection* bundles a number of exercises of one type or all types of exercises within certain barriers in the document. Those exercise collections can be printed at any place in the document.

goal *Goals* are a certain type of properties with a numerical value the sum of which is available throughout the document.

parameter *Parameters* are options of exercise types which are the same for each exercise of a type and can be retrieved and used in exercise templates.

3. How to Read the Manual

property *Properties* are options of exercises which are individual for each exercise and can be retrieved and used in exercise templates.

tag *Tags* are a certain type of properties with a csv list as value which can be used for selective usage of exercises.

template *Templates* are generic code frameworks which are used for typesetting **xsim**'s objects such as exercises, solutions, or grading tables.

3.2. Package Options

xsim has these package options:

verbose

Writes extensive information about what **xsim** is doing into the log file.

final

If used the exercise and solution environments will not rewrite the environment body files.

clear-aux

If used every time the total number of exercise changes **xsim** will write *less* information to the auxfile on the next run and only if the number of exercises stays stable between compilations the needed information will be written to the auxfile. *This needs more compilations until everything stabilizes but should reduce the probability of possibly faulty exercises after changes to the document.* The **final** option automatically disables this option. See also sections 5 on page 6 and B.2 on page 47.

Those options are used the usual way as package option

```
\usepackage[verbose]{xsim}
```

or as global option

```
\documentclass[verbose]{article}
```

or via the setup command:

```
\xsimsetup{<options>}
```

Set up **xsim**'s package options and all other options described at other places in the manual.

3.3. Setting Options

Apart from the package options already described in section 3.2 **xsim** has further options. Those can be “toplevel” options or options belonging to a module.

`toplevel` = { $\langle value \rangle$ }

A `toplevel` option.

`module/sublevel` = { $\langle value \rangle$ } A `sublevel` option belonging to the module `module`

Both kinds of options are set with `\xsimsetup`:

```

1 \xsimsetup{
2   topLevel = {value} ,
3   module/sublevel = {value}
4 }
```

3.4. Command descriptions

Some commands do have a `*` symbol printed next to their names. This indicates that the command is expandable, *i. e.*, it is usable in an `\edef` or `\write` context and will expand according to its description. All other commands are engine protected, *i. e.*, in the sense of ϵ -TeX's `\protected`.

Some command name descriptions end with `TF`.

`\SomeCommandTF` $\langle arguments \rangle$ { $\langle true \rangle$ }{ $\langle false \rangle$ }

A command with maybe some arguments and ending with the two arguments $\langle true \rangle$ and $\langle false \rangle$.

This means two things: the command is a conditional which tests something and depending on the outcome of the test leaves either the $\langle true \rangle$ argument (T) or the $\langle false \rangle$ argument (F) in the input stream. It also means two additional commands exist:

`\SomeCommandT` $\langle arguments \rangle$ { $\langle true \rangle$ }

The same as `\SomeCommandTF` but only with the $\langle true \rangle$ argument and no $\langle false \rangle$ argument.

`\SomeCommandF` $\langle arguments \rangle$ { $\langle false \rangle$ }

The same as `\SomeCommandTF` but only with the $\langle false \rangle$ argument and no $\langle true \rangle$ argument.

4. Exercises and Solutions

The two predefined environments for exercises and solutions are the following ones:

`\begin{exercise}`[$\langle properties \rangle$]

Input and typeset an exercise. See section 7 on page 10 for details on exercise properties.

`\begin{solution}`[$\langle options \rangle$]

Input and typeset the solution to the exercise of the previous exercise environment. See section 11 on page 24 for details on options of solutions.

5. How the Exercise Environments Work

```
1 \begin{exercise}
2   A first example for an exercise.
3 \end{exercise}
4 \begin{solution}
5   A first example for a solution.
6 \end{solution}
```

Exercise 1

A first example for an exercise.

As can be seen in the example a solution is not printed with the default setup. This can be changed using the following option.

`solution/print = true|false`

Default: false

Set if solutions are printed or not.

The option (belonging to the module `solution`) can either be set locally as option to the solution environment

```
1 \begin{solution}[print=true]
2   A first example for a solution.
3 \end{solution}
```

or with the setup command for all following solutions:

```
1 \xsimsetup{
2   solution/print = true
3 }
```

There is an completely analogous option for the exercise environment:

`exercise/print = true|false`

Default: true

Set if exercises are printed or not.

More details on those two environments can be found in section 8 on page 17.

5. How the Exercise Environments Work

Both environments write the contents of their bodies verbatim to external files following a certain naming structure:

- `<jobname>-<type>-<id>-exercise|solution-body.tex`

5. How the Exercise Environments Work

The name starts with the name of the job (which is the name of the document itself) followed by type and id of the corresponding exercise and then followed by the environment type. For example both environments from the first example have been written to files named

- `xsim_manual-exercise-1-exercise-body.tex` and
- `xsim_manual-exercise-1-solution-body.tex`, respectively.

Details on the $\langle type \rangle$ of an exercise will be given in section 6 on the following page. *The $\langle id \rangle$ of an exercise is a positive integer unique to each exercise environment regardless if the exercise is being printed or used at all.*

These external files are input when the respective exercise or solution is printed. An advantage of using external files is that *verbatim material is allowed* inside the environments. Each of those files contains some information about itself and where and why it was generated¹:

```
1 % -----
2 % file `xsim_manual-exercise-1-exercise-body.tex'
3 %   in folder `exercises/'
4 %
5 %     exercise of type `exercise' with id `1'
6 %
7 % generated by the `exercise' environment of the
8 %   `xsim' package v0.10a (2017/10/04)
9 % from source `xsim_manual' on 2017/10/04 on line 1
10 % -----
11 A first example for an exercise.
```

Arguably one downside of the approach using external files for each exercise and its solution is that your project folder will be cluttered with files. In order to deal with this somehow **XSIM** offers the following option:

`path = {\langle path name \rangle}` (initially empty)

With this option a subfolder or path within the main project folder can be given. Exercises will be written to and included from this path. *The path must exist on your system before you can use it!* This document uses `path = {exercises}`.

`file-extension = {\langle string \rangle}` Default: `tex`

This option let's you choose the extension of the auxiliary files.

Another thing to keep in mind: the environment in many ways works the same way as the `filecontents`. *This also means that you cannot have comments on the first line of the environments:*

1. In this example the sourcecode line number is misleading as the example where the file was generated itself was an external file where the exercise environment indeed was on line 1.

6. New Exercise Types

```
1 \begin{exercise}[points=2] % this will cause trouble
2   Lorem ipsum
3 \end{exercise}
```

!

xsim writes a lot of stuff to the auxfile for re-using information on subsequent compilations. If you add exercises, change properties *etc.* it might happen that wrong information is staying in the auxfile and is wrongly used by **xsim**. In such cases deleting the auxfile and doing a few fresh compilations may resolve your problems. Sometimes the *existence of exercise or solution files from earlier compilations* may lead to wrong lists of exercises or solutions. In such cases it can be useful to delete all those files and doing a fresh compilation. It may be helpful to use a subfolder for those external files which will make deleting them a little bit easier. (Don't forget to both create the subfolder and set **path** accordingly then.) Using the **clear-aux** option might help to reduce erroneous exercises.

6. New Exercise Types

It is easy to define new exercise environments together with a corresponding solution environment using the following command:

\DeclareExerciseType{*<type>*}{*<parameters>*}

Declare a new exercise type analogous to the exercise and solution environments.

Declaring a new exercise type will also define a new command:

\numberof{*<exercise-env>*}*s*

These commands hold the absolut number of used exercises of type *<type>*. The meaning of *<exercise-env>* will become clear below when the exercise parameters are explained. It is always the same as the exercise environment name.

```
1 There are \numberofexercises~exercises and \numberofproblems~problem in this
2 manual.
```

There are 12 exercises and 1 problem in this manual.

xsim's pre-defined environment pair has been defined as follows:

```
1 \DeclareExerciseType{exercise}{
2   exercise-env      = exercise ,
3   solution-env      = solution ,
```


6. New Exercise Types

```
4 exercise-name      = \XSIMtranslate{exercise} ,
5 solution-name      = \XSIMtranslate{solution} ,
6 exercise-template = default ,
7 solution-template = default
8 }
```

The above already is an example for almost all parameters that can (and often must) be set. Here is the complete list:

exercise-env = {<exercise environment name>}

The name for the environment used for the exercises of type <type>. *This parameter is mandatory.* It can't be changed afterwards.

solution-env = {<solution environment name>}

The name for the environment used for the solutions of type <type>. *This parameter is mandatory.* It can't be changed afterwards.

exercise-name = {<exercise name>}

The name of the exercises of type <type> – used for typesetting. *This parameter is mandatory.*

solution-name = {<solution name>}

The name of the solutions of type <type> – used for typesetting. *This parameter is mandatory.*

exercise-template = {<exercise template>}

The template used for typesetting the exercises of type <type>. *This parameter is mandatory.* See section 13 on page 28 for details on templates.

solution-template = {<solution template>}

The template used for typesetting the exercises of type <type>. *This parameter is mandatory.* See section 13 on page 28 for details on templates.

counter = {<counter name>}

The counter used for the exercises of type <type>. If not explicitly set the counter with the same name as **exercise-env** is used. Otherwise the specified counter is used. This enables to have different types of exercises sharing a common counter. *This parameter can't be changed afterwards.* If the explicit or implicit counter does not exist, yet, it will be defined.

solution-counter = {<counter name>}

The counter used for the solutions of type <type>. If not explicitly set the counter with the same name as **solution-env** is used. Otherwise the specified counter is used. This enables to have different types of solutions sharing a common counter although this doesn't actually make much sense. But it can be useful to avoid using an already existing counter. *This parameter can't be changed afterwards.* If the explicit or implicit counter does not exist, yet, it will be defined. The sole purpose of this counter is to be able to label solutions so they can be **\pageref**ed.

7. Exercise Properties

`number = {\langle integer \rangle}`

An internal parameter that is used to keep track of the number of exercises of a type. This parameter cannot be set or changed by the user.

It is possible to change some of the parameters after an exercise type has been defined. Those include `exercise-name`, `solution-name`, `exercise-template`, and `solution-template`:

`\SetExerciseParameter{\langle type \rangle}{\langle parameter \rangle}{\langle value \rangle}`

Usable to set a single parameter to a new value.

`\SetExerciseParameters{\langle type \rangle}{\langle parameters \rangle}`

Set several parameters at once. `\langle parameters \rangle` is a csv list of key/value pairs.

If you try to set an already set but fixed parameter like `exercise-env` a warning will be written to the log file. For all parameters that can be changed also options exist which can be set via `\xsimsetup`. They are explained in section 8.2 on page 17.



All exercises of a type use the parameters (e. g., `exercise-template`) that are *currently active*. If you want exercises with a different look or different names in the same document you should use different exercises types.

7. Exercise Properties

7.1. Predefined Properties

Exercise like the exercise environment and possibly others defined with `\DeclareExerciseType` have a number of predefined properties:

`id = {\langle integer \rangle}`

Holds the internal id of an exercise. *Cannot be set by the user.*

`ID = {\langle text \rangle}`

Holds the user id of an exercise if defined. Otherwise it is equal to `id`.

`counter = {\langle text \rangle}`

Holds the counter value representation of an exercise (i. e., what you usually know as `\the\langle counter \rangle`). *Cannot be set by the user.*

`counter-value = {\langle integer \rangle}`

Holds the counter value of an exercise (i. e., what you usually know as `\arabic{\langle counter \rangle}`). *Cannot be set by the user.*

`subtitle = {\langle text \rangle}`

Holds the subtitle of an exercise.

`points = {\langle number \rangle}`

Holds the reachable points of an exercise.

7. Exercise Properties

`bonus-points = {⟨number⟩}`

Holds the reachable bonus-points of an exercise.

`print = true|false`

Holds the print boolean of an exercise.

`print! = true|false`

Holds a special print boolean of an exercise, see page 16.

`use = true|false`

Holds the usage boolean of an exercise.

`use! = true|false`

Holds a special usage boolean of an exercise, see page 16.

`used = true|false`

True if an exercise has been used at least once. For an existing exercise this is only false for exercises that have been collected (*cf.* section 9 on page 19).

`tags = {⟨csv list of tags⟩}`

Holds the list of tags the exercise should be associated with.

`topics = {⟨csv list of topics⟩}`

Holds the list of topics the exercise should be associated with.

`page = {⟨text⟩}`

Holds the page counter value representation of an exercise (*i. e.*, what you usually know as `\thepage`).

`page-value = {⟨integer⟩}`

Holds the page counter value of an exercise (*i. e.*, what you usually know as `\arabic{page}`).

`section = {⟨text⟩}`

Holds the section counter value representation of an exercise (*i. e.*, what you usually know as `\thesection`).

`section-value = {⟨integer⟩}`

Holds the section counter value of an exercise (*i. e.*, what you usually know as `\arabic{section}`).

`chapter = {⟨text⟩}`

Holds the chapter counter value representation of an exercise (*i. e.*, what you usually know as `\thechapter`). *Only if a command `\chapter` and a counter `chapter` exist.*

`chapter-value = {⟨integer⟩}`

Holds the chapter counter value of an exercise (*i. e.*, what you usually know as `\arabic{chapter}`). *Only if a command `\chapter` and a counter `chapter` exist.*

7. Exercise Properties

`sectioning` = $\{\langle section\ numbers\rangle\}$

Holds five brace groups which in turn hold the section numbers (integers) of the exercise in the order $\{\langle chapter\rangle\}\{\langle section\rangle\}\{\langle subsection\rangle\}\{\langle subsubsection\rangle\}\{\langle paragraph\rangle\}$.

Some of these properties are fixed and cannot be set by the user. Those include `id`, `counter`, and `counter-value`. The others can be set using the optional argument of the exercise environment.

```
1 \begin{exercise}[subtitle={This is a subtitle},points=4,bonus-points=1]
2   An exercise where some properties have been set.
3 \end{exercise}
```

Exercise 2 *This is a subtitle*

An exercise where some properties have been set.

4 (+1) p.

7.2. Declaring Own Properties

`xsim` offers the possibility to declare additional exercise properties:

`\DeclareExerciseProperty!*-{\langle property\rangle}`

Declares the property $\langle property\rangle$.

If used with the optional `!` a **unique property** is defined which means that each exercise must have a property value distinct from all other exercises (all means all – *independent from the exercise type*).

If used with the optional `*` a **boolean property** is defined which means that it only should get the values `true` or `false` and if used without value it gets the value `true` instead of an empty value. If any other value is used the property is set to `false`. A boolean property obviously cannot be unique. The optional `*` takes precedence over the optional `!`, i. e., if both are present the property is boolean *but not* unique.

If used with the optional `-` a property is defined which won't get updated through subsequent compilation runs but is only set when the exercise is used.

`\DeclareExercisePropertyAlias{\langle property 1\rangle}\{\langle property 2\rangle}`

Declares $\langle property 1\rangle$ to be an alias of $\langle property 2\rangle$. This means that each time $\langle property 2\rangle$ is set $\langle property 1\rangle$ will be set to the same value *unless* it has been set already. As an example: property `ID` is an alias of property `id`.

This is better demonstrated with an example:

```
1 \begin{exercise}
2   \lipsum[4] % from package `lipsum'
3   \verb+\GetExerciseProperty{id}+: \GetExerciseProperty{id} \par
```

7. Exercise Properties

```
4 \verb+\GetExerciseAliasProperty{ID}+: \GetExerciseAliasProperty{ID} \par
5 \verb+\GetExerciseProperty{ID}+: \GetExerciseProperty{ID}
6 \end{exercise}
7 \begin{exercise}[ID=foo-bar]
8 \lipsum[4]
9 \verb+\GetExerciseProperty{id}+: \GetExerciseProperty{id} \par
10 \verb+\GetExerciseAliasProperty{ID}+: \GetExerciseAliasProperty{ID} \par
11 \verb+\GetExerciseProperty{ID}+: \GetExerciseProperty{ID}
12 \end{exercise}
```

Exercise 3

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

```
\GetExerciseProperty{id}: 3
\GetExerciseAliasProperty{ID}: 3
\GetExerciseProperty{ID}: 3
```

Exercise 4

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

```
\GetExerciseProperty{id}: 4
\GetExerciseAliasProperty{ID}: 4
\GetExerciseProperty{ID}: foo-bar
```

The power of properties will get more clear when reading section 13 on page 28 about templates.

7.3. A Special Kind of Property: Exercise Goals

Exercise goals are a generic concept in **xsim** for exercise properties like **points** or **bonus-points**. Those are properties which can (only) get a decimal number as value the sum of which is calculated and available (after a compilation) throughout the document.

```
\DeclareExerciseGoal{<goal>}
```

Declare a new exercise goal named *<goal>* and also a property called *<goal>*.

7. Exercise Properties

\TotalExerciseTypeGoal{ $\langle type \rangle$ }{ $\langle goal \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Get the sum of goal $\langle goal \rangle$ for all exercises of type $\langle type \rangle$. $\langle singular \rangle$ and $\langle plural \rangle$ are placed after the sum in the input stream depending on whether the sum equals 1 or not.

\TotalExerciseTypeGoals{ $\langle type \rangle$ }{ $\langle list of goals \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Get the sum of goal all goals in $\langle list of goals \rangle$ for all exercises of type $\langle type \rangle$. The goal names in $\langle list of goals \rangle$ must be separated with +. $\langle singular \rangle$ and $\langle plural \rangle$ are placed after the sum in the input stream depending on whether the sum equals 1 or not.

\TotalExerciseGoal{ $\langle goal \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Get the sum of goal $\langle goal \rangle$ for all exercises. $\langle singular \rangle$ and $\langle plural \rangle$ are placed after the sum in the input stream depending on whether the sum equals 1 or not.

\TotalExerciseGoals{ $\langle list of goals \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Get the sum of goal all goals in $\langle list of goals \rangle$ for all exercises. The goal names in $\langle list of goals \rangle$ must be separated with +. $\langle singular \rangle$ and $\langle plural \rangle$ are placed after the sum in the input stream depending on whether the sum equals 1 or not.

\AddtoExerciseTypeGoal{ $\langle type \rangle$ }{ $\langle goal \rangle$ }{ $\langle value \rangle$ }

Adds $\langle value \rangle$ to the goal $\langle goal \rangle$ of exercise type $\langle type \rangle$.

\AddtoExerciseTypeGoalPrint{ $\langle type \rangle$ }{ $\langle goal \rangle$ }{ $\langle value \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Adds $\langle value \rangle$ to the goal $\langle goal \rangle$ of exercise type $\langle type \rangle$. The value and – depending on whether the value equals 1 or not – $\langle singular \rangle$ or $\langle plural \rangle$ are left in the input stream.

\AddtoExerciseGoal{ $\langle goal \rangle$ }{ $\langle value \rangle$ }

Adds $\langle value \rangle$ to the goal $\langle goal \rangle$ of the current exercise type. (To be used within exercises.)

\AddtoExerciseGoalPrint{ $\langle goal \rangle$ }{ $\langle value \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Adds $\langle value \rangle$ to the goal $\langle goal \rangle$ of the current exercise type. The value and – depending on whether the value equals 1 or not – $\langle singular \rangle$ or $\langle plural \rangle$ are left in the input stream. (To be used within exercises.)

\ExerciseGoalValuePrint{ $\langle value \rangle$ }{ $\langle singular \rangle$ }{ $\langle plural \rangle$ }

Print $\langle value \rangle$ and – depending on whether the value equals 1 or not – $\langle singular \rangle$ or $\langle plural \rangle$.

\printgoal{ $\langle value \rangle$ }

Print $\langle value \rangle$ according to option **goal-print**. Defined in terms of **\ExerciseGoalValuePrint**.

\printpoints{ $\langle type \rangle$ }

Print the sum of points for all exercises of type $\langle type \rangle$ followed by an appropriate translation of the words “point” or “points”, respectively.² Defined in terms of **\TotalExerciseTypeGoal**.

\printtotalpoints

Print the sum of points for all exercises followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of **\TotalExerciseGoal**.

2. See section 14 on page 42 for details on the definition and usage of language dependent words.

7. Exercise Properties

`\addpoints*{⟨value⟩}`

Adds $\langle value \rangle$ to the points of the current exercise type. (To be used within exercises.) Prints the value followed by an appropriate translation of the words “point” or “points”, respectively. The starred version prints nothing. Defined in terms of `\AddtoExerciseGoal` and `\AddtoExerciseGoalPrint`.

`\points{⟨value⟩}`

Print $\langle value \rangle$ followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of `\ExerciseGoalValuePrint`.

`\printbonus{⟨type⟩}`

Print the sum of bonus points for all exercises of type $\langle type \rangle$ followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of `\TotalExerciseTypeGoal`.

`\printtotalbonus`

Print the sum of bonus points for all exercises followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of `\TotalExerciseGoal`.

`\addbonus*{⟨value⟩}`

Adds $\langle value \rangle$ to the bonus points of the current exercise type. (To be used within exercises.) Prints the value followed by an appropriate translation of the words “point” or “points”, respectively. The starred version prints nothing. Defined in terms of `\AddtoExerciseGoal` and `\AddtoExerciseGoalPrint`.

The two existing goals are defined with

```
1 \DeclareExerciseGoal{points}
2 \DeclareExerciseGoal{bonus-points}
```

When goal values are printed the decimal number is fed to a function which can be changed using the following option:

`goal-print = {⟨code⟩}`

Default: #1

How to format goal values. Use #1 to refer to the actual number.

At last some examples for a custom command: let’s say you want a command which prints the complete sum for all exercises of all exercise types of both `points` and `bonus-points` added up:

```
1 \NewDocumentCommand\printsumofpointsandbonus{}{%
2   \TotalExerciseGoals{points+bonus-points}
3   {\,\XSIMtranslate{point}}
4   {\,\XSIMtranslate{points}}}%
5 }
```

7. Exercise Properties

Here is how you could mimick the command `\totalpoints` from exsheets:

```
1 \NewDocumentCommand\pointsandbonus{}{%
2   \TotalExerciseGoal{points}{}{}%
3   \IfExerciseGoalsSumF{bonus-points}{=0}
4     {\, (+\, \TotalExerciseGoal{bonus-points}{}{} )}%
5   \, \XSIMtranslate{points}%
6 }
```

7.4. A Special Kind of Property: Exercise Tags

Exercise tags are a generic concept in `xsim` for exercise properties like `tags` or `topics`. Those are properties which can (only) get a csv list of strings as value. Those strings can be used to selectively use exercises. See section 8 on the next page for details on *usage* of exercises and the difference to *printing* an exercise and how to use exercise tags for selection.

`\DeclareExerciseTagging{<tag>}`

This defines an exercise tagging group named `<tag>`. It also defines a property named `<tag>`. In addition two options are defined: an option named `<tag>` which can be used for selection and an boolean option `<tag>/ignore-untagged`.

The two existing tagging groups have been defined and preset with the following code:

```
1 \DeclareExerciseTagging{tags}
2 \DeclareExerciseTagging{topics}
3 \xsimsetup{tags/ignore-untagged=false}
```

This means that these options are available:

`tags = {<csv list of tags>}`

Choose the set of tags whose associated exercises should be printed.

`topics = {<csv list of topics>}`

Choose the set of topics whose associated exercises should be printed.

`tags/ignore-untagged = true|false`

Default: false

If set to true exercises with no tags will be printed even if tags have been chosen with the option `tags`.

`topics/ignore-untagged = true|false`

Default: true

If set to true exercises with no topics will be printed even if topics have been chosen with the option `topics`.

It may happen that you choose certain tags for printing and want one or two exercises to be printed or used even if they don't match the tagging criteria. For this reason two additional properties exist which can be set to an exercise:

8. Using and Printing an Exercise

`print! = true|false`

If set to true the exercise will be printed (and thus used) regardless of other conditions.

`use! = true|false`

If set to true the exercise will be used regardless of other conditions.

8. Using and Printing an Exercise

8.1. What the Environments do

When an exercise is started with `\begin{exercise}` (or other environments defined through `\DeclareExerciseType`) then different things happen depending on different settings:

- If the *insert mode* is active nothing happens, see section 9 on page 19 for details on this.
- Else the id integer is incremented.
- If the exercise is *used* the corresponding counter is stepped and the exercise is added to the “use list”. The properties `counter` and `use` are updated accordingly.
- If an exercise is *printed* then it is also *used*. An exercise that isn’t used cannot be printed. Being printed means two things: being added to the “print list” and being typeset at the position where the exercise is placed in the source file. If an exercise is *not printed but used* it means that the counter will be stepped. This can be useful for creating an exercise sheet only containing the solutions for some exercises.
- If an exercise is printed certain hooks and template code is inserted around the environment body.

```
1 \begin{exercise}[print=false]
2   This exercise will not be printed but the exercise counter will be
3   incremented nonetheless. Its solution will be printed in the list of
4   solutions.
5 \end{exercise}
6 \begin{solution}
7   The solution of the exercise that has not been printed.
8 \end{solution}
```

The schematic structure of an exercise is shown in figure 1 on the next page.

8.2. Environment Options & Hooks

For each exercise type there are the following options for both environments, the environments’ names are the module names for the options (here using the “exercise” type):

8. Using and Printing an Exercise




FIGURE 1: Schematic structure of an exercise or solution.

- `exercise/print = true|false` Default: true
 Determines if exercises of type “exercise” are printed.
- `exercise/use = true|false` Default: true
 Determines if exercises of type “exercise” are used.
- `exercise/within = {<counter>}` (initially empty)
 Adds the exercise counter to the reset list of the counter <counter>. *Beware that if the counter is a shared counter this will affect all objects using this counter!*
- `exercise/the-counter = {<code>}`
 An interface for redefining the counter representation command `\the<counter>`.
- `exercise/template = {<template>}`
 An interface for `\SetExerciseParameter{exercise}{exercise-template}{<template>}`.
- `solution/template = {<template>}`
 An interface for `\SetExerciseParameter{exercise}{solution-template}{<template>}`.
- `exercise/name = {<name>}`
 An interface for `\SetExerciseParameter{exercise}{exercise-name}{<name>}`.
- `solution/name = {<name>}`
 An interface for `\SetExerciseParameter{exercise}{solution-name}{<name>}`.
- `exercise/pre-hook = {<code>}` (initially empty)
 The code for the *pre exercise hook* for exercises of the type “exercise”.
- `exercise/begin-hook = {<code>}` (initially empty)
 The code for the *begin exercise hook* for exercises of the type “exercise”.

9. Collecting Exercises

<code>exercise/end-hook = {<code>}</code>	(initially empty)
The code for the <i>end exercise hook</i> for exercises of the type “exercise”.	
<code>exercise/post-hook = {<code>}</code>	(initially empty)
The code for the <i>post exercise hook</i> for exercises of the type “exercise”.	
<code>solution/print = true false</code>	Default: false
Determines if solutions of type “exercise” are printed.	
<code>solution/pre-hook = {<code>}</code>	(initially empty)
The code for the <i>pre solution hook</i> for solutions of the type “exercise”.	
<code>solution/begin-hook = {<code>}</code>	(initially empty)
The code for the <i>begin solution hook</i> for solutions of the type “exercise”.	
<code>solution/end-hook = {<code>}</code>	(initially empty)
The code for the <i>end solution hook</i> for solutions of the type “exercise”.	
<code>solution/post-hook = {<code>}</code>	(initially empty)
The code for the <i>post solution hook</i> for solutions of the type “exercise”.	

8.3. (Re-) Inserting a Certain Exercise

If you know type and `id` of an exercise you can (re-)insert every existing exercise, *i. e.*, every exercise whose external file exists.

`\printexercise{<type>}{<id>}`
Inserts the exercise of type `<type>` with the `id` `<id>`.

```
1 \printexercise{exercise}{5}
```

Exercise 5

This exercise will not be printed but the exercise counter will be incremented nonetheless. Its solution will be printed in the list of solutions.

9. Collecting Exercises

9.1. Background

XSIM knows the concept of “exercise collections”. A collection of exercises can be useful when you want to print a certain group of exercises several times. Each collection must have a unique name with which you can refer to the corresponding collection. A collection is realized by declaring the collection and by surrounding the exercises belonging to the collection with a certain pair of commands (this is explained in the next section).

Let's say you have several files of math exercises where one only contains geometry exercises and another only calculus exercises and so on. Surrounding the `\input` of each file with said pair of commands for a certain collection all exercises of the corresponding file now are a collection which then can be printed at once wherever you want the collection of exercises to be printed. By choosing certain tags (see section 7.4 on page 16) inside each collection you could even cherry-pick exercises from the external file.

9.2. Usage

A collection must be declared in the preamble. Using a pair of commands explained below exercises between those commands are added to the corresponding collection but not printed. After a collection is completed the collection can be printed as often as needed.

`\DeclareExerciseCollection{<collection name>}`

Define a new collection `<collection name>` in the document preamble.

`\collectexercisetype{<collection name>}{<exercise type>}`

Opens the collection `<collection name>` which now collects all exercises of type `<exercise type>` until the collection is closed with `\collectexercisesstop`. Collections of other types are not collected.³

`\collectexercises{<collection name>}`

Opens the collection `<collection name>` which now collects all exercises until the collection is closed with `\collectexercisesstop`.⁴

`\collectexercisesstop{<collection name>}`

Closes the collection `<collection name>`.⁵

`\printcollection[<options>]{<collection name>}`

Prints the collection `<collection name>`, i. e., all exercises collected earlier. This command cannot be used before the corresponding collection has been closed correctly.

Valid options are the following:

`print-collection/headings = true | false`

Default: false

If true a heading for each exercise type is inserted.

`print-collection/headings-template = {<template>}`

Default: collection

The heading template used when `headings = {true}`.

`print-collection/print = exercises | solutions | both`

Default: exercises

Determines whether `\printcollection` prints the exercises or the solutions of the collection. When you choose both exercises and solutions are printed alternately.

3. This command starts a group with `\begingroup!`

4. This command starts a group with `\begingroup!`

5. This command ends a group with `\endgroup!`

9. Collecting Exercises

Those options can also be set via `\xsimsetup` using the module `print-collection`.



Please be aware that exercises are not used or printed while they are collected. Nonetheless the property `use` is set to `true` (so that solutions can be printed even if the exercises are not) and the property `print` is set to `false`. Also their counters are *not stepped* during the process. This only happens when they are printed the first time, cf. the `used` property. At that time also the properties `page`, `section` and `chapter` are set and the property `print` is set to `true`.

The usage should be clear:

```
1 \collectexercises{foo}
2 \begin{exercise}
3   This exercise is added to the collection `foo'.
4 \end{exercise}
5 \begin{exercise}
6   This exercise is also added to the collection `foo'.
7 \end{exercise}
8 \begin{exercise}
9   So is this.
10 \end{exercise}
11 \begin{exercise}
12   As well as this one.
13 \end{exercise}
14 \collectexercisesstop{foo}
```

Once the collection is closed it can be printed:

```
1 \printcollection{foo}
```

Exercise 6

This exercise is added to the collection ‘foo’.

Exercise 7

This exercise is also added to the collection ‘foo’.

Exercise 8

So is this.

Exercise 9

As well as this one.

You can open several collections at the same time:

```

1 \collectexercises{foo}
2   ...
3 \collectexercisestype{bar}{exercises}
4   ...
5 \collectexercisesstop{bar}
6   ...
7 \collectexercisesstop{foo}

```

Exercises will be added to each open collection.

There is one generic collection called “all exercises”. As the name already suggests it will hold all exercises. So if you say

```

1 \printcollection{all exercises}

```

all exercises will be printed.

If you use `\labels` inside of exercises and you print exercises more than once in your document (by reusing a collection for example) you will get

!

```

1 LaTeX Warning: There were multiply-defined labels.

```

Equally if you have environments like `\begin{equation}` which step a counter inside an exercise or solution the counter will be stepped each time the exercise is used.

At last now an example using external files, collections and tags:

```

1 % preamble:
2 % \DeclareExerciseCollection{foo-easy}
3 % \DeclareExerciseCollection{foo-medium}
4 % \DeclareExerciseTagging{difficulty}
5
6 % document:
7 \collectexercises{foo-easy}
8 \xsimsetup{difficulty=easy}
9 \input{foo.tex}

```

10. Printing Random Exercises From a Collection

```
10 \collectexercisestop{foo-easy}
11 % collection 'foo-easy' now contains all exercises of file 'foo.tex' tagged
12 % with 'difficulty=easy'
13
14 \collectexercisestop{foo-medium}
15 \xsimsetup{difficulty=medium}
16 \input{foo.tex}
17 \collectexercisestop{foo-medium}
18 % collection 'foo-medium' now contains all exercises of file 'foo.tex'
19 % tagged with 'difficulty=medium'
```



The recommended usage is similar to the last example. Actually a collection can be printed *before* it is opened, too. (This needs *at least* two compilations, though.) However, it is safer printing a collection only once and only *after it has been collected*. No guaranties are given that properties are set correctly if you use the collection before. You usually also will make sure that the exercises in a collection are unique, *i. e.*, that an exercise is not part of several collections – at least not if both collections are printed in the same document.

10. Printing Random Exercises From a Collection

xsim provides the possibility of selecting random exercises from a collection (*cf.* section 9 on page 19).

`\printrandomexercises[⟨options⟩]{⟨number⟩}`

This command prints `⟨number⟩` random exercises from the collection chosen with option `collection`, see below. When this command is used it generates a random list of integers which is written to the aux file. On the subsequent compilations the according exercises are printed. *If you want to regenerate the random list you have to delete the aux file before compiling.*

Valid options for this command are:

`random/sort = true|false` Default: true

Determines whether the random chosen exercises should be sorted according to their order of definition in the collection or not.

`random/collection = {⟨collection⟩}` Default: all exercises

The collection from which the exercises are to be chosen from.

`random/exclude = {⟨csv list of ids⟩}`

A list of `ids` or `IDs` of exercises *not* to be chosen.

`random/print = exercises|solutions|both` Default: exercises

Determines whether `\printrandomexercises` prints the exercises or the solutions. When you choose both exercises and solutions are printed alternately.

```
1 \printrandomexercises[collection=foo]{2}
```

Exercise 6

This exercise is added to the collection ‘foo’.

Exercise 8

So is this.

The example above of course doesn’t make much sense but if you have a collection which collects exercises from an external file and the exercises haven’t been printed in the document before then you will get a list of subsequently numbered exercises.

11. Printing Solutions

There are different commands for printing the solutions to exercises:

```
\printsolutionstype*[\<options>]{\<exercise type>}
```

Prints the solutions of all used exercises of type *<exercise type>*. The starred version only prints the solutions of all printed exercises of type *<exercise type>*.

```
\printsolutions*[\<options>]
```

Prints the solutions of all used exercises of all types ordered by type. The starred version only prints the solutions of all printed exercises of all types.

```
\printallsolutions*[\<options>]
```

Prints the solutions of all used exercises of all types ordered by appearance in the document. The starred version only prints the solutions of all printed exercises of all types.

```
\printsolution[\<options>]{\<type>}{\<id>}
```

Prints the solution of the exercise of type *<type>* with the *id* *<id>*.

```
1 \printsolutionstype{exercise}
```

Solutions to the Exercises

Solution 1

A first example for a solution.

Solution 5

The solution of the exercise that has not been printed.

Solution 11

Try to fill in these blanks. All of them are created by using the `\blank` command.

The options can be divided into two groups. The ones in the first group modify the layout.

`print-solutions/headings = true|false` Default: true

If true a heading for each exercise type is inserted.

`print-solutions/headings-template = {<template>}` Default: default

The heading template used when `headings = {true}`.

The ones in the second group set conditions selecting which solutions are printed. If you combine those conditions a solution is printed if it meets either of the conditions.

`print-solutions/section = true|false|<integer>` Default: false

If you set `section = {true}` only solutions of exercises of the current section are printed. If you set `section = {4}` only solutions of exercises in a section with number 4 are printed.

`print-solutions/chapter = true|false|<integer>` Default: false

If you set `chapter = {true}` only solutions of exercises of the current chapter are printed. If you set `chapter = {4}` only solutions of exercises in a chapter with number 4 are printed.

`print-solutions/collection = false|<collection name>` Default: false

If used only solutions of exercises belonging to collection `<collection name>` are printed.

The conditions can be combined. The following call will only print solutions from exercises in section 3 of chapter 2:

```
\printsolutions[chapter=2,section=3]
```

!

The selection per section or per chapter relies on the *counter numbers* of the sections or chapters, respectively. This means if section numbers are reset (e.g. by `\chapter` or `\appendix`) and you have exercises from *different* sections with *the same section number* the solutions of *all those exercises* will be printed. This means you only should use the `section` selection when section are the top document level headings (apart from parts) and you have no exercises in the appendix. Similar considerations are valid for the `chapter` selection.

All options can also be set via `\xsimsetup` using the module `print-solutions`.

```
\printsolutions[section=4,headings-template=per-section]
```

Solutions to the Exercises of Section 4

Solution 1

A first example for a solution.

```
1 \printsolution{exercise}{5}
```

Solution 5

The solution of the exercise that has not been printed.

12. Grading Tables

When you create exercises it may not only be desirable to be able to add points and bonus-points to a question (see section 7.3 on page 13 about exercise goals) but also to be able to output a grading table. **xsim** has built-in means for this.

`\gradingtable[⟨options⟩]`

Print a grading table.

Valid options for this command are

`template = {⟨template⟩}`

Default: default

Choose the template used for the grading table.

`type = {⟨exercise type⟩}`

(initially empty)

Choose the exercise type for which the table is printed.

Both option defaults can be changed with `\xsimsetup` setting the options using `grading-table`:

```
1 \xsimsetup{
2   grading-table/template = default*
3 }
```

An example:

```
1 \gradingtable[type=exercise]
```

12. Grading Tables

Exercise	Points	reached
1	0	
2	4	
3	0	
4	0	
5	0	
6	0	
7	0	
8	0	
9	0	
10	2.5	
11	0	
12	0	
total	6.5	

Or using the “default*” template:

```
1 \gradingtable[template=default*,type=exercise]
```

Exercise	1	2	3	4	5	6	7	8	9	10	11	12	total
Points	0	4	0	0	0	0	0	0	0	2.5	0	0	6.5
reached													

Available templates and how to define new ones are explained in sections 13.4.3 on page 35 and 13.5 on page 35. **XSIM** per default provides two templates “default” and “default*”, the first one has a vertical layout, the second a horizontal layout. Both templates can be used per type like in the examples above or for all types at once by leaving the specification **type** away:

```
1 \gradingtable
```

	Points reached
Exercise 1	0
Exercise 2	4
Exercise 3	0
Exercise 4	0
Exercise 5	0
Exercise 6	0
Exercise 7	0
Exercise 8	0
Exercise 9	0
Exercise 10	2.5
Exercise 11	0
Exercise 12	0
Problem 1	5
total	11.5

13. Styling the Exercises – Templates

13.1. Background

Whenever **xsim** outputs something to be typeset it uses so-called templates for the task. **xsim** knows of three different kinds of templates:

- environment templates (see section 13.4.1 on page 35),
- heading templates (see section 13.4.2 on page 35) and
- grading table templates (see section 13.4.3 on page 35)

The most important one for the styling of the exercises are the environment templates. Those templates give you complete control over the look and arrangement of an exercise. To be able to do this **xsim** provides a large number of commands which can be used only inside template definitions.⁶ Those commands are explained in the next section. Their usage will hopefully become clear in the examples in section 13.5 on page 35. Having full control over the layout comes at a price: you need to be able to program yourself in order to achieve certain layouts.⁷

6. The last sentence is wrong: those commands can be used anywhere but most of them only give useful results inside of templates.

7. I plan to incorporate the most common layouts – and maybe some fancy ones, too – in the examples section 13.5 on page 35 but at the time of writing this is still up in the air.

13.2. Templates Provided by the Package

XSIM comes with a few predefined layouts:

default The template activated per default and the only one available without further action.

runin A layout rather similar to the one by package `exsheets`, see section 13.5.3 on page 37. Available through the style file `layouts` (see section B.7 on page 49 for more information on style files).

margin A layout rather similar to the one by package `exsheets`, see section 13.5.4. Available through the style file `layouts` (see section B.7 on page 49 for more information on style files).

Layout “default”

Exercise 10 *The Subtitle*

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem.

_____/
2.5 p.

Layout “runin”

Exercise 10 *The Subtitle* Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem.

2.5 points

Layout “margin”

Exercise 10 (2.5 p.) Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem.

13.3. Commands for Usage in Template Definitions

13.3.1. Goals

`\IfExerciseGoalTF{<goal>}{<relation and value>}{<true>}{<false>}`
Checks the sum of goal `<goal>` against `<relation and value>`.

13. Styling the Exercises – Templates

`\IfExerciseGoalSingularTF{<goal>}{<true>}{<false>}`

Checks if the value of the goal `<goal>` of the current exercise equals 1. This is the same as `\IfExerciseGoalTF{<goal>}{=1}{<true>}{<false>}`.

`\IfExerciseTypeGoalsSumTF{<type>}{<list of goals>}{<relation and value>}{<true>}{<false>}`

Ckecks the sum of all goals in `<list of goals>` for the exercises of type `<type>` against `<relation and value>`.

`\IfExerciseGoalsSumTF{<type>}{<list of goals>}{<relation and value>}{<true>}{<false>}`

Ckecks the sum of all goals in `<list of goals>` for all exercises of all types against `<relation and value>`.

`\TotalExerciseTypeGoal{<goal>}{<type>}{<singular>}{<plural>}`

Print the sum of goal `<goal>` for the exercises of type `<type>` and append `<singular>` or `<plural>` depending on wether the sum equals 1 or not.

`\TotalExerciseGoal{<goal>}{<singular>}{<plural>}`

Print the sum of goal `<goal>` for all exercises of all types and append `<singular>` or `<plural>` depending on wether the sum equals 1 or not.

13.3.2. Properties

* `\IfExercisePropertyExistTF{<property>}{<true>}{<false>}`

Tests wether an exercise property with the name `<property>` is defined.

`\IfExercisePropertySetTF{<property>}{<true>}{<false>}`

Tests wether the exercise property `<property>` has been set for the current exercise.

* `\GetExerciseProperty{<property>}`

Retrieves the value of the property `<property>` for the current exercise.

`\GetExercisePropertyTF{<property>}{<true>}{<false>}`

Tests wether the exercise property `<property>` has been set for the current exercise. Inside the `<true>` branch you can refer to the retrieved value either with `#1` or with `\PropertyValue`. *This command expands its contents inside a group.*

`\GetExerciseBody{exercise|solution}`

Retrieves the environment body of either the exercise or the corresponding solution of the current exercise.

* `\GetExerciseIdForProperty{<property>}{<value>}`

Retrieves the property `id` of the exercise where the property `<property>` has the value `<value>`. *This only works for unique properties!*

`\GetExerciseTypeForProperty{<property>}{<value>}`

Retrieves the property `type` of the exercise where the property `<property>` has the value `<value>`. *This only works for unique properties!*

Introduced in
version 0.10
(September 19,
2017)

13. Styling the Exercises – Templates

Changed in version 0.9 (June 20, 2017)	$\backslash\text{SetExerciseProperty}\{\langle\text{property}\rangle\}\{\langle\text{value}\rangle\}$ Set the property $\langle\text{property}\rangle$ of the current exercise to $\langle\text{value}\rangle$.
Introduced in version 0.9 (June 20, 2017)	$\backslash\text{SetExpandedExerciseProperty}\{\langle\text{property}\rangle\}\{\langle\text{value}\rangle\}$ Expand $\langle\text{value}\rangle$ $\backslash\text{edef}$ -like and set the property $\langle\text{property}\rangle$ of the current exercise to the result of the expansion.
Introduced in version 0.9 (June 20, 2017)	$\backslash\text{ExerciseSetProperty}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}\{\langle\text{value}\rangle\}$ Set the property $\langle\text{property}\rangle$ of the exercise of type $\langle\text{type}\rangle$ and id $\langle\text{id}\rangle$ to $\langle\text{value}\rangle$.
Introduced in version 0.9 (June 20, 2017)	$\backslash\text{ExerciseSetExpandedProperty}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}\{\langle\text{value}\rangle\}$ Expand $\langle\text{value}\rangle$ $\backslash\text{edef}$ -like and set the property $\langle\text{property}\rangle$ of the exercise of type $\langle\text{type}\rangle$ and id $\langle\text{id}\rangle$ to the result of the expansion.
	$*\backslash\text{IfExerciseBooleanProperty}\text{TF}\{\langle\text{property}\rangle\}\{\langle\text{true}\rangle\}\{\langle\text{false}\rangle\}$ Checks whether the boolean property $\langle\text{property}\rangle$ has value true or $\langle\text{false}\rangle$ and leaves the corresponding argument in the input stream. Gives an error if $\langle\text{property}\rangle$ is not a boolean property.
	$*\backslash\text{GetExerciseAliasProperty}\{\langle\text{property}\rangle\}$ Retrieves the value of the property of which $\langle\text{property}\rangle$ is an alias of for the current exercise.
	$\backslash\text{SaveExerciseProperty}\{\langle\text{property}\rangle\}\langle\text{macro}\rangle$ Saves the value of the property $\langle\text{property}\rangle$ for the current exercise in macro $\langle\text{macro}\rangle$.
	$\backslash\text{GlobalSaveExerciseProperty}$ Globally saves the value of the property $\langle\text{property}\rangle$ for the current exercise in macro $\langle\text{macro}\rangle$.
	$\backslash\text{ExercisePropertyIfSet}\text{TF}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}\{\langle\text{true}\rangle\}\{\langle\text{false}\rangle\}$ Test if the property $\langle\text{property}\rangle$ has been set for the exercise of type $\langle\text{type}\rangle$ with id $\langle\text{id}\rangle$.
	$*\backslash\text{ExercisePropertyGet}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}$ Retrieves the value of the property $\langle\text{property}\rangle$ for the exercise of type $\langle\text{type}\rangle$ with id $\langle\text{id}\rangle$.
	$*\backslash\text{ExercisePropertyGetAlias}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}$ Retrieves the value of the property of which $\langle\text{property}\rangle$ is an alias of for the exercise of type $\langle\text{type}\rangle$ with id $\langle\text{id}\rangle$.
	$\backslash\text{ExercisePropertySave}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}\langle\text{macro}\rangle$ Saves the value of the property $\langle\text{property}\rangle$ for the exercise of type $\langle\text{type}\rangle$ with id $\langle\text{id}\rangle$ in macro $\langle\text{macro}\rangle$.
	$\backslash\text{ExercisePropertyGlobalSave}\{\langle\text{type}\rangle\}\{\langle\text{id}\rangle\}\{\langle\text{property}\rangle\}\langle\text{macro}\rangle$ Globally saves the value of the property $\langle\text{property}\rangle$ for the exercise of type $\langle\text{type}\rangle$ with id $\langle\text{id}\rangle$ in macro $\langle\text{macro}\rangle$.

13.3.3. Parameters

* `\GetExerciseParameter{<parameter>}`

Retrieves the value of the parameter `<parameter>` for the current exercise type.

`\GetExerciseParameterTF{<parameter>}{<true>}{<false>}`

Retrieves the value of the parameter `<parameter>` for the current exercise type. Inside the `<true>` branch you can refer to the retrieved value either with `#1` or with `\ParameterValue`. *This command expands its contents inside a group.*

Introduced in
version 0.9 (June
20, 2017)

* `\GetExerciseName`

Retrieves the value of the parameter `exercise-name` for the current exercise or of the parameter `solution-name` for the current solution.

* `\ExerciseParameterGet{<type>}{<parameter>}`

Retrieves the value of the parameter `<parameter>` for the exercise of type `<type>` with id `<id>`.

* `\IfExerciseParameterSetTF{<parameter>}{<true>}{<false>}`

Test if the parameter `<parameter>` has been set for the current exercise type.

Introduced in
version 0.9 (June
20, 2017)

* `\ExerciseParameterIfSetTF{<type>}{<parameter>}{<true>}{<false>}`

Test if the parameter `<parameter>` has been set for the exercise type `<type>`.

Introduced in
version 0.9 (June
20, 2017)

13.3.4. Tags

`\ForEachExerciseTag{<type>}{<code>}`

Loops over all tags of tag type `<type>` for the current exercise applying `<code>` each time. Inside `<code>` you can refer to the corresponding tag with `#1`.

`\ListExerciseTags{<type>}{<between>}`

Lists all tags of tag type `<type>` for the current exercise using `<between>` as a separator.

`\UseExerciseTags{<type>}{<between two>}{<between>}{<between last two>}`

Lists all tags of tag type `<type>` for the current exercise using `<between>` as a separator and `<between last two>` as separator between the last two tags of the list. If the list only consists of two tags `<between two>` is used as separator.

13.3.5. Further Commands for Usage in Template Definitions

`\UseExerciseTemplate{<type>}{<name>}`

Retrieve template `<name>` of type `<type>`. This can be useful if you want to define a template which just adds some code to an existing template (an automated `\label`, say).

* `\ExerciseType`

Can be used to refer to the current exercise type.

* `\ExerciseID`

Can be used to refer to the current exercise id.

* `\ExerciseCollection`

Can be used in certain templates to refer to the collection that is currently inserted.

* `\numberofusedexercises`

Holds the total number of used exercises. Useful in table template definitions.

* `\ExerciseTableType{<code>}`

In table template definitions this macro either expands to the given exercise type or – if no type has been given – to `<code>`.

* `\IfInsideSolutionTF{<true>}{<false>}`

Tests if the template is used inside a solution environment or not.

* `\IfPrintSolutionTF{<true>}{<false>}`

Tests if the option `print` for the solutions of the current `\ExerciseType` is set to true or false.

`\IfExistSolutionTF{<true>}{<false>}`

Tests if a solution for the current exercise exists.

`\ForEachPrintedExerciseByType{<code>}`

Loops over each *printed* exercise ordered by the exercise types and within each type by id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the `counter` property of the exercise
- #4: the `subtitle` property of the exercise
- #5: the `points` property of the exercise
- #6: the `bonus-points` property of the exercise

`\ForEachUsedExerciseByType{<code>}`

Loops over each *used* exercise ordered by the exercise types and within each type by id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the `counter` property of the exercise
- #4: the `subtitle` property of the exercise
- #5: the `points` property of the exercise
- #6: the `bonus-points` property of the exercise

`\ForEachPrintedExerciseByID`

Loops over each *printed* exercise order by the exercise id. Inside `<code>` you can refer to several properties of the corresponding exercise:

Introduced in
version 0.9 (June
20, 2017)

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the `counter` property of the exercise
- #4: the `subtitle` property of the exercise
- #5: the `points` property of the exercise
- #6: the `bonus-points` property of the exercise

\ForEachUsedExerciseByID

Loops over each *used* exercise order by the exercise id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the `counter` property of the exercise
- #4: the `subtitle` property of the exercise
- #5: the `points` property of the exercise
- #6: the `bonus-points` property of the exercise

*** \XSIMtranslate{<keyword>}**

Delivers the translation of `<keyword>` according to the current document language (in the meaning of a babel [Bra16] or polyglossia [Cha15] language). Existing keywords and keyword translations (and how to add new ones) are explained in section 14 on page 42.

\XSIMexpandcode{<code>}

Expands `<code>` like `\edef` does and leaves the result in the input stream.

*** \XSIMifchapterTF{<true>}{<false>}**

Returns `<true>` if both a macro `\chapter` and a counter `chapter` are defined and `<false>` otherwise.

\XSIMmixedcase{<code>}

Converts the full expansion⁸ of `<code>` to mixed case:

```
\XSIMmixedcase{this is some text} This is some text
This command expands <code> before converting it.
```

\XSIMputright<macro>{<code>}

Extends the macro definition of `<macro>` with `<code>` putting it to the right. This is more or less a local version of the LaTeX kernel macro `\g@addto@macro`.

*** \XSIMifeqTF{<code 1>}{<code 2>}{<true>}{<false>}**

Checks if the full expansion⁸ of `<code 1>` and `<code 2>` is the same tokenlist.

*** \XSIMifblankTF{<code>}{<true>}{<false>}**

Checks if the full expansion⁸ of `<code>` is blank (*i. e.*, if it is empty or only consists of spaces).

⁸. This is a `\romannumeral` expansion [Flo].

13.4. Declaring Templates

13.4.1. Environment Templates

`\DeclareExerciseEnvironmentTemplate{<name>}{<begin code>}{<end code>}`

Declare the environment template `<name>`.

Environment templates are used by the exercise and solution environments. Those are the templates set with the parameters `exercise-template` and `solution-template`.

The predefined template is called “default”, see section 13.5.1.

13.4.2. Heading Templates

`\DeclareExerciseHeadingTemplate{<name>}{<code>}`

Declare the heading template `<name>`.

Heading templates are used by `\printsolutions`, `\printsolutionstype` and `\printcollection`. Those are the templates set with the option `headings-template` of the modules `print-solutions` and `print-collection`.

The predefined templates are “default”, “collection”, “per-section” and “per-chapter” see section 13.5.5 on page 39.

13.4.3. Grading Table Templates

`\DeclareExerciseTableTemplate{<name>}{<code>}`

Declare the grading table template `<name>`.

Table templates are used by `\gradingtable`. Those are the templates set with the option `template` of module `grading-table`

The predefined templates are “default” and “default”, see sections 13.5.6 on page 39 and 13.5.7 on page 40.

13.5. Examples

The repository of this package⁹ currently includes 34 example documents demonstrating how different aspects of this package work or how different kinds of problems can be solved or how different kinds of layouts can be achieved as well as how solve concrete problems that have come up in different L^AT_EX forums, see section F on page 55.

13.5.1. The default Exercise Template

Below the definition of the default exercise template provided by `xsim` is shown:

9. GitHub: <https://github.com/cgnieder/xsim/>, CTAN: <http://www.ctan.org/pkg/xsim/>

```

1 \DeclareExerciseEnvironmentTemplate{default}{%
2   \subsection*
3   {%
4     \XSIMmixedcase{\GetExerciseName}\nobreakspace
5     \GetExerciseProperty{counter}%
6     \IfInsideSolutionF
7     {%
8       \GetExercisePropertyT{subtitle}
9       { {\normalfont\itshape\PropertyValue}}}%
10    }%
11  }
12  \GetExercisePropertyT{points}
13  {%
14    \marginpar
15    {%
16      \IfInsideSolutionF{\rule{1.2cm}{1pt}\slash}%
17      \printgoal{\PropertyValue}
18      \GetExercisePropertyT{bonus-points}{~(+\printgoal{\PropertyValue})}
19    }%
20    ~\XSIMtranslate {point-abbr}%
21  }%
22 }
23 {}

```

13.5.2. A New Exercise Type Using tcolorbox

Let's say we want exercises to be put in a `tcolorbox`. We want a bold title and, if given, an italic subtitle. Exercises should also have the points after the subtitle in parentheses if given. Let's also say we want those to be an additional exercise type in addition to the ones **XSIM** already provides. This is shown with the following code which is also how the problems in this manual have been defined:

```

1 \DeclareExerciseEnvironmentTemplate{tcolorbox}
2 {%
3   \tcolorbox[
4     colback = red!5!white ,
5     colframe = red!75!black ,
6     colbacktitle = yellow!50!red ,
7     coltitle = red!25!black ,
8     breakable ,
9     drop shadow ,
10    beforeafter skip = .5\baselineskip ,
11    title =
12      \textbf{\GetExerciseName~\GetExerciseProperty{counter}}}%

```

13. Styling the Exercises – Templates

```

13     \GetExercisePropertyT{subtitle}{ \textit{\PropertyValue}}}%
14     \IfInsideSolutionF{%
15         \GetExercisePropertyT{points}{ % notice the space
16             (%
17                 \printgoal{\PropertyValue}
18                 \IfExerciseGoalSingularTF{points}
19                 {\XSIMtranslate{point}}
20                 {\XSIMtranslate{points}}}%
21             )%
22         }%
23     }%
24 ]%
25 }
26 {\endcolorbox}
27
28 \DeclareExerciseType{problem}{
29     exercise-env = problem ,
30     solution-env = answer ,
31     exercise-name = Problem ,
32     solution-name = Answer ,
33     exercise-template = tcolorbox ,
34     solution-template = tcolorbox
35 }

```

See it in action:

```

1 \begin{problem}[subtitle=My subtitle,points=5]
2   This is a problem using a subtitle and points.
3 \end{problem}
4 \begin{answer}
5   This is the answer to problem~\GetExerciseProperty{counter}.
6 \end{answer}

```

Problem 1 *My subtitle* (5 points)

This is a problem using a subtitle and points.

13.5.3. Mimicking exsheets' runin Template

The following example shows how you could mimick exsheets' runin template. The outcome isn't exactly the same since exsheets doesn't use `\marginpar` but the result should look very similar. A safer definition would use a real sectioning command for the title.

```

1 \usepackage{needspace}
2 \DeclareExerciseEnvironmentTemplate{runin}
3 {
4     \par\vspace{\baselineskip}
5     \Needspace*{2\baselineskip}
6     \noindent
7     \textbf{\XSIMmixedcase{\GetExerciseName}~\GetExerciseProperty{counter}}%
8     \GetExercisePropertyT{subtitle}{ \textit{\#1}} % <<< notice the space
9     \IfInsideSolutionF{%
10         \GetExercisePropertyT{points}{%
11             \marginpar{%
12                 \printgoal{\PropertyValue}%
13                 \GetExercisePropertyT{bonus-points}{+\printgoal{\PropertyValue}}%
14                 \, \IfExerciseGoalSingularTF{points}
15                     {\XSIMtranslate{point}}
16                     {\XSIMtranslate{points}}}%
17             }%
18         }%
19     }%
20 }
21 {}

```

The following example shows how you could mimick exsheets' margin template.

```

1 \DeclareExerciseEnvironmentTemplate{margin}
2 {%
3     \trivlist
4     \item[\llap{%
5         \smash{%
6             \tabular[t]{@{}r@{}}
7             \textbf{\XSIMmixedcase{\GetExerciseName}}~\GetExerciseProperty{
counter}}
8             \IfExercisePropertySetT{points}}{%
9                 \tabularnewline
10                (%
11                \printgoal{\GetExerciseProperty{points}}}%
12                \GetExercisePropertyT{bonus-points}{+\printgoal{#1}}}%
13                \,\XSIMtranslate{point-abbr}}%
14            )%
15        }%
16    \endtabular
17 }%
18 }]\relax

```

```

19 }
20 {\endtrivlist}

```

13.5.5. The Headings Templates

XSIM defines four heading templates which only differ by which text they output:

```

1 \DeclareExerciseHeadingTemplate{default}
2   {\section*{\XSIMtranslate{default-heading}}}
3 \DeclareExerciseHeadingTemplate{collection}
4   {\section*{\XSIMtranslate{collection-heading}}}
5 \DeclareExerciseHeadingTemplate{per-section}
6   {\section*{\XSIMtranslate{per-section-heading}}}
7 \DeclareExerciseHeadingTemplate{per-chapter}
8   {\section*{\XSIMtranslate{per-chapter-heading}}}

```

Section 14 on page 42 shows how the translations are defined.

13.5.6. The default Table Template

This template is the one used for grading tables per default. It has a vertical layout.

```

1 \DeclareExerciseTableTemplate{default}{%
2   \XSIMputright\ExerciseTableCode{%
3     \toprule
4     \XSIMifblankTF{\ExerciseType}
5       {}
6       {\XSIMmixedcase{\GetExerciseParameter{exercise-name}}}
7     &
8     \XSIMmixedcase{\XSIMtranslate{points}} &
9     \XSIMtranslate{reached} \\
10    \midrule
11  }%
12  \ForEachUsedExerciseByType{%
13    \XSIMifeqTF{#1}{\ExerciseTableType{#1}}
14      {%
15        \XSIMifblankTF{\ExerciseType}
16          {%
17            \XSIMputright\ExerciseTableCode{%
18              \XSIMmixedcase{\ExerciseParameterGet{#1}{exercise-name}} }%
19            }%
20          }
21        {}%
22      \XSIMputright\ExerciseTableCode

```

13. Styling the Exercises – Templates

```

23      {#3 & \XSIMifblankTF{#5}{\printgoal{0}}{\printgoal{#5}} & \\\ }%
24      }
25      {%
26      }
27      \XSIMputright\ExerciseTableCode{%
28      \midrule
29      \XSIMtranslate{total} &
30      \XSIMifblankTF{\ExerciseType}
31      {\TotalExerciseGoal{points}}{}}
32      {\TotalExerciseTypeGoal{\ExerciseType}{points}}{}} &
33      \\\ \bottomrule
34      }%
35      \XSIMexpandcode{%
36      \noexpand\begin{tabular}{\XSIMifblankTF{\ExerciseType}{l}{c}cc}
37      \noexpand\ExerciseTableCode
38      \noexpand\end{tabular}%
39      }%
40      }

```

The part

```

1 \XSIMifblankTF{\ExerciseType}{ ... }{ ... }

```

repeatedly checks if an exercise type has been given for the table. This makes it possible to design the table differently if it is for one exercise type only (the true case) or for all exercise types (the false case). `\ExerciseTableType{<code>}` either expands to the given exercise type or to `<code>`.

13.5.7. The default* Table Template

The second of the predefined grading table templates. It has a horizontal layout.



If you have a lot of exercises the width of a table with this layout may exceed the text width of the document!

```

1 \DeclareExerciseTableTemplate{default*}{%
2   \XSIMputright\ExerciseTableCode{%
3     \toprule
4     \XSIMifblankTF{\ExerciseType}
5     {}
6     {\XSIMmixedcase{\GetExerciseParameter{exercise-name}}}
7     &%
8   }%

```


13. Styling the Exercises – Templates

```

9 \ForEachUsedExerciseByType{%
10 \XSIMifeqTF {#1} { \ExerciseTableType {#1} }
11 {
12 \XSIMifblankTF{\ExerciseType}
13 {%
14 \XSIMputright\ExerciseTableCode{%
15 \XSIMmixedcase{\ExerciseParameterGet{#1}{exercise-name} }%
16 }%
17 }
18 {}%
19 \XSIMputright\ExerciseTableCode{#3 &}
20 }
21 {}%
22 }%
23 \XSIMputright\ExerciseTableCode{%
24 \XSIMtranslate{total} \\\
25 \midrule
26 \XSIMmixedcase{\XSIMtranslate{points}} &
27 }%
28 \ForEachUsedExerciseByType{%
29 \XSIMifeqTF{#1}{\ExerciseTableType{#1}}
30 {%
31 \XSIMputright\ExerciseTableCode{%
32 \XSIMifblankTF{#5}{\printgoal{0}}{\printgoal{#5}} &}%
33 }
34 {}%
35 }%
36 \XSIMputright\ExerciseTableCode{%
37 \XSIMifblankTF{\ExerciseType}
38 {\TotalExerciseGoal{points}}{}}
39 {\TotalExerciseTypeGoal{\ExerciseType}{points}}{}}%
40 \\\ \midrule
41 \XSIMtranslate{reached} &%
42 }%
43 \ForEachUsedExerciseByType{%
44 \XSIMifeqTF{#1}{\ExerciseTableType{#1}}
45 {\XSIMputright\ExerciseTableCode{&}}
46 {}%
47 }%
48 \XSIMputright\ExerciseTableCode{ \\\ \bottomrule }%
49 \def\numberofcolumns{%
50 \XSIMifblankTF{\ExerciseType}
51 {\numberofusedexercises}
52 {\csname numberof \ExerciseType s\endcsname}%
53 }%
54 \XSIMifeqF{\numberofcolumns}{0}
55 {%

```

```

56     \begin{tabular}{l*{\numberofcolumns}{c}c}
57         \ExerciseTableCode
58     \end{tabular}%
59 }%
60 }

```

The part

```

1 \XSIMifblankTF{\ExerciseType}{ ... }{ ... }

```

repeatedly checks if an exercise type has been given for the table. This makes it possible to design the table differently if it is for one exercise type only (the `true` case) or for all exercise types (the `false` case). `\ExerciseTableType{<code>}` either expands to the given exercise type or to `<code>`.

14. Exercise Translations

`\DeclareExerciseTranslation{<language>}{<keyword>}{<translation>}`

Declare the translation of `<keyword>` for language `<language>`.

`\DeclareExerciseTranslations{<keyword>}{<translations>}`

Declare the translations of `<keyword>` for several languages at once. See an example of the usage below.

`*\XSIMtranslate{<keyword>}`

Delivers the translation of `<keyword>` according to the current document language (in the meaning of a babel [Bra16] or polyglossia [Cha15] language).

`\ForEachExerciseTranslation{<code>}`

Loops over all translations of all keywords known to `\XSIM`. Inside `<code>` you can refer to the keyword with #1, to the language with #2, and to the translation with #3.

As an example how to use `\DeclareExerciseTranslations` here is how the translations for exercise have been defined:

```

1 \DeclareExerciseTranslations{exercise}{
2   Fallback = exercise ,
3   English  = exercise ,
4   French   = exercice ,
5   German   = "\Ubung
6 }

```

Table 1 on the following page shows all existing keywords with all predefined translations.

14. Exercise Translations

TABLE 1: Translation keywords predefined by **XSIM**.

keyword	language	translation
exercise	Fallback	exercise
exercise	English	exercise
exercise	French	exercice
exercise	German	\''Ubung
question	Fallback	question
question	English	question
question	French	question
question	German	Aufgabe
solution	Fallback	solution
solution	English	solution
solution	French	solution
solution	German	L\'osung
point-abbr	Fallback	p.
point-abbr	English	p.
point-abbr	French	p.
point-abbr	German	P.
point	Fallback	point
point	English	point
point	French	point
point	German	Punkt
points	Fallback	points
points	English	points
points	French	points
points	German	Punkte
reached	Fallback	reached
reached	English	reached
reached	French	atteint
reached	German	erreicht
total	Fallback	total
total	English	total
total	French	totalement
total	German	insgesamt
default-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\GetExerciseParameter {exercise-name}s}
default-heading	English	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\GetExerciseParameter {exercise-name}s}

continues

15. Cloze Tests and Blank Lines

keyword	language	translation
default-heading	German	\XSIMmixedcase {\GetExerciseParameter {solution-name}en} zu den \XSIMmixedcase {\GetExerciseParameter {exercise-name}en}
collection-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {exercise-name}s}
collection-heading	English	\XSIMmixedcase {\GetExerciseParameter {exercise-name}s}
collection-heading	German	\XSIMmixedcase {\GetExerciseParameter {exercise-name}en}
per-section-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\GetExerciseParameter {exercise-name}s} of Section\nobreakspace \ExerciseSection
per-section-heading	English	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\GetExerciseParameter {exercise-name}s} of Section\nobreakspace \ExerciseSection
per-section-heading	German	\XSIMmixedcase {\GetExerciseParameter {solution-name}en} zu den \XSIMmixedcase {\GetExerciseParameter {exercise-name}en} in Abschnitt\nobreakspace \ExerciseSection
per-chapter-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\GetExerciseParameter {exercise-name}s} of Chapter\nobreakspace \ExerciseChapter
per-chapter-heading	English	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\GetExerciseParameter {exercise-name}s} of Chapter\nobreakspace \ExerciseChapter
per-chapter-heading	German	\XSIMmixedcase {\GetExerciseParameter {solution-name}en} zu den \XSIMmixedcase {\GetExerciseParameter {exercise-name}en} in Kapitel\nobreakspace \ExerciseChapter

15. Cloze Tests and Blank Lines

Similar to exsheets **xSIM** provides a command **\blank**:

\blank*[*<options>*]{*<text to be filled in>*}

Creates a blank in normal text or in an exercise but fills the text of its argument if inside a solution. If used at the *begin of a paragraph* **\blank** will do two things: it will set the

15. Cloze Tests and Blank Lines

linespread according to an option explained below and will insert `\par` after the lines. The starred version doesn't do these things.

Those are the options for customization:

`blank/blank-style = {<code>}` Default: `\underline{#1}`

Instructions for typesetting the blank cloze. Refer to the filled in space with #1.

`blank/filled-style = {<code>}` Default: `\underline{#1}`

Instructions for typesetting the filled cloze. Refer to the filled in text with #1

`style = {<code>}`

Shortcut for setting both `blank-style` and `filled-style` at once.

`blank/scale = {<decimal number>}` Default: 1

Scales the blank to `<decimal number>` times its natural width.

`blank/width = {<dim>}` (initially empty)

Sets the blank to a width of `<dim>`. This takes precedence over `scale`.

`blank/linespread = {<decimal number>}` Default: 1

Set the linespread for the blank lines. This only has an effect if `\blank` is used at the begin of a paragraph.

`blank/line-increment = {<dim>}` Default: 1pt

The blank line is built in multiples of this value. If the value is too large you may end up with uneven lines. If the value is too small you may end up with a non-ending compilation. Experiment with values to find the suiting one for your use case.

`blank/line-minimum-length = {<dim>}` Default: 2em

The minimal length a line must have before it is built step by step.

```
1 This is a \blank{blank} outside in normal text.
2 \begin{exercise}
3   Try to fill in \blank[width=4cm]{these} blanks. All of them
4   \blank{are created} by using the \cs{blank} \blank{command}.
5 \end{exercise}
6 \xsimsetup{blank/filled-style=\textcolor{red}{#1}}
7 \begin{solution}[print]
8   Try to fill in \blank[width=4cm]{these} blanks. All of them
9   \blank{are created} by using the \cs{blank} \blank{command}.
10 \end{solution}
```

This is a _____ outside in normal text.

A. Future Plans

Exercise 11

Try to fill in _____ blanks. All of them _____ by using the `\blank` _____.

Solution 11

Try to fill in **these** blanks. All of them **are created** by using the `\blank command`.

A number of empty lines are easily created by setting the `width` option:

```
1 Write up the pros and cons of \xsim\ over \pkg{exsheets}:  
2  
3 \blank[width=4.8\linewidth,linespread=1.5]{}  
-----
```

Write up the pros and cons of **XSIM** over exsheets:

A. Future Plans

XSIM is complete in so far as it is perfectly usable to create exams or exercise and solution sections in books with the most freedom in layout already. But still there are features which would be useful additions. Below I list all ideas that I currently plan to add to **XSIM**:

- a document class `xsim-exam` for creating exams; this class should itself feature the possibility of creating different versions of an exam, maybe already provide multiple choice questions and so on; one could also think about automatic creation of running headers and footers, *i. e.*, means for changing the layout of the exam; following the spirit of **XSIM** this should probably be done using templates as well.

I am very open to suggestions regarding features, both in general and specifically regarding the document class.

B. FAQ & How to...

This section serves as a kind of gallery showing solutions to common problems. I expect this section to grow over the years. Some examples especially regarding other layouts are also

shown in example files added to this package.

B.1. ...Know if **xsim** Needs Another Compilation?

If **xsim** wants you to recompile your document it writes the following to the logfile:

```
1 *****
2 * xsim warning: "rerun"
3 *
4 * Exercise properties may have changed. Rerun to get them synchronized.
5 *****
```

So just check the logfile regularly (which you should be doing anyway) and keep your eyes open.

B.2. ...Resolve Getting Repeatedly Wrong Exercise Properties or Wrong Exercise Lists?

xsim writes a lot of stuff to the auxfile for re-using information on subsequent compilations. If you add exercises, change properties *etc.* it might happen that wrong information is staying in the auxfile and is wrongly used by **xsim**. In such cases deleting the auxfile and doing a few fresh compilations may resolve your problems.

Sometimes the *existence of exercise or solution files from earlier compilations* may lead to wrong lists of exercises or solutions. In such cases it can be useful to delete all those files and doing a fresh compilation. It may be helpful to use a subfolder for those external files which will make deleting them a little bit easier. (Don't forget to both create the subfolder and set **path** accordingly then.)

Using the **clear-aux** option might help to reduce erroneous exercises.

B.3. ...Resolve Strange Errors After Updating?

xsim writes a lot of stuff to the auxfile. An update may well change how this is done so deleting the auxfile and doing a few fresh compilations may resolve your problems.

B.4. ! TeX capacity exceeded, sorry [text input levels=15]. Why?

Did you try to use an exercise or solution in a macro of some sort? This generally will fail.¹⁰ But there should never be the need to hide the environments inside of a macro, anyway.

B.5. Runaway argument? !File ended while scanning use of ^M. Why?

Did you try to use an exercise or solution in a macro of some sort? This generally will fail. But there should never be the need to hide the environments inside of a macro, anyway.

10. The reasons are similar to the ones given here: <https://tex.stackexchange.com/a/295422/>.

B.6. ...Put a Star (or Another Symbol) in Headings of Exercises That Are Special?

The code below shows one possible modification of an exercise template which allows to easily create bonus exercises:

```

1 % preamble:
2 \usepackage{amsmath}
3 % declare boolean property:
4 \DeclareExerciseProperty*{bonus}
5 \DeclareExerciseEnvironmentTemplate{bonus}
6 {
7   \subsection*
8   {
9     % test for boolean property and insert star symbol if true:
10    \IfExerciseBooleanPropertyT{bonus}{\llap{$\bigstar$ }Bonus }%
11    \XSIMmixedcase{\GetExerciseName}\nobreakspace
12    \GetExerciseProperty{counter}%
13    \IfInsideSolutionF
14    {
15      \IfExercisePropertySetT{subtitle}
16      { {\normalfont\itshape\GetExerciseProperty{subtitle}}}%
17    }%
18  }
19  \GetExercisePropertyT{points}
20  {
21    \marginpar
22    {
23      \IfInsideSolutionF{\rule{1.2cm}{1pt}\slash}%
24      \PropertyValue
25      \GetExercisePropertyT{bonus-points}
26      {\nobreakspace(+\PropertyValue)}%
27      \nobreakspace\XSIMtranslate{point-abbr}%
28    }%
29  }%
30 }
31 {}

```

The usage is now as follows:

```

1 \xsimsetup{exercise/template = bonus}
2 % set the boolean property to true
3 \begin{exercise}[bonus]
4   A bonus question.
5 \end{exercise}

```


★ Bonus Exercise 12

A bonus question.

B.7. ...Create and Use **xsim** Style Files?

xsim offers you the possibility to create own *style files*. Let's say you want to have a style called `math-exam`. Then you need to save all necessary definitions in a file called:

`xsim.math-exam.code.tex`

The first command in the file should be `\xsimstyle{math-exam}`. This file can now be loaded into your document using `\loadxsimstyle{math-exam}`:

```
1 \documentclass[DIV=18,parskip=half]{scrartcl}
2 \usepackage[T1]{fontenc}
3 \usepackage[utf8]{inputenc}
4
5 \usepackage[clear-aux]{xsim}
6 \loadxsimstyle{math-exam}
7
8 \title{Math Exam \#3}
9 \date{2017-03-28}
```

In this style file stuff like template and property definitions should happen. This is more or less a convenient way to

- keep the preamble “clean” and
- define re-usable styles without the need of copying the document preamble to another document.

A style file is like a package or class file, *i. e.*, @ has category code 11 (letter).

The formal description of the commands:

`\xsimstyle*{<style name>}`

The first command in a **xsim** style file called `xsim.<style name>.code.tex` which defines the **xsim** style `<style name>`. The starred version activates `expl3` syntax.¹¹

`\loadxsimstyle{<csv list of style names>}`

Load one or more styles into the document.



At the moment this mechanism offers no advantages over creating a custom package or simply `\input`ing a file. Future versions might provide additional features.

¹¹. Those users who want this will know what it means. If you don't know what it means you will not need it.

B.8. ...Print All Solutions Grouped by Section?

Here is an idea how to get a list of all solutions grouped by the section the corresponding exercises are appearing in.

```
1 % preamble:
2 % \usepackage{etoolbox}
3 % \newcounter{sections}
4
5 % document:
6 \setcounter{sections}{1}
7 \whileboolexpr
8 { test {\ifnumless{\value{sections}}{\value{section}+1}} }
9 {
10   \printsolutions[section=\value{sections},headings-template=per-section]
11   \stepcounter{sections}
12 }
```

For this manual we then get the following list.¹²

Solutions to the Exercises of Section 4

Solution 1

A first example for a solution.

Solutions to the Exercises of Section 8

Solution 5

The solution of the exercise that has not been printed.

Answers to the Problems of Section 13

Answer 1 *My subtitle*

This is the answer to problem 1.

12. Taking care of the fact that we're in the appendix now which means we can't use `\value{section}`. Therefore this manual does `\edef\lastsection{\arabic{section}}` right before `\appendix`

Solutions to the Exercises of Section 15

Solution 11

Try to fill in these blanks. All of them are created by using the `\blank` command.

C. The `xsimverb` package

`XSIM` comes bundled with another package called `xsimverb`. This package loads a very small subset of `XSIM` which allows to create environments which write their contents verbatim to external files. It provides the following commands (which of course are also available in `XSIM`, too):

`\XSIMfilewritestart*{<file name>}`

Start writing to the file named `<file name>`. This should be the *last* command in the *begin* definition of an environment. If it is used in an environment with arguments where the *last* argument is optional you should check if the optional argument is given and use the starred version if the test is negative. This is demonstrated in an example below using `xparse`'s `\NewDocumentEnvironment`. If you want an environment with only an optional argument you should use `xparse`'s commands to define it. Due to the way how `\newenvironment` scans for optional arguments you'll otherwise may end up with leading spaces gobbled from the first line in your environment.

`\XSIMfilewritestop`

Stop writing to the file. This should be the *first* command in the *end* definition of an environment.

`\XSIMsetfilebegin{<code>}`

This command can be used to write something to the external file *before* the environment contents. Must be set before `\XSIMfilewritestart` in the *begin* definition.

`\XSIMsetfileend{<code>}`

This command can be used to write something to the external file *after* the environment contents. Must be set before `\XSIMfilewritestart` in the *begin* definition.

`\XSIMgobblechars{<integer>}`

Determines how many characters are cut off of the beginning of each line of the environment body before it is written to the file. The default value is 0.

An example of how to use those commands:

```
1 \documentclass{article}
2 \usepackage{xsimverb,listings}
3
4 \makeatletter
```

D. All Exercise Examples

```
5 \NewDocumentEnvironment{example}{o}
6   {%
7     \XSIMsetfilebegin{\@percentchar\space file ``\jobname.tmp'}%
8     \XSIMsetfileend{\@percentchar\space bye bye}%
9     \IfNoValueTF{#1}
10      {\XSIMfilewritestart*{\jobname.tmp}}
11      {\XSIMfilewritestart{\jobname.tmp}}%
12   }
13   {%
14     \XSIMfilewritestop
15     \lstinputlisting[language={\LaTeX\TeX}]{\jobname.tmp}%
16     \input{\jobname.tmp}
17   }
18 \makeatother
19
20 \begin{document}
21
22 \begin{example}
23 bla bla \LaTeX
24 \end{example}
25
26 \end{document}
```

The tmp file produced by the above example will contain the following three lines (if the file itself was called test.tex):

```
1 % file `test.tmp'
2 bla bla \LaTeX
3 % bye bye
```

D. All Exercise Examples



You will notice that some exercises from section 13.5 on page 35 look differently in this section. That is because all exercises of a type use the template that's *currently active*. If you want exercises with a different look you should use different exercises types.

The following list is created with this code:

```
1 \xsimsetup{exercise/template = bonus}
2 \printcollection[headings]{all exercises}
```

Exercises

Exercise 1

A first example for an exercise.

Exercise 2 *This is a subtitle*

An exercise where some properties have been set.

4 (+1) p.

Exercise 3

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

```
\GetExerciseProperty{id}: 3  
\GetExerciseAliasProperty{ID}: 3  
\GetExerciseProperty{ID}: 3
```

Exercise 4

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

```
\GetExerciseProperty{id}: 4  
\GetExerciseAliasProperty{ID}: 4  
\GetExerciseProperty{ID}: foo-bar
```

Exercise 5

This exercise will not be printed but the exercise counter will be incremented nonetheless. Its solution will be printed in the list of solutions.

Exercise 6

This exercise is added to the collection 'foo'.

Exercise 7

This exercise is also added to the collection 'foo'.

E. All Solution Examples

Exercise 8

So is this.

Exercise 9

As well as this one.

Exercise 10 *The Subtitle*

_____/2.5 p.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem.

Exercise 11

Try to fill in _____ blanks. All of them _____ by using the `\blank` _____.

★ Bonus Exercise 12

A bonus question.

Problems

Problem 1 *My subtitle* (5 points)

This is a problem using a subtitle and points.

E. All Solution Examples

Solutions to the Exercises

Solution 1

A first example for a solution.

Solution 5

The solution of the exercise that has not been printed.

Solution 11

Try to fill in these blanks. All of them are created by using the `\blank` command.

Answers to the Problems

Answer 1 *My subtitle*

This is the answer to problem 1.


F. Example Documents Coming With This Package

The repository of this package¹³ currently includes 34 example documents demonstrating how different aspects of this package work or how different kinds of problems can be solved or how different kinds of layouts can be achieved as well as how to solve concrete problems that have come up in different L^AT_EX forums.

Example 1 “blanks” [T_EX] [PDF]

```


1 \documentclass{article}
2 \usepackage[utf8]{inputenc}
3 \usepackage[ngerman]{babel}
4
5 \usepackage{xsim, lipsum, xcolor}
6
7 \xsimsetup{
8   solution/print = true ,
9   blank/filled-style = \underline{\textcolor{red}{#1}}
10 }
```



Example 2 “boxed-headings” [T_EX] [PDF]

```

1 \documentclass{article}
2
3 \usepackage{tcolorbox}
4 \usepackage{xsim}
5 \usepackage{needspace}
6
7 \DeclareExerciseEnvironmentTemplate{custom}
8 {%
9   \Needspace*{5\baselineskip}
10  \begin{tcolorbox}
```



13. GitHub: <https://github.com/cgnieder/xsim/>, CTAN: <http://www.ctan.org/pkg/xsim/>


F. Example Documents Coming With This Package

Example 3 “code-and-output” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsimverb,listings,xcolor}
3
4 \lstdefinestyle{mystyle}{
5   language = [AlLaTeX]TeX ,
6   basicstyle = \ttfamily ,
7   columns = fullflexible ,
8   commentstyle = \color{gray!70} ,
9   keywordstyle = \color{red!70!black}
10 }

```




Example 4 “collections” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim}
3
4 \DeclareExerciseCollection{foo-easy}
5 \DeclareExerciseCollection{foo-medium}
6 \DeclareExerciseTagging{difficulty}
7
8 \usepackage{filecontents,lipsum}
9 \begin{filecontents*}{foo.tex}
10 \begin{exercise}[difficulty=easy,points=1]

```




Example 5 “crossref” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim,lipsum,hyperref}
3
4 \DeclareExerciseHeadingTemplate{custom}
5   {\section{\XSIMtranslate{default-heading}}}
6
7 \DeclareExerciseEnvironmentTemplate{custom}
8   {%
9     \IfInsideSolutionTF
10      {\label{sol:\ExerciseID}}

```




F. Example Documents Coming With This Package

Example 6 “description-list” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim,lipsum}
3
4 \DeclareExerciseEnvironmentTemplate{item}
5   {\item[\XSIMmixedcase{\GetExerciseName}~\
6     GetExerciseProperty{counter}]}
7   {}
8 \xsimsetup{
9   exercise/template=item,
10  solution/template=item,
11  print-solutions/headings-template=none

```




Example 7 “different-point-types” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim}
3
4 \DeclareExerciseGoal{A}
5 \DeclareExerciseGoal{C}
6 \DeclareExerciseGoal{E}
7
8 \newcommand*\printA{\TotalExerciseGoal{A}{~A~point}{~A~
9   points}}
10 \newcommand*\printC{\TotalExerciseGoal{C}{~C~point}{~C~
11   points}}
12 \newcommand*\printE{\TotalExerciseGoal{E}{~E~point}{~E~
13   points}}

```




Example 8 “difficulties” [T_EX] [PDF]

```

1 \documentclass{article}
2
3 \usepackage[clear-aux]{xsim}
4 \DeclareExerciseTagging{difficulty}
5 \xsimsetup{
6   difficulty={easy,hard}
7 }
8
9 \DeclareExerciseEnvironmentTemplate{custom}
10 {

```




F. Example Documents Coming With This Package

Example 9 “hints” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/224408/
2 \documentclass{article}
3 \usepackage{xsim}
4
5 \usepackage{needspace}
6
7 \DeclareExerciseProperty{hint}
8
9 % we'll use a description list for the hints:
10 \newcommand\printhints{%

```




Example 10 “floating” [T_EX] [PDF]

```

1 % floating exercises:
2 \documentclass{article}
3 \usepackage{xsim,newfloat,caption,lipsum}
4
5 \DeclareFloatingEnvironment[
6   fileext=loe,
7   listname={List of Exercises},
8   name=Exercise,
9   placement=htp,
10 ]{ex}

```




Example 11 “grade-distribution” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim}
3
4 \xsimsetup{grades/split=;}
5
6 \DeclareGradeDistribution{
7   1 = 1 ;
8   1,5 = .9167 ;
9   2 = .8333 ;
10  2,5 = .75 ;

```




F. Example Documents Coming With This Package

Example 12 “listings” [T_EX] [PDF]

```

1 % http://tex.stackexchange.com/questions/131546/
2 \documentclass{article}
3
4 \usepackage{xcolor}
5 \usepackage{listings}
6 \usepackage{xsim}
7
8 \lstset{
9   frame=single,
10  xleftmargin=20pt,

```




Example 13 “multiplechoice” [T_EX] [PDF]

```

1 \documentclass{scrartcl}
2 \usepackage[clear-aux]{xsim}
3
4 \usepackage{enumitem,amssymb,fmtcount}
5 \newlist{choices}{itemize}{1}
6 \setlist[choices]{label=$\Box$}
7 \newcommand*\choice{\item}
8
9 \DeclareExerciseProperty{choices}
10 \DeclareExerciseProperty*{multiple}

```




Example 14 “listofexercises” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/94766/
2 \documentclass[a4paper,10pt]{book}
3 \usepackage[utf8]{inputenc}
4
5 \usepackage{xsim}
6 \xsimsetup{
7   exercise/within=chapter,
8   exercise/template=theorem ,
9   exercise/the-counter=\thechapter.\arabic{exercise}
10 }

```




F. Example Documents Coming With This Package

Example 15 “pointsums” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim,lipsum}
3
4 \NewDocumentCommand\printcompletepoints{}{%
5   \TotalExerciseGoals{points + bonus-points}
6   {\,\,\XSIMtranslate{point}}
7   {\,\,\XSIMtranslate{points}}}%
8 }
9
10 \NewDocumentCommand\pointsandbonus{}{%

```




Example 16 “randomexercises” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim}
3
4 \DeclareExerciseCollection{foo}
5
6 \usepackage{filecontents}
7 \begin{filecontents*}{random.tex}
8 \begin{exercise}[ID=A]
9   exercise A
10 \end{exercise}

```




Example 17 “various” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim,lipsum,tcolorbox}
3
4 \DeclareExerciseType{question}{
5   exercise-env = question ,
6   solution-env = hint ,
7   exercise-name = Question ,
8   solution-name = Hint ,
9   exercise-template = default ,
10  solution-template = default ,

```




F. Example Documents Coming With This Package

Example 18 “texsx-13635” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/13635/
2 \documentclass{article}
3 \usepackage{xsim}
4
5 \DeclareExerciseEnvironmentTemplate{theorem:remark}
6 {
7   \par\addvspace{\baselineskip}
8   \noindent
9   \textit{\%
10     \IfInsideSolutionF{\XSIMmixedcase{\%
        GetExerciseName}\~}\%

```




Example 19 “texsx-155630” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/155630/
2 \documentclass{article}
3 \usepackage{xsim}
4
5 \DeclareExerciseCollection{foo}
6
7 \begin{document}
8
9 \collectexercisefoo
10 \begin{exercise}

```




Example 20 “texsx-199360” [T_EX] [PDF]

```

1 % http://tex.stackexchange.com/a/199360/
2 \documentclass{scrartcl}
3 \usepackage[clear-aux]{xsim}
4
5 \usepackage{tcolorbox,blindtext}
6
7 \DeclareExerciseEnvironmentTemplate{custom}
8 {
9   \begin{tcolorbox}[
10     width = \textwidth ,


```



F. Example Documents Coming With This Package


Example 21 “texsx-299534” [T_EX] [PDF]

```
1 % http://tex.stackexchange.com/q/299534/
2 \documentclass{article}
3 \usepackage{pythontex}
4 \usepackage{xsim}
5
6 \begin{document}
7
8 \section{Test}
9
10 \begin{exercise}[subtitle = Codeless Question,points
    =10]
```




Example 22 “texsx-305110” [T_EX] [PDF]

```
1 % https://tex.stackexchange.com/q/305110
2 \documentclass[12pt, a4paper]{book}
3 \usepackage{xsim}
4
5 \xsimsetup{
6   exercise/within = section ,
7   exercise/the-counter = \thesection.\arabic{exercise}
8 }
9
10 \begin{document}
```



Example 23 “texsx-308883” [T_EX] [PDF]

```
1 % https://tex.stackexchange.com/q/308883/
2 \documentclass{article}
3 \usepackage{xsim,siunitx}
4 \xsimsetup{goal-print={\num{#1}}}
5 \sisetup{output-decimal-marker={,}}
6
7 \begin{document}
8
9 \begin{exercise}[points=2.5]
10   foo
```




F. Example Documents Coming With This Package

Example 24 “texsx-338165” [T_EX] [PDF]

```

1 % http://tex.stackexchange.com/q/338165
2 \documentclass{article}
3 \usepackage[T1]{fontenc}
4 \usepackage{leading,microtype}
5 \usepackage[french]{babel}
6
7 \usepackage{tasks}
8 \usepackage{xsim}
9 \usepackage{tcolorbox}
10 \tcuselibrary{breakable, skins}

```




Example 25 “texsx-350028” [T_EX] [PDF]

```

1 % http://tex.stackexchange.com/q/350028/
2 \documentclass{book}
3
4 \usepackage{xsimverb}
5 \usepackage{xsim}
6 \usepackage[most]{tcolorbox}
7 \tcuselibrary{skins,breakable}
8
9 \DeclareExerciseEnvironmentTemplate{tcolorbox}
10 {%

```




Example 26 “texsx-369065” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/369065/
2 \documentclass{article}
3 \usepackage{xsim,tcolorbox,needspace}
4
5 \xsimsetup{
6   exercise/within=section ,
7   exercise/the-counter = \thesection.\arabic{exercise}
8   ,
9   exercise/template=cyan-box ,
10  exercise/name=Example ,
11  solution/template=red ,

```




F. Example Documents Coming With This Package

Example 27 “texsx-369636” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/369686/
2 \documentclass[a4paper,11pt]{article}
3 \usepackage[top=2cm, bottom=3cm, left=4cm, right=4cm]{
  geometry}
4
5 \usepackage[T1]{fontenc}
6 \usepackage{fourier}
7 \usepackage{tgpagella}
8 \usepackage{utf8}{inputenc}
9
10 \usepackage{xsim,needspace,adjustbox,scrextend}

```




Example 28 “texsx-369803” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/369803
2 \documentclass[a4paper,parskip=half]{scrartcl}
3 \usepackage{utf8}{inputenc}
4 \usepackage[ngerman]{babel}
5
6 \usepackage{amsmath}
7 \usepackage{amsthm}
8 \usepackage{amsfonts}
9 \usepackage{amssymb}

```




Example 29 “texsx-370642” [T_EX] [PDF]

```

1 % https://tex.stackexchange.com/q/370642/
2 \documentclass[a4paper,12pt]{article}
3 \usepackage{xsim}
4
5 \DeclareExerciseEnvironmentTemplate{simple}
6 {
7   \par\noindent\textbf{\GetExerciseProperty{counter}}.
8 }
9
10 \xsimsetup{exercise/template=simple}
11
12 \begin{document}

```




F. Example Documents Coming With This Package

Example 30 “texsx-391530” [T_EX] [PDF]

```

1 \documentclass{article}
2 \usepackage{xsim}
3
4 \DeclareExerciseType{subquestion}{
5   exercise-env = question ,
6   solution-env = answer ,
7   exercise-name = Question ,
8   solution-name = Answer ,
9   exercise-template = item ,
10  solution-template = item

```



Example 31 “texwelt-6698” [T_EX] [PDF]

```

1 % http://texwelt.de/wissen/fragen/6698/
2 \documentclass{article}
3 \usepackage[utf8]{inputenc}
4 \usepackage[ngerman]{babel}
5
6 \usepackage{needspace}
7 \usepackage{xsim}
8 \xsimsetup{
9   exercise/name = Aufgabe ,
10  solution/name = Lösung ,

```




Example 32 “texwelt-15093” [T_EX] [PDF]

```

1 % http://texwelt.de/wissen/fragen/15093/
2 \documentclass[paper=a4]{scrartcl}
3 \usepackage[utf8]{inputenc}
4 \usepackage[ngerman]{babel}
5
6 \usepackage{xsim,needspace}
7
8 \DeclareExerciseTagging{AFB}
9 \DeclareExerciseEnvironmentTemplate{myexam}
10 {

```




Example 33 “golatex-16824” [T_EX] [PDF]

```

1 % http://golatex.de/schueler-und-lehrerloesung-im-
  gleichen-texfile-t16824.html
2 \documentclass[fontsize=12pt,parskip=half]{scrartcl}
3 \usepackage[utf8]{inputenc}
4 \usepackage[T1]{fontenc}
5 \usepackage[ngerman]{babel}
6
7 \newlength\breite
8 \setlength\breite{160mm}
9 \newlength\hoehe
10 \setlength\hoehe{80mm}


```

Example 34 “golatex-18844” [T_EX] [PDF]

```

1 % http://golatex.de/aufgabe-loesungs-umgebung-t18844.
  html
2 \documentclass[18pt,a4paper]{article}
3 \usepackage[utf8]{inputenc}
4 \usepackage[ngerman]{babel}
5
6 \usepackage{xsim,tcolorbox}
7 \usepackage{amsmath}
8 \xsimsetup{
9   exercise/within = section ,
10  exercise/the-counter = \thesection.\arabic{exercise}
11  ,

```



G. References

- [Bra16] Johannes BRAAMS, current maintainer: Javier BEZOS.
babel. version 3.9q, Feb. 24, 2016 (or newer).
URL: <http://mirror.ctan.org/macros/latex/required/babel/>.
- [Cha15] François CHARETTE, current maintainer: Arthur REUTENAUER.
polyglossia. version 1.42.0, Aug. 6, 2015 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/polyglossia/>.
- [Fea05] Simon FEAR. booktabs. version 1.61803, Apr. 14, 2005 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/booktabs/>.
- [Flo] Bruno Le FLOCH. *Cunning (La)TeX tricks*.
URL: <http://tex.stackexchange.com/a/19769/> (visited on 03/02/2017).

G. References

- [L3Pa] THE L^AT_EX₃ PROJECT TEAM.
l3kernel. version SVN 6377, Jan. 19, 2016 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/l3kernel/>.
- [L3Pb] THE L^AT_EX₃ PROJECT TEAM.
l3packages. version SVN 6377, Jan. 19, 2016 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/l3packages/>.
- [Leh15] Philipp LEHMAN, current maintainer: Joseph WRIGHT.
etoolbox. version 2.2a, Aug. 2, 2015 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/etoolbox/>.
- [MCo8] Frank MITTELBACH and David CARLISLE.
array. version 2.4c, Sept. 9, 2008 (or newer).
URL: <http://mirror.ctan.org/macros/latex/required/tools/>.
- [Nie15] Clemens NIEDERBERGER. translations. version 1.2e, Nov. 7, 2015 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/translations/>.
- [Nie17] Clemens NIEDERBERGER. exsheets. version 0.21i, Feb. 8, 2017 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/exsheets/>.
- [var] VARIOUS. *Questions tagged ‘exsheets’*.
URL: <http://tex.stackexchange.com/questions/tagged/exsheets> (visited on 05/15/2017).

H. Index

A

`\addbonus` 15
`\addpoints` 15
`\AddtoExerciseGoal` 14 f.
`\AddtoExerciseGoalPrint` 15
`\AddtoExerciseTypeGoal` 14
`\AddtoExerciseTypeGoalPrint` 14
array (package) 2

B

babel (package) 34, 42
`begin-hook` 18 f.
BEZOS, Javier 34, 42
`\blank` 25, 44 ff., 51, 54 f.
`blank-style` 45
`bonus-points` (property) 11, 13, 15, 33 f.
booktabs (package) 2
BRAAMS, Johannes 34, 42

C

CARLISLE, David 2
`chapter` 25
`chapter` (property) 11, 21
`chapter-value` (property) 11
CHARETTE, François 34, 42
`clear-aux` 4, 8, 47
`\collectexercisestop` 20–23, 61
`\collectexercisestype` 20, 22
`collection` 23, 25
`counter` (parameter) 9
`counter` (property) 10, 12, 17, 33 f.
`counter-value` (property) 10, 12
Cunning (La)TeX tricks 34

D

`\DeclareExerciseCollection` .. 20, 56, 60 f.
`\DeclareExerciseEnvironmentTemplate`
35 f., 38, 48, 55 ff., 61, 63 ff.
`\DeclareExerciseGoal` 13, 15, 57
`\DeclareExerciseHeadingTemplate` . 35, 39,

56

`\DeclareExerciseProperty` 12, 48, 58 f.
`\DeclareExercisePropertyAlias` 12
`\DeclareExerciseTableTemplate` .. 35, 39 f.
`\DeclareExerciseTagging` 16, 56 f., 65
`\DeclareExerciseTranslation` 42
`\DeclareExerciseTranslations` 42
`\DeclareExerciseType` .. 8, 10, 17, 37, 60, 65
`\DeclareGradeDistribution` 58

E

`end-hook` 19
equation (environment) 22
etoolbox (package) 2
`exclude` 23
exercise (environment) 5–8, 10, 17
`exercise-env` (parameter) 9 f.
`exercise-name` (parameter) 9 f., 32
`exercise-template` (parameter) 9 f., 35
`\ExerciseCollection` 33
`\ExerciseGoalValuePrint` 14 f.
`\ExerciseID` 32, 56
`\ExerciseParameterGet` 32, 39, 41
`\ExerciseParameterIfSetTF` 32
`\ExercisePropertyGet` 31
`\ExercisePropertyGetAlias` 31
`\ExercisePropertyGlobalSave` 31
`\ExercisePropertyIfSetTF` 31
`\ExercisePropertySave` 31
`\ExerciseSetExpandedProperty` 31
`\ExerciseSetProperty` 31
`\ExerciseTableCode` 39–42
`\ExerciseTableType` 33, 39, 41
`\ExerciseType` 32 f., 39–42
expl3 (package) 2
exsheets (package) 3, 16, 29, 37, 44, 46

F

FEAR, Simon 2
`file-extension` 7
filecontents (environment) 7
`filled-style` 45

INDEX

- final** 4
FLOCH, Bruno Le 34
\ForEachExerciseTag 32
\ForEachExerciseTranslation 42
\ForEachPrintedExerciseByID 33
\ForEachPrintedExerciseByType 33
\ForEachUsedExerciseByID 34
\ForEachUsedExerciseByType 33, 39, 41
- G**
\GetExerciseAliasProperty 13, 31
\GetExerciseBody 30
\GetExerciseIdForProperty 30
\GetExerciseName 32, 36, 38, 48, 57, 61
\GetExerciseParameter 32, 39 f.
\GetExerciseParameterTF 32
\GetExerciseProperty 12 f., 30, 36 ff., 48, 57, 64
\GetExercisePropertyTF 30
\GetExercisePropertyT 36 ff., 48
\GetExerciseTypeForProperty 30
\GlobalSaveExerciseProperty 31
goal-print 14 f.
grading-table (option class) 26, 35
\gradingtable 26 f., 35
- H**
headings 20, 25
headings-template 20, 25, 35
- I**
ID (property) 10, 12, 23
id (property) 10, 12, 19, 23 f., 30
\IfExerciseBooleanPropertyTF 31
\IfExerciseBooleanPropertyT 48
\IfExerciseGoalTF 29
\IfExerciseGoalSingularTF 30
\IfExerciseGoalSingularTF 37 f.
\IfExerciseGoalsSumTF 30
\IfExerciseGoalsSumF 16
\IfExerciseGoalTF 30
\IfExerciseParameterSetTF 32
\IfExercisePropertyExistTF 30
\IfExercisePropertySetTF 30
- L**
l3kernel (bundle) 2
l3packages (bundle) 2
LEHMAN, Philipp 2
line-increment 45
line-minimum-length 45
linespread 45
\ListExerciseTags 32
\loadxsimstyle 49
LPPL 2
- M**
MITTELBACH, Frank 2
- N**
name 18
\NewDocumentEnvironment 51
NIEDERBERGER, Clemens 2 f.
number (parameter) 10
\numberofhAexercise-envfiBs 8
\numberofexercises 8
\numberofusedexercises 33, 41
- P**
page (property) 11, 21
page-value (property) 11
\ParameterValue 32
path 7 f., 47
points (property) 10, 13, 15, 33 f.
\points ... 8, 12, 15 f., 36–41, 48, 56 f., 60, 62
polyglossia (package) 34, 42
post-hook 19
pre-hook 18 f.
print 6, 18 ff., 23, 33
print (property) 11, 21
print-collection (option class) 21, 35
- \IfExercisePropertySetT** 38, 48
\IfExerciseTypeGoalsSumTF 30
\IfExistSolutionTF 33
\IfInsideSolutionTF 33
\IfInsideSolutionF 36 ff., 48, 61
\IfInsideSolutionTF 56
\IfPrintSolutionTF 33
ignore-untagged 16

INDEX

- `print-solutions` (option class) 25, 35
- `print!` (property) 11, 17
- `\printallsolutions` 24
- `\printbonus` 15
- `\printcollection` 20 ff., 35, 52
- `\printexercise` 19
- `\printgoal` 14, 36 ff., 40 f.
- `\printpoints` 14
- `\printrandomexercises` 23 f.
- `\printsolution` 24, 26
- `\printsolutions` 24 f., 35, 50
- `\printsolutionstyle` 24, 35
- `\printtotalbonus` 15
- `\printtotalpoints` 14
- `\PropertyValue` 30, 36 ff., 48

- Q**
- Questions tagged ‘exsheets’* 3

- R**
- REUTENAUER, Arthur 34, 42

- S**
- `\SaveExerciseProperty` 31
- `scale` 45
- `section` 25
- `section` (property) 11, 21
- `section-value` (property) 11
- `sectioning` (property) 12
- `\SetExerciseParameter` 10, 18
- `\SetExerciseParameters` 10
- `\SetExerciseProperty` 31
- `\SetExpandedExerciseProperty` 31
- `solution` (environment) 5 f., 8
- `solution-counter` (parameter) 9
- `solution-env` (parameter) 9
- `solution-name` (parameter) 9 f., 32
- `solution-template` (parameter) 9 f., 35
- `sort` 23
- `style` 45
- style file 29, 49
- `subtitle` (property) 10, 33 f.

- T**
- `tags` 16
- `tags` (property) 11, 16
- `template` 18, 26, 35
- THE L^AT_EX₃ PROJECT TEAM 2
- `the-counter` 18
- `topics` 16
- `topics` (property) 11, 16
- `\TotalExerciseGoal` 14 ff., 30, 40 f., 57
- `\TotalExerciseGoals` 14 f., 60
- `\TotalExerciseTypeGoal` 14 f., 30, 40 f.
- `\TotalExerciseTypeGoals` 14
- translations (package) 2
- `type` 26 f.
- `type` (property) 30

- U**
- `use` 18
- `use` (property) 11, 17, 21
- `use!` (property) 11, 17
- `used` (property) 11, 21
- `\UseExerciseTags` 32
- `\UseExerciseTemplate` 32

- V**
- VARIOUS 3
- `verbose` 4

- W**
- `width` 45 f.
- `within` 18
- WRIGHT, Joseph 2

- X**
- xparse (package) 2, 51
- `\XSIMexpandcode` 34, 40
- `\XSIMfilewritestart` 51 f.
- `\XSIMfilewritestop` 51 f.
- `\XSIMgobblechars` 51
- `\XSIMifblankTF` 34
- `\XSIMifblankTF` 39–42
- `\XSIMifchapterTF` 34
- `\XSIMifeqTF` 34
- `\XSIMifeqF` 41
- `\XSIMifeqTF` 39, 41
- `\XSIMmixedcase` 34, 36, 38–41, 48, 57, 61
- `\XSIMputright` 34, 39 ff.

INDEX

<code>\XSIMsetfilebegin</code>	51 f.	<code>\xsimstyle</code>	49
<code>\XSIMsetfileend</code>	51 f.	<code>\XSIMtranslate</code> 9, 15 f., 34, 36–42, 48, 56, 60	
<code>\xsimsetup</code> 4 ff., 10, 16, 21 ff., 25 f., 45, 48, 52,		<code>xsimverb</code> (package).....	51
55, 57 ff., 62–66			