

XSIM

vo.1pre-9 2017/03/10

eXercise Sheets IMproved

Clemens NIEDERBERGER

<https://github.com/cgnieder/xsim>

contact@mychemistry.eu

Table of Contents

1. Licence, Requirements and README	2	8.3. (Re-)Inserting a Certain Exercise	15
2. Motivation and Background	2	9. Collecting Exercises	15
3. How to Read the Manual	3	9.1. Background	15
3.1. Nomenclature	3	9.2. Usage	15
3.2. Package Options	3	10. Printing Solutions	18
3.3. Setting Options	4	11. Grading Tables	19
3.4. Command descriptions	4	12. Styling the Exercises – Templates	21
4. Exercises and Solutions	5	12.1. Background	21
5. How the Exercise Environments Work	6	12.2. Commands for Usage in Template Definitions	21
6. New Exercise Types	7	12.2.1. Goals	21
7. Exercise Properties	9	12.2.2. Properties	22
7.1. Predefined Properties	9	12.2.3. Parameters	23
7.2. Declaring Own Properties . .	10	12.2.4. Tags	23
7.3. A Special Kind of Property: Exercise Goals	11	12.2.5. Further Commands for Usage in Template Definitions	23
7.4. A Special Kind of Property: Exercise Tags	12	12.3. Declaring Templates	25
8. Using and Printing an Exercise	13	12.3.1. Environment Templates	25
8.1. What the Environments do . .	13	12.3.2. Heading Templates . .	25
8.2. Environment Options & Hooks	13	12.3.3. Grading Table Templates	26
		12.4. Examples	26
		12.4.1. The default Exercise Template	26

1. Licence, Requirements and README

12.4.2.	A New Exercise Type Using tcolorbox	26	A.2.	...Resolve Getting Repeatedly Wrong Exercise Properties or Wrong Exercise Lists?	36
12.4.3.	Mimicking exsheets' runin Template	28	A.3.	...Resolve Strange Errors Af- ter Updating?	36
12.4.4.	Mimicking exsheets' margin Template	29	A.4.	...Print All Solutions Grouped by Section?	36
12.4.5.	The Headings Templates	30			
12.4.6.	The default Table Template	30	B.	The xsimverb package	37
12.4.7.	The default* Table Template	31	C.	All Exercise Examples	39
13.	Exercise Translations	33	D.	All Solution Examples	41
14.	Other Commands	36	E.	References	41
A.	How to...	36	F.	Index	42
A.1.	...Know if xSIM Needs An- other Compilation?	36			

1. Licence, Requirements and README

Permission is granted to copy, distribute and/or modify this software under the terms of the L^AT_EX Project Public License (LPPL), version 1.3 or later (<http://www.latex-project.org/lppl.txt>). The software has the status “maintained.”

xSIM loads the packages expl3 [L3Pa], xparse [L3Pb], etoolbox [Leh15], booktabs [Fea05] and translations [Nie15]. All of these packages are present on a modern and up to date T_EX distribution such as T_EX Live or MiK_TE_X so no further action should be needed.

2. Motivation and Background

It has been quite a while since I first published exsheets [Nie17] in Juni 2012. Since then it has gained a user base and a little bit of popularity as the number of questions on tex.sx shows (99 at the time of writing) [var]. User questions, bug reports and feature requests improved it over the time. It still has a version number starting with a zero, though, which in my versioning system means I still consider it experimental.

This is due to several facts. It lacks a few features which I consider essential for a full version 1. For one thing it is not possible to have several kinds of exercises numbered independently. Using verbatim material such as listings inside exercises and solutions is not possible and the current workaround isn’t that ideal either. One request which dates back quite a while now was to have different types of points to exercises...

All of those aren’t easy to add due to the way exsheets is implemented right now. As a consequence I wanted to re-implement exsheets for a long time. This is what lead to **xSIM**. Internally the package works completely different.

xSIM will be the official successor of exsheets which is now considered obsolete but will stay alive and will still receive bugfix releases. However, new features will not be added to exsheets any more.

3. How to Read the Manual

3.1. Nomenclature

Throughout this manual certain terms are used. This section explains their meaning in this manual.

collection A *collection* bundles a number of exercises of one type or all types of exercises within certain barriers in the document. Those exercise collections can be printed at any place in the document.

goal *Goals* are a certain type of properties with a numerical value the sum of which is available throughout the document.

parameter *Parameters* are options of exercise types which are the same for each exercise of a type and can be retrieved and used in exercise templates.

property *Properties* are options of exercises which are individual for each exercise and can be retrieved and used in exercise templates.

tag *Tags* are a certain type of properties with a csv list as value which can be used for selective usage of exercises.

template *Templates* are generic code frameworks which are used for typesetting **xSIM**'s objects such as exercises, solutions, or grading tables.

3.2. Package Options

xSIM has two package options:

verbose

Writes extensive information about what **xSIM** is doing into the log file.

final

If used the exercise and solution environments will not rewrite the environment body files.

Those options are used the usual way as package option

```
\usepackage[verbose]{xsim}
```

or as global option

```
1 \documentclass[verbose]{article}
```

or via the setup command:

```
\xsimsetup{<options>}
```

Set up **xsim**'s two package options and all other options described at other places in the manual.

3.3. Setting Options

Apart from the package options already described in section 3.2 on the preceding page **xsim** has further options. Those can be “toplevel” options or options belonging to a module.

```
toplevel = {<value>}
```

A topLevel option.

```
module » sublevel = {<value>} A sublevel option belonging to the module module
```

Both kinds of options are set with `\xsimsetup`:

```
1 \xsimsetup{
2   topLevel = {value} ,
3   module/sublevel = {value}
4 }
```

3.4. Command descriptions

Some commands do have a ***** symbol printed next to their names. This indicates that the command is expandable, *i. e.*, it is usable in an `\edef` or `\write` context and will expand according to its description. All other commands are engine protected, *i. e.*, in the sense of ϵ -TeX's `\protected`.

Some command name descriptions end with `\TF`.

```
\SomeCommandTF<arguments>{<true>}{<false>}
```

A command with maybe some arguments and ending with the two arguments `<true>` and `<false>`.

This means two things: the command is a conditional which tests something and depending on the outcome of the test leaves either the `<true>` argument (T) or the `<false>` argument (F) in the input stream. It also means to additional commands exist:

```
\SomeCommandT<arguments>{<true>}
```

The same as `\SomeCommandTF` but only with the `<true>` argument and no `<false>` argument.

```
\SomeCommandF<arguments>{<false>}
```

The same as `\SomeCommandTF` but only with the `<false>` argument and no `<true>` argument.

4. Exercises and Solutions

The two predefined environments for exercises and solutions are the following ones:

`\begin{exercise}[\langle properties \rangle]`

Input and typeset an exercise. See section 7 on page 9 for details on exercise properties.

`\begin{solution}[\langle options \rangle]`

Input and typeset the solution to the exercise of the previous exercise environment. See section 10 on page 18 for details on options of solutions.

```

1 \begin{exercise}
2   A first example for an exercise.
3 \end{exercise}
4 \begin{solution}
5   A first example for a solution.
6 \end{solution}

```

Exercise 1

A first example for an exercise.

As can be seen in the example a solution is not printed with the default setup. This can be changed using the following option.

`solution » print = true|false`

Default: false

Set if solutions are printed or not.

The option (belonging to the module `solution`) can either be set locally as option to the solution environment

```

1 \begin{solution}[print=true]
2   A first example for a solution.
3 \end{solution}

```

or with the setup command for all following solutions:

```

1 \xsimsetup{
2   solution/print = true
3 }

```

There is an completely analogous option for the exercise environment:

`exercise » print = true|false`

Default: true

Set if exercises are printed or not.

More details on those two environments can be found in section 8 on page 13.

5. How the Exercise Environments Work

Both environments write the contents of their bodies verbatim to external files following a certain naming structure:

- `\jobname\<type>\<id>-exercise|solution-body.tex`

The name starts with the name of the job (which is the name of the document itself) followed by type and id of the corresponding exercise and then followed by the environment type. For example both environments from the first example have been written to files named

- `xsim_manual-exercise-1-exercise-body.tex` and
- `xsim_manual-exercise-1-solution-body.tex`, respectively.

Details on the `\type` of an exercise will be given in section 6 on the following page. *The `\id` of an exercise is a positive integer unique to each exercise environment regardless if the exercise is being printed or used at all.*

These external files are input when the respective exercise or solution is printed. An advantage of using external files is that *verbatim material is allowed* inside the environments. Each of those files contains some information about itself and where and why it was generated¹:

```

1 % -----
2 % file `xsim_manual-exercise-1-exercise-body.tex'
3 %   in folder `exercises/'
4 %
5 %       exercise of type `exercise' with id `1'
6 %
7 % generated by the `exercise' environment of the
8 %   `xsim' package v0.1pre-9 (2017/03/10)
9 % from source `xsim_manual' on 2017/03/10 on line 1
10 % -----
11 A first example for an exercise.
```

Arguably one downside of the approach using external files for each exercise and its solution is that your project folder will be cluttered with files. In order to deal with this somehow **xsim** offers the following option:

`path = {\path name}` (initially empty)

With this option a subfolder or path within the main project folder can be given. Exercises will be written to and included from this path. *The path must exist on your system before you can use it!* This document uses `path = {exercises}`.

1. In this example the sourcecode line number is misleading as the example where the file was generated itself was an external file where the exercise environment indeed was on line 1.

XSIM writes a lot of stuff to the auxfile for re-using information on subsequent compilations. If you add exercises, change properties *etc.* it might happen that wrong information is staying in the auxfile and is wrongly used by **XSIM**. In such cases deleting the auxfile and doing a few fresh compilations may resolve your problems.

Sometimes the existing of exercise or solution files from earlier compilations may lead to wrong lists of exercises or solutions. In such cases it can be useful to delete all those files and doing a fresh compilation. It may be helpful to use a subfolder for those external files which will make deleting them a little bit easier. (Don't forget to both create the subfolder and set **path** accordingly then.)

6. New Exercise Types

It is easy to define new exercise environments together with a corresponding solution environment using the following command:

\DeclareExerciseType{*<type>*}{*<parameters>*}

Declare a new exercise type analogous to the exercise and solution environments.

Declaring a new exercise type will also define a new command:

\numberof*<exercise-env>*s

These commands hold the absolute number of used exercises of type *<type>*. The meaning of *<exercise-env>* will become clear below when the exercise parameters are explained. It is always the same as the exercise environment name.

```
1 There are \numberofexercises~exercises and \numberofproblems~problem in this
2 manual.
```

There are 8 exercises and 1 problem in this manual.

XSIM's pre-defined environment pair has been defined as follows:

```
1 \DeclareExerciseType{exercise}{
2   exercise-env      = exercise ,
3   solution-env      = solution ,
4   exercise-name     = \XSIMtranslate{exercise} ,
5   solution-name     = \XSIMtranslate{solution} ,
6   exercise-template = default ,
7   solution-template = default
8 }
```

The above already is an example for almost all parameters that can (and often must) be set. Here is the complete list:

6. New Exercise Types

`exercise-env` = $\{\langle exercise\ environment\ name \rangle\}$

The name for the environment used for the exercises of type $\langle type \rangle$. *This parameter is mandatory.* It can't be changed afterwards.

`solution-env` = $\{\langle solution\ environment\ name \rangle\}$

The name for the environment used for the solutions of type $\langle type \rangle$. *This parameter is mandatory.* It can't be changed afterwards.

`exercise-name` = $\{\langle exercise\ name \rangle\}$

The name of the exercises of type $\langle type \rangle$ – used for typesetting. *This parameter is mandatory.*

`solution-name` = $\{\langle solution\ name \rangle\}$

The name of the solutions of type $\langle type \rangle$ – used for typesetting. *This parameter is mandatory.*

`exercise-template` = $\{\langle exercise\ template \rangle\}$

The template used for typesetting the exercises of type $\langle type \rangle$. *This parameter is mandatory.* See section 12 on page 21 for details on templates.

`solution-template` = $\{\langle solution\ template \rangle\}$

The template used for typesetting the exercises of type $\langle type \rangle$. *This parameter is mandatory.* See section 12 on page 21 for details on templates.

`counter` = $\{\langle counter\ name \rangle\}$

The counter used for the exercises of type $\langle type \rangle$. If not explicitly set the counter with the same name as `exercise-env` is used. Otherwise the specified counter is used. This enables to have different types of exercises sharing a common counter.

`number` = $\{\langle integer \rangle\}$

An internal parameter that is used to keep track of the number of exercises of a type. This parameter cannot be set or changed by the user.

It is possible to change some of the parameters after an exercise type has been defined. Those include `exercise-name`, `solution-name`, `exercise-template`, `solution-template`, and `counter`:

`\SetExerciseParameter` $\{\langle type \rangle\}\{\langle parameter \rangle\}\{\langle value \rangle\}$

Usable to set a single parameter to a new value.

`\SetExerciseParameters` $\{\langle type \rangle\}\{\langle parameters \rangle\}$

Set several parameters at once. $\langle parameters \rangle$ is a csv list of key/value pairs.

If you try to set an already set but fixed parameter like `exercise-env` a warning will be written to the log file. If you set `counter` to another value you must make sure that the new value is a valid and defined counter.

7. Exercise Properties

7.1. Predefined Properties

Exercise like the exercise environment and possibly others defined with `\DeclareExerciseType` have a number of predefined properties:

`id = {\langle integer \rangle}`

Holds the internal id of an exercise. *Cannot be set by the user.*

`ID = {\langle text \rangle}`

Holds the user id of an exercise if defined. Otherwise it is equal to `id`.

`counter = {\langle integer \rangle}`

Holds the counter value of an exercise. *Cannot be set by the user.*

`subtitle = {\langle text \rangle}`

Holds the subtitle of an exercise.

`points = {\langle number \rangle}`

Holds the reachable points of an exercise.

`bonus-points = {\langle number \rangle}`

Holds the reachable bonus-points of an exercise.

`print = true|false`

Holds the print boolean of an exercise.

`use = true|false`

Holds the usage boolean of an exercise.

`tags = {\langle csv list of tags \rangle}`

Holds the list of tags the exercise should be associated with.

`topics = {\langle csv list of topics \rangle}`

Holds the list of topics the exercise should be associated with.

Some of these properties are fixed and cannot be set by the user. Those include `id` and `counter`. The others can be set using the optional argument of the exercise environment.

```

1 \begin{exercise}[subtitle={This is a subtitle},points=4,bonus-points=1]
2   An exercise where some properties have been set.
3 \end{exercise}
```

Exercise 2 *This is a subtitle*

An exercise where some properties have been set.

4 (+1) p.

7.2. Declaring Own Properties

XSIM offers the possibility to declare additional exercise properties:

\DeclareExerciseProperty*{⟨property⟩}

Declares the property ⟨property⟩. If used with the optional star a unique property is defined which means that each exercise must have a property value distinct from all other exercises (all means all – *independent from the exercise type*).

\DeclareExercisePropertyAlias{⟨property 1⟩}{⟨property 2⟩}

Declares ⟨property 1⟩ to be an alias of ⟨property 2⟩. This means that each time ⟨property 2⟩ is set ⟨property 1⟩ will be set to the same value *unless* it has been set already. As an example: property **ID** is an alias of property **id**.

This is better demonstrated with an example:

```

1 \begin{exercise}
2   \lipsum[4] % from package `lipsum'
3   \verb+\GetExerciseProperty{id}+: \GetExerciseProperty{id} \par
4   \verb+\GetExerciseAliasProperty{ID}+: \GetExerciseAliasProperty{ID} \par
5   \verb+\GetExerciseProperty{ID}+: \GetExerciseProperty{ID}
6 \end{exercise}
7 \begin{exercise}[ID=foo-bar]
8   \lipsum[4]
9   \verb+\GetExerciseProperty{id}+: \GetExerciseProperty{id} \par
10  \verb+\GetExerciseAliasProperty{ID}+: \GetExerciseAliasProperty{ID} \par
11  \verb+\GetExerciseProperty{ID}+: \GetExerciseProperty{ID}
12 \end{exercise}

```

Exercise 3

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

\GetExerciseProperty{id}: 3

\GetExerciseAliasProperty{ID}: 3

\GetExerciseProperty{ID}: 3

Exercise 4

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum

wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

`\GetExerciseProperty{id}: 4`

`\GetExerciseAliasProperty{ID}: 4`

`\GetExerciseProperty{ID}: foo-bar`

The power of properties will get more clear when reading section 12 on page 21 about templates.

7.3. A Special Kind of Property: Exercise Goals

Exercise goals are a generic concept in **xsim** for exercise properties like **points** or **bonus-points**. Those are properties which can (only) get a decimal number as value the sum of which is calculated and available (after a compilation) throughout the document.

`\DeclareExerciseGoal{<goal>}`

Declare a new exercise goal named `<goal>` and also a property called `<goal>`.

`\TotalExerciseTypeGoal{<type>}{<goal>}{<singular>}{<plural>}`

Get the sum of goal `<goal>` for all exercises of type `<type>`. `<singular>` and `<plural>` are placed after the sum in the input stream depending on whether the sum equals 1 or not.

`\TotalExerciseGoal{<goal>}{<singular>}{<plural>}`

Get the sum of goal `<goal>` for all exercises. `<singular>` and `<plural>` are placed after the sum in the input stream depending on whether the sum equals 1 or not.

`\printpoints{<type>}`

Print the sum of points for all exercises of type `<type>` followed by an appropriate translation of the words “point” or “points”, respectively.² Defined in terms of `\TotalExerciseTypeGoal`.

`\printtotalpoints`

Print the sum of points for all exercises followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of `\TotalExerciseGoal`.

`\printbonus{<type>}`

Print the sum of bonus points for all exercises of type `<type>` followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of `\TotalExerciseTypeGoal`.

`\printtotalbonus`

Print the sum of bonus points for all exercises followed by an appropriate translation of the words “point” or “points”, respectively. Defined in terms of `\TotalExerciseGoal`.

The two existing goals are defined with

². See section 13 on page 33 for details on the definition and usage of language dependent words.

```

1 \DeclareExerciseGoal{points}
2 \DeclareExerciseGoal{bonus-points}

```

When goal values are printed the decimal number is fed to a function which can be changed using the following option:

`goal-print = {⟨code⟩}`

Default: #1

How to format goal values. Use #1 to refer to the actual number.

7.4. A Special Kind of Property: Exercise Tags

Exercise tags are a generic concept in **XSIM** for exercise properties like **tags** or **topics**. Those are properties which can (only) get a csv list of strings as value. Those strings can be used to selectively use exercises. See section 8 on the next page for details on *usage* of exercises and the difference to *printing* an exercise and how to use exercise tags for selection.

`\DeclareExerciseTagging`

`tag` This defines an exercise tagging group name `⟨tag⟩`. It also defines a property named `⟨tag⟩`. In addition to options it defines: and option named `⟨tag⟩` which can be used for selection and an boolean option `⟨tag⟩/ignore-untagged`.

The two existing tagging groups have been defined and preset with the following code:

```

1 \DeclareExerciseTagging{tags}
2 \DeclareExerciseTagging{topics}
3 \xsimsetup{tags/ignore-untagged=false}

```

this means that these options are available:

`tags = {⟨csv list of tags⟩}`

Choose the set of tags whose associated exercises should be printed.

`topics = {⟨csv list of topics⟩}`

Choose the set of tags whose associated exercises should be printed.

`tags » ignore-tagging = true|false`

Default: false

If set to true exercises with no tags will be printed even if tags have been chosen with the option `tags`.

`topics » ignore-tagging = true|false`

Default: true

If set to true exercises with no topics will be printed even if tags have been chosen with the option `tags`.

8. Using and Printing an Exercise

8.1. What the Environments do

When an exercise is started with `\begin{exercise}` (or other environments defined through `\DeclareExerciseType`) then different things happen depending on different settings:

- If the *insert mode* is active nothing happens, see section 9 on page 15 for details on this.
- Else the id integer is incremented.
- If the exercise is *used* the corresponding counter is stepped and the exercise is added to the “use list”. The properties `counter` and `use` are updated accordingly.
- If an exercise is printed then it is also used. An exercise that isn’t used cannot be printed. Being printed means two things: being added to the “print list” and being typeset at the position where the exercise is placed in the source file. If an exercise is *not printed but used* it means that the counter will be stepped. This can be useful for creating an exercise sheet only containing the solutions for some exercises.
- If an exercise is printed certain hooks and template code is inserted around the environment body.

```

1 \begin{exercise}[print=false]
2   This exercise will not be printed but the exercise counter will be
3   incremented nonetheless. Its solution will be printed in the list of
4   solutions.
5 \end{exercise}
6 \begin{solution}
7   The solution of the exercise that has not been printed.
8 \end{solution}

```

The schematic structure of an exercise is shown in figure 1 on the next page.

8.2. Environment Options & Hooks

For each exercise type there are the following options for both environments, the environments’ names are the module names for the options (here using the “exercise” type):

`exercise` » `print = true|false` Default: true
 Determines if exercises of type “exercise” are printed.

`exercise` » `use = true|false` Default: true
 Determines if exercises of type “exercise” are used.

8. Using and Printing an Exercise




FIGURE 1: Schematic structure of an exercise or solution.

`exercise` » `within = {⟨counter⟩}` (initially empty)
 Adds the exercise counter to the reset list of the counter `⟨counter⟩`. *Beware that if the counter is a shared counter this will affect all objects using this counter!*

`exercise` » `pre-hook = {⟨code⟩}` (initially empty)
 The code for the *pre exercise hook* for exercises of the type “exercise”.

`exercise` » `begin-hook = {⟨code⟩}` (initially empty)
 The code for the *begin exercise hook* for exercises of the type “exercise”.

`exercise` » `end-hook = {⟨code⟩}` (initially empty)
 The code for the *end exercise hook* for exercises of the type “exercise”.

`exercise` » `post-hook = {⟨code⟩}` (initially empty)
 The code for the *post exercise hook* for exercises of the type “exercise”.

`solution` » `print = true|false` Default: false
 Determines if solutions of type “exercise” are printed.

`solution` » `pre-hook = {⟨code⟩}` (initially empty)
 The code for the *pre solution hook* for solutions of the type “exercise”.

`solution` » `begin-hook = {⟨code⟩}` (initially empty)
 The code for the *begin solution hook* for solutions of the type “exercise”.

`solution` » `end-hook = {⟨code⟩}` (initially empty)
 The code for the *end solution hook* for solutions of the type “exercise”.

`solution` » `post-hook = {⟨code⟩}` (initially empty)
 The code for the *post solution hook* for solutions of the type “exercise”.

8.3. (Re-)Inserting a Certain Exercise

If you know type and `id` of an exercise you can (re-)insert every existing exercise, *i. e.*, every exercise whose external file exists.

`\printexercise{⟨type⟩}{⟨id⟩}`

Inserts the exercise of type `⟨type⟩` with the `id` `⟨id⟩`.

```
1 \printexercise{exercise}{5}
```

Exercise 5

This exercise will not be printed but the exercise counter will be incremented nonetheless. Its solution will be printed in the list of solutions.

9. Collecting Exercises

9.1. Background

XSIM knows the concept of “exercise collections”. A collection of exercises can be useful when you want to print a certain group of exercises several times. Each collection must have a unique name with which you can refer to the corresponding collection. A collection is realized by declaring the collection and by surrounding the exercises belonging to the collection with a certain pair of commands (this is explained in the next section).

Let’s say you have several files of math exercises where one only contains geometry exercises and another only calculus exercises and so on. Surrounding the `\input` of each file with said pair of commands for a certain collection all exercises of the corresponding file now are a collection which then can be printed at once wherever you want the collection of exercises to be printed. By choosing certain tags (see section 7.4 on page 12) inside each collection you could even cherry-pick exercises from the external file.

9.2. Usage

A collection must be declared in the preamble. Using a pair of commands explained below exercises between those commands are added to the corresponding collection but not printed. After a collection is completed the collection can be printed as often as needed.

`\DeclareExerciseCollection{⟨collection name⟩}`

Define a new collection `⟨collection name⟩` in the document preamble.

`\collectexercisetype{⟨collection name⟩}{⟨exercise type⟩}`

Opens the collection `⟨collection name⟩` which now collects all exercises of type `⟨exercise type⟩` until the collection is closed with `\collectexercisestop`. Collections of other types are not collected. *This command starts a group!*

9. Collecting Exercises

`\collectexercises{⟨collection name⟩}`

Opens the collection `⟨collection name⟩` which now collects all exercises until the collection is closed with `\collectexercisesstop`. *This command starts a group!*

`\collectexercisesstop{⟨collection name⟩}`

Closes the collection `⟨collection name⟩`. *This command ends a group!*

`\printcollection[⟨options⟩]{⟨collection name⟩}`

Prints the collection `⟨collection name⟩`, i. e., all exercises collected earlier. This command cannot be used before the corresponding collection has been closed correctly.

Valid options are the following:

`headings = true|false`

Default: false

If true a heading for each exercise type is inserted.

`headings-template = {⟨template⟩}`

Default: collection

The heading template used when `headings = {true}`.

Those options can also be set via `\xsimsetup` using the module `print-collection`.

The usage should be clear:

```
1 \collectexercises{foo}
2 \begin{exercise}
3   This exercise is added to the collection 'foo'.
4 \end{exercise}
5 \collectexercisesstop{foo}
```

Once the collection is closed it can be printed:

```
1 \printcollection{foo}
```

Exercise 6

This exercise is added to the collection 'foo'.

Actually a collection can be printed *before* it is opened, too. This needs at least two compilations, though.

You can open several collections at the same time:

```
1 \collectexercises{foo}
2   ...
3 \collectexercisestype{bar}{exercises}
4   ...
```


9. Collecting Exercises

```
5 \collectexercisesstop{bar}
6 ...
7 \collectexercisesstop{foo}
```

Exercises will be added to each open collection.

There is one generic collection called “all exercises”. As the name already suggests it will hold all exercises. So if you say

```
1 \printcollection{all exercises}
```

all exercises will be printed.

If you use `\labels` inside of exercises and you print exercises more than once in your document (by reusing a collection for example) you will get

```
1 LaTeX Warning: There were multiply-defined labels.
```

Equally if you have environments like `\begin{exercise}` which step a counter inside an exercise or solution the counter will be stepped each time the exercise is used.

At last now an example using external files, collections and tags:

```
1 % preamble:
2 % \DeclareExerciseCollection{foo-easy}
3 % \DeclareExerciseCollection{foo-medium}
4 % \DeclareExerciseTagging{difficulty}
5
6 % document:
7 \collectexercises{foo-easy}
8 \xsimsetup{difficulty=easy}
9 \input{foo.tex}
10 \collectexercisesstop{foo-easy}
11 % collection `foo-easy' now contains all exercises of file `foo.tex' tagged
12 % with `difficulty=easy'
13
14 \collectexercises{foo-medium}
15 \xsimsetup{difficulty=medium}
16 \input{foo.tex}
17 \collectexercisesstop{foo-medium}
18 % collection `foo-medium' now contains all exercises of file `foo.tex'
19 % tagged with `difficulty=medium'
```

10. Printing Solutions

There are two commands for printing the solutions to exercises – one for printing the solutions of a specific exercise type and another for printing all solutions.

`\printsolutionstype*[\langle options \rangle]{\langle exercise type \rangle}`

Prints the solutions of all used exercises of type $\langle exercise type \rangle$. The starred version only prints the solutions of all printed exercises of type $\langle exercise type \rangle$.

`\printsolutions*[\langle options \rangle]`

Prints the solutions of all used exercises of all types. The starred version only prints the solutions of all printed exercises of all types, ordered by type.

`\printsolution[\langle options \rangle]{\langle type \rangle}{\langle id \rangle}`

Prints the solution of the exercise of type $\langle type \rangle$ with the `id` $\langle id \rangle$.

```
1 \printsolutionstype{exercise}
```

Solutions to the Exercises

Solution 1

A first example for a solution.

Solution 5

The solution of the exercise that has not been printed.

The options can be divided into two groups. The ones in the first group modify the layout.

`headings = true|false`

Default: `true`

If `true` a heading for each exercise type is inserted.

`headings-template = {\langle template \rangle}`

Default: `default`

The heading template used when `headings = {true}`.

The ones in the second group set conditions selecting which solutions are printed. If you combine those conditions a solution is printed if it meets either of the conditions.

`section = true|false|\langle integer \rangle`

Default: `false`

If you set `section = {true}` only solutions of exercises of the current section are printed. If you set `section = {4}` only solutions of exercises in a section with number 4 are printed.

`chapter = true|false|\langle integer \rangle`

Default: `false`

If you set `chapter = {true}` only solutions of exercises of the current chapter are printed. If you set `chapter = {4}` only solutions of exercises in a chapter with number 4 are printed.

11. Grading Tables

`collection = false|⟨collection name⟩` Default: `false`
If used only solutions of exercises belonging to collection `⟨collection name⟩` are printed.

The selection per section or per chapter relies on the *counter numbers* of the sections or chapters, respectively. This means if section numbers are reset (e. g. by `\chapter` or `\appendix`) and you have exercises from *different* sections with *the same section number* the solutions of *all those exercises* will be printed. This means you only should use the `section` selection when section are the top document level headings (apart from parts) and you have no exercises in the appendix. Similar considerations are valid for the `chapter` selection.

All options can also be set via `\xsimsetup` using the module `print-solutions`.

```
1 \printsolutions[section=4,headings-template=per-section]
```

Solutions to the Exercises of Section 4

Solution 1

A first example for a solution.

```
1 \printsolution{exercise}{5}
```

Solution 5

The solution of the exercise that has not been printed.

11. Grading Tables

When you create exercises it may not only be desirable to be able to add points and bonus-points to a question (see section 7.3 on page 11 about exercise goals) but also to be able to output a grading table. `XSIM` has built-in means for this.

`\gradingtable[⟨options⟩]`

Print a grading table.

Valid options for this command are

`template = {⟨template⟩}` Default: `default`

Choose the template used for the grading table.

`type = {⟨exercise type⟩}` (initially empty)

Choose the exercise type for which the table is printed.

11. Grading Tables

Both option defaults can be changed with `\xsimsetup` setting the options using `grading-table`:

```
1 \xsimsetup{
2   grading-table/template = default*
3 }
```

An example:

```
1 \gradingtable[type=exercise]
```

Exercise	Points	reached
1	0	
2	4	
3	0	
4	0	
5	0	
6	0	
7.	2.5	
8.	2.5	
total		9

Or using the “default*” template:

```
1 \gradingtable[template=default*,type=exercise]
```

Exercise	1	2	3	4	5	6	7.	8.	total
Points	0	4	0	0	0	0	2.5	2.5	9
reached									

Available templates and how to define new ones are explained in sections 12.3.3 on page 26 and 12.4 on page 26. `\xsim` per default provides two templates “default” and “default*”, the first one has a vertical layout, the second a horizontal layout. Both templates can be used per type like in the examples above or for all types at once by leaving the specification `type` away:

```
1 \gradingtable
```

	Points reached
Exercise 1	0
Exercise 2	4
Exercise 3	0
Exercise 4	0
Exercise 5	0
Exercise 6	0
Exercise 7.	2.5
Exercise 8.	2.5
Problem 1	5
total	14

12. Styling the Exercises – Templates

12.1. Background

Whenever **XSIM** outputs something to be typeset it uses so-called templates for the task. **XSIM** knows of three different kinds of templates:

- environment templates (see section 12.3.1 on page 25),
- heading templates (see section 12.3.2 on page 25) and
- grading table templates (see section 12.3.3 on page 26)

The most important one for the styling of the exercises are the environment templates. Those templates give you complete control over the look and arrangement of an exercise. To be able to do this **XSIM** provides a large number of commands which can be used only inside template definitions.³ Those commands are explained in the next section. Their usage will hopefully become clear in the examples in section 12.4 on page 26. Having full control over the layout comes at a price: you need to be able to program yourself in order to achieve certain layouts.⁴

12.2. Commands for Usage in Template Definitions

12.2.1. Goals

`\IfExerciseGoal``IF``{<goal>}{<relation and value>}{<true>}{<false>}`
 Checks the sum of goal `<goal>` against `<relation and value>`.

3. The last sentence is wrong: those commands can be used anywhere but most of them only give useful results inside of templates.

4. I plan to incorporate the most common layouts – and maybe some fancy ones, too – in the examples section 12.4 on page 26 but at the time of writing this is still up in the air.

`\IfExerciseGoalSingularTF{<goal>}{<true>}{<false>}`

Checks if the value of the goal `<goal>` of the current exercise equals 1. This is the same as

`\IfExerciseGoalTF{<goal>}{=1}{<true>}{<false>}`.

`\TotalExerciseTypeGoal{<goal>}{<type>}{<singular>}{<plural>}`

Print the sum of goal `<goal>` for the exercises of type `<type>` and append `<singular>` or `<plural>` depending on whether the sum equals 1 or not.

`\TotalExerciseGoal{<goal>}{<singular>}{<plural>}`

Print the sum of goal `<goal>` for all exercises of all types and append `<singular>` or `<plural>` depending on whether the sum equals 1 or not.

12.2.2. Properties

* `\IfExercisePropertyExistTF{<property>}{<true>}{<false>}`

Tests whether an exercise property with the name `<property>` is defined.

`\IfExercisePropertySetTF{<property>}{<true>}{<false>}`

Tests whether the exercise property `<property>` has been set for the current exercise.

* `\GetExerciseProperty{<property>}`

Retrieves the value of the property `<property>` for the current exercise.

* `\GetExerciseAliasProperty{<property>}`

Retrieves the value of the property of which `<property>` is an alias of for the current exercise.

`\SaveExerciseProperty{<property>}{<macro>}`

Saves the value of the property `<property>` for the current exercise in macro `<macro>`.

`\GlobalSaveExerciseProperty`

Globally saves the value of the property `<property>` for the current exercise in macro `<macro>`.

`\ExercisePropertyIfSetTF{<type>}{<id>}{<property>}{<true>}{<false>}`

Test if the property `<property>` has been set for the exercise of type `<type>` with id `<id>`.

* `\ExercisePropertyGet{<type>}{<id>}{<property>}`

Retrieves the value of the property `<property>` for the exercise of type `<type>` with id `<id>`.

* `\ExercisePropertyGetAlias{<type>}{<id>}{<property>}`

Retrieves the value of the property of which `<property>` is an alias of for the exercise of type `<type>` with id `<id>`.

`\ExercisePropertySave{<type>}{<id>}{<property>}{<macro>}`

Saves the value of the property `<property>` for the exercise of type `<type>` with id `<id>` in macro `<macro>`.

`\ExercisePropertyGlobalSave{<type>}{<id>}{<property>}{<macro>}`

Globally saves the value of the property `<property>` for the exercise of type `<type>` with id `<id>` in macro `<macro>`.

12.2.3. Parameters

- * `\GetExerciseParameter{<parameter>}`
Retrieves the value of the parameter *<parameter>* for the current exercise.
- * `\GetExerciseName`
Retrieves the value of the parameter `exercise-name` for the current exercise or of the parameter `solution-name` for the current solution.
- * `\ExerciseParameterGet{<type>}{<id>}{<parameter>}`
Retrieves the value of the parameter *<parameter>* for the exercise of type *<type>* with id *<id>*.

12.2.4. Tags

- `\ForEachExerciseTag{<type>}{<code>}`
Loops over all tags of tag type *<type>* for the current exercise applying *<code>* each time. Inside *<code>* you can refer to the corresponding tag with #1.
- `\ListExerciseTags{<type>}{<between>}`
Lists all tags of tag type *<type>* for the current exercise using *<between>* as a separator.
- `\UseExerciseTags{<type>}{<between two>}{<between>}{<between last two>}`
Lists all tags of tag type *<type>* for the current exercise using *<between>* as a separator and *<between last two>* as separator between the last two tags of the list. If the list only consists of two tags *<between two>* is used as separator.

12.2.5. Further Commands for Usage in Template Definitions

- * `\ExerciseType`
Can be used to refer to the current exercise type.
- * `\ExerciseID`
Can be used to refer to the current exercise id.
- * `\ExerciseCollection`
Can be used in certain templates to refer to the collection that is currently inserted.
- * `\numberofusedexercises`
Holds the total number of used exercises. Useful in table template definitions.
- * `\ExerciseTableType{<code>}`
In table template definitions this macro either expands to the given exercise type or – if no type has been given – to *<code>*.
- * `\IfInsideSolutionTF{<true>}{<false>}`
Tests if the template is used inside a solution environment or not.

`\ForEachPrintedExerciseByType{<code>}`

Loops over each *printed* exercise ordered by the exercise types and within each type by id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the counter of the exercise
- #4: the subtitle of the exercise
- #5: the points of the exercise
- #6: the bonus points of the exercise

`\ForEachUsedExerciseByType{<code>}`

Loops over each *used* exercise ordered by the exercise types and within each type by id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the counter of the exercise
- #4: the subtitle of the exercise
- #5: the points of the exercise
- #6: the bonus points of the exercise

`\ForEachPrintedExerciseByID`

Loops over each *printed* exercise order by the exercise id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the counter of the exercise
- #4: the subtitle of the exercise
- #5: the points of the exercise
- #6: the bonus points of the exercise

`\ForEachUsedExerciseByID`

Loops over each *used* exercise order by the exercise id. Inside `<code>` you can refer to several properties of the corresponding exercise:

- #1: the type of the exercise
- #2: the id of the exercise
- #3: the counter of the exercise
- #4: the subtitle of the exercise

- #5: the points of the exercise
- #6: the bonus points of the exercise

* `\XSIMtranslate{⟨keyword⟩}`

Delivers the translation of `⟨keyword⟩` according to the current document language (in the meaning of a babel [Bra16] or polyglossia [Cha15] language). Existing keywords and keyword translations (and how to add new ones) are explained in section 13 on page 33.

`\XSIMexpandcode{⟨code⟩}`

Expands `⟨code⟩` like `\edef` does and leaves the result in the input stream.

`\XSIMmixedcase{⟨code⟩}`

Converts `⟨code⟩` to mixed case:

`\XSIMmixedcase{this is some text}` This is some text

This command expands `⟨code⟩` before converting it.

`\XSIMputright⟨macro⟩{⟨code⟩}`

Extends the macro definition of `⟨macro⟩` with `⟨code⟩` putting it to the right. This is like a local version of the LaTeX kernel macro `\g@addto@macro`.

* `\XSIMifeqTF{⟨code 1⟩}{⟨code 2⟩}{⟨true⟩}{⟨false⟩}`

Checks if the full expansion⁵ of `⟨code 1⟩` and `⟨code 2⟩` is the same tokenlist.

* `\XSIMifblankTF{⟨code⟩}{⟨true⟩}{⟨false⟩}`

Checks if the full expansion⁵ of `⟨code⟩` is blank (*i. e.*, if it is empty or only consists of spaces).

12.3. Declaring Templates

12.3.1. Environment Templates

`\DeclareExerciseEnvironmentTemplate{⟨name⟩}{⟨begin code⟩}{⟨end code⟩}`

Declare the environment template `⟨name⟩`.

Environment templates are used by the exercise and solution environments. Those are the templates set with the parameters `exercise-template` and `solution-template`.

12.3.2. Heading Templates

`\DeclareExerciseHeadingTemplate{⟨name⟩}{⟨code⟩}`

Declare the heading template `⟨name⟩`.

Heading templates are used by `\printsolutions`, `\printsolutionstype` and `\printcollection`. Those are the templates set with the option `headings-template` of the modules `print-solutions` and `print-collection`.

5. This is a `\romannumeral` expansion [Flo].

12.3.3. Grading Table Templates

`\DeclareExerciseTableTemplate{<name>}{<code>}`

Declare the grading table template `<name>`.

Table templates are used by `\gradingtable`. Those are the templates set with the option `template` of module `grading-table`

12.4. Examples

12.4.1. The default Exercise Template

Below the definition of the default exercise template provided by **XSIM** is shown:

```

1 \DeclareExerciseEnvironmentTemplate{default}{%
2   \subsection*
3   {%
4     \XSIMmixedcase{\GetExerciseName}\nobreakspace
5     \GetExerciseProperty{counter}%
6     \IfInsideSolutionF
7     {%
8       \IfExercisePropertySetT{subtitle}
9       { {\normalfont\itshape\GetExerciseProperty{subtitle}}}%
10    }%
11  }
12  \IfExercisePropertySetT{points}
13  {%
14    \marginpar
15    {%
16      \IfInsideSolutionF{\rule{1.2cm}{1pt}\slash}%
17      \GetExerciseProperty{points}%
18      \IfExercisePropertySetT{bonus-points}
19      {~(+\GetExerciseProperty{bonus-points})}%
20      ~\XSIMtranslate {point-abbr}%
21    }%
22  }%
23 }
24 {}

```

12.4.2. A New Exercise Type Using `tcolorbox`

Let's say we want exercises to be put in a `tcolorbox`. We want a bold title and, if given, an italic subtitle. Exercises should also have the points after the subtitle in parentheses if given. Let's also say we want those to be an additional exercise type in addition to the ones **XSIM** already provides. This is shown with the following code which is also how the problems in this manual have been defined:

```

1 \DeclareExerciseEnvironmentTemplate{tcolorbox}
2   {%
3     \tcolorbox[
4       colback = red!5!white ,
5       colframe = red!75!black ,
6       colbacktitle = yellow!50!red ,
7       coltitle = red!25!black ,
8       breakable ,
9       drop shadow ,
10      beforeafter skip = .5\baselineskip ,
11      title =
12        \textbf{\GetExerciseName~\GetExerciseProperty{counter}}%
13        \IfExercisePropertySetT{subtitle}
14          { \textit{\GetExerciseProperty{subtitle}}}%
15        \IfInsideSolutionF{%
16          \IfExercisePropertySetT{points}{ % notice the space
17            (%
18              \GetExerciseProperty{points}
19              \IfExerciseGoalSingularTF{points}
20                {\XSIMtranslate{point}}
21                {\XSIMtranslate{points}}%
22            )%
23          }%
24        }%
25      ]%
26    }
27  {\endtcolorbox}
28
29 \DeclareExerciseType{problem}{
30   exercise-env = problem ,
31   solution-env = answer ,
32   exercise-name = Problem ,
33   solution-name = Answer ,
34   exercise-template = tcolorbox ,
35   solution-template = tcolorbox
36 }

```

See it in action:

```

1 \begin{problem}[subtitle=My subtitle,points=5]
2   This is a problem using a subtitle and points.
3 \end{problem}
4 \begin{answer}
5   This is the answer to problem~\GetExerciseProperty{counter}.
6 \end{answer}

```

Problem 1 *My subtitle* (5 points)

This is a problem using a subtitle and points.

12.4.3. *Mimicking exsheets' runin Template*

The following example shows how you could mimick exsheets' runin template. The outcome isn't exactly the same since exsheets doesn't use `\marginpar` but the result should look very similar.

```

1 \usepackage{needspace}
2 \DeclareExerciseEnvironmentTemplate{runin}
3 {
4   \par\vspace{\baselineskip}
5   \Needspace*{2\baselineskip}
6   \noindent
7   \textbf{\XSIMmixedcase{\GetExerciseName}~\GetExerciseProperty{counter}}%
8   \IfExercisePropertySetT{subtitle}
9     { \textit{\GetExerciseProperty{subtitle}}} %
10  \IfExercisePropertySetT{points}{%
11    \marginpar{%
12      \GetExerciseProperty{points}%
13      \IfExercisePropertySetT{bonus-points}
14        {+\GetExerciseProperty{bonus-points}}%
15      \,\IfExerciseGoalSingularTF{points}
16        {\XSIMtranslate{point}}
17        {\XSIMtranslate{points}}}%
18    }%
19  }%
20 }
21 {}

```

See it in action:

```

1 \SetExerciseParameter{exercise}{exercise-template}{runin}
2 \renewcommand*\theexercise{\arabic{exercise}.}
3 \begin{exercise}[subtitle=exsheets' runin,points=2.5]
4   \lipsum[4]
5 \end{exercise}

```

Exercise 7. *exsheets' runin* Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

2.5 points

12.4.4. Mimicking exsheets' margin Template

The following example shows how you could mimick exsheets' margin template.

```

1 \usepackage{needspace}
2 \DeclareExerciseEnvironmentTemplate{margin}
3 {%
4   \par\vspace{\baselineskip}
5   \Needspace*{2\baselineskip}
6   \noindent
7   \llap{%
8     \smash{%
9       \tabular[t]{@{}r@{}}
10      \textbf{\XSIMmixedcase{\GetExerciseName}~\GetExerciseProperty{
counter}}}}
11     \IfExercisePropertySetT{points}{%
12       \tabularnewline
13       (\GetExerciseProperty{points}%
14       \IfExercisePropertySetT{bonus-points}
15       {+\GetExerciseProperty{bonus-points}}}%
16       \,\XSIMtranslate{point-abbr})%
17     }%
18   \endtabular
19 } % notice the space
20 }%
21 }
22 {}

```

See it in action:

```

1 \SetExerciseParameter{exercise}{exercise-template}{margin}
2 \renewcommand*{\theexercise}{\arabic{exercise}.}
3 \begin{exercise}[subtitle=exsheets' margin,points=2.5]
4   \lipsum[4]
5 \end{exercise}

```

Exercise 8. Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt (2.5p.) ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

12.4.5. The Headings Templates

XSIM defines four heading templates which only differ by which text they output:

```

1 \DeclareExerciseHeadingTemplate{default}
2   {\section*{\XSIMtranslate{default-heading}}}
3 \DeclareExerciseHeadingTemplate{collection}
4   {\section*{\XSIMtranslate{collection-heading}}}
5 \DeclareExerciseHeadingTemplate{per-section}
6   {\section*{\XSIMtranslate{per-section-heading}}}
7 \DeclareExerciseHeadingTemplate{per-chapter}
8   {\section*{\XSIMtranslate{per-chapter-heading}}}
```

Section 13 shows how the translations are defined.

12.4.6. The default Table Template

This template is the one used for grading tables per default. It has a vertical layout.

```

1 \DeclareExerciseTableTemplate{default}{%
2   \XSIMputright\ExerciseTableCode{%
3     \toprule
4     \XSIMifblankTF{\ExerciseType}
5       {}
6       {\XSIMmixedcase{\GetExerciseParameter{exercise-name}}}
7     &
8     \XSIMmixedcase{\XSIMtranslate{points}} &
9     \XSIMtranslate{reached} \\
10    \midrule
11  }%
12  \ForEachUsedExerciseByType{%
13    \XSIMifeqTF{#1}{\ExerciseTableType{#1}}
14      {%
15        \XSIMifblankTF{\ExerciseType}
16        {%
```

```

17      \XSIMputright\ExerciseTableCode{%
18      \XSIMmixedcase{\ExerciseParameterGet{#1}{exercise-name} }%
19      }%
20      }
21      {}%
22      \XSIMputright\ExerciseTableCode
23      {#3 & \XSIMifblankTF{#5}{0}{#5} & \\\ }%
24      }
25      {}%
26      }
27      \XSIMputright\ExerciseTableCode{%
28      \midrule
29      \XSIMtranslate{total} &
30      \XSIMifblankTF{\ExerciseType}
31      {\TotalExerciseGoal{points}{}{}}
32      {\TotalExerciseTypeGoal{\ExerciseType}{points}{}{}} &
33      \\\ \bottomrule
34      }%
35      \XSIMexpandcode{%
36      \noexpand\begin{tabular}{\XSIMifblankTF{\ExerciseType}{l}{c}cc}
37      \noexpand\ExerciseTableCode
38      \noexpand\end{tabular}%
39      }%
40      }

```

The part

```

1 \XSIMifblankTF{\ExerciseType}{ ... }{ ... }

```

repeatedly checks if an exercise type has been given for the table. This makes it possible to design the table differently if it is for one exercise type only (the `true` case) or for all exercise types (the `false` case). `\ExerciseTableType{<code>}` either expands to the given exercise type or to `<code>`.

12.4.7. The `default*` Table Template

The second of the predefined grading table templates. It has a horizontal layout.

If you have a lot of exercises the width of a table with this layout may exceed the text width of the document!

```

1 \DeclareExerciseTableTemplate{default*}{%
2   \XSIMputright\ExerciseTableCode{%

```

```

3      \toprule
4      \XSIMifblankTF{\ExerciseType}
5      {}
6      {\XSIMmixedcase{\GetExerciseParameter{exercise-name}}}
7      &%
8  }%
9  \ForEachUsedExerciseByType{%
10     \XSIMifeqTF {#1} { \ExerciseTableType {#1} }
11     {
12         \XSIMifblankTF{\ExerciseType}
13         {%
14             \XSIMputright\ExerciseTableCode{%
15                 \XSIMmixedcase{\ExerciseParameterGet{#1}{exercise-name} }%
16             }%
17         }
18         {}%
19         \XSIMputright\ExerciseTableCode{#3 &}
20     }
21     {}%
22 }%
23 \XSIMputright\ExerciseTableCode{%
24     \XSIMtranslate{total} \\\
25     \midrule
26     \XSIMmixedcase{\XSIMtranslate{points}} &
27 }%
28 \ForEachUsedExerciseByType{%
29     \XSIMifeqTF{#1}{\ExerciseTableType{#1}}
30     {\XSIMputright\ExerciseTableCode{\XSIMifblankTF{#5}{0}{#5} &}}
31     {}%
32 }%
33 \XSIMputright\ExerciseTableCode{%
34     \XSIMifblankTF{\ExerciseType}
35     {\TotalExerciseGoal{points}{}{}}
36     {\TotalExerciseTypeGoal{\ExerciseType}{points}{}{}}%
37     \\\ \midrule
38     \XSIMtranslate{reached} &%
39 }%
40 \ForEachUsedExerciseByType{%
41     \XSIMifeqTF{#1}{\ExerciseTableType{#1}}
42     {\XSIMputright\ExerciseTableCode{&}}
43     {}%
44 }%
45 \XSIMputright\ExerciseTableCode{ \\\ \bottomrule }%
46 \def\numberofcolumns{%
47     \XSIMifblankTF{\ExerciseType}
48     {\numberofusedexercises}
49     {\csname numberof \ExerciseType s\endcsname}%
50 }%

```



```

51 \XSIMifeqF{\numberofcolumns}{0}
52   {%
53     \begin{tabular}{l*{\numberofcolumns}{c}c}
54       \ExerciseTableCode
55     \end{tabular}%
56   }%
57 }

```

The part

```

1 \XSIMifblankTF{\ExerciseType}{ ... }{ ... }

```

repeatedly checks if an exercise type has been given for the table. This makes it possible to design the table differently if it is for one exercise type only (the `true` case) or for all exercise types (the `false` case). `\ExerciseTableType{<code>}` either expands to the given exercise type or to `<code>`.

13. Exercise Translations

`\DeclareExerciseTranslation{<keyword>}{<language>}{<translation>}`

Declare the translation of `<keyword>` for language `<language>`.

`\DeclareExerciseTranslations{<keyword>}{<translations>}`

Declare the translations of `<keyword>` for several languages at once. See an example of the usage below.

`*\XSIMtranslate{<keyword>}`

Delivers the translation of `<keyword>` according to the current document language (in the meaning of a babel [Bra16] or polyglossia [Cha15] language).

`\ForEachExerciseTranslation{<code>}`

Loops over all translations of all keywords known to **XSIM**. Inside `<code>` you can refer to the keyword with #1, to the language with #2, and to the translation with #3.

As an example how to use `\DeclareExerciseTranslations` here is how the translations for exercise have been defined:

```

1 \DeclareExerciseTranslations{exercise}{
2   Fallback = exercise ,
3   English  = exercise ,
4   French   = exercise ,
5   German   = \text{Übung}
6 }

```

13. Exercise Translations

Table 1 shows all existing keywords with all predefined translations.

TABLE 1: Translation keywords predefined by **XSIM**.

keyword	language	translation
exercise	Fallback	exercise
exercise	English	exercise
exercise	French	exercice
exercise	German	\ "Ubung
question	Fallback	question
question	English	question
question	French	question
question	German	Aufgabe
solution	Fallback	solution
solution	English	solution
solution	French	solution
solution	German	L\ "osung
point-abbr	Fallback	p.
point-abbr	English	p.
point-abbr	French	p.
point-abbr	German	P.
point	Fallback	point
point	English	point
point	French	point
point	German	Punkt
points	Fallback	points
points	English	points
points	French	points
points	German	Punkte
reached	Fallback	reached
reached	English	reached
reached	French	atteint
reached	German	erreicht
total	Fallback	total
total	English	total
total	French	totalement
total	German	insgesamt
default-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\ExerciseType s}

continues

13. Exercise Translations

keyword	language	translation
default-heading	English	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\ExerciseType s}
default-heading	German	\XSIMmixedcase {\GetExerciseParameter {solution-name}en} zu den \XSIMmixedcase {\ExerciseType en}
collection-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {exercise-name}s}
collection-heading	English	\XSIMmixedcase {\GetExerciseParameter {exercise-name}s}
collection-heading	German	\XSIMmixedcase {\GetExerciseParameter {exercise-name}en}
per-section-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\ExerciseType s} of Section\nobreakspace \ExerciseSection
per-section-heading	English	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\ExerciseType s} of Section\nobreakspace \ExerciseSection
per-section-heading	German	\XSIMmixedcase {\GetExerciseParameter {solution-name}en} zu den \XSIMmixedcase {\ExerciseType en} in Abschnitt\nobreakspace \ExerciseSection
per-chapter-heading	Fallback	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\ExerciseType s} of Chapter\nobreakspace \ExerciseChapter
per-chapter-heading	English	\XSIMmixedcase {\GetExerciseParameter {solution-name}s} to the \XSIMmixedcase {\ExerciseType s} of Chapter\nobreakspace \ExerciseChapter
per-chapter-heading	German	\XSIMmixedcase {\GetExerciseParameter {solution-name}en} zu den \XSIMmixedcase {\ExerciseType en} in Kapitel\nobreakspace \ExerciseChapter

14. Other Commands

A. How to...

This section serves as a kind of gallery showing solutions to common problems. I expect this section to grow over the years.

A.1. ...Know if **xsim** Needs Another Compilation?

If **xsim** wants you to recompile your document it writes the following to the logfile:

```

1 *****
2 * xsim warning: "rerun"
3 *
4 * Exercise properties may have changed. Rerun to get them synchronized.
5 *****

```

So just check the logfile regularly (which you should be doing anyway) and keep your eyes open.

A.2. ...Resolve Getting Repeatedly Wrong Exercise Properties or Wrong Exercise Lists?

xsim writes a lot of stuff to the auxfile for re-using information on subsequent compilations. If you add exercises, change properties *etc.* it might happen that wrong information is staying in the auxfile and is wrongly used by **xsim**. In such cases deleting the auxfile and doing a few fresh compilations may resolve your problems.

Sometimes the existing of exercise or solution files from earlier compilations may lead to wrong lists of exercises or solutions. In such cases it can be useful to delete all those files and doing a fresh compilation. It may be helpful to use a subfolder for those external files which will make deleting them a little bit easier. (Don't forget to both create the subfolder and set **path** accordingly then.)

A.3. ...Resolve Strange Errors After Updating?

xsim writes a lot of stuff to the auxfile. An update may well change how this is done so deleting the auxfile and doing a few fresh compilations may resolve your problems.

A.4. ...Print All Solutions Grouped by Section?

Here is an idea how to get a list of all solutions grouped by the section the corresponding exercises are appearing in.

```
1 % preamble:
2 % \usepackage{etoolbox}
3 % \newcounter{sections}
4
5 % document:
6 \setcounter{sections}{1}
7 \whileboolexpr
8   { test {\ifnumless{\value{sections}}{\value{section}+1}} }
9   {
10    \printsolutions[section=\value{sections},headings-template=per-section]
11    \stepcounter{sections}
12  }
```

For this manual we then get the following list.⁶

Solutions to the Exercises of Section 4

Solution 1

A first example for a solution.

Solutions to the Exercises of Section 8

Solution 5

The solution of the exercise that has not been printed.

Answers to the Problems of Section 12

Answer 1 *My subtitle*

This is the answer to problem 1.

B. The xsimverb package

xSIM comes bundled with another package called xsimverb. This package loads a very small subset of **xSIM** which allows to create environments which write their contents verbatim to external files. It provides the following commands (which of course are also available in **xSIM**, too):

6. Taking care of the fact that we're in the appendix now which means we can use `\value{section}`. Therefore this manual does `\edef\lastsection{\arabic{section}}` right before `\appendix`

B. The `xsimverb` package

`\XSIMfilewritestart*{⟨file name⟩}`

Start writing to the file named *⟨file name⟩*. This should be the *last* command in the *begin* definition of an environment. If it is used in an environment with arguments where the *last* argument is optional you should check if the optional argument is given and used the starred version if the test is positive. This is demonstrated in an example below using `xparse`'s `\NewDocumentEnvironment` but the same is true for environments defined with `\newenvironment`. In other cases the starred version is not needed.

`\XSIMfilewritestop`

Stop writing to the file. This should be the *first* command in the *end* definition of an environment.

`\XSIMsetfilebegin{⟨code⟩}`

This command can be used to write something to the external file *before* the environment contents. Must be set before `\XSIMfilewritestart` in the *begin* definition.

`\XSIMsetfileend{⟨code⟩}`

This command can be used to write something to the external file *after* the environment contents. Must be set before `\XSIMfilewritestart` in the *begin* definition.

`\XSIMgobblechars{⟨integer⟩}`

Determines how many characters are cut off of the beginning of each line of the environment body before it is written to the file. The default value is 0.

An example of how to use those commands:

```
1 \documentclass{article}
2 \usepackage{xsimverb,listings}
3
4 \makeatletter
5 \NewDocumentEnvironment{example}{0}
6   {%
7     \XSIMsetfilebegin{\@percentchar\space file ``\jobname.tmp'}%
8     \XSIMsetfileend{\@percentchar\space bye bye}%
9     \IfNoValueTF{#1}
10      {\XSIMfilewritestart{\jobname.tmp}}
11      {\XSIMfilewritestart*{\jobname.tmp}}%
12   }
13   {%
14     \XSIMfilewritestop
15     \lstinputlisting[language={LaTeX}TeX]{\jobname.tmp}%
16     \input{\jobname.tmp}
17   }
18 \makeatother
19
20 \begin{document}
21
22 \begin{example}
```

```
23 bla bla \LaTeX
24 \end{example}
25
26 \end{document}
```

The tmp file produced by the above example will contain the following three lines (if the file itself was called `test.tex`):

```
1 % file `test.tmp'
2 bla bla \LaTeX
3 % bye bye
```

C. All Exercise Examples

Exercises

Exercise 1

A first example for an exercise.

Exercise 2 *This is a subtitle*

An exercise where some properties have been set.

4 (+1) p.

Exercise 3

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

```
\GetExerciseProperty{id}: 3
\GetExerciseAliasProperty{ID}: 3
\GetExerciseProperty{ID}: 3
```

Exercise 4

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit

C. All Exercise Examples

purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

```
\GetExerciseProperty{id}: 4  
\GetExerciseAliasProperty{ID}: 4  
\GetExerciseProperty{ID}: foo-bar
```

Exercise 5

This exercise will not be printed but the exercise counter will be incremented nonetheless. Its solution will be printed in the list of solutions.

Exercise 6

This exercise is added to the collection ‘foo’.

Exercise 7. *exsheets’ runin*

————/2.5 p.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Exercise 8. *exsheets’ margin*

————/2.5 p.

Quisque ullamcorper placerat ipsum. Cras nibh. Morbi vel justo vitae lacus tincidunt ultrices. Lorem ipsum dolor sit amet, consectetur adipiscing elit. In hac habitasse platea dictumst. Integer tempus convallis augue. Etiam facilisis. Nunc elementum fermentum wisi. Aenean placerat. Ut imperdiet, enim sed gravida sollicitudin, felis odio placerat quam, ac pulvinar elit purus eget enim. Nunc vitae tortor. Proin tempus nibh sit amet nisl. Vivamus quis tortor vitae risus porta vehicula.

Problems

Problem 1 *My subtitle* (5 points)

This is a problem using a subtitle and points.

D. All Solution Examples

Solutions to the Exercises

Solution 1

A first example for a solution.

Solution 5

The solution of the exercise that has not been printed.

Answers to the Problems

Answer 1 *My subtitle*

This is the answer to problem 1.

E. References

- [Bra16] Johannes BRAAMS, current maintainer: Javier BEZOS.
babel. version 3.9q, Feb. 24, 2016 (or newer).
URL: <http://mirror.ctan.org/macros/latex/required/babel/>.
- [Cha15] François CHARETTE, current maintainer: Arthur REUTENAUER.
polyglossia. version 1.42.0, Aug. 6, 2015 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/polyglossia/>.
- [Fea05] Simon FEAR. booktabs. version 1.61803, Apr. 14, 2005 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/booktabs/>.
- [Flo] Bruno Le FLOCH. *Cunning (La)TeX tricks*.
URL: <http://tex.stackexchange.com/a/19769/> (visited on 03/02/2017).
- [L3Pa] THE L^AT_EX₃ PROJECT TEAM. l3kernel. version SVN 6377, Jan. 19, 2016 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/l3kernel/>.
- [L3Pb] THE L^AT_EX₃ PROJECT TEAM.
l3packages. version SVN 6377, Jan. 19, 2016 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/l3packages/>.
- [Leh15] Philipp LEHMAN, current maintainer: Joseph WRIGHT.
etoolbox. version 2.2a, Aug. 2, 2015 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/etoolbox/>.
- [Nie15] Clemens NIEDERBERGER. translations. version 1.2e, Nov. 7, 2015 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/translations/>.
- [Nie17] Clemens NIEDERBERGER. exsheets. version 0.21i, Feb. 8, 2017 (or newer).
URL: <http://mirror.ctan.org/macros/latex/contrib/exsheets/>.

[var] VARIOUS. ‘*exsheets*’ questions.
 URL: <http://tex.stackexchange.com/questions/tagged/exsheets> (visited on 03/06/2017).

F. Index

Symbols

‘*exsheets*’ questions 2

B

babel (package) 25, 33
begin-hook 14
 BEZOS, Javier 25, 33
bonus-points (property) 9, 11
 booktabs (package) 2
 BRAAMS, Johannes 25, 33

C

chapter 18 f.
 CHARETTE, François 25, 33
`\collectexercises` 16 f.
`\collectexercisesstop` 15 ff.
`\collectexercisestype` 15 f.
collection 19
counter (parameter) 8
counter (property) 9, 13
Cunning (La)TeX tricks 25

D

`\DeclareExerciseCollection` 15
`\DeclareExerciseEnvironmentTemplate`
 25–29
`\DeclareExerciseGoal` 11 f.
`\DeclareExerciseHeadingTemplate` .. 25, 30
`\DeclareExerciseProperty` 10
`\DeclareExercisePropertyAlias` 10
`\DeclareExerciseTableTemplate` ... 26, 30 f.
`\DeclareExerciseTagging` 12
`\DeclareExerciseTranslation` 33
`\DeclareExerciseTranslations` 33
`\DeclareExerciseType` 7, 9, 13, 27

E

end-hook 14

etoolbox (package) 2
 exercise (environment) .. 5 ff., 9 f., 13, 15–20,
 27–33
exercise-env (parameter) 8
exercise-name (parameter) 8, 23
exercise-template (parameter) 8, 25
`\ExerciseCollection` 23
`\ExerciseID` 23
`\ExerciseParameterGet` 23, 31 f.
`\ExercisePropertyGet` 22
`\ExercisePropertyGetAlias` 22
`\ExercisePropertyGlobalSave` 22
`\ExercisePropertyIfSetTF` 22
`\ExercisePropertySave` 22
`\ExerciseTableCode` 30–33
`\ExerciseTableType` 23, 30, 32
`\ExerciseType` 23, 30–33
 expl3 (package) 2
 exsheets (package) 2 f., 28

F

FEAR, Simon 2
final 3
 FLOCH, Bruno Le 25
`\ForEachExerciseTag` 23
`\ForEachExerciseTranslation` 33
`\ForEachPrintedExerciseByID` 24
`\ForEachPrintedExerciseByType` 24
`\ForEachUsedExerciseByID` 24
`\ForEachUsedExerciseByType` 24, 30, 32

G

`\GetExerciseAliasProperty` 10, 22
`\GetExerciseName` 23, 26–29
`\GetExerciseParameter` 23, 30, 32
`\GetExerciseProperty` 10, 22, 26–29
`\GlobalSaveExerciseProperty` 22

INDEX

<code>goal-print</code>	12	<code>print-collection</code> (option class).....	16, 25
<code>grading-table</code> (option class).....	20, 26	<code>print-solutions</code> (option class).....	19, 25
<code>\gradingtable</code>	19 f., 26	<code>\printbonus</code>	11
H		<code>\printcollection</code>	16 f., 25
<code>headings</code>	16, 18	<code>\printexercise</code>	15
<code>headings-template</code>	16, 18, 25	<code>\printpoints</code>	11
I		<code>\printsolution</code>	18 f.
<code>ID</code> (property).....	9 f.	<code>\printsolutions</code>	18 f., 25, 37
<code>id</code> (property).....	9 f., 15, 18	<code>\printsolutionstype</code>	18, 25
<code>\IfExerciseGoalTF</code>	21	<code>\prinntotalbonus</code>	11
<code>\IfExerciseGoalSingularTF</code>	22	<code>\prinntotalpoints</code>	11
<code>\IfExerciseGoalSingularTF</code>	27 f.	R	
<code>\IfExerciseGoalTF</code>	22	REUTENAUER, Arthur.....	25, 33
<code>\IfExercisePropertyExistTF</code>	22	S	
<code>\IfExercisePropertySetTF</code>	22	<code>\SaveExerciseProperty</code>	22
<code>\IfExercisePropertySetT</code>	26–29	<code>section</code>	18 f.
<code>\IfInsideSolutionTF</code>	23	<code>\SetExerciseParameter</code>	8, 28 f.
<code>\IfInsideSolutionF</code>	26 f.	<code>\SetExerciseParameters</code>	8
<code>ignore-tagging</code>	12	<code>solution</code> (environment).....	5 ff., 13, 27
L		<code>solution-env</code> (parameter).....	8
<code>l3kernel</code> (bundle).....	2	<code>solution-name</code> (parameter).....	8, 23
<code>l3packages</code> (bundle).....	2	<code>solution-template</code> (parameter).....	8, 25
LEHMAN, Philipp.....	2	<code>subtitle</code> (property).....	9
<code>\ListExerciseTags</code>	23	T	
LPPL.....	2	<code>tags</code>	12
N		<code>tags</code> (property).....	9, 12
<code>\NewDocumentEnvironment</code>	38	<code>template</code>	19, 26
NIEDERBERGER, Clemens.....	2	THE L ^A T _E X3 PROJECT TEAM.....	2
<code>number</code> (parameter).....	8	<code>\theexercise</code>	28 f.
<code>\numberofhAexercise-envfiBs</code>	7	<code>topics</code>	12
<code>\numberofexercises</code>	7	<code>topics</code> (property).....	9, 12
<code>\numberofusedexercises</code>	23, 32	<code>\TotalExerciseGoal</code>	11, 22, 31 f.
P		<code>\TotalExerciseTypeGoal</code>	11, 22, 31 f.
<code>path</code>	6 f., 36	<code>translations</code> (package).....	2
<code>points</code> (property).....	9, 11	<code>type</code>	19 f.
<code>polyglossia</code> (package).....	25, 33	U	
<code>post-hook</code>	14	<code>use</code>	13
<code>pre-hook</code>	14	<code>use</code> (property).....	9, 13
<code>print</code>	5, 13 f.	<code>\UseExerciseTags</code>	23
<code>print</code> (property).....	9	V	
		VARIOUS.....	2

INDEX

<code>verbose</code>	3	<code>\XSIMifblankTF</code>	25
W		<code>\XSIMifblankTF</code>	30–33
<code>within</code>	14	<code>\XSIMifeqTF</code>	25
WRIGHT, Joseph	2	<code>\XSIMifeqF</code>	33
X		<code>\XSIMifeqTF</code>	30, 32
<code>xparse</code> (package)	2, 38	<code>\XSIMmixedcase</code>	25 f., 28–32
<code>\XSIMexpandcode</code>	25, 31	<code>\XSIMputright</code>	25, 30 ff.
<code>\XSIMfilewritestart</code>	38	<code>\XSIMsetfilebegin</code>	38
<code>\XSIMfilewritestop</code>	38	<code>\XSIMsetfileend</code>	38
<code>\XSIMgobblechars</code>	38	<code>\xsimsetup</code>	4 f., 12, 16 f., 19 f.
		<code>\XSIMtranslate</code>	7, 25–33
		<code>xsimverb</code> (package)	37