

# **AC6369F Datasheet**

**Zhuhai Jieli Technology Co.,LTD**

**Version: V1.1**

**Date: 2022.07.19**

**Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.**

# AC6369F Features

## CPU

- 32-bit DSP supports hardware Float Point Unit (FPU)
- Up to 160MHz programmable processor
- 64 Vectored interrupts
- 4 Levels interrupt priority

## Bluetooth

- Compliant with Bluetooth V5.3+BR+EDR+BLE specification
- Meet class1 class2 and class3 transmitting power requirement
- Support GFSK and  $\pi/4$  DQPSK all packet types
- Provides +6dbm transmitting power
- receiver with -90dBm sensitivity
- Fast AGC for enhanced dynamic range
- Supports  
a2dp\avctp\avdtp\avrcp\hfp\spp\smf\att\gap\gatt\rfcomm\sdp\l2cap profile

## Temperature

- Operating temperature: -40°C to +125°C
- Storage temperature: -65°C to +150°C

## Peripherals

- One full speed USB 2.0 OTG controller
- Six multi-function 32-bit timers, support capture and PWM mode
- Three full-duplex basic UART, UART0 and UART1 supports DMA mode
- Two SPI interface supports host and device mode
- One hardware IIC interface supports host and device mode
- 10-bit ADC for analog sampling
- External wake up/interrupt on all GPIOs

## PMU

- Low voltage LDO for internal digital and analog circuit supply
- 3uA current consumption in the soft-off mode
- Built-in LDO for the core, I/O, Bluetooth and flash
- VBAT is 2.2V to 3.4V
- VDDIO is 2.2V to 3.4V

## Packages

- SOP16

## Applications

- Bluetooth IOT

## Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

# 1、 Pin Definition

## 1.1 Pin Assignment




Figure 1-1 AC6369F Package Diagram

## 1.2 Pin Description

Table 1-1 AC6369F Pin Description

PIN NO.	Name	I/O Type	Drive (mA)	Function	Other Function
1	PB6	I/O		GPIO	IIC_SCL_C: IIC SCL(C); SPI2_CLKA: SPI2 Clock(A); ADC8: ADC Input Channel 8; TMR3: Timer3 Clock Input; UART1TXA: Uart1 Data Out(A);
2	PB5	I/O		GPIO (High Voltage Resistance)	PWM3: Timer3 PWM Output; SPI2_DIA: SPI2 Data In(A); CAP1: Timer1 Capture; UART0TXC: Uart0 Data Out(C); UART0RXC: Uart0 Data In(C);
3	PB4	I/O		GPIO	ADC7: ADC Input Channel 7; UART2TXC: Uart2 Data Out(C); UART2RXC: Uart2 Data In(C);
4	VBAT	P	/		Battery Power Supply
	VDDIO	P	/		IO Power 3.3v
5	VSS	P	/		Ground
6	BT_RF	/			BT Antenna
7	BTOSCI	I			BT OSC In
8	BTOSCO	O			BT OSC Out
9	PC5	I/O		GPIO	IIC_SDA_B: IIC SDA(B); ADC12: ADC Input Channel 12; TMR1: Timer1 Clock Input; UART2RXD: Uart2 Data In(D);
10	PC4	I/O		GPIO	IIC_SCL_B: IIC SCL(B); ADC11: ADC Input Channel 11; PWM1: Timer1 PWM Output; UART2TXD: Uart2 Data Out (D);
11	USBDM	I/O		USB Negative Data (pull down)	IIC_SDA_A: IIC SDA(A); SPI2_DOB: SPI2 Data Out(B); ADC14: ADC Input Channel 14; UART1RXD: Uart1 Data In(D);

### Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

12	USBDP	I/O		USB Positive Data (pull down)	IIC_SCL_A: IIC SCL(A); SPI2_CLKB: SPI2 Clock(B); ADC13: ADC Input Channel 13; UART1TXD: Uart1 Data Output(D);
13	PA5	I/O		GPIO	IIC_SCL_D: IIC SCL(D); PWM0: Timer0 PWM Output; UART0TXA: Uart0 Data Output(A);
14	PA3	I/O		GPIO	ADC2: ADC Input Channel 2; PWM5: Timer5 PWM Output UART2TXA: Uart2 Data Output(A);
15	PA0	I/O		GPIO	ADC0: ADC Input Channel 0; UART1TXC: Uart1 Data Output(C);
16	PB7	I/O		GPIO	IIC_SDA_C: IIC DAT(C); SPI2_DOA: SPI2 Data Out(A); ADC9: ADC Input Channel 9; PWM5: Timer5 PWM Output; UART1RXA: Uart1 Data In(A);

**Confidential**

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

## 2、Electrical Characteristics

### 2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-40	+125	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	-0.3	3.6	V
V <sub>3.3IO</sub>	3.3V IO Input Voltage	-0.3	3.6	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below

### 2.2 PMU Characteristics

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.2	3.0	3.4	V	
V <sub>VDDIO</sub>	Voltage Input	—	3.0	—	V	

### 2.3 IO Input/Output Electrical Logical Characteristics

Table 2-3

IO input characteristics						
Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V <sub>IL</sub>	Low-Level Input Voltage	-0.3	—	0.3* VDDIO	V	VDDIO = 3.3V
V <sub>IH</sub>	High-Level Input Voltage	0.7* VDDIO	—	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V <sub>OL</sub>	Low-Level Output Voltage	—	—	0.33	V	VDDIO = 3.3V
V <sub>OH</sub>	High-Level Output Voltage	2.7	—	—	V	VDDIO = 3.3V

## 2.4 Internal Resistor Characteristics

Table 2-4

Port		General Output	High Drive	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA5 PB4,PB6,PB7 PC4~PC5		8mA	24mA	10K	10K	1、USBDM & USBDP default pull down 2、PB5 can pull-up resistance to 5V 3、internal pull-up/pull-down resistance   accuracy ±20%
PA0	Output 0	8mA	24mA	10K	10K	
	Output 1	8mA	64mA			
PB5		8mA	—	10K	10K	
USBDP		4mA	—	1.5K	15K	
USBDM		4mA	—	180K	15K	

## 2.5 BT Characteristics

### 2.5.1 Transmitter

Basic Data Rate

Table 2-5

Parameter		Min	Typ	Max	Unit	Test Conditions
RF Transmit Power			4	6	dBm	25°C, Power Supply VBAT=5V 2441MHz
RF Power Control Range			20		dB	
20dB Bandwidth			950		KHz	
Adjacent Channel	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
Transmit Power	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

**Enhanced Data Rate****Table 2-6**

Parameter		Min	Typ	Max	Unit	Test Conditions
Relative Power			-1		dB	25°C, Power Supply VBAT=5V 2441MHz
$\pi/4$ DQPSK Modulation Accuracy	DEVM RMS		6		%	
	DEVM 99%		10		%	
	DEVM Peak		15		%	
Adjacent Channel	+2MHz		-40		dBm	
	-2MHz		-38		dBm	
Transmit Power	+3MHz		-44		dBm	
	-3MHz		-35		dBm	

**2.5.2 Receiver****Basic Data Rate****Table 2-7**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	25°C, Power Supply VBAT=5V 2441MHz
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

**Enhanced Data Rate****Table 2-8**

Parameter		Min	Typ	Max	Unit	Test Conditions
Sensitivity			-90		dBm	25°C, Power Supply VBAT=5V 2441MHz
Co-channel Interference Rejection			-13		dB	
Adjacent Channel Interference Rejection	+1MHz		+5		dB	
	-1MHz		+2		dB	
	+2MHz		+37		dB	
	-2MHz		+36		dB	
	+3MHz		+40		dB	
	-3MHz		+35		dB	

**Confidential**

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.



### 3、 Package Information

#### 3.1 SOP16




Figure 3-1 AC6369F Package

## 4、Revision History

Date	Revision	Description
2020.07.20	V1.0	Initial Release
2022.07.19	V1.1	Update Bluetooth Feature

### Confidential

The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.