Evaluation of Feb 28 benchmark vs v4.2.1 and verkko

Justin Zook, Nate Olson, and NIST team 3/21/23

Overall stats improved

 Benchmarking of verkko-dipcall vs TR benchmark within both benchmark regions

```
"TP-base": 3616,
"TP-comp": 3627,
"FP": 58,
"FN": 43,
"precision": 0.9842605156037992,
"recall": 0.9882481552336704,
"f1": 0.9862503046963221,
```

Region summary

```
"TP": 2459,"TN": 35894,"FP": 53,"FN": 33,
```

 Benchmarking of v4.2.1 small variants vs TR benchmark within both benchmark regions (excludes most SVs)


```
"TP-base": 1131,
"TP-comp": 1133,
"FP": 19,
"FN": 7,
"precision": 0.98350694444444444,
"recall": 0.9938488576449912,
"f1": 0.9886508560464089,
```

Region summary:


```
"TP": 909,"TN": 7261,"FP": 17,"FN": 6,
```

v4 FP: TR benchmark correctly identifies error in v4 benchmark coming from noisy HiFi reads


v4 calls 6bp del instead of 4bp del



v4 FP: TR benchmark miscalls del outside TR region




v4 FP: TR benchmark misses del outside TR region



v4 FN: TR benchmark and v4 seem correct, but v4 isn't

phased

TR calls 5bp ins here instead of separate 4bp and 1bp ins in v4, which are the same but v4 isn't phased, so we should try our phased v4



v4 FN: v4 called incorrect because of different representation and no phasing?

