

The homeworkassignment*class[†]

Adrian C. Hinrichs

adrian.hinrichs@rwth-aachen.de

Alexander Bartolomey

alexander.bartolomey@rwth-aachen.de

May 3, 2019

Contents

1	Abstract	2
2	Dependencies	2
2.1	Mandatory Dependencies	2
2.2	Recommended Dependencies	3
3	Options	4
4	Layout	8
4.1	Headers & Footers	8
4.2	Enhance Math Environments	9
4.3	Fonts	9
4.4	Serife (Default)	9
4.5	Sans Serif	9
4.5.1	Monospace	10
5	Commands	10
5.1	Constants	10
5.2	Document Informations	10
5.2.1	Inherited from <code>article</code>	11
5.3	Sectioning	11
5.3.1	Obsoledation of <code>\section</code> etc.	11
5.3.2	internal Sectioning	11
5.3.3	‘better’ Sectioning	13

*The name was changed with version v3.0, to become compatible with CTANs guidelines and to maintain a degree of backwards compatibility. The class was called `HomeworkAssignment` prior to v3.0

[†]This document corresponds to homeworkassignment v4.1b, dated 2019/05/03.

5.3.4	Even Better Sectioning-Environments	14
5.4	Useful Macros	15
5.4.1	QUOD ERAT DEMUNSTRANDUM, End of Proof	15
5.4.2	QUOD NON ERAT DEMUNSTARNDUM AT IUCUNDUM EST	16
5.4.3	Stolen Goods	16
5.4.4	Rounding	18
5.4.5	ToDos	19
5.5	Grading Table	19
5.5.1	Internal commands	20
5.6	Title	21
5.7	Counters	22
6	Environments	22
6.1	Proof	22
6.2	Proof by contradiction	23
7	Development and support	24
8	Changelog	24
8.1	Version-Scheme	26
9	Translations	27

1 Abstract

This class provides a relative simple document-type for homework, mainly created for assignments at the University. This class is inherited from `article`, it is not perfect, but I am trying my very best.

2 Dependencies

2.1 Mandatory Dependencies

This class is build uppon `article`, so of course the first dependency is:

`article` 1992 LESLIE LAMPORT, 1994-97 FRANK MITTELBACH JOHANNES BRAAMS,
THE L^AT_EX-TEAM, <https://www.ctan.org/pkg/kvoptions>,

Because I am very lazy, the `homeworkassignment` is “a little bit” bloated. These are all required packages:

`kvoptions` HEIKO OBERDIEK, <https://www.ctan.org/pkg/kvoptions>,
for key=value-style options

`suffix` DAVID KASTRUP, <https://www.ctan.org/pkg/suffix>,
Makes it easy to define `\macro*` commands

`xifthen` JOSSELIN NOIREL, <https://www.ctan.org/pkg/xifthen>,
For if-else-structures

`translations` CLEMENS NIEDERBERGER, <https://www.ctan.org/pkg/translations>,
Implements an easy method of translations.

`amsmath` THE L^AT_EX-TEAM, FRANK MITTELBACH RAINER SCHÖPF, ET AL.,
<https://www.ctan.org/pkg/amsmath>,
For better math-typesetting

`amssymb` AMERICAN MATHEMATICAL SOCIETY, mirror.ctan.org/fonts/amsfonts/doc/amssymb.pdf,
For more mathematical symbols

`etoolbox` PHILIPP LEHMAN (INACTIVE), JOSEPH WRIGHT, <https://www.ctan.org/pkg/etoolbox>,
The package is a toolbox of programming facilities geared primarily towards L^AT_EXclass and package authors

`array` FRANK MITTELBACH, DAVID CARLISLE, THE L^AT_EX-TEAM, <https://www.ctan.org/pkg/array>,
A new implementations for tables and arrays

`xparse` FRANK MITTELBACH, CHRIS ROWLEY, DAVID CARLISLE, THE L^AT_EX3 PROJECT, <https://ctan.org/pkg/xparse>,
The package provides a high-level interface for producing documentlevel commands. In that way, it offers a replacement for L^AT_EX 2_ε's `\newcommand` macro, with significantly improved functionality.

`gillius` BOB TENNENT, <https://ctan.org/pkg/gillius>,
A Gillian Sans inspired font, used for all sans serifs fonts

`hyperref` [HTTPS://CTAN.ORG/PKG/HYPERREF](https://CTAN.ORG/PKG/HYPERREF), SebastianRahtz, HeikoOberdiek,
For hyperrefs, obviously

`xcolor` DR. UWE KERN, <https://www.ctan.org/pkg/xcolor>,
For coloring of ToDos

array possibly can be removed

2.2 Recommended Dependencies

These are not loaded automatically, but require a switch as option (see section 3). The switch is typically the name of the package.

`tikz` TILL TANTAU, MARK WIBROW, CHRISTIAN FEUERSÄNGER ET AL., <https://www.ctan.org/pkg/pgf>,
An incredible powerfull image tool. When loading TikZ, the homeworkas-signment automatically loads a shipload of TikZ-libraris and own styles. See section 3 for more informations

I intend to move these styles to a own package, so that they are usable without the homeworkas-signment

listings CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN, <https://www.ctan.org/pkg/listings>,
 For source-code. Sourcecode in the homeworkassignment is automatically
 framed, printed in scriptsize, and linebeals will be introduced

Loads required Packages

```

1 \RequirePackage{suffix}
2 \RequirePackage{fancyhdr}
3 \RequirePackage{xifthen}
4 \RequirePackage{translations}
5 \PassOptionsToPackage{fleqn}{amsmath}
6 \RequirePackage{amsmath}
7 \RequirePackage{amssymb}
8 \RequirePackage{etoolbox}
9 \RequirePackage{array}
10 \RequirePackage{xparse}
11 \RequirePackage{ifxetex}
12
13 \RequirePackage{wasysym}
14 \RequirePackage{adjustbox}
15
16 \RequirePackage{eso-pic}
17
18 \RequirePackage{xcolor}

```

3 Options

KV-Options is essential for this.

```

19 \RequirePackage{kvoptions}
20 \SetupKeyvalOptions{ family=hwa,
21   prefix=hwa@ }
22 \DeclareDefaultOption{\PassOptionsToClass{\CurrentOptionKey}{article}}

```

problemstyle=<1> These options allow the customizatuion of the displayed numbers. For Example,
 subproblemstyle=<1> if problemstyle=Roman, subproblemstyle=arabic, subsubproblemstyle=roman
 subsubproblemstyle=<1> is passed, The first subsubproblem of the first subproblem of the first problem
 would be labeled as **i)** of **Problem I.1**.

Available options are arabic, Alph, alph, Roman, and roman. Standard values are:
 problemstyle=arabic, subproblemstyle=alph, subsubproblemstyle=roman.

```

23 \DeclareStringOption[arabic]{problemsty}
24 \DeclareStringOption[alph]{subproblemsty}
25 \DeclareStringOption[roman]{subsubproblemsty}

```

tikz Loads TikZ-Package and a couple of styles, useful for papers in computer science
 and mathematics. See 3 for more informations

```

26 \DeclareBoolOption[false]{tikz}

```

helvet Helvet replaces the standard TeX Gyre sans serif font with a Helvetica clone. See
 4.3

	27 \DeclareBoolOption[false]{helvet}
listings	Loads listings package and sets listing layout to use a small fontsize. Adds indication for linebreaks.
	28 \DeclareBoolOption[false]{listings}
oneside, twoside	Changes layout. oneside is the complementary option to twoside Standard layout is twopaged.
	29 \DeclareBoolOption[true]{twoside}
	30 \DeclareComplementaryOption{oneside}{twoside}
onecolumn, twocolumn	Changes layout. onecolumn is the complementary option to twocolumn. Standard Layout has one columns
	31 \DeclareBoolOption[false]{twocolumn}
	32 \DeclareComplementaryOption{onecolumn}{twocolumn}
punchmark	Adds a mark for an hole puncher. Standard Layout has no marking.
	33 \DeclareBoolOption[false]{punchmark}
hlines=<1>	KeyValue-option. Takes the level of hlines. Available are all,decreased,header, none, with decreasing number of lines; none displays none, header only the one under headers and decreased adds the big line in the title, while all displays all.
	34 \DeclareStringOption[all]{hlines}
todos=<1>	KeyValue-option. Takes which Todos shall be displayed. Available are all (default),nolist,none. See subsection 5.4.5 for explanation of the levels.
	35 \DeclareStringOption[all]{todos}
unicode-math	Loads the unicode-math-package and overwrites the damn \QED-Command unicode-math introduces, that creates a filled out box and only works in math-mode, but not telling you that it only works in math-mode or overwrites an already existing command. For a reason, that currently (06 th of December 2018) slips my mind completly, unicode-math needs to be loaded after article, because it needs to be defined

ATTENTION: Please do never, never, never, never, never ever load unicode-math your self, because this breaks **everything**¹

\end{rant}

If XeTeX is used, the default option for this is true, otherwise it is false.
For the handling of the option, see 5.4.1

```

36 \ifxetex
37 \DeclareBoolOption[true]{unicodemath}
38 \else
39 \DeclareBoolOption[false]{unicodemath}
40 \fi

```

Loads article and processes the options

```

41 \ProcessKeyvalOptions*
42 \ifhwa@twoside
43 \PassOptionsToClass{twoside}{article}
44 \else
45 \PassOptionsToClass{oneside}{article}
46 \fi
47 \ifhwa@twocolumn
48 \PassOptionsToClass{twocolumn}{article}
49 \else
50 \PassOptionsToClass{onecolumn}{article}
51 \fi
52 \LoadClass{article}
53
54 \newboolean{hwa@todos@inplace}
55 \newboolean{hwa@todos@list}
56 \setboolean{hwa@todos@inplace}{true}
57 \setboolean{hwa@todos@list}{true}
58 \ifthenelse{\equal{\hwa@todos}{all}}{
59 }{
60   \ifthenelse{\equal{\hwa@todos}{nolist}}{
61     \ClassWarning{homeworkassignment}{You specified todos=none,
62       there will be no list of TODO}
63     \setboolean{hwa@todos@list}{false}
64   }{
65     \ifthenelse{\equal{\hwa@todos}{none}}{
66       \ClassWarning{homeworkassignment}{You specified todos=none,
67         there will be no TODOs printed in the final document}
68       \setboolean{hwa@todos@list}{false}
69       \setboolean{hwa@todos@inplace}{false}
70     }{
71       \ClassError{homeworkassignment}{\hwa@todos is not a valid value
72         for the option ‘todos’}
73     }
74   }
75 }

```

Load Hyperref (breaks if it is loaded before article

```

76 \RequirePackage{hyperref}

```

Loads listings, if wanted

```

77 \ifhwa@listings
78 \RequirePackage{listings}
79 \lstset{
80   frame = single,
81   breaklines = true,
82   postbreak=\raisebox{0ex}[0ex][0ex]{\ensuremath{\hookrightarrow}\space}},
83   basicstyle=\scriptsize
84 }
85 \else

```

```

86 \empty
87 \fi

```

`\hwa@hline@L...` Defines new commands to output desired lines and change the constant `\hwa@headrulewidth`

ATTENTION: `\hwa@hline@LONE` breaks the line automatically, in opposite to `\hwa@hline@LTWO`

```

88
89 \newcommand{\hwa@hline@LONE}{\vspace{.25cm} {\hrule height 2pt}
90   \vspace{.25cm}}
91 \newcommand{\hwa@hline@LTWO}{\vspace{.5cm} \hrule \vspace{.25cm}}
92 \newcommand{\hwa@headrulewidth}{.7pt}
93 \ifthenelse{\equal{\hwa@hlines}{all}}{
94   \renewcommand{\hwa@hline@LONE}{\vspace{.25cm} {\hrule height 2pt}
95     \vspace{.25cm}}
96   \renewcommand{\hwa@headrulewidth}{.7pt}
97   \renewcommand{\hwa@hline@LTWO}{\vspace{.5cm} \hrule \vspace{.25cm}}
98 }{
99   \ifthenelse{\equal{\hwa@hlines}{decreased}}{
100     \renewcommand{\hwa@hline@LONE}{\vspace{.25cm} {\hrule height 2pt}
101       \vspace{.25cm}}
102     \renewcommand{\hwa@headrulewidth}{.7pt}
103   }{\ifthenelse{\equal{\hwa@hlines}{header}}{
104     \renewcommand{\hwa@headrulewidth}{.7pt}
105   }{\ifthenelse{\equal{\hwa@hlines}{none}}{
106     \renewcommand{\hwa@headrulewidth}{0pt}
107   }{
108     \ClassError{homeworkassignment}{Value '\hwa@lines' for key 'hlines'
109       is not known}{The option hlines takes an argument to set which
110       hlines are drawn. Possible values are 'all','decreased' , 'header', and
111       'none'. 'all' is standard.}
112   }
113 }
114 \renewcommand{\hwa@hline@LONE}{~\vspace{.5cm}}
115 }
116 \renewcommand{\hwa@hline@LTWO}{\vspace{.75cm}}
117 }

```

If TikZ is wanted, load useful styles

```

118 \ifhwa@tikz
119 \RequirePackage{tikz}
120 \usetikzlibrary{shapes,arrows,positioning,decorations,
121   automata,backgrounds,petri,bending,
122   shapes.multipart}
123 \tikzset{
124   treenode/.style = {shape=circle, rounded corners,
125     draw, align=center},

```

```

126 graynode/.style = {fill=gray},
127 normalnode/.style = {treenode, font=\Large, bottom color=white},
128 array/.style = {rectangle split,
129     rectangle split horizontal,
130     rectangle split,
131     draw}
132 }
133 \fi

```

Make sure that this is the last Package loaded

```

134 \RequirePackage{geometry}
135 \ifhwa@twocolumn
136 \geometry{top=2cm, bottom=2cm, left=2cm,
137     headsep=14pt,hmarginratio={1:1}}
138 \else
139 \geometry{top=2cm, bottom=2cm, width=35em,
140     headsep=14pt,hmarginratio={4:3}}
141 \fi

```

4 Layout

Initially, the homeworkassignment had a verry *special* appereance, which became much more customizable with version 3.0, see ?? if you want to know how.

4.1 Headers & Footers

Sets the page-headers.

All headers are cleared before they get any Text — just to be sure.

The headers have the date on the subject and the author on the right side, the tutorial, sheat-title and deadline on the left side, the pagenumber is displayed in the right footer.

If the document is twopaged, the informations in the headers are splittet, so that author and subject are displayed only on odd pages and the title on even, the pagenumber is displayed on the right side on odd pages and on the left side on even pages.

On the first page, only the date and tutorial will be displayed in the header, the rest of infomration should be in the title.

```

142 \fancypagestyle{firstpage}{
143     %
144     \fancyhf{}
145     % clear all six fields
146     \renewcommand{\headrulewidth}{\hwa@headrulewidth}
147     \renewcommand{\footrulewidth}{0pt}
148     \fancyfoot[R]{\thepage}
149     \fancyhead[L]{\hwa@tutorium}
150     \fancyhead[R]{\@date } }

```



```

151 \fancypagestyle{followingpage}{
152   \fancyhf{}
153   \ifhwa@twoside % IF
154   \fancyhead[R0]{\@author}
155   \fancyhead[L0]{\hwa@kurs\
156     \hwa@tutorium}
157   \fancyhead[LE]{
158     \ifthenelse{\equal{\hwa@sheetTitle}{}}{\hwa@sheetTitle\}
159     \GetTranslation{abgabe}: \hwa@abgabe
160   }
161   \fancyfoot[R0,LE]{\thepage}
162
163   \else %ELSE
164
165   \fancyhead[R]{\hwa@kurs\
166     \@author}
167   \fancyhead[L]{\hwa@tutorium\
168     \ifthenelse{\equal{\hwa@sheetTitle}{}}{\hwa@sheetTitle\}
169     \GetTranslation{abgabe}: \hwa@abgabe}
170   \fancyfoot[R]{\thepage}
171   \fi %ENDIF
172   \renewcommand{\headrulewidth}{\hwa@headrulewidth}
173   \renewcommand{\footrulewidth}{0pt}
174 }
175 \pagestyle{followingpage}

```

4.2 Enhance Math Environments

A couple of things to make math environments more beautiful and compact.

`\theequation` Displays equation-numbers as upper-case roman numbers.

```
176 \renewcommand{\theequation}{\Roman{equation}}
```

`\allowdisplaybreaks` Allow pagebreaks in mathmode

```
177 \allowdisplaybreaks
```

4.3 Fonts

4.4 Serif (Default)

The default font for text in HWA is the TeX Gyre clone of Palatino, Pagella.

4.5 Sans Serif

`helvet` The default sans serif font is TeX Gyre Adventor. Including `helvet` in the class options will replace the default sans serif font Adventor with the Helvetica equivalent of TeX Gyre, Heros, for a more metric appearance.

```
178 \ifthenelse{\boolean{xetex}}{
```

```

179 \RequirePackage{fontspec}
180 \ifhwa@helvet
181   \setsansfont{TeX Gyre Heros}
182 \else
183   \setsansfont{TeX Gyre Adventor}
184 \fi
185 \setmainfont{TeX Gyre Pagella}
186 \setmonofont{Fira Mono}
187 }{
188 \ifhwa@helvet
189   \RequirePackage{tgheros}
190 \else
191   \RequirePackage{tgadventor}
192 \fi
193 \RequirePackage{tgpagella}
194 \RequirePackage{FiraMono}
195 }

```

4.5.1 Monospace

5 Commands

5.1 Constants

Defines some constants

`\hwa@pointboxsize` Explains it self.

```
196 \newcommand{\hwa@pointboxsize}{3em}
```

5.2 Document Informations

`\subject`, `\kurs` Sets the subject of the document. Takes the subject as argument. Standard Value is “Kein Kurs”
`\kurs` is deprecated.

```

197 \newcommand{\hwa@kurs}{?\GetTranslation{subject}?\} % To store the value
198 \newcommand{\subject}[1]{\renewcommand{\hwa@kurs}{#1}}
199 \newcommand{\kurs}[1]{\subject{#1}}

```

`\tutorial`, `\tutorium` Sets the tutorial of the author. Takes it as an argument. Standard Value is empty, so that this command can be omitted.
`\tutorium` is deprecated.

```

200 \newcommand{\hwa@tutorium}{?\GetTranslation{uebungsgruppe}?\} % To store the value
201 \newcommand{\tutorial}[1]{\renewcommand{\hwa@tutorium}{#1}}
202 \newcommand{\tutorium}[1]{\tutorial{#1}}

```

`\deadline`, `\abgabe` Sets the deadline of the document. Takes it as an argument. Standard value is `\today`.
`\abgabe` is deprecated

```
203 \newcommand{\hwa@abgabe}{\today} % To store the value
204 \newcommand{\deadline}[1]{\def\hwa@abgabe{#1}}
205 \newcommand{\abgabe}[1]{\deadline{#1}}
```

`\sheetTitle` Sets a descriptonal Title of the Sheet, will be written in the header of every page.

```
206 \newcommand{\hwa@sheetTitle}{}
207 \newcommand{\sheetTitle}[1]{\def\hwa@sheetTitle{#1}}
```

5.2.1 Inherited from article

`\author` Sets the author of the document.
`\date` Sets the date of the document.

5.3 Sectioning

Because the class is designed for Assignments, the sectioning-commands are different from Article, as layed out in the following.

5.3.1 Obsoledation of `\section` etc.

```
208 \renewcommand{\section}[1]{\ClassError{homeworkassignment}{The
209   Section-Command is disabled by homeworkassignment, please use one
210   of the improved mechanisms for new Exercises}}
211 \renewcommand{\subsection}[1]{\ClassError{homeworkassignment}{The
212   Subsection-Command is disabled by homeworkassignment, please use one
213   of the improved mechanisms for new Exercises}}
214 \renewcommand{\subsubsection}[1]{\ClassError{homeworkassignment}{The
215   Subsubsection-Command is disabled by homeworkassignment, please use one
216   of the improved mechanisms for new Exercises}}
```

5.3.2 internal Sectioning

`\hwa@problem`
`\hwa@subproblem`
`\hwa@subsubproblem` These commands work like their counterpart in article, except that there will be no number, nor will they increase a counter. Nevertheless, they will be shown in the table of contents. With version 4.0 they were made private, because I figured that they are not usefull enough and I am now able to introduce environments with the old names

```
217 \DeclareDocumentCommand\hwa@problem{m o}{\@startsection{problem}%Name
218   {1}%Level
219   {\z@}%indent
220   {-2em \@plus -1em \@minus -1em}%beforeskip
```

```

221 {1ex \@plus .5ex}%afterskip
222 {\normalfont\Large\sffamily\bfseries}%style
223 *{#1
224 \IfNoValueF{#2}{
225 \hfill
226 \frame{\framebox[\hwa@pointboxsize]{
227 \hfill\normalfont{\large/\small{#2}}}}
228 }
229 }
230 \addcontentsline{toc}{section}{#1}
231 }
232
233 \DeclareDocumentCommand\hwa@subproblem{m o}{\@startsection{subproblem}%Name
234 {2}%Level
235 {\z@}%indent
236 {-1em \@plus -.5em \@minus -.5em}%beforeskip
237 {.5ex \@plus .5ex}%afterskip
238 {\normalfont\large\sffamily\bfseries}%style
239 *{#1
240 \IfNoValueF{#2}{
241 \hfill\framebox[\hwa@pointboxsize]{
242 \hfill\normalfont\large/\small{#2}}
243 }
244 }
245 \addcontentsline{toc}{subsection}{#1}
246 }
247
248 \DeclareDocumentCommand\hwa@subsubproblem{m o}{\@startsection{subsubproblem}%Name
249 {3}%Level
250 {\z@}%indent
251 {-.5em}%beforeskip
252 {.5em}%afterskip
253 {\normalfont\sffamily\bfseries}%style
254 *{#1
255 \IfNoValueF{#2}{
256 \hfill\framebox[\hwa@pointboxsize]{
257 \hfill\normalfont\large/\scriptsize{#2}}
258 }
259 }
260 }
261

```

`\keyword` Creates a new Paragraph ,which will start with the Argument in Bold, followed by two non-breaking spaces.

```

262 \newcommand{\keyword}[1]{\@startsection{keyword}%Name
263 {4}%Level
264 {\parindent}%indent
265 {-.1em}%beforeskip
266 {\z@}%afterskip

```

```

267 {\normalfont \sffamily\bfseries}%style
268 *{#1~~}
269 }

```

The following Macros make use of `\keyword`, so it is suggested to use them instead.

```

\solution      They work like \keyword, but take only an optional Argument print out “So-
\proof         lution”, “Proof” “Given”, “To show”, “Assumption”, and “Suppose that”, re-
\given         spectively 2, via \keyword. If an argument is passed, they print out this argument
\toShow        after the keyword. They are not mentioned in the table of contents.
\toDisprove    270 \newcommand{\solution}[1] [] {\keyword{\GetTranslation{loesung}\ifstrempy{#1}{~}{~#1}:}}
\assumption    271 \newcommand{\toShow}[1] [] {\keyword{\GetTranslation{zuZeigen}\ifstrempy{#1}{~}{~#1}:}}
\supposeThat   272 \newcommand{\toDisprove}[1] [] {
                273   \keyword{\GetTranslation{zuWiderlegen}\ifstrempy{#1}{~}{~#1}:}}
                274 \newcommand{\given}[1] [] {\keyword{\GetTranslation{gegeben}\ifstrempy{#1}{~}{~#1}:}}
                275 \newcommand{\assumption}[1] [] {\keyword{\GetTranslation{Annahme}\ifstrempy{#1}{~}{~#1}:}}
                276 \newcommand{\supposeThat}[1] [] {\keyword{\GetTranslation{Angenommen-dass}\ifstrempy{#1}{~}{~#1}:}}

```

5.3.3 ‘better’ Sectioning

The following commands are an augmented version of the “plain” commands.

```

\newproblem
\newproblem*   These commands require no argument, and automatically create a numbered ti-
\newsubproblem tle. They have two optional arguments: \newproblem[#1]{#2} where #1 is the
\newsbsubproblem (sub(sub))problem-number and #2 are the points. If there is a number of Points
                  assigned to a (sub(sub))problem, then the command will generate a box to write
                  the reched number of points down next to it.

```

Normally, `\newproblem` adds the new Created Problem to the grading-table (see subsection 5.5), `\newproblem*` does not do this.

They use coutners, of course:

```

277 \newcounter{problem} \setcounter{problem}{0}
278 \newcounter{subproblem}[problem] \setcounter{subproblem}{0}
279 \newcounter{subsubproblem}[subproblem] \setcounter{subsubproblem}{0}
280
281 \DeclareDocumentCommand\newproblem{0{ } g}{
282   \stepcounter{problem}% to reset the lower counters
283   \ifthenelse{\equal{#1}{}}{
284     % empty
285   }{
286     \setcounter{problem}{#1}
287   }

```

²As of v1.6, Translations are added, depending on the choosen Language, there may be an other Text displayed.
See section 9 for all Translations

```

288
289 \IfNoValueTF{#2}{
290   \hwa@problem{\GetTranslation{aufgabe} \hwa@problemno}
291   \addToGradingTable{\# \hwa@problemno}
292 }{
293   \hwa@problem{\GetTranslation{aufgabe} \hwa@problemno}[#2]
294   \addToGradingTable{\# \hwa@problemno}{/#2}
295 }
296 }
297
298 \WithSuffix\newcommand\newproblem*[1] [] {\stepcounter{problem}
299 \ifthenelse{\equal{#1}{}} { } {
300   \stepcounter{problem}% to reset the lower counters
301   \setcounter{problem}{#1}}
302 \hwa@problem{\GetTranslation{aufgabe} \hwa@problemno}
303 }
304
305 \DeclareDocumentCommand\newsubproblem{0{ } g}{
306   \stepcounter{subproblem}
307   \ifthenelse{\equal{#1}{}} { } {
308     \setcounter{subproblem}{#1}}
309   \IfNoValueTF{#2}{
310     \hwa@subproblem{\GetTranslation{aufgabe}
311     \hwa@problemno}{.\hwa@subproblemno}
312   }
313   {
314     \hwa@subproblem{\GetTranslation{aufgabe}
315     \hwa@problemno}{.\hwa@subproblemno}[#2]
316   }
317 }
318
319 \DeclareDocumentCommand\newsussubproblem{0{ } g}{
320   \stepcounter{subsubproblem}
321   \ifthenelse{\equal{#1}{}} { } {\setcounter{subsubproblem}{#1}}
322   \IfNoValueTF{#2}{
323     \hwa@subsubproblem{\hwa@subsubproblemno}}
324   }
325   {
326     \hwa@subsubproblem{\hwa@subsubproblemno}[#2]
327   }
328 }
329

```

5.3.4 Even Better Sectioning-Environments

```

h   jk
330 \NewDocumentEnvironment{problem}{0{ } g}{
331   \newproblem[#1]{#2}
332   \newcommand{\task}[1]{

```

```

333   \begin{framed}
334     \keyword{Problem:} ##1
335   \end{framed}
336 }
337 }{}
338 \NewDocumentEnvironment{problem*}{0}{ g}{
339   \newproblem*[#1]{#2}
340   \newcommand{\task}[1]{
341     \begin{framed}
342       \keyword{Problem:} ##1
343     \end{framed}
344   }
345   \NewDocumentEnvironment{subproblem}{0}{ g}{
346     \newsubproblem[#1]{#2}
347     \NewDocumentEnvironment{subsubproblem}{0}{ g}{
348       \newssubsubproblem[#1]{#2}
349     }{}
350   }{}
351 }{}

```

5.4 Useful Macros

5.4.1 QUOD ERAT DEMUNSTRANDUM, End of Proof

`\QED`
`\EOP` Display a flushed-right *QED*, \square , or \blacksquare , respectively. `\qed` is not implemented, to
`\eop` keep compatibility to several Math-packages, which define the later.

```

352 \newcommand{\hwa@QED}{\begin{flushright}
353   \textsc{Qed}
354 \end{flushright}}
355 }
356 \newcommand{\QED}{\hwa@QED}
357
358 \ifhwa@unicodemath
359 \RequirePackage{unicode-math}
360 \AtBeginDocument{\let\QEDSymbol\QED}
361 \renewcommand{\QED}{\hwa@QED}
362 }
363 \fi
364
365 \newcommand{\EOP}{\begin{flushright}
366   \(\square\)
367 \end{flushright}}
368 }
369 \newcommand{\eop}{\hfill\(\blacksquare\)}

```

5.4.2 QUOD NON ERAT DEMUNSTARNDUM AT IUCUNDUM EST

`\QNE`
`\qned` Display a right-flushed *triangle*. `\QNE` displays it in a new line, `\qned` at the end of the same line.
 In Mathematical proofs this symbol is used to mark things, which we did not intend to proof, but are interesting anyway or things wick are not proofed mathematically, but are explained in a way which lets no doubt on their correctness.

```

370 \newcommand{\QNE}{\begin{flushright} \(\triangle\)
371 \end{flushright}
372 }
373 \newcommand{\qned}{\hfill\(\triangle\)}
```

5.4.3 Stolen Goods

»Das ist alles nur geklaut«

~Tobias Künzel

These Commands are not mine, they are all stolen from Alexander Bartolomey's³ `amath-Class`⁴

<code>\N</code>			
<code>\Z</code>	Defines a set of mathematical sets, which are verry usefull (see Table 1)		
<code>\R</code>			
<code>\Q</code>	Command	Output	Description
<code>\Compl</code>	<code>\N</code>	\mathbb{N}	Natural Numbers
<code>\F</code>	<code>\Z</code>	\mathbb{Z}	Whole Numbers
<code>\Primes</code>	<code>\Q</code>	\mathbb{Q}	Rational Numbers
	<code>\R</code>	\mathbb{R}	Real Numbers
	<code>\Compl</code>	\mathbb{C}	Complex Numbers
	<code>\F_n</code>	\mathbb{F}_n	Prime Field to base n
	<code>\Primes</code> ⁵	\mathbb{P}	Set of all Primes

Table 1: Field-Commands

```

374 \newcommand{\N}{\ensuremath{\mathbb{N}}}
375 \newcommand{\Z}{\ensuremath{\mathbb{Z}}}
376 \newcommand{\R}{\ensuremath{\mathbb{R}}}
377 \newcommand{\Q}{\ensuremath{\mathbb{Q}}}
378 \newcommand{\Compl}{\ensuremath{\mathbb{C}}}
379 \newcommand{\F}{\ensuremath{\mathbb{F}}}
380 % The last one is mine
```

³"Occloxiun" on GitHub:<https://github.com/occloxiun>

⁴`amath.sty` is part of Alexander Bartolomey's Alphabet Classes: <https://github.com/occloxiun/AlphabetClasses>

⁵Has to be `\Primes`, because `\P` is already in use

381 \newcommand{\Primes}{\ensuremath{\mathbb{P}}}

\GL		
\id	Output useful plaintext operators and functions. See table 2. Require math-	
\Var	mode	
\Perm		
\MComb		
\Comb	Command	Output
\Pot	\GL	GL
\Map	\id	id
\Hom	\Var	Var
\Ker	\Perm	Perm
\Intpol	\Comb	Comb
\Pol	\MComb	MComb
\Sol	\Pot	Pot
\Bin	\Map	Map
\charakteristik	\Hom	Hom
\fo	\Intpol	Intpol
\first	\Pol	Pol
\la	\Sol	Sol
\diff	\Bin	Bin
\partdiff	\charakteristik	char
\dx	\diff{<1>}	$\frac{d}{d<1>}$
\divides	\partdiff{<1>}	$\frac{\partial}{\partial<1>}$
\property	\divides and property	Prints a vertical line
\dim	\dx	dx
\Im	\excup	\cup
\excup	\fo	fo
\falls	\first	fi
	\la	la

Table 2: Common Functions

\falls prints out »falls«⁶

```

382 \DeclareMathOperator{\GL}{GL}
383 \DeclareMathOperator{\id}{id}
384 \DeclareMathOperator{\Var}{Var}
385 \DeclareMathOperator{\Perm}{Perm}
386 \DeclareMathOperator{\MComb}{MComb}
387 \DeclareMathOperator{\Comb}{Comb}
388 \DeclareMathOperator{\Pot}{Pot}
389 \DeclareMathOperator{\Map}{Map}
390 \DeclareMathOperator{\Hom}{Hom}
391 \DeclareMathOperator{\Ker}{Ker}
392 \DeclareMathOperator{\Intpol}{Intpol}

```

⁶In German, actual Translation may differ

```

393 \DeclareMathOperator{\Pol}{Pol}
394 \DeclareMathOperator{\Sol}{Sol}
395 \DeclareMathOperator{\Bin}{Bin}
396 \DeclareMathOperator{\charakteristik}{char}
397 \DeclareMathOperator{\fo}{fo}
398 \DeclareMathOperator{\first}{fi}
399 \DeclareMathOperator{\la}{la}
400
401 \newcommand{\diff}[1]{\ensuremath{\frac{d}{d\#1}}}
402 \newcommand{\partdiff}[1]{\ensuremath{\frac{\partial}{\partial\#1}}}
403 \newcommand{\dx}{\:dx}
404 \newcommand{\divides}{\ensuremath{\mid}}
405 \newcommand{\property}{\ensuremath{\imath}}
406
407 \renewcommand{\dim}[1][\text]{\ensuremath{\text{\dim}_{\#1}}}
408 \renewcommand{\Im}{\ensuremath{\text{\Im}}}
409
410 \newcommand{\excup}{\ensuremath{\stackrel{\cup}{\sim}}}
411 \newcommand{\falls}{\text{\GetTranslation{falls}}}

```

5.4.4 Rounding

Require mathmode

Command	Output	Meaning
$\lfloor <1> \rfloor$	$\lfloor <1> \rfloor$	floor $<1>$
$\lceil <1> \rceil$	$\lceil <1> \rceil$	ceil $<1>$
$\text{roundHU}\langle 1 \rangle$	$\lceil <1> \rceil$	Round $<1>$ “half up” ($\lceil <1> + \frac{1}{2} \rceil$)
$\text{roundHD}\langle 1 \rangle$	$\lfloor <1> \rfloor$	Round $<1>$ “half down” ($\lfloor <1> - \frac{1}{2} \rfloor$)

Table 3: Rounding Functions

```

412 \newcommand{\floor}[1]{\ensuremath{\left\lfloor \#1 \right\rfloor}}
413 \newcommand{\ceil}[1]{\ensuremath{\left\lceil \#1 \right\rceil}}
414 \newcommand{\roundHU}[1]{\ensuremath{\left\lceil \#1 \right\rceil}}
415 \newcommand{\roundHD}[1]{\ensuremath{\left\lfloor \#1 \right\rfloor}}

```

$\backslash\text{bigforall}$

$\backslash\text{bigexists}$ Redefines big versions of quantors, adds an h-skip to normal version.

```

416 \let\forall\forall
417 \let\exists\exists
418 \renewcommand{\forall}{\hspace{2pt}\forall\hspace{2pt}}
419 \renewcommand{\exists}{\hspace{2pt}\exists\hspace{2pt}}
420 \newcommand{\bigforall}{\mathsurround{4pt}\forall}
421 \newcommand{\bigexists}{\mathsurround{4pt}\exists}

```

5.4.5 ToDos

Utility for the Documentation of ToDos

`\todo` Creates a todo at the location of the command, highlighted in red. The ToDos will be listed after maketitle, unless the option `todos=nolist` or `todos=none` is specified.

```
422 \DeclareDocumentCommand\todo{G{}}{
423   \ifthenelse{\boolean{hwa@todos@inplace}}{
424     {\color{red}\textbf{~\label{TODO\alph{todoNum}}TODO~}\#1~}
425     \xdef\hwa@todoList@aux{\hwa@todoList@aux
426       \string\item\string\hyperref[TODO\alph{todoNum}]{TODO #1}
427     }
428     \stepcounter{todoNum}
429   }{}
430 }
```

Uses the internal `hwa@todo-counter`

```
431 \newcounter{todoNum} \setcounter{todoNum}{1}
```

`\hwa@tableOfTodos` Prints all ToDos

```
432 \DeclareDocumentCommand\hwa@tableOfTodos{}{
433   \ifthenelse{\boolean{hwa@todos@list}}{
434     \ifthenelse{\equal{\hwa@todoList }{\empty}}{\%Nothing
435     }{
436       {\color{red}
437         \hwa@problem{Table of ToDos}
438         \begin{itemize}
439           \hwa@todoList
440         \end{itemize}}
441     }
442   }{}
443 }
```

5.5 Grading Table

This Document-Class is still mainly designed for Homework, so it would be nice, if there was a table to write Grades into, wouldn't it?

`\addToGradingTable` Adds the given parameter as an exercise to the Grading-Table. All Problems, created with `\newproblem` are added automatically.

```
444 \DeclareDocumentCommand\addToGradingTable{m g}{
445   \xdef\hwa@gradingtbl@aux@defs{\hwa@gradingtbl@aux@defs|p{\hwa@pointboxsize}}
446   \xdef\hwa@gradingtbl@aux@lineOne{\hwa@gradingtbl@aux@lineOne{\#1} &}
447   \IfNoValueTF{\#2}{
448     \xdef\hwa@gradingtbl@aux@lineTwo{\hwa@gradingtbl@aux@lineTwo &}
449   }{
450     \xdef\hwa@gradingtbl@aux@lineTwo{\hwa@gradingtbl@aux@lineTwo\vfill\hfill
```

```

451      {\string\small #2} &}
452   }
453 }

```

`\makeGradingTable` Outputs a table to fill in the reached Points. Only shows Problems created by `\newproblem`.

Displays the according number of maximum points for each problem, if specified.

Displays the total number of maximum Problems, if given by Argument Like `\tableofcontent`, it needs a second run of \LaTeX , until all are added.

It will never overflow the Line-Width, thanks to an `adjustbox`. [#1]: *Optional*.

The total number of points reachable.

```

454 \DeclareDocumentCommand\makeGradingTable{o}{
455   \begin{table}[hb]
456     \centering
457     \large
458     \begin{adjustbox}{max width=\linewidth}
459       \expandafter\tabular\expandafter{\hwa@gradingtbl@defs ||p{\hwa@pointboxsize}||}\hline
460       \hwa@gradingtbl@lineOne \(\Sigma\) \\\hline\small
461       \hwa@gradingtbl@lineTwo \IfNoValueTF{#1}{~}{\vfill\hfill/#1}\vspace{.15cm}\\\hline
462     \endtabular
463   \end{adjustbox}
464 \end{table}
465 }

```

See example documents for output

5.5.1 Internal commands

`\hwa@gradingtbl@...` Defines macros whose contents will be written to the AUX-File and read in the next run, and the usable commands. The later will contain the information, but have to be defined (incase the aux-file does not exist)

```

466 \edef\hwa@gradingtbl@aux@defs{}
467 \newcommand{\hwa@gradingtbl@aux@lineOne}{}
468 \newcommand{\hwa@gradingtbl@aux@lineTwo}{}
469
470 \edef\hwa@gradingtbl@defs{}
471 \newcommand{\hwa@gradingtbl@lineOne}{}
472 \newcommand{\hwa@gradingtbl@lineTwo}{}

```

`\hwa@todoList@...` See `\hwa@gradingtbl@...`

```

473 \newcommand{\hwa@todoList}{}
474 \newcommand{\hwa@todoList@aux}{}
475 % \end{macro}
476 % \begin{macro}{\write\@auxout}
477 %   Write to aux
478 %   \begin{macrocode}
479 \AtEndDocument{%
480   \immediate\write\@auxout{%

```

```

481 \gdef\string\hwa@gradingtbl@defs{\hwa@gradingtbl@aux@defs}
482 }
483 \immediate\write\@auxout{%
484 \gdef\string\hwa@gradingtbl@lineOne{\hwa@gradingtbl@aux@lineOne}%
485 }
486 \immediate\write\@auxout{%
487 \gdef\string\hwa@gradingtbl@lineTwo{\hwa@gradingtbl@aux@lineTwo}%
488 }
489 \immediate\write\@auxout{%
490 \gdef\string\hwa@todoList{\hwa@todoList@aux}%
491 }
492 }

```

5.6 Title

`\maketitle` Overrides maketitle.

```

493 \renewcommand{\maketitle}{
494 \thispagestyle{firstpage}
495 \ifhwa@twocolumn{
496 \twocolumn[
497 \hwa@maketitletext
498 ]}
499 }\else{
500 \hwa@maketitletext
501 }\fi
502 \hwa@tableOfTodos
503 }

```

`\hwa@maketitletext` Prints out the title with author etc. Used to reduce code duplication for two- and onecolumn styles

```

504 \newcommand{\hwa@maketitletext}{
505 \begin{centering}
506 \huge{\textsf{\textbf{\hwa@kurs}}}\hwa@hline@LONE \large
507 \ifthenelse{equal{\hwa@sheetTitle}{}}{\textbf{\hwa@sheetTitle}}{}
508 \GetTranslation{abgabe}: \hwa@abgabe\
509 \hwa@hline@LTWO
510 \normalsize{\@author}\
511 \hwa@hline@LTWO \normalsize
512 \end{centering}
513 }
514 \ifthenelse{\boolean{hwa@punchmark}}{
515 \newcommand{\hwa@punchmarkRad}{3mm}
516 \newcommand{\hwa@punchmarkDistanceX}{12mm}
517 \newcommand{\hwa@punchmarkDistanceY}{40mm}
518 \AtBeginDocument{
519 % Where will the punch be?
520 \AddToShipoutPictureBG*{\AtPageUpperLeft{
521 \put(\LenToUnit{\hwa@punchmarkDistanceX-\hwa@punchmarkRad*2},\LenToUnit{-.5\paperheight-\hwa@punchmarkRad*2}){
522 \put(\LenToUnit{\hwa@punchmarkDistanceX-\hwa@punchmarkRad*2},\LenToUnit{-.5\paperheight+\hwa@punchmarkRad*2}){

```

```

523 % Punch-Positioningmark
524 \AddToShipoutPictureBG*{\AtPageUpperLeft{
525     \put(\LenToUnit{5mm},\LenToUnit{-.5\paperheight}){\tikz{\draw (0,0) -- (5mm,0);}}}
526 }
527 }{
528 }

```

5.7 Counters

The actual counters are defined in subsection 5.3.3.

Counter-Commands These are used to output the Exercise numbers in the desired style

```

529 \newcommand{\hwa@problemno}{\arabic{problem}}
530 \newcommand{\hwa@subproblemno}{\alph{subproblem}}
531 \newcommand{\hwa@subsubproblemno}{\roman{subsubproblem}}

```

\hwa@parseCounterStyle This takes a style-input (#1), one of the three previous defined commands (#2) and the corresponding counter (#3) to redefine #1, so that it corresponds to #2. See ?? for example usement.

```

532 \newcommand{\hwa@parseCounterStyle}[3]{
533     \ifthenelse{\equal{#1}{arabic}}{\renewcommand{#2}{\arabic{#3}}}
534     \ifthenelse{\equal{#1}{roman}}{\renewcommand{#2}{\roman{#3}}}
535     \ifthenelse{\equal{#1}{alph}}{\renewcommand{#2}{\alph{#3}}}
536     \ifthenelse{\equal{#1}{Alph}}{\renewcommand{#2}{\Alph{#3}}}
537     \ifthenelse{\equal{#1}{Roman}}{\renewcommand{#2}{\Roman{#3}}}
538     \renewcommand{#2}{\Roman{#3}}}
539     \ClassError{homeworkassignment}{Invalid Value #1 for
540         option Counter-Styling}{Possible Values are alph,
541         arabic, Arabic, roman or Roman.}

```

Redefines the three counter-commands:

```

542 \hwa@parseCounterStyle{\hwa@problemsty}{\hwa@problemno}{problem}
543 \hwa@parseCounterStyle{\hwa@subproblemsty}{\hwa@subproblemno}{subproblem}
544 \hwa@parseCounterStyle{\hwa@subsubproblemsty}{\hwa@subsubproblemno}{subsubproblem}

```

6 Environments

6.1 Proof

Used for proofs. Starts bth proof and ends with a End-Of-Proof symbol.

```

545 \NewDocumentEnvironment{proof}{G}{\GetTranslation{beweis}} 0{\QED}
546 {
547     \keyword{#1:~~}
548 }
549 {
550     #2
551 }

```

6.2 Proof by contradiction

Used for proofes. Starts bth proof and ends with a End-Of-Proof symbol.

```
552 \NewDocumentEnvironment{contradiction}{}  
553 {  
554   \begin{proof}{\GetTranslation{beweis}~\GetTranslation{per}~\GetTranslation{Widerspruch}}[\hfi  
555   }  
556   {  
557     \end{proof}  
558 }
```

7 Development and support

The package is developed at *GitHub*:

<https://github.com/ACHinrichs/LaTeX-templates>

Please refer to that site for any bug report or development information.

8 Changelog

v1.0 - 2016/10/23 Initial

v1.1 - 2016/11/02 ...

v1.2 - 2016/11/03 ...

v1.3 - 2016/12/01 • Provide the Class as .dtx file and more

v1.4 - 2017/04/29 • “Minor” bugfixes

v1.5 - 2017/04/29 • Problems are displayed in the table of contents. Type of numeration is now configurable.

v1.5.1 - 2017/04/29 • Bugfix

v1.5.2 - 2017/04/29 • Add version-number

v1.6 - 2017/05/02 • Add Translations (German and English)

- Add `\given` and `\toShow`
- Add `\QED`, `\EOP`, and `\eop`

v1.6.3 - 2017/05/05 • Bugfixes

v1.6.4 - 2017/05/09 • Change `\eop` to be in the same line

v1.7 - 2017/05/09 • Add \QNEd

v2.0 - 2017/05/23 "Layout 2.0"

- Change Margins
- Add Option to select older Page-Style
- Change standardlayout to twocolumn and twoside
- ~~Steal~~ Use Macros by Alexander Bartolomey (See 5.4.3)
- Add some TikZ-Styles
- Add round functions

v2.2 - 2017/06/17 • Add Grading-table

- Add `\keyword`, `\assumption`, and `\supposeThat`

- Add `\newproblem*`
 - Add `\sheetTitle`
 - Change equation-numbering to uppercase roman
- v2.2.1 - 2017/06/20** • Fix error with commands like `\solution` and `\keyword`.
- v2.4 - 2017/04/07** • Fix math alignment
- Add option for flushed left equations
 - Update amath port to use
- v3.0 - 2017/12/26** “WS 2017”
- Rename to `homeworkassignment`
 - Add Environment for various proofs
 - Add points for exercises and a place to fill them in
 - Add option to remove or decrease or remove the hlines
 - Remove legacy styles
 - Rework the documentation
 - Beautify Maths
 - Fix OneColumn-Maktitle-Bug
 - Fix Subproblem-Counter not being reset
 - Merry Christmas!
- v3.2 - 2018/12/06** Nikolaus Release
- Make XeLaTeX-Compatible
 - Fix `\newproblem` requiring a Problem-Number
 - Add `\toDisprove` macro similar to the `\toShow` macro
 - Add option for punchmarks
 - Add option to load `unicode-math` and work around a incompatibility
- v4.0 - 2019/04/17** Pre-Easter Release
- Add option to use `unicode-math`
 - Rename `\C` to `\Comp1`, because of a `unicode-math` incompatibility
 - Rework Fonts
 - Make `onecolumn` the default
 - Implement `ToDo`s
 - Replace `\problem`-commands by `problem` environments (which behave like `\newproblem`)
 - Add `Task-Command`
- v4.1 - 2019/05/03** Experimental Font Support
- Included `helvet` binary option for a more metric font support
 - Language and grammar fixes

8.1 Version-Scheme

Since Version 2.0 the following version-scheme applies:

Major Version has to be increased, if

- there are changes, which create visible changes in the output of existing documents (except for bugfixes), or
- a command is removed or changed in a way, that existing documents do not compile with the new version.

Minor Version has to be increased, if

- new backwards compatible commands are introduced
 - Bugfixes may be introduced too.

The minor version of stable releases is always even, the minor version of development versions is always odd. (0 counts as even).

Patches May be introduced on Stable Branch. With every non-document-breaking bugfix, the patch-number has to be incremented.

Because Fixing Bugs is a part of development, development-versions do not have numeric patch-numbers, but alphabetic identifiers, directly after the minor-version.

9 Translations

Homeworkassignment currently supports English and German, fallback language is German. Unfortunately these two are the only Languages I am capable of translating reliable, so if you want to use an other language, I would be very happy if you would help me to translate homeworkassignment! Please open an issue, author a pull-request or send me an e-mail.

```
559 \DeclareTranslationFallback{aufgabe}{Aufgabe}
560 \DeclareTranslationFallback{loesung}{L\"osung}
561 \DeclareTranslationFallback{beweis}{Beweis}
562 \DeclareTranslationFallback{uebungsgruppe}{\"Ubungsgruppe}
563 \DeclareTranslationFallback{abgabe}{Abgabe}
564 \DeclareTranslationFallback{zuZeigen}{Zu zeigen}
565 \DeclareTranslationFallback{zuWiderlegen}{Zu widerlegen}
566 \DeclareTranslationFallback{gegeben}{Gegeben}
567 \DeclareTranslationFallback{falls}{falls}
568 \DeclareTranslationFallback{Annahme}{Annahme}
569 \DeclareTranslationFallback{Angenommen-dass}{Angenommen, dass}
570 \DeclareTranslationFallback{per}{per}
571 \DeclareTranslationFallback{Widerspruch}{Widerspruch}
572
573 \DeclareTranslation{German}{aufgabe}{Aufgabe}
574 \DeclareTranslation{German}{loesung}{L\"osung}
575 \DeclareTranslation{German}{beweis}{Beweis}
576 \DeclareTranslation{German}{uebungsgruppe}{\"Ubungsgruppe}
577 \DeclareTranslation{German}{abgabe}{Abgabe}
578 \DeclareTranslation{German}{zuZeigen}{Zu zeigen}
579 \DeclareTranslation{German}{zuWiderlegen}{Zu widerlegen}
580 \DeclareTranslation{German}{gegeben}{Gegeben}
581 \DeclareTranslation{German}{falls}{falls}
582 \DeclareTranslation{German}{Falls}{Falls}
583 \DeclareTranslation{German}{Annahme}{Annahme}
584 \DeclareTranslation{German}{Angenommen-dass}{Angenommen, dass}
585 \DeclareTranslation{German}{per}{per}
586 \DeclareTranslation{German}{Widerspruch}{Widerspruch}
587
588 \DeclareTranslation{English}{aufgabe}{Problem}
589 \DeclareTranslation{English}{loesung}{Solution}
590 \DeclareTranslation{English}{beweis}{Proof}
591 \DeclareTranslation{English}{uebungsgruppe}{Tutorial}
592 \DeclareTranslation{English}{abgabe}{Deadline}
593 \DeclareTranslation{English}{zuZeigen}{To show}
594 \DeclareTranslation{English}{zuWiderlegen}{To disprove}
595 \DeclareTranslation{English}{gegeben}{Given}
596 \DeclareTranslation{English}{falls}{if}
597 \DeclareTranslation{English}{Falls}{If}
598 \DeclareTranslation{English}{Annahme}{Assumption}
599 \DeclareTranslation{English}{Angenommen-dass}{Suppose that}
600 \DeclareTranslation{English}{per}{by}
```

601 \DeclareTranslation{English}{Widerspruch}{contradiction}

End

The End

602 \endinput