

The homeworkassignment*class[†]

Adrian C Hinrichs
adrian.hinrichs@rwth-aachen.de

November 18, 2017

Contents

1	Abstract	2
2	Dependencies	2
2.1	Mandatory Dependencies	2
2.2	Recommended Dependencies	3
3	Options	4
4	Page-Layout	6
4.1	Headers & Footers	6
4.2	Enhance Mathenvironments	7
5	Commands	8
5.1	Counters and Constants	8
5.2	Document Informations	8
5.2.1	Inherited from <code>article</code>	9
5.3	Sectioning	9
5.3.1	‘plain’ Sectioning	9
5.3.2	‘better’ Sectioning	10
5.4	Useful Macros	12
5.4.1	QUOD ERAT DEMUNSTARNDUM, End of Proof	12
5.4.2	QUOD NON ERAT DEMUNSTARNDUM AT IUCUNDUM EST	12
5.4.3	Stolen Goods	12
5.4.4	Rounding	13
5.5	Grading Table	14
6	Development and support	15

*The name was changed with version v3.0, to become compatible with CTANs guidelines and to maintain a degree of backwards compatibility. The class was called `HomeworkAssignment` prior to v3.0

[†]This document corresponds to `homeworkassignment` v2.5f, dated 2017/11/18.

7	Changelog	15
7.1	Version-Scheme	16
8	Examples	17
9	Translations	17
10	Implementation	18
10.1	Packages & Options	18
10.2	TikZ-Styles	18
10.3	Geometry	18
10.4	Internal commands	18
10.4.1	Counter-Commands	18
10.4.2	Counter-Style Parser	18
10.4.3	Counter-Commands II	19
10.4.4	Grading-table	19
10.5	Commands	20

1 Abstract

This class provides a relative simple document-type for homework, mainly created for assignments at the University This class is inherited from `article`, it is not perfect, but I am trying my very best.

2 Dependencies

2.1 Mandatory Dependencies

This class is build uppon article, so of course the first dependency is:

`article` 1992 LESLIE LAMPORT, 1994-97 FRANK MITTELBACH JOHANNES BRAAMS, THE L^AT_EX-TEAM, <https://www.ctan.org/pkg/kvoptions>,

Because I am very lazy, the `homeworkassignment` is “a little bit” bloated. These are all required packages:

`kvoptions` HEIKO OBERDIEK, <https://www.ctan.org/pkg/kvoptions>,
for `key=value`-style options

`suffix` DAVID KASTRUP, <https://www.ctan.org/pkg/suffix>,
Makes it easy to define `\macro*` commands

`xifthen` JOSSELIN NOIREL, <https://www.ctan.org/pkg/xifthen>,
For if-else-structures

`translations` CLEMENS NIEDERBERGER, <https://www.ctan.org/pkg/translations>,
Implements an easy method of translations.

amsmath THE L^AT_EX-TEAM, FRANK MITTELBACH RAINER SCHÖPF, ET AL.,
<https://www.ctan.org/pkg/amsmath>,
 For better math-typesetting

amssymb AMERICAN MATHEMATICAL SOCIETY, [mirror.ctan.org/fonts/amsfonts/doc/amssymb.pdf](https://www.ctan.org/mirror.ctan.org/fonts/amsfonts/doc/amssymb.pdf),
 For more mathematical symbols

etoolbox PHILIPP LEHMAN (INACTIVE), JOSEPH WRIGHT, <https://www.ctan.org/pkg/etoolbox>,
 The package is a toolbox of programming facilities geared primarily towards L^AT_EXclass and package authors

array FRANK MITTELBACH, DAVID CARLISLE, THE L^AT_EX-TEAM, <https://www.ctan.org/pkg/array>,
 A new implementations for tables and arrays

xparse FRANK MITTELBACH, CHRIS ROWLEY, DAVID CARLISLE, THE L^AT_EX3 PROJECT, <https://ctan.org/pkg/xparse>,
 The package provides a high-level interface for producing documentlevel commands. In that way, it offers a replacement for L^AT_EX2_ε's `\newcommand` macro, with significantly improved functionality.

gillius BOB TENNENT, <https://ctan.org/pkg/gillius>,
 A Gillian Sans inspired font, used for all sans serifs fonts

array possibly can be removed

2.2 Recommended Dependencies

These are not loaded automatically, but require a switch as option (see section 3). The switch is typically the name of the package.

tikz TILL TANTAU, MARK WIBROW, CHRISTIAN FEUERSÄNGER ET AL., <https://www.ctan.org/pkg/pgf>,
 An incredible powerfull image tool. When loading TikZ, the homeworkassignment automatically loads a shipload of TikZ-librarys and own styles. See section 3 for more informations

listings CARSTEN HEINZ, BROOKS MOSES, JOBST HOFFMANN, <https://www.ctan.org/pkg/listings>,
 For source-code. Sourcecode in the homeworkassignment is automatically framed, printed in `scriptsize`, and linebeals will be introduced

I intend to move these styles to a own package, so that they are usable without the homeworkassignment

Loads required Packages

```
1 \RequirePackage{suffix}
2 \RequirePackage{fancyhdr}
3 \RequirePackage{xifthen}
4 \RequirePackage{translations}
5 \PassOptionsToPackage{fleqn}{amsmath}
6 \RequirePackage{amsmath}
```

```

7 \RequirePackage{amssymb}
8 \RequirePackage{etoolbox}
9 \RequirePackage{array}
10 \RequirePackage{xparse}
11 \RequirePackage{gillius2}

```

3 Options

KV-Options is essential for this.

```

12 \RequirePackage{kvoptions}
13 \SetupKeyvalOptions{ family=hwa,
14   prefix=hwa@ }
15 \DeclareDefaultOption{\PassOptionsToClass{\CurrentOptionKey}{article}}

```

`problemstyle=<1>` These options allow the customization of the displayed numbers. For Example, if
`subproblemstyle=<1>` `problemstyle=Roman`, `subproblemstyle=arabic`, `subsubproblemstyle=roman`
`subsubproblemstyle=<1>` is passed, The first subsubproblem of the first subproblem of the first problem
would be labeled as **i**) of **Problem I.1**.

Available options are `arabic`, `Alph`, `alph`, `Roman`, and `roman`. Standard values are:
`problemstyle=arabic`, `subproblemstyle=alph`, `subsubproblemstyle=roman`.

```

16 \DeclareStringOption[arabic]{problemsty}
17 \DeclareStringOption[alph]{subproblemsty}
18 \DeclareStringOption[roman]{subsubproblemsty}

```

`tikz` Loads TikZ-Package and a couple of Styles, usefull for Papers in Computer-Science
and mathematics. See 3 for more informations

```

19 \DeclareBoolOption[false]{tikz}

```

`listings` Loads Listings Package and sets listing-layout to use a small fontsize. Adds
indication for linebreaks.

```

20 \DeclareBoolOption[false]{listings}

```

`oneside, twoside` Changes layout. `oneside` is the complementary option to `twoside`
Standard layout is `twopaged`.

```

21 \DeclareBoolOption[true]{twoside}
22 \DeclareComplementaryOption{oneside}{twoside}

```

`onecolumn, twocolumn` Changes layout. `onecolumn` is the complementary option to `twocolumn`.
Standard Layout has two columns

```

23 \DeclareBoolOption[true]{twocolumn}
24 \DeclareComplementaryOption{onecolumn}{twocolumn}

```

`hlines=<1>` Key-Value-option. Takes the level of hlines. Available are `all`, `decreased`, `header`,
`none`, with decreasing number of lines; `none` displays none, `header` only the one
under headers and `decreased` adds the big line in the title, while `all` displays all.

```

25 \DeclareStringOption[all]{hlines}

```

Loads article and processes the options

```

26 \ProcessKeyvalOptions*
27 \ifhwa@twoside

```

```

28 \PassOptionsToClass{twoside}{article}
29 \else
30 \PassOptionsToClass{oneside}{article}
31 \fi
32 \ifhwa@twocolumn
33 \PassOptionsToClass{twocolumn}{article}
34 \else
35 \PassOptionsToClass{onecolumn}{article}
36 \fi
37 \ifhwa@listings
38 \RequirePackage{listings}
39 \lstset{
40   frame = single,
41   breaklines = true,
42   postbreak=\raisebox{0ex}[0ex][0ex]{\ensuremath{\hookrightarrow}\space}},
43   basicstyle=\scriptsize
44 }
45 \else
46 \empty
47 \fi
48 \LoadClass{article}

```

`\hwa@hline@L...` Defines new commands to output desired lines and change the constant `\hwa@headrulewidth`

ATTENTION: `\hwa@hline@LONE` breaks the line automatically, in opposite to `\hwa@hline@LTWO`

```

49
50 \newcommand{\hwa@hline@LONE}{\vspace{.25cm} {\hrule height 2pt}
51   \vspace{.25cm}}
52 \newcommand{\hwa@hline@LTWO}{\vspace{.5cm} \hrule \vspace{.25cm}}
53 \newcommand{\hwa@headrulewidth}{.7pt}
54 \ifthenelse{equal{\hwa@hlines}{all}}{
55   \renewcommand{\hwa@hline@LONE}{\vspace{.25cm} {\hrule height 2pt}
56     \vspace{.25cm}}
57   \renewcommand{\hwa@headrulewidth}{.7pt}
58   \renewcommand{\hwa@hline@LTWO}{\vspace{.5cm} \hrule \vspace{.25cm}}
59 }{
60   \ifthenelse{equal{\hwa@hlines}{decreased}}{
61     \renewcommand{\hwa@hline@LONE}{\vspace{.25cm} {\hrule height 2pt}
62       \vspace{.25cm}}
63     \renewcommand{\hwa@headrulewidth}{.7pt}
64   }{\ifthenelse{equal{\hwa@hlines}{header}}{
65     \renewcommand{\hwa@headrulewidth}{.7pt}
66   }{\ifthenelse{equal{\hwa@hlines}{none}}{
67     \renewcommand{\hwa@headrulewidth}{0pt}
68   }{
69     \ClassError{homeworkassignment}{Value '\hwa@lines' for key 'hlines'

```

```

70         is not known}{The option hlines takes an argument to set which
71         hlines are drawn. Possible values are 'all','decreased' , 'header', and
72         'none'. 'all' is standard.}
73     }
74 }
75 \renewcommand{\hwa@hline@LONE}{~\\vspace{.5cm}}
76 }
77 \renewcommand{\hwa@hline@LTWO}{\vspace{.75cm}}
78 }

```

If tikz is Wanted, load Usefull Styles

```

79 \ifhwa@tikz
80 \RequirePackage{tikz}
81 \usetikzlibrary{shapes,arrows,positioning,decorations,
82     automata,backgrounds,petri,bending,
83     shapes.multipart}
84 \tikzset{
85     treenode/.style = {shape=circle, rounded corners,
86         draw, align=center},
87     graynode/.style = {fill=gray},
88     normalnode/.style = {treenode, font=\Large, bottom color=white},
89     array/.style = {rectangle split,
90         rectangle split horizontal,
91         rectangle split,
92         draw}
93 }
94 \fi

```

Make sure that this is the last Package loaded

```

95 \RequirePackage{geometry}
96 \ifhwa@twocolumn
97 \geometry{top=2cm, bottom=2cm, left=2cm,
98     headsep=14pt,hmarginratio={1:1}}
99 \else
100 \geometry{top=2cm, bottom=2cm, width=35em,
101     headsep=14pt,hmarginratio={4:3}}
102 \fi

```

4 Page-Layout

Initially, the homeworkassignment had a verry *special* appereance, which became much mor customizable with version 3.0, see ?? if you want to know how.

4.1 Headers & Footers

Sets the page-headers.

All headers are cleared before they get any Text — just to be sure.

The headers have the date on the subject and the author on the right side, the tutorial, sheet-title and deadline on the left side, the pagenumber is displayed in the right footer.

If the document is twopaged, the informations in the headers are splittet, so that author and subject are displayed only on odd pages and the title on even, the pagenumber is displayed on the right side on odd pages and on the left side on even pages.

On the first page, only the date and tutorial will be displayed in the header, the rest of infomration should be in the title.

```

103 \fancypagestyle{firstpage}{
104   %
105   \fancyhf{}
106   % clear all six fields
107   \renewcommand{\headrulewidth}{\hwa@headrulewidth}
108   \renewcommand{\footrulewidth}{0pt}
109   \fancyfoot[R]{\thepage}
110   \fancyhead[L]{\hwa@tutorial}
111   \fancyhead[R]{\@date } }
112 \fancypagestyle{followingpage}{
113   \fancyhf{}
114   \ifhwa@twoside % IF
115   \fancyhead[R0]{\@author}
116   \fancyhead[L0]{\hwa@kurs\
117     \hwa@tutorial}
118   \fancyhead[LE]{
119     \ifthenelse{\equal{\hwa@sheetTitle}{}}{\}{\hwa@sheetTitle\\}
120     \GetTranslation{abgabe}: \hwa@abgabe
121   }
122   \fancyfoot[R0,LE]{\thepage}
123
124   \else %ELSE
125
126   \fancyhead[R]{\hwa@kurs\
127     \@author}
128   \fancyhead[L]{\hwa@tutorial\
129     \ifthenelse{\equal{\hwa@sheetTitle}{}}{\}{\hwa@sheetTitle\\}
130     \GetTranslation{abgabe}: \hwa@abgabe}
131   \fancyfoot[R]{\thepage}
132   \fi %ENDIF
133   \renewcommand{\headrulewidth}{\hwa@headrulewidth}
134   \renewcommand{\footrulewidth}{0pt}
135 }
136 \pagestyle{followingpage}

```

4.2 Enhance Mathenvironments

A couple of thigns, to make math-environments more beautifull and compact.

`\theequation` Displays equation-numbers as upper-case roman numbers.
137 `\renewcommand{\theequation}{\Roman{equation}}`

`\allowdisplaybreaks` Allow pagebreaks in Mathmode
138 `\allowdisplaybreaks`

5 Commands

5.1 Counters and Constants

Defines some constants

`\hwa@pointboxsize` Explains it self.
139 `\newcommand{\hwa@pointboxsize}{3em}`

5.2 Document Informations

`\subject`, `\kurs` Sets the subject of the document. Takes the subject as argument. Standard Value is “Kein Kurs”
`\kurs` is deprecated.

```
140 \newcommand{\hwa@kurs}{?\GetTranslation{subject}??} % To store the value
141 \newcommand{\subject}[1]{\renewcommand{\hwa@kurs}{#1}}
142 \newcommand{\kurs}[1]{\subject{#1}}
```

`\tutorial`, `\tutorium` Sets the tutorial of the author. Takes it as an argument. Standard Value is empty, so that this command can be omitted.
`\tutorium` is deprecated.

```
143 \newcommand{\hwa@tutorium}{?\GetTranslation{uebungsgruppe}??} % To store the value
144 \newcommand{\tutorial}[1]{\renewcommand{\hwa@tutorium}{#1}}
145 \newcommand{\tutorium}[1]{\tutorial{#1}}
```

`\deadline`, `\abgabe` Sets the deadline of the document. Takes it as an argument. Standard value is `\today`.
`\abgabe` is deprecated

```
146 \newcommand{\hwa@abgabe}{\today} % To store the value
147 \newcommand{\deadline}[1]{\def\hwa@abgabe{#1}}
148 \newcommand{\abgabe}[1]{\deadline{#1}}
```

`\sheetTitle` Sets a descriptonal Title of the Sheet, will be written in the header of every page.
149 `\newcommand{\hwa@sheetTitle}{}`
150 `\newcommand{\sheetTitle}[1]{\def\hwa@sheetTitle{#1}}`

5.2.1 Inherited from article

`\author` Sets the author of the document.
`\date` Sets the date of the document.

5.3 Sectioning

Because the class is designed for Assignments, the sectioning-commands are different from Article

5.3.1 ‘plain’ Sectioning

`\problem`
`\subproblem` These commands work like their counterpart in article, except that there will be
`\subsubproblem` no number, nor will they increase a counter. Nevertheless, they will be shown in the table of contents.

```
151 \DeclareDocumentCommand\problem{m o}{\@startsection{problem}%Name
152   {1}%Level
153   {\z@}%indent
154   {-2em \@plus -1em \@minus -1em}%beforeskip
155   {1ex \@plus .5ex}%afterskip
156   {\normalfont\Large\sffamily\bfseries}%style
157   *{#1
158     \IfNoValueF{#2}{
159       \hfill
160       \frame{\framebox[\hwa@pointboxsize]{
161         \hfill \normalfont{\large/\small{#2}}}}
162     }
163   }
164   \addcontentsline{toc}{section}{#1}
165 }
166
167 \DeclareDocumentCommand\subproblem{m o}{\@startsection{subproblem}%Name
168   {2}%Level
169   {\z@}%indent
170   {-1em \@plus -.5em \@minus -.5em}%beforeskip
171   {.5ex \@plus .5ex}%afterskip
172   {\normalfont\large\sffamily\bfseries}%style
173   *{#1
174     \IfNoValueF{#2}{
175       \hfill \framebox[\hwa@pointboxsize]{
176         \hfill \normalfont\large/\small{#2}}
177     }
178   }
179   \addcontentsline{toc}{subsection}{#1}
180 }
181
```

```

182 \DeclareDocumentCommand\subsubproblem{m o}{\@startsection{subsubproblem}%Name
183   {3}%Level
184   {\z@}%indent
185   {- .5em}%beforeskip
186   {.5em}%afterskip
187   {\normalfont \sffamily\bfseries}%style
188   *{#1
189     \IfNoValueF{#2}{
190       \hfill \framebox[\hwa@pointboxsize]{
191         \hfill\normalfont\large/\scriptsize{#2}}
192     }
193   }
194 }
195

```

\keyword Creates a new Paragraph ,which will start with the Argument in Bold, followed by two non-breaking spaces.

```

196 \newcommand{\keyword}[1]{\@startsection{keyword}%Name
197   {4}%Level
198   {\parindent}%indent
199   {- .1em}%beforeskip
200   {\z@}%afterskip
201   {\normalfont \sffamily\bfseries}%style
202   *{#1~~}
203 }

```

The following Macros make use of **\keyword**, so it is suggested to use them instead.

\solution \proof \given \toShow \assumption \supposeThat	They work like \keyword , but take only an optional Argument print out “Solution”, “Proof” “Given”, “To show”, “Assumption”, and “Suppose that”, respectively ¹ , via \keyword . If an argument is passed, they print out this argument after the keyword. They are not mentioned in the table of contents.	<pre> 204 \newcommand{\solution}[1][\keyword{\GetTranslation{loesung}}\ifstrempy{#1}{~#1:}} 205 \newcommand{\proof}[1][\keyword{\GetTranslation{beweis}}\ifstrempy{#1}{~#1:}} 206 \newcommand{\toShow}[1][\keyword{\GetTranslation{zuZeigen}}\ifstrempy{#1}{~#1:}} 207 \newcommand{\given}[1][\keyword{\GetTranslation{gegeben}}\ifstrempy{#1}{~#1:}} 208 \newcommand{\assumption}[1][\keyword{\GetTranslation{Annahme}}\ifstrempy{#1}{~#1:}} 209 \newcommand{\supposeThat}[1][\keyword{\GetTranslation{Angenommen-dass}}\ifstrempy{#1}{~#1:}} </pre>
---	--	---

5.3.2 ‘better’ Sectioning

The following commands are an augmented version of the “plain” commands.

\newproblem \newproblem* \newsproblem \newsproblem	These commands require no argument, and automatically create a numbered title. <hr style="width: 20%; margin-left: 0;"/> ¹ As of v1.6, Translations are added, depending on the choosen Language, there may be an other Text displayed. See section 9 for all Translations
---	---

The optional Argument is the new value for the corresponding counter.
Normally, `\newproblem` adds the new Created Problem to the grading-table (see subsection 5.5), `\newproblem*` does not do this.

They use counters, of course:

```

210 \newcounter{problem} \setcounter{problem}{0}
211 \newcounter{subproblem}[problem] \setcounter{subproblem}{0}
212 \newcounter{subsubproblem}[subproblem] \setcounter{subsubproblem}{0}
213
214 \DeclareDocumentCommand\newproblem{0}{ g}{
215   \IfNoValueTF{#2}{
216     \newproblem* [#1]
217     \addToGradingTable{\# \hwa@problemno}
218   }{
219     \IfNoValueF{#1}{
220       \stepcounter{problem}% to reset the lower counters
221       \setcounter{problem}{#1}
222     }
223     \problem{\GetTranslation{aufgabe} \hwa@problemno}[#2]
224     \addToGradingTable{\# \hwa@problemno}{/#2}
225   }
226 }
227
228 \WithSuffix\newcommand\newproblem* [1] [] {\stepcounter{problem}
229   \ifthenelse{\equal{#1}{}} { } {
230     \stepcounter{problem}% to reset the lower counters
231     \setcounter{problem}{#1}}
232   \problem{\GetTranslation{aufgabe} \hwa@problemno}
233 }
234
235 \DeclareDocumentCommand\newsubproblem{0}{ g}{
236   \stepcounter{subproblem}
237   \ifthenelse{\equal{#1}{}} { } {
238     \setcounter{subproblem}{#1}}
239   \IfNoValueTF{#2}{
240     \subproblem{\GetTranslation{aufgabe}
241       \hwa@problemno}.\hwa@subproblemno}
242   }
243   {
244     \subproblem{\GetTranslation{aufgabe}
245       \hwa@problemno}.\hwa@subproblemno}[#2]
246   }
247 }
248
249 \DeclareDocumentCommand\newsbsubproblem{0}{ g}{
250   \stepcounter{subsubproblem}
251   \ifthenelse{\equal{#1}{}} { } {\setcounter{subsubproblem}{#1}}
252   \IfNoValueTF{#2}{
253     \subsubproblem{\hwa@subsubproblemno}}

```

```

254 }
255 {
256   \subsubproblem{\hwa@subsubproblemno})[#2]
257 }
258 }
259

```

5.4 Useful Macros

5.4.1 QUOD ERAT DEMUNSTARNDUM, End of Proof

```

\QED
\EOP  Display a flushed-right QED,  $\square$ , or  $\blacksquare$ , respectively. \qed is not implemented, to
\eop  keep compatibility to several Math-packages, which define the later.

260 \newcommand{\QED}{\begin{flushright}
261   \textsc{Qed}
262 \end{flushright}}
263 }
264 \newcommand{\EOP}{\begin{flushright}
265   \(\square\)
266 \end{flushright}}
267 }
268 \newcommand{\eop}{\hfill\(\blacksquare\)}

```

5.4.2 QUOD NON ERAT DEMUNSTARNDUM AT IUCUNDUM EST

```

\QNED
\qned  Display a flushed-right triangle. \QNED displays it in a new line, \qned at the end
      of the same line.
      In Mathematical proofs this symbol is used to mark things, which we did not intend
      to proof, but are interesting anyway or things wich are not proofed mathematically,
      but are explained in a ay, whcih lets no doubt on their correctness.

269 \newcommand{\QNED}{\begin{flushright} \(\triangle\)
270 \end{flushright}}
271 } \newcommand{\qned}{\hfill\(\triangle\)}

```

5.4.3 Stolen Goods

»Das ist alles nur geklaut«

~Tobias Künzel

These Commands are not mine, they are all stolen from Alexander Bartolomey's²
`amath-Class`³

\N Defines a set of mathematical sets, which are verry usefull (see Table 1)

\Z

\R

\Q

\C

\F

\Primes

²“Occloxiun” on GitHub:<https://github.com/occloxiun>

³`amath.sty` is part of Alexander Bartolomey's Alphabet Classes: <https://github.com/occloxiun/AlphabetClasses>

Command	Output	Description
<code>\N</code>	\mathbb{N}	Natural Numbers
<code>\Z</code>	\mathbb{Z}	Whole Numbers
<code>\Q</code>	\mathbb{Q}	Rational Numbers
<code>\R</code>	\mathbb{R}	Real Numbers
<code>\C</code>	\mathbb{C}	Complex Numbers
<code>\F_n</code>	\mathbb{F}_n	Prime Field to base n
<code>\Primes</code> ⁴	\mathbb{P}	Set of all Primes

Table 1: Field-Commands

Functions and Operators Output usefull Plaintext-Operators and Functions. See table 2. Require Mathmode

Command	Output
<code>\divides</code> and <code>property</code>	Prints a vertical Bar
<code>\Var</code>	Var
<code>\Perm</code>	Perm
<code>\Comb</code>	Comb
<code>\MComb</code>	MComb
<code>\Pot</code>	Pot
<code>\Map</code>	Map
<code>\Bin</code>	Bin
<code>\GL</code>	GL
<code>\id</code>	id
<code>\dx</code>	dx
<code>\excup</code>	$\dot{\cup}$
<code>\diff{<1>}</code>	$\frac{d}{d<1>}$

Table 2: Text-like Functions

`\falls` prints out »falls«⁵

5.4.4 Rounding

Require Mathmode

Command	Output	Meaning
<code>\floor{<1>}</code>	$\lfloor <1> \rfloor$	floor $<1>$
<code>\ceil{<1>}</code>	$\lceil <1> \rceil$	ceil $<1>$
<code>\roundHU{<1>}</code>	$\lfloor <1> \rfloor$	Round $<1>$ “half up” ($\lfloor <1> + \frac{1}{2} \rfloor$)
<code>\roundHD{<1>}</code>	$\lfloor <1> \rfloor$	Round $<1>$ “half down” ($-\lfloor <1> - \frac{1}{2} \rfloor$)

Table 3: Rounding Functions

⁴Has to be `\Primes`, because `\P` is already in use

⁵In German, actual Translation may differ

5.5 Grading Table

This Document-Class is still mainly designed for Homework, so it would be nice, if there was a table to write Grades into, wouldn't it?

`\addToGradingTable` Adds the given parameter as an exercise to the Grading-Table. All Problems, created with `\newproblem` are added automatically.

`\makeGradingTable` Prints out the Table containig all Defined exercises (\neq Problems). Like `\tableofcontent`, it needs a second run of L^AT_EX, until all are added. See example documents fot output

6 Development and support

The package is developed at *GitHub*:

<https://github.com/ACHinrichs/LaTeX-templates>

Please refer to that site for any bug report or development information.

7 Changelog

v1.0 - 2016/10/23 Initial

v1.1 - 2016/11/02 ...

v1.2 - 2016/11/03 ...

v1.3 - 2016/12/01 • Provide the Class as .dtx file and more

v1.4 - 2017/04/29 • “Minor” bugfixes

v1.5 - 2017/04/29 • Problems are displayed in the table of contents. Type of numeration is now configurable.

v1.5.1 - 2017/04/29 • Bugfix

v1.5.2 - 2017/04/29 • Add version-number

v1.6 - 2017/05/02 • Add Translations (German and English)

 • Add `\given` and `\toShow`

 • Add `\QED`, `\EOP`, and `\eop`

v1.6.3 - 2017/05/05 • Bugfixes

v1.6.4 - 2017/05/09 • Change `\eop` to be in the same line

v1.7 - 2017/05/09 • Add `\QED`

v2.0 - 2017/05/23 “Layout 2.0”

 • Change Margins

 • Add Option to select older Page-Style

 • Change `standardlayout` to `twocolumn` and `twoside`

 • Steal Use Macros by Alexander Bartolomey (See 5.4.3)

 • Add some TikZ-Styles

 • Add round functions

v2.2 - 2017/06/17 • Add Grading-table

 • Add `\keyword`, `\assumption`, and `\supposeThat`

- Add `\newproblem*`
 - Add `\sheetTitle`
 - Change equation-numbering to uppercase roman
- v2.2.1 - 2017/06/20** • Fix error with commands like `\solution` and `\keyword`.
- v2.4 - 2017/04/07** • Fix math alignment
- Add option for flushed left equations
 - Update amath port to use
- v3.0 - pending** “WS 2017”
- Rename to `homeworkassignment`
 - Add Environment for various proofs
 - Add points for exercises and a place to fill them in
 - Add option to remove or decrease the hlines

7.1 Version–Scheme

Since Version 2.0 the following version–scheme applies:

Major Version has to be increased, if

- there are changes, which create visible changes in the output of existing documents (except for bugfixes), or
- a command is removed or changed in a way, that existing documents do not compile with the new version.

Minor Version has to be increased, if

- new backwards compatible commands are introduced
- Bugfixes may be introduced too.

The minor version of stable releases is always even, the minor version of development versions is always odd. (0 counts as even).

Patches May be introduced on Stable Branch. With every non-document-breaking bugfix, the patch–number has to be incremented.

Because Fixing Bugs is a part of development, development–versions do not have numeric patch–numbers, but alphabetic identifiers, directly after the minor–version.

8 Examples

For examples, please see the Git-Repo at <https://github.com/ACHinrichs/LaTeX-templates>

9 Translations

Homeworkassignment currently supports English and German, fallback language is German. Unfortunately these two are the only Languages I am capable of translating reliably, so if you want to use an other language, I would be very happy if you would help me to translate homeworkassignment! Please open an issue, author a pull-request or send me an e-mail.

```
272 \DeclareTranslationFallback{aufgabe}{Aufgabe}
273 \DeclareTranslationFallback{loesung}{L\"osung}
274 \DeclareTranslationFallback{beweis}{Beweis}
275 \DeclareTranslationFallback{uebungsgruppe}{\"Ubungsgruppe}
276 \DeclareTranslationFallback{abgabe}{Abgabe}
277 \DeclareTranslationFallback{zuZeigen}{Zu zeigen}
278 \DeclareTranslationFallback{gegeben}{Gegeben}
279 \DeclareTranslationFallback{falls}{falls}
280 \DeclareTranslationFallback{Annahme}{Annahme}
281 \DeclareTranslationFallback{Angenommen-dass}{Angenommen, dass}
282
283 \DeclareTranslation{German}{aufgabe}{Aufgabe}
284 \DeclareTranslation{German}{loesung}{L\"osung}
285 \DeclareTranslation{German}{beweis}{Beweis}
286 \DeclareTranslation{German}{uebungsgruppe}{\"Ubungsgruppe}
287 \DeclareTranslation{German}{abgabe}{Abgabe}
288 \DeclareTranslation{German}{zuZeigen}{Zu zeigen}
289 \DeclareTranslation{German}{gegeben}{Gegeben}
290 \DeclareTranslation{German}{falls}{falls}
291 \DeclareTranslation{German}{Falls}{Falls}
292 \DeclareTranslation{German}{Annahme}{Annahme}
293 \DeclareTranslation{German}{Angenommen-dass}{Angenommen, dass}
294
295 \DeclareTranslation{English}{aufgabe}{Problem}
296 \DeclareTranslation{English}{loesung}{Solution}
297 \DeclareTranslation{English}{beweis}{Proof}
298 \DeclareTranslation{English}{uebungsgruppe}{Tutorial}
299 \DeclareTranslation{English}{abgabe}{Deadline}
300 \DeclareTranslation{English}{zuZeigen}{To show}
301 \DeclareTranslation{English}{gegeben}{Given}
302 \DeclareTranslation{English}{falls}{if}
303 \DeclareTranslation{English}{Falls}{If}
304 \DeclareTranslation{English}{Annahme}{Assumption}
305 \DeclareTranslation{English}{Angenommen-dass}{Suppose that}
```

10 Implementation

The following part is very boring, but I have not found a solution to create a .cls-file without including the implemetation into the document. Loads L^AT_EX2e and sets the Version Loads the `article`, which is the base-class.

10.1 Packages & Options

10.2 TikZ-Styles

10.3 Geometry

10.4 Internal commands

`\hwa@maketitletext` Prints out the title with author etc. Used to reduce code duplication for two- and onecolumn styles

```

306 \newcommand{\hwa@maketitletext}{
307   \begin{centering}
308     \huge{\textsf{\textbf{\hwa@kurs}}}\hwa@hline@LONE \large
309     \ifthenelse{\equal{\hwa@sheetTitle}{}}{\textsf{\hwa@sheetTitle}}{\}
310     \GetTranslation{abgabe}: \hwa@abgabe\
311     \hwa@hline@LTW0
312     \normalsize{\@author}\
313     \hwa@hline@LTW0 \normalsize
314   \end{centering}
315 }
```

10.4.1 Counter-Commands

Counter-Commands These are used to output the Exercise numbers in the desired style

```

316 \newcommand{\hwa@problemno}{\arabic{problem}}
317 \newcommand{\hwa@subproblemno}{\alph{subproblem}}
318 \newcommand{\hwa@subsubproblemno}{\roman{subsubproblem}}
```

10.4.2 Counter-Style Parser

Counter-Style Parser This takes a style-input (#1), one of the three previous defined commands (#2) and the coresponding counter (#3) to redefine #1, so that it corresponds to #2. See 10.4.3 for example usement.

```

319 \newcommand{\hwa@parseCounterStyle}[3]{
320   \ifthenelse{\equal{#1}{arabic}}{\renewcommand{#2}{\arabic{#3}} }{
321     \ifthenelse{\equal{#1}{roman}}{\renewcommand{#2}{\roman{#3}} }{
322       \ifthenelse{\equal{#1}{alph}}{\renewcommand{#2}{\alph{#3}} }{
323         \ifthenelse{\equal{#1}{Alph}}{\renewcommand{#2}{\Alph{#3}} }{
324           \ifthenelse{\equal{#1}{Roman}}{
325             \renewcommand{#2}{\Roman{#3}} }{
326             \ClassError{homeworkassignment}{Invalid Value #1 for
327               option Counter-Styling}{Possible Values are alph,
328               arabic, Arabic, roman or Roman.} } } } }
```

10.4.3 Counter-Commands II

Counter-Style ParserCommands II Redefines the three counter-commands

```
329 \hwa@parseCounterStyle{\hwa@problemsty}{\hwa@problemno}{problem}
330 \hwa@parseCounterStyle{\hwa@subproblemsty}{\hwa@subproblemno}{subproblem}
331 \hwa@parseCounterStyle{\hwa@subsubproblemsty}{\hwa@subsubproblemno}{subsubproblem}
```

10.4.4 Grading-table

\hwa@gradingtbl@... Defines macros whose contents will be written to the AUX-File and read in the next run, and the usable commands. The later will contain the information, but have to be defined (incase the aux-file does not exist)

```
332 \edef\hwa@gradingtbl@aux@defs{}
333 \newcommand{\hwa@gradingtbl@aux@lineOne}{}
334 \newcommand{\hwa@gradingtbl@aux@lineTwo}{}
335
336 \edef\hwa@gradingtbl@defs{}
337 \newcommand{\hwa@gradingtbl@lineOne}{}
338 \newcommand{\hwa@gradingtbl@lineTwo}{}

```

\addToGradingTable

```
339 \DeclareDocumentCommand\addToGradingTable{m g}{
340   \edef\hwa@gradingtbl@aux@defs{\hwa@gradingtbl@aux@defs|p{\hwa@pointboxsize}}
341   \edef\hwa@gradingtbl@aux@lineOne{\hwa@gradingtbl@aux@lineOne{#1} &}
342   \IfNoValueTF{#2}{
343     \edef\hwa@gradingtbl@aux@lineTwo{\hwa@gradingtbl@aux@lineTwo &}
344   }{
345     \edef\hwa@gradingtbl@aux@lineTwo{\hwa@gradingtbl@aux@lineTwo\vfill\hfill
346       {\string\small #2} &}
347   }
348 }
```

W rite to aux

```
349 \AtEndDocument{%
350   \immediate\write\@auxout{%
351     \gdef\string\hwa@gradingtbl@defs{\hwa@gradingtbl@aux@defs}
352   }
353   \immediate\write\@auxout{%
354     \gdef\string\hwa@gradingtbl@lineOne{\hwa@gradingtbl@aux@lineOne}%
355   }
356   \immediate\write\@auxout{%
357     \gdef\string\hwa@gradingtbl@lineTwo{\hwa@gradingtbl@aux@lineTwo}%
358   }
359 }
```

\makeGradingTable Outputs a table to fill in the reached Points. Only shows Problems created by \newproblem.

Displays the according number of maximum points for each problem, if specified.
Displays the total number of maximum Problems, if given by Argument

Arguments [1]: *Optional*. The total number of points reachable.

```

360 \DeclareDocumentCommand\makeGradingTable{o}{
361   \begin{table}[hb]
362     \centering
363     \large
364     \expandafter\table\expandafter{\hwa@gradingtbl@defs | p{\hwa@pointboxsize}|}\hline
365     \hwa@gradingtbl@lineOne   $\Sigma$          \\\hline\small
366     \hwa@gradingtbl@lineTwo   \IfNoValueTF{#1}{~}{\vfill\hfill/#1}\vspace{.15cm}\\\hline
367   \end{table}
368 \end{table}
369 }

```

10.5 Commands

`\deadline` Defines `\deadline`. `\abgabe` equals `\deadline`

`\maketitle` Overrides `\maketitle`.

```

370
371 \renewcommand{\maketitle} {
372   \thispagestyle{firstpage}
373   \ifhwa@twocolumn{
374     \twocolumn[{
375       \hwa@maketitletext
376     }]
377   } \else{
378     \hwa@maketitletext
379   } \fi
380 }

```

Defines and initialize all counters.

Defines ‘plain’ sectioning-commands. See 5.3 for more informations.

Defines ‘better’ sectioning commands. See 5.3 and 5.3.2 for more informations.

t demonstrandum at iucundum est

Rounding brackets

Round brackets

```

381 \newcommand{\floor}[1]{\ensuremath{\left\lfloor #1 \right\rfloor}}
382 \newcommand{\ceil}[1]{\ensuremath{\left\lceil #1 \right\rceil}}
383 \newcommand{\roundHU}[1]{\ensuremath{\left\lceil #1 \right\rfloor}}
384 \newcommand{\roundHD}[1]{\ensuremath{\left\lfloor #1 \right\rceil}}

```

The following Macros are all stolen (and adapted) from `occlonium` (see 5.4.3)

Math Common Set Symbols

```

385 \newcommand{\N}{\ensuremath{\mathbb{N}}}
386 \newcommand{\Z}{\ensuremath{\mathbb{Z}}}
387 \newcommand{\R}{\ensuremath{\mathbb{R}}}
388 \newcommand{\Q}{\ensuremath{\mathbb{Q}}}

```

```

389 \newcommand{\C}{\ensuremath{\mathbb{C}}}
390 \newcommand{\F}{\ensuremath{\mathbb{F}}}
391 % The last one is mine
392 \newcommand{\Primes}{\ensuremath{\mathbb{P}}}

```

Mathematical Functions

```

393 \DeclareMathOperator{\GL}{GL}
394 \DeclareMathOperator{\id}{id}
395 \DeclareMathOperator{\Var}{Var}
396 \DeclareMathOperator{\Perm}{Perm}
397 \DeclareMathOperator{\MComb}{MComb}
398 \DeclareMathOperator{\Comb}{Comb}
399 \DeclareMathOperator{\Pot}{Pot}
400 \DeclareMathOperator{\Map}{Map}
401 \DeclareMathOperator{\Hom}{Hom}
402 \DeclareMathOperator{\Ker}{Ker}
403 \DeclareMathOperator{\Intpol}{Intpol}
404 \DeclareMathOperator{\Pol}{Pol}
405 \DeclareMathOperator{\Sol}{Sol}
406 \DeclareMathOperator{\Bin}{Bin}
407 \DeclareMathOperator{\charakteristik}{char}
408 \newcommand{\diff}[1]{\ensuremath{\frac{d}{d\#1}}}
409 \newcommand{\dx}{\:dx}
410
411 \newcommand{\divides}{\ensuremath{\mid}}
412 \newcommand{\property}{\ensuremath{\models}}
413
414 \renewcommand{\dim}[1][\text{\text{dim}}_{\#1}]
415 \renewcommand{\Im}{\text{\text{Im}}}
416
417 \newcommand{\excup}{\ensuremath{\stackrel{\cdot}{\cup}}}
418
419 \newcommand{\falls}{\text{\text{\GetTranslation{falls}}}}

```

Math Big Quantors

```

420 \let\forall\forall
421 \let\exists\exists
422 \renewcommand{\forall}{\hspace{2pt}\forall\hspace{2pt}}
423 \renewcommand{\exists}{\hspace{2pt}\exists\hspace{2pt}}
424 \newcommand{\bigforall}{\mbox{\raisebox{-2pt}{\Large $\mathsurround{4pt}\forall$}}}
425 \newcommand{\bigexists}{\mbox{\raisebox{-2pt}{\Large $\mathsurround{4pt}\exists$}}}

The End
426 \endinput

```