

# Coarse-grained IE:Event Extraction

## How To Predict The Stock Based On News Events

Zhang Haijun  
MSc candidate

Department of Computer Science and Engineering  
Shanghai Jiao Tong University

October 18, 2017

- 1 Introduction
- 2 Representation
- 3 Extraction
- 4 Embedding
- 5 Application(Stock Prediction)

- 1 Introduction
- 2 Representation
- 3 Extraction
- 4 Embedding
- 5 Application(Stock Prediction)

- 1 Introduction
- 2 Representation
- 3 Extraction
- 4 Embedding
- 5 Application(Stock Prediction)

- 1 Introduction
- 2 Representation
- 3 Extraction
- 4 Embedding
- 5 Application(Stock Prediction)

- 1 Introduction
- 2 Representation
- 3 Extraction
- 4 Embedding
- 5 Application(Stock Prediction)

## Example news [Ding et al., 2014]

[Steve Jobs Death: \*\*Apple Stock\*\* \(AAPL\) Dips - ABC News](#)

[abcnews.go.com > Money](#) ▼

Oct 6, 2011 - Shares of **Apple** Inc. fell as trading began in New York on Thursday morning, the day after former CEO Steve Jobs passed away.

[Google's stock falls after grim earnings come out early - Oct. 18, 2012](#)

[money.cnn.com/2012/10/18/technology/google-earnings/](#) ▼

Oct 18, 2012 - **Google's** third-quarter earnings results missed analysts' estimates on both sales and profit, in a report that was accidentally released early.

Figure: Example news for Apple Inc. and Google Inc.

## Example news

The two news are described below:

- 1 Shares of Apple Inc. fell as trading began in New York on Thursday morning, the day after its former CEO Steve Jobs passed away.
- 2 Google's stock fell after grim earnings came out

Which inspires us that:

- If extracting events from unstructured text accurately, we can do better for downstream application.



## Example news

The two news are described below:

- 1 Shares of Apple Inc. fell as trading began in New York on Thursday morning, the day after its former CEO Steve Jobs passed away.
- 2 Google's stock fell after grim earnings came out

Which inspires us that:

- If extracting events from unstructured text accurately, we can do better for downstream application.

# Unstructured Features

## Shallow Features:

- 1 Bags of words
- 2 Noun phrases
- 3 Named entities

eg : "Apple has sued Samsung Electronics for copying 'the look and feel' of its iPad tablet and iPhone smartphone."

**Bags of words feature** : "Apple", "sued", "Samsung", "Electronics", "copying", ...

## Shortcoming:

- 1 Such unstructured representation can not indicate the actor(subject) and object of the event.
- 2 It can not focus on key events information embedded in free text, which introduces additional noise.

# Unstructured Features

## Shallow Features:

- 1 Bags of words
- 2 Noun phrases
- 3 Named entities

**eg :** "Apple has sued Samsung Electronics for copying 'the look and feel' of its iPad tablet and iPhone smartphone."

**Bags of words feature :** "Apple", "sued", "Samsung", "Electronics", "copying", ...

## Shortcoming:

- 1 Such unstructured representation can not indicate the actor(subject) and object of the event.
- 2 It can not focus on key events information embedded in free text, which introduces additional noise.

# Unstructured Features

## Shallow Features:

- 1 Bags of words
- 2 Noun phrases
- 3 Named entities

**eg :** "Apple has sued Samsung Electronics for copying 'the look and feel' of its iPad tablet and iPhone smartphone."

**Bags of words feature :** "Apple", "sued", "Samsung", "Electronics", "copying", ...

## Shortcoming:

- 1 Such unstructured representation can not indicate the actor(subject) and object of the event.
- 2 It can not focus on key events information embedded in free text, which introduces additional noise.

# Structured Features

Representation	$E = (O_1, P, O_2, T)$
$O_1$	Actor (Subject) of event
$P$	Action (Predicate) of event
$O_2$	Object of event
$T$	Timestamp of event

**eg :** Sep 3, 2013, - Microsoft agrees to buy Nokia's mobile phone business for \$7.2 billion.

## Structured Representation:

- Actor = Microsoft
- Action = buy
- Object = Nokia's mobile phone business
- Time = Sep 3, 2013

# Structured Features


Representation	$E = (O_1, P, O_2, T)$
$O_1$	Actor (Subject) of event
$P$	Action (Predicate) of event
$O_2$	Object of event
$T$	Timestamp of event

**eg :** Sep 3, 2013, - Microsoft agrees to buy Nokia's mobile phone business for \$7.2 billion.

## Structured Representation:

- Actor = Microsoft
- Action = buy
- Object = Nokia's mobile phone business
- Time = Sep 3, 2013

# Event Extraction



**Figure:** Event Extraction With Stanford Open IE tool

## Candidate Tuples Of The Event:

- 1 (Microsoft, buy, Nokia's mobile phone business, Sep 3 2013)
- 2 (Nokia, 's, mobile phone business, Sep 3 2013)

# Event Extraction





Figure: Event Extraction With Stanford Open IE tool

## Candidate Tuples Of The Event:

- 1 (Microsoft, buy, Nokia's mobile phone business, Sep 3 2013)
- 2 (Nokia, 's, mobile phone business, Sep 3 2013)



# Filter Out Bad Event Tuples



**Figure:** Filter Out Bad Tuples With tools like Dependency Parsing

## Candidate Tuples Of The Event:

- ① (Microsoft, buy, Nokia's mobile phone business, Sep 3 2013)
- ② (Nokia, 's, mobile phone business, Sep 3 2013)

# Filter Out Bad Event Tuples




Figure: Filter Out Bad Tuples With tools like Dependency Parsing

## Candidate Tuples Of The Event:

- ① (Microsoft, buy, Nokia's mobile phone business, Sep 3 2013)
- ② ~~(Nokia, 's, mobile phone business, Sep 3 2013)~~

# Event Generalization

**Example :** "Instant view: Private sector adds 114,000 jobs in July."

*(private sector, adds, 114 000 jobs)*

## Event Generalization:

- ① 'adds' and 'jobs' can be 'add' and 'job' respectively using some Stemmer tools
- ② 'add' belongs to 'multiply' class With the help of VerbNet

*(private sector, multiply\_class, 114 000 job)*

# Event Generalization

**Example :** "Instant view: Private sector adds 114,000 jobs in July."

*(private sector, adds, 114 000 jobs)*

## Event Generalization:

- ① 'adds' and 'jobs' can be 'add' and 'job' respectively using some Stemmer tools
- ② 'add' belongs to 'multiply' class With the help of VerbNet

*(private sector, multiply\_class, 114 000 job)*

# Why Embedding?

Two events (*Nvidia fourth quarter results, miss, views*) and (*Delta profit, didn't reach, estimates*) has different structured representation, which increases the data sparsity

With Embedding these two things can have the similar vector. [Ding et al., 2015]

# Embedding With Neural Tensor Network




Figure: Neural tensor network for event embeddings

$$R_1 = f(O_1^T T_1^{[1:k]} P + W \begin{bmatrix} O_1 \\ P \end{bmatrix} + b_1) \text{ (the same with } R_2 \text{ and } U)$$

# Neural Tensor Network Training

Training loss:

$$\text{loss}(E, E^T) = \max(0, 1 - f(E) + f(E^T)) + \lambda \|\Phi\|_2^2$$

where  $E = (O_1, P, O_2)$  and  $E^T = (O_1^T, P, O_2)$

---

## Algorithm 1: Event Embedding Training Process

---

**Input:**  $\mathcal{E} = (E_1, E_2, \dots, E_n)$  a set of event tuples; the model  $EELM$

**Output:** updated model  $EELM'$

1 random replace the event argument and got the corrupted event tuple

2  $\mathcal{E}^r \leftarrow (E_1^r, E_2^r, \dots, E_n^r)$

3 **while**  $\mathcal{E} \neq []$  **do**

4      $\text{loss} \leftarrow \max(0, 1 - f(E_i) + f(E_i^r) + \lambda \|\Phi\|_2^2)$

5     **if**  $\text{loss} > 0$  **then**


6          $\text{Update}(\Phi)$

7     **else**

8          $\mathcal{E} \leftarrow \mathcal{E} / \{E_i\}$

9 **return**  $EELM$


# Embedding With External Knowledge



**Figure:** Incorporating knowledge graph into the learning process for event embeddings [Ding et al., 2016]



# Training With External Knowledge



**Figure:** Architecture of the joint embedding model (only showing the tensor layer)


$$L = \alpha L_\epsilon + (1 - \alpha) L_\kappa$$

$$L_\epsilon = \text{loss}(E, E^T) = \max(0, 1 - f(E) + f(E^T)) + \lambda \|\Phi\|_2^2$$

$$L_\kappa = \sum_{i=1}^N \sum_{m=1}^M \max(0, 1 - g(T^{(i)}) + g(T_c^{(i)})) + \lambda \|\Omega\|_2^2$$

$$\text{where } E = (O_1, P, O_2), T^{(i)} = (e_1^{(i)}, R, e_2^{(i)})$$

# Training With External Knowledge



**Figure:** Architecture of the joint embedding model (only showing the tensor layer)


$$L = \alpha L_\epsilon + (1 - \alpha) L_\kappa$$

$$L_\epsilon = \text{loss}(E, E^T) = \max(0, 1 - f(E) + f(E^T)) + \lambda \|\Phi\|_2^2$$

$$L_\kappa = \sum_{i=1}^N \sum_{m=1}^M \max(0, 1 - g(T^{(i)}) + g(T_c^{(i)})) + \lambda \|\Omega\|_2^2$$

$$\text{where } E = (O_1, P, O_2), T^{(i)} = (e_1^{(i)}, R, e_2^{(i)})$$


# Prediction Model



**Figure:** Architecture of the prediction model based on a deep convolutional neural network.

Table 3: Experimental results on index prediction.

	Acc	MCC
Luss and d'Aspremont (2012)	56.38%	0.0711
Ding et al. (2014)	58.83%	0.1623
WB-CNN	60.57%	0.1986
Ding et al. (2015)	64.21%	0.4035
KGEB-CNN	<b>66.93%</b>	<b>0.5072</b>



Thank You!



Ding, X., Zhang, Y., Liu, T., and Duan, J. (2014).

Using structured events to predict stock price movement:  
An empirical investigation.

In Proceedings of the 2014 Conference on Empirical  
Methods in Natural Language Processing (EMNLP), pages  
1415–1425, Doha, Qatar. Association for Computational  
Linguistics.



Ding, X., Zhang, Y., Liu, T., and Duan, J. (2015).

Deep learning for event-driven stock prediction.

In Proceedings of IJCAI, BueNos Aires, Argentina.



Ding, X., Zhang, Y., Liu, T., and Duan, J. (2016).

Knowledge-driven event embedding for stock prediction.

In Proceedings of COLING 2016, pages 2133–2142, Osaka,  
Japan. Association for Computational Linguistics.