Large-Scale Machine Translation between Arabic and Hebrew: Available Corpora and Initial Results

Yonatan Belinkov and James Glass

MIT Computer Science and Artificial Intelligence Laboratory Cambridge, MA 02139, USA {belinkov, glass}@mit.edu

Abstract

Machine translation between Arabic and Hebrew has so far been limited by a lack of parallel corpora, despite the political and cultural importance of this language pair. Previous work relied on manually-crafted grammars or pivoting via English, both of which are unsatisfactory for building a scalable and accurate MT system. In this work, we compare standard phrase-based and neural systems on Arabic-Hebrew translation. We experiment with tokenization by external tools and subword modeling by character-level neural models, and show that both methods lead to improved translation performance, with a small advantage to the neural models.

1 Introduction

Arabic and Hebrew are Semitic languages spoken by peoples with complicated cultural and political relationships. They share important similar characteristics in all linguistic levels, including orthography, morphology, syntax, and lexicon. Yet there is relatively little previous research on machine translation between the two languages, despite its potential benefit for promoting understanding between their speakers. The main reason for this lacuna is a lack of parallel Arabic-Hebrew texts. This has led researchers to consider alternative approaches, such as pivoting via English (El Kholy and Habash, 2014; El Kholy and Habash, 2015) or developing transferbased systems built with synchronous context free grammars (Shilon et al., 2012). Both approaches are unsatisfactory: the transfer-based system relies on manually-crafted grammars and lexicons, therefore

suffering from robustness issues, and pivoting via a morphologically-poor language like English leads to under-specification of potentially useful features.

Recently, a number of large-scale parallel Arabic-Hebrew corpora have been compiled, mostly from multilingual transcriptions of spoken language available online (Cettolo et al., 2012; Lison and Tiedemann, 2016). These resources finally allow for training full-scale statistical machine translation systems on the Arabic-Hebrew pair. Our first contribution is in evaluating such standard systems on a clearly-defined dataset. We compare phrase-based machine translation (PBMT) with neural machine translation (NMT), using state-of-the-art implementations.

Like other Semitic languages, Arabic and Hebrew feature rich morphology and frequent cliticization (joining of prepositions, conjunctions, to the main word). These characteristics lead to increased ambiguity and pose a challenge to machine translation. A common solution is apply tokenization by external tools, shown help translation between Arabic/Hebrew to and **English** (El Kholy and Habash, 2012; Singh and Habash, 2012). Our second contribution is thus in evaluating tokenization by external tools for the Arabic-Hebrew language pair. We also experiment with character-level neural models that have recently become popular for dealing with morphologically-rich languages (Kim et al., 2016).

In this work, we focus on Arabic-to-Hebrew translation. Arabic has relatively more available resources such as tokenizers and morphological analyzers, making this translation direction more approachable. We leave the investigation of Hebrew-to-Arabic translation for future work.

Our results show that phrase-based and neural MT systems reach comparable performance, with a small advantage to neural models. We also ascertain the importance of sub-word modeling, where neural character models rival or surpass morphology-aware tokenization by standard tools. We conclude by pointing to potential directions for future research.

2 Related Work

There is relatively little previous research on machine translation between Arabic and Hebrew, despite cultural and political relations between their speakers, and despite their linguistic similarities. The most relevant work is by Shilon et al. (2012), who built a statistical transfer-based system for translating from Arabic to Hebrew and vice versa. Their work relies on synchronous context free grammars and lexicons in the two languages, an approach that they advocate as being better suited to this pair for two main reasons: (a) a lack of available parallel corpora; and (b) the rich morphology of Arabic and Hebrew that requires linguistic knowledge. Here, we explore an alternative to this approach by exploiting Arabic-Hebrew parallel texts that have recently become available, enabling us to train standard statistical MT systems.¹ We further explore methods for handling morphology both by using traditional tools for morphological analysis and tokenization, and by training a *character*-level neural MT system.

Other work directly targeting machine translation between Arabic and Hebrew includes (El Kholy and Habash, 2014), which used pivoting via English. They improved translation quality by carefully designing the alignment symmetrization process in a phrase-based system. In later work, El Kholy and Habash (2015) incorporated morphological constraints for pivoting in a phrase-based system, which they augmented with parallel Arabic-Hebrew data (from an earlier version of the corpus we use in this paper). While pivoting is an appealing solution to scarcity in parallel corpora, Shilon et al. (2012) convincingly show how pivoting through a morphologically-poor language like

English leads to under-specification of linguistic features and loss of information.

There is a fairly decent body of work on translation between Arabic and English, using a variety of methods; see the survey in (Algudsi et al., 2014). In particular, the importance of morphologytokenization when translating and to Arabic has been confirmed in phrasebased (Badr et al., 2008; Habash and Sadat, 2006; El Kholy and Habash, 2012) and neural machine translation, in both hybrid (Devlin et al., 2014) and end-to-end systems (Almahairi et al., 2016). Work on Hebrew translation is more limited, but previous studies on translating Hebrew to English also demonstrated the need for morphological analysis and tokenization (Lavie et al., 2004; Lembersky et al., 2012; Singh and Habash, 2012).

3 Linguistic Description

We give here a short description of similarities and differences between Arabic and Hebrew, referring to (Shilon et al., 2012) for a comprehensive discussion.

As Semitic languages, Arabic and Hebrew share several characteristics. Both orthographies commonly omit vowels and other diacritics in writing, leading to increased ambiguity. The scripts are distinct, but there is substantial overlap in the alphabets. Many clitics (prepositions, conjunctions, definite articles) are prefixed or suffixed to words. Both languages have a rich morphology with a complex system of verbal inflection. Their inflection paradigms partially, but not completely, overlap. Syntactically, the languages have both verbal and verbless sentences. Arabic, in particular, has a more complicated agreement system. Some systematic word order patterns can be noted (SVO for Hebrew, VSO for Arabic), but these have exceptions and depend on genre.

Shilon et al. (2012) discuss the challenges such characteristics pose for machine translation between Arabic and Hebrew. In this work, we mostly address orthographic and morphological challenges, which call for solutions like tokenization and representing sub-word elements.

4 Parallel Corpora

Until recently, there were not many available parallel corpora of Arabic and Hebrew.

¹Cettolo (2016) describes the corpus and baseline MT systems in work concurrent with this paper.

Corpus	Sents	Ar words	He words
OpenSubtitles	14.6M	108M	111M
OpenSubtitles-Alt	9.5M	71M	76M
WIT^3	0.2M	3.4M	3.1M
GNOME	0.6M	2.1M	2.6M
KDE	80.5K	0.5M	0.4M
Ubuntu	51.3K	0.2M	0.2M
Shilon et al.	1.6K	28K	25K
Tatoeba	0.9K	90K	0.6M
GlobalVoices	76	3.2K	3.7K

Table 1: Statistics of parallel Arabic-Hebrew corpora. See text for references and more details.

Shilon et al. (2012) prepared a parallel corpus of several hundred sentences from the news domain, too small for training a statistical system but potentially useful for evaluation. Since then, two large resources have become available. First, WIT³ provides multilingual transcriptions of TED talks (Cettolo et al., 2012) and its 2016 release includes about 3 million words of Arabic-Hebrew parallel texts (Cettolo, 2016). As a corpus of TED talks, it has several interesting features: diversity of topics, spoken language transcriptions, and user-generated translations, although the review process ensures a reasonable translation quality. The original transcriptions are segmented at the caption level and WIT³ automatically joins them into sentences.

Second, OPUS provides a collection of translation texts from the web. The largest Arabic-Hebrew parallel corpus is OpenSubtitles, comprising automatically aligned movie and TV subtitles. The 2016 release contains more than 100 million words (Lison and Tiedemann, 2016). In addition, OPUS provides a version with alternative translations, with some 70 million words of Arabic-Hebrew texts (Tiedemann, 2016). Having alternative translations can be valuable for evaluation with multiple references, although many alternatives are simply duplicates. While this is by far the largest available Arabic-Hebrew parallel corpus, it suffers from the usual problems of OpenSubtitles texts: usergenerated content, questionable translation quality, and automatic caption alignment. In addition, the right-to-left scripts cause problems with punctuation marks such as misplacement and wrong tokeniza-

Smaller Arabic-Hebrew corpora in OPUS include localization files (Ubuntu, KDE, GNOME),

each totaling between 200 thousand to 2 million words, as well as user-contributed translations from Tatoeba, and news stories from GlobalVoices (Tiedemann, 2009; Tiedemann, 2012). Table 1 summarizes statistics about available Arabic-Hebrew corpora.

5 Experimental Setup

5.1 Machine Translation Systems

Phrase-Based MT We build a standard PBMT system using Moses (Koehn et al., 2007). Word alignment is extracted by fast_align (Dyer et al., 2013) and symmetrized with the grow-diag-final-and strategy, and lexical reordering follows the msd-bidirectional-fe configuration. Sentences longer than 80 words are filtered during training. We train a 5-gram language model on the training set target side using KenLM (Heafield et al., 2013) and tune with MERT to optimize BLEU. These are common Moses settings that have also been used in Arabic-English translation (Almahairi et al., 2016).

Neural MT We train a neural translation system using a Torch (Collobert et al., 2011) implementation of attention sequence-to-sequence learning (Kim, 2016). We keep the default settings and experiment with two architectures: a small 2-layer 500 unit LSTM (on both encoder and decoder sides) and a larger 4-layer 1000 unit LSTM. Sentences are limited to 50 words and the vocabulary size is limited to 50,000 on both source and target sides. The model is trained on a single GPU using SGD. Decoding is done with beam search and a width of 5.

5.2 Tokenization and Sub-Word Models

Morphological processing and tokenization are considered crucial for machine translation from and to Semitic languages like Arabic and Hebrew (Section 2). This is typically applied as a preprocessing step, requiring language-specific tools. An alternative option is to incorporate language-agnostic sub-word elements inside the training algorithm. We describe the two options next.

Tokenization We experiment with tokenization of the Arabic source side using two tools: MADAMIRA (Pasha et al., 2014), a standard

	Train	Tune	Test
Sents	0.2M	7.3K	874
Ar words	3.2M	102.2K	13.7K
He words	3.0M	93.1K	12.7K

Table 2: Number of sentences and (space-delimited) words in the WIT³ corpus of TED talks used in our experiments.

morphological analyzer and disambiguator, and segmenter (Abdelali et al., 2016), a much faster ranker that has been shown to perform comparably to MADAMIRA. In both cases we segment the Arabic according to the ATB scheme that tends to perform better than other schemes in translating between Arabic and English (El Kholy and Habash, 2012; This scheme separates all Sajjad et al., 2013). clitics other than the definite article. While it is possible that other schemes will work better for Arabic-Hebrew translation, exploring this option is left for future work. The tokenized text is also normalized with the tools' default settings. On the Hebrew side, we only separate punctuation marks.

Character-level models Character-level models have been shown to benefit neural MT, especially for languages with large vocabularies. For instance, Sennrich et al. (2016) convert words to sub-word elements using byte-pair encoding and obtain significant gains on English-German/Russian translation. The method was also applied to Arabic-English translation (Abdelali et al., 2016). Here we experiment with a character-level convolutional neural network (charCNN) that replaces input word vectors with learned representations based on character vectors (Kim et al., 2016). We use the default settings in (Kim, 2016).

5.3 Data and Evaluation

We mainly experiment with the WIT³ corpus of TED talks (Section 4). It is a fairly large corpus (3 million words), with high-quality translations and diverse topics. We use the designated train.tags files for training, IWSLT16.TED.tst2010-2014 for tuning, and IWSLT16.TED.dev2010 for testing. We keep IWSLT16.TED.tst2015-2016 as a held-out set for future evaluations. Table 2 provides some statistics about the datasets.

We also performed initial separate experiments with the OpenSubtitles corpus. However, the trans-

System	BLEU	Meteor	PPL
PBMT	9.31	32.30	478.4
PBMT+Tok-Farasa	9.51	33.38	335.5
PBMT+Tok-MADAMIRA	9.63	32.90	342.5
NMT	9.91	30.55	2.275
NMT Large	9.92	30.46	2.214
NMT+UNK Replace	10.12	31.84	2.275
NMT+charCNN	10.65	32.43	2.239
NMT+charCNN+UNK Repl.	10.86	33.61	2.239

Table 3: Results on WIT³. Differences in BLEU scores in the first block are not statistically significant (at p < 0.05); differences between the two blocks are significant; the difference between small and large NMT models is not significant; differences between word and character NMT models are significant. Perplexity (PPL) scores are computed from the PBMT language model and the NMT decoder's classification loss, respectively.

lation quality was very poor, mostly due to the extremely noisy nature of the dataset. Therefore we leave the exploration of this corpus for future work.

We compute BLEU scores using the multi-bleu.perl script included with Moses. Significance testing follows (Koehn, 2004; Riezler and Maxwell, 2005). We also report Meteor scores (version 1.5), using Meteor Universal (Denkowski and Lavie, 2014) to build language resources based on the phrase table learned by the PBMT system.

6 Results

Table 3 summarizes the results for Arabic-to-Hebrew translation on the WIT³ corpus of TED talks. As expected, tokenization helps phrase-based MT, although the differences in BLEU scores are not statistically significant. In terms of BLEU, neural MT performs significantly better than phrasebased MT, and char-based models lead to substantial and statistically significant improvement. Another small improvement is gained by replacing generated unknown words with translations of their aligned source words based on the attention weights (Jean et al., 2015). Using a larger and deeper NMT model does not lead to significant improvement, possibly due to the size of the training data.

We note that the generally low BLEU scores can be attributed to the single-reference evaluation mode, as well as the challenging nature of the data (spoken language transcripts, automatically aligned captions, diverse topics). Similar BLEU scores were reported for translating from English into Arabic and Hebrew in previous evaluations of TED talks translation (Cettolo et al., 2014).

Looking at Meteor scores, we again see that tokenization helps, but this time the basic NMT system is inferior to PBMT. However, as Meteor Universal uses the phrase-table learned by the PBMT system, it might be biased towards PBMT. Using a characterbased model and UNK replacement can close this gap, leading to the best performing system.

7 Conclusion and Future Work

We presented initial experiments in large-scale Arabic-to-Hebrew machine translation, comparing both phrase-based and neural MT. We also evaluated the contribution of tokenization to the PBMT system and of character-level models to the NMT system.

This work is a first step that can be extended in a number of ways. First, experimenting with the Hebrew-to-Arabic direction might reveal new insights. Second, other combinations of tokenization and character-level models can be explored (e.g. character-level neural models on tokenized or bytepair encoded text). The parallel corpora can also be cleaned and improved, especially by adding multiple reference translations. Finally, modeling interrelations between the two languages in a more direct manner is an appealing direction, given the similarities across linguistic levels.

Acknowledgments

The authors would like to thank Mauro Cettolo for useful suggestions with regards to the Arabic-Hebrew TED talks corpus, Pierre Lison and Jörg Tiedemann for help with getting access to the Open-Subtitles corpus, and Reshef Shilon for fruitful discussions. This work was supported by the Qatar Computing Research Institute (QCRI). Any opinions, findings, conclusions, or recommendations expressed in this paper are those of the authors, and do not necessarily reflect the views of the funding organizations.

References

[Abdelali et al.2016] Ahmed Abdelali, Kareem Darwish, Nadir Durrani, and Hamdy Mubarak. 2016. Farasa: A

- Fast and Furious Segmenter for Arabic. In *Proceedings of the 2016 Conference of the North American Chapter of the Association for Computational Linguistics: Demonstrations*, pages 11–16, San Diego, California.
- [Almahairi et al.2016] Amjad Almahairi, Kyunghyun Cho, Nizar Habash, and Aaron Courville. 2016. First Result on Arabic Neural Machine Translation. *arXiv* preprint arXiv:1606.02680.
- [Alqudsi et al.2014] Arwa Alqudsi, Nazlia Omar, and Khalid Shaker. 2014. Arabic machine translation: a survey. *Artificial Intelligence Review*, 42(4):549–572.
- [Badr et al. 2008] Ibrahim Badr, Rabih Zbib, and James Glass. 2008. Segmentation for English-to-Arabic Statistical Machine Translation. In *Proceedings of the 46th Annual Meeting of the Association for Computational Linguistics on Human Language Technologies: Short Papers*, HLT-Short '08, pages 153–156, Columbus, Ohio.
- [Cettolo et al.2012] Mauro Cettolo, Christian Girardi, and Marcello Federico. 2012. WIT³: Web Inventory of Transcribed and Translated Talks. In *Proceedings of* the 16th Conference of the European Association for Machine Translation (EAMT), pages 261–268, Trento, Italy.
- [Cettolo et al. 2014] Mauro Cettolo, Jan Niehues, Sebastian Stüker, Luisa Bentivogli, and Marcello Federico. 2014. Report on the 11th IWSLT evaluation campaign, IWSLT 2014. In Proceedings of the International Workshop on Spoken Language Translation, Hanoi, Vietnam.
- [Cettolo2016] Mauro Cettolo. 2016. An Arabic-Hebrew parallel corpus of TED talks. In *Proceedings of the AMTA 2016 Workshop on Semitic Machine Translation (SeMaT)*, Austin, Texas.
- [Collobert et al.2011] Ronan Collobert, Koray Kavukcuoglu, and Clément Farabet. 2011. Torch7: A Matlab-like Environment for Machine Learning. In BigLearn, NIPS Workshop.
- [Denkowski and Lavie2014] Michael Denkowski and Alon Lavie. 2014. Meteor Universal: Language Specific Translation Evaluation for Any Target Language. In *Proceedings of the EACL 2014 Workshop* on Statistical Machine Translation.
- [Devlin et al.2014] Jacob Devlin, Rabih Zbib, Zhongqiang Huang, Thomas Lamar, Richard Schwartz, and John Makhoul. 2014. Fast and Robust Neural Network Joint Models for Statistical Machine Translation. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1370–1380, Baltimore, Maryland.
- [Dyer et al.2013] Chris Dyer, Victor Chahuneau, and Noah A. Smith. 2013. A Simple, Fast, and Effective

- Reparameterization of IBM Model 2. In *Proceedings* of the 2013 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, pages 644–648, Atlanta, Georgia.
- [El Kholy and Habash2012] Ahmed El Kholy and Nizar Habash. 2012. Orthographic and morphological processing for English–Arabic statistical machine translation. *Machine Translation*, 26(1):25–45.
- [El Kholy and Habash2014] Ahmed El Kholy and Nizae Habash. 2014. Alignment Symmetrization Optimization Targeting Phrase Pivot Statistical Machine Translation. In *Proceedings of The European Association for Machine Translation (EAMT14)*.
- [El Kholy and Habash2015] Ahmed El Kholy and Nizar Habash. 2015. Morphological Constraints for Phrase Pivot Statistical Machine Translation. *Proceedings of MT Summit XV*, page 104.
- [Habash and Sadat2006] Nizar Habash and Fatiha Sadat. 2006. Arabic Preprocessing Schemes for Statistical Machine Translation. In Proceedings of the Human Language Technology Conference of the NAACL, Companion Volume: Short Papers, NAACL-Short '06, pages 49–52, New York, New York.
- [Heafield et al.2013] Kenneth Heafield, Ivan Pouzyrevsky, Jonathan H. Clark, and Philipp Koehn. 2013. Scalable Modified Kneser-Ney Language Model Estimation. In *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics*, pages 690–696, Sofia, Bulgaria.
- [Jean et al.2015] Sébastien Jean, Kyunghyun Cho, Roland Memisevic, and Yoshua Bengio. 2015. On Using Very Large Target Vocabulary for Neural Machine Translation. In Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics and the 7th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), pages 1–10, Beijing, China.
- [Kim et al.2016] Yoon Kim, Yacine Jernite, David Sontag, and Alexander Rush. 2016. Character-Aware Neural Language Models. In *AAAI Conference on Artificial Intelligence*.
- [Kim2016] Yoon Kim. 2016. Seq2seq-attn. ken Language Transl https://github.com/harvardnlp/seq2seq-attn. Heidelberg, Germany.
- [Koehn et al.2007] Philipp Koehn, Hieu Hoang, Alexandra Birch, Chris Callison-Burch, Marcello Federico, Nicola Bertoldi, Brooke Cowan, Wade Shen, Christine Moran, Richard Zens, Chris Dyer, Ondřej Bojar, Alexandra Constantin, and Evan Herbst. 2007. Moses: Open Source Toolkit for Statistical Machine Translation. In Proceedings of the 45th Annual Meeting of the ACL on Interactive Poster and Demonstration Sessions, ACL '07, pages 177–180, Prague, Czech Republic.

- [Koehn2004] Philipp Koehn. 2004. Statistical Significance Tests for Machine Translation Evaluation. In *Proceedings of EMNLP* 2004, pages 388–395, Barcelona, Spain.
- [Lavie et al.2004] Alon Lavie, Shuly Wintner, Yaniv Eytani, Erik Peterson, and Katharina Probst. 2004. Rapid prototyping of a transfer-based Hebrew-to-English machine translation system. In 10th International Conference on Theoretical and Methodological Issues in Machine Translation (TMI).
- [Lembersky et al.2012] Gennadi Lembersky, Noam Ordan, and Shuly Wintner. 2012. Language Models for Machine Translation: Original vs. Translated Texts. *Computational Linguistics*, 38(4):799–826.
- [Lison and Tiedemann2016] Pierre Lison and Jörg Tiedemann. 2016. OpenSubtitles2016: Extracting Large Parallel Corpora from Movie and TV Subtitles. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC 2016)*, Portorož, Slovenia.
- [Pasha et al.2014] Arfath Pasha, Mohamed Al-Badrashiny, Mona Diab, Ahmed El Kholy, Ramy Eskander, Nizar Habash, Manoj Pooleery, Owen Rambow, and Ryan Roth. 2014. MADAMIRA: A Fast, Comprehensive Tool for Morphological Analysis and Disambiguation of Arabic. In *Proceedings of the Ninth International Conference on Language Resources and Evaluation (LREC'14)*, Reykjavik, Iceland.
- [Riezler and Maxwell2005] Stefan Riezler and John T Maxwell. 2005. On some pitfalls in automatic evaluation and significance testing for MT. In *Proceedings of the ACL workshop on intrinsic and extrinsic evaluation measures for machine translation and/or summarization*, pages 57–64.
- [Sajjad et al.2013] Hassan Sajjad, Francisco Guzmán, Preslav Nakov, Ahmed Abdelali, Kenton Murray, Fahad Al Obaidli, and Stephan Vogel. 2013. QCRI at IWSLT 2013: Experiments in Arabic-English and English-Arabic Spoken Language Translation. In Proceedings of the 10th International Workshop on Spoken Language Translation (IWSLT'13), volume 13, -at Heidelberg, Germany.
- [Sennrich et al.2016] Rico Sennrich, Barry Haddow, and Alexandra Birch. 2016. Neural Machine Translation of Rare Words with Subword Units. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1715–1725, Berlin, Germany.
- [Shilon et al.2012] Reshef Shilon, Nizar Habash, Alon Lavie, and Shuly Wintner. 2012. Machine Translation Between Hebrew and Arabic. *Machine Translation*, 26(1-2):177–195.

- [Singh and Habash2012] Nimesh Singh and Nizar Habash. 2012. Hebrew Morphological Preprocessing for Statistical Machine Translation. In *Proceedings of The European Association for Machine Translation (EAMT12)*.
- [Tiedemann2009] Jörg Tiedemann. 2009. News from OPUS A Collection of Multilingual Parallel Corpora with Tools and Interfaces. In *Recent Advances in Natural Language Processing*, volume V, pages 237–248. Borovets, Bulgaria.
- [Tiedemann2012] Jörg Tiedemann. 2012. Parallel Data, Tools and Interfaces in OPUS. In *Proceedings of* the Eight International Conference on Language Resources and Evaluation (LREC'12), Istanbul, Turkey.
- [Tiedemann2016] Jörg Tiedemann. 2016. Finding Alternative Translations in a Large Corpus of Movie Subtitle. In *Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC 2016)*, Portorož, Slovenia.