

CAMS

Computer Account Management System

WRITTEN USE CASES

219 use cases across 29 modules and 3 actors
Administrator 91 · Teacher 107 · Student 21

About this document

Each written use case below follows the ten fields set out for a use case specification: use case name, purpose, actors, input parameters, output parameters, pre-condition, post-condition, successful scenario, exception scenario and additional remarks.

Each use case is named after the function in the CAMS source that implements it. A use case named `CREATE STUDENT` describes `AdminController.CreateStudent`; one named `LOGIN ASYNC` describes `AuthenticationService.LoginAsync`, used where the behaviour has no endpoint of its own and is reached through an include relationship.


The fields that can be got wrong are read out of the source rather than written from memory. Input parameters come from the action signature and its `[Bind]` list, so a use case cannot name a field the form does not submit. The pre-condition comes from the `[Authorize]` attribute, including the `[TeacherSharedAction]` marker that admits a teacher to an administrator action. The antiforgery step appears only where the controller validates one, and a hub method is described as a SignalR relay rather than a form post, because that is what it is.

The companion diagram is `CAMS-Use-Case-Diagram.drawio`, in the same folder.

Admin

PROCESS LOG IN AccountController

System Use Case:



Written Use Case:

A-001 LOGIN USER

Use Case Name: LOGIN USER

Purpose: Let a person sign in to the CAMS web portal with a username and password, and place them in the part of the system their role allows.

Actors: Admin

Input Parameters:

- username : string
- password : string

Output Parameters:

- An authentication cookie carrying the account role as a claim, and a redirect to the landing page for that role.

Pre-Condition:

- None. This is the sign-in endpoint and is reachable without an account session; the CAMS server must be running and reachable.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the CAMS sign-in page.
2. The Admin enters a username and a password and submits the form.
3. The server validates the antiforgery token that accompanied the form.
4. The server checks the credentials against each account table in turn and finds the matching account.
5. The server confirms the account is active and not locked out.
6. The server issues an authentication cookie carrying the role as a claim.
7. The Admin is redirected to the landing page for that role.

Exception Scenario:

- **The username matches no account** — the page reports that the sign-in failed, without saying which half was wrong.
- **The password does not match the stored hash** — the failed-attempt counter is raised and the same message is shown.
- **The account is locked out** — the sign-in is refused until the lockout expires, even with the right password.
- **The account is deactivated** — the sign-in is refused and the person is told to contact an administrator.

Additional Remarks:

- Implemented by `AccountController.Login (POST)`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.

- Pulls in **LOGIN ASYNC** (<<include>>).

A-002 **LOGOUT USER**

Use Case Name: LOGOUT USER

Purpose: End the signed-in session and clear the authentication cookie, so the next visitor to the browser starts as an anonymous user.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The authentication cookie is cleared and the browser is returned to the sign-in page.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin chooses to sign out.
2. The server closes any lab session the account still has open.
3. The server clears the authentication cookie.
4. The browser is returned to the sign-in page as an anonymous visitor.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AccountController.Logout` (POST).
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Pulls in **LOGOUT ASYNC** (<<include>>).

A-003 **LOGIN ASYNC**

Use Case Name: LOGIN ASYNC

Purpose: Check the supplied password against the stored hash, confirm the account is active and not locked out, and decide which of the three account tables the person belongs to.

Actors: Admin, None; this behaviour runs inside **LOGIN USER**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A `LoginResult` naming the role, the account id and the display name, or a result saying the credentials were rejected.

Pre-Condition:

- The sign-in use case has supplied a username and a password.
- **LOGIN USER** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The sign-in use case passes the username, the password, the workstation name and the caller address.
2. The service looks the username up in the administrator, teacher and student tables.
3. The stored hash is verified against the supplied password.
4. The active flag and the lockout expiry are checked.
5. On success the failed-attempt counter is cleared and the role and account id are returned; on failure the counter is raised.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `LoginAsync`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Drawn as <<include>> from **LOGIN USER**.

A-004 **LOGOUT ASYNC**

Use Case Name: LOGOUT ASYNC

Purpose: Close any lab session the student still has open and record the sign-out.

Actors: Admin, None; this behaviour runs inside **LOGOUT USER**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **LOGOUT USER** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs LogoutAsync and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by LogoutAsync.
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Drawn as <<include>> from **LOGOUT USER**.

VIEW ADMIN HOME `AdminController`

System Use Case:



Written Use Case:

A-005 ADMIN INDEX

Use Case Name: ADMIN INDEX

Purpose: Show the administrator landing page, summarising the state of the laboratory.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Index` (GET).
- Appears in the *VIEW ADMIN HOME* module of the use case diagram.

A-006 **VIEW SETTINGS**

Use Case Name: VIEW SETTINGS

Purpose: Show the settings page for the signed-in user.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Settings (GET)`.
- Appears in the *VIEW ADMIN HOME* module of the use case diagram.

A-007 LAN CONFIG

Use Case Name: LAN CONFIG

Purpose: Show the network configuration the server detected, as a read-only diagnostic.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.LanConfig (GET)`.
- Appears in the *VIEW ADMIN HOME* module of the use case diagram.

A-008 **CHANGE PASSWORD**

Use Case Name: CHANGE PASSWORD

Purpose: Let the signed-in user replace their own password after proving they know the current one.

Actors: Admin

Input Parameters:

- input : PasswordChangeInput

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.ChangePassword` (POST).
- Appears in the *VIEW ADMIN HOME* module of the use case diagram.
- Pulls in **CHANGE ADMIN PASSWORD ASYNC** (<<include>>).

A-009 **CHANGE ADMIN PASSWORD ASYNC**

Use Case Name: CHANGE ADMIN PASSWORD ASYNC

Purpose: Verify the current password and replace the stored hash for an administrator account.

Actors: Admin, None; this behaviour runs inside **CHANGE PASSWORD**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **CHANGE PASSWORD** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `ChangeAdminPasswordAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `ChangeAdminPasswordAsync`.
- Appears in the *VIEW ADMIN HOME* module of the use case diagram.
- Drawn as <<include>> from **CHANGE PASSWORD**.

MANAGE ADMIN ACCOUNT `AdminController`

System Use Case:



Written Use Case:

A-010 **CREATE ADMIN**

Use Case Name: CREATE ADMIN

Purpose: Record a new administrator account in the system.

Actors: Admin

Input Parameters:

- admin : Admin

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateAdmin` (POST).
- Appears in the *MANAGE ADMIN ACCOUNT* module of the use case diagram.

A-011 UPDATE ADMIN

Use Case Name: UPDATE ADMIN

Purpose: Amend the stored details of an existing administrator account.

Actors: Admin

Input Parameters:

- admin : Admin
- newPassword : string?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateAdmin` (POST).
- Appears in the *MANAGE ADMIN ACCOUNT* module of the use case diagram.

A-012 DELETE ADMIN

Use Case Name: DELETE ADMIN

Purpose: Remove a administrator account from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteAdmin` (POST).
- Appears in the *MANAGE ADMIN ACCOUNT* module of the use case diagram.

MANAGE TEACHER ACCOUNT AdminController

System Use Case:



Written Use Case:

A-013 **VIEW TEACHERS**

Use Case Name: VIEW TEACHERS

Purpose: List the teachers the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Teachers` (GET).
- Appears in the *MANAGE TEACHER ACCOUNT* module of the use case diagram.

A-014 **CREATE TEACHER**

Use Case Name: CREATE TEACHER

Purpose: Record a new teacher account in the system.

Actors: Admin

Input Parameters:

- teacher : Teacher

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateTeacher` (POST).
- Appears in the *MANAGE TEACHER ACCOUNT* module of the use case diagram.

A-015 **UPDATE TEACHER**

Use Case Name: UPDATE TEACHER

Purpose: Amend the stored details of an existing teacher account.

Actors: Admin

Input Parameters:

- teacher : Teacher
- newPassword : string?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateTeacher` (POST).
- Appears in the *MANAGE TEACHER ACCOUNT* module of the use case diagram.

A-016 DELETE TEACHER

Use Case Name: DELETE TEACHER

Purpose: Remove a teacher account from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteTeacher` (POST).
- Appears in the *MANAGE TEACHER ACCOUNT* module of the use case diagram.

A-017 UNLOCK ACCOUNT

Use Case Name: UNLOCK ACCOUNT

Purpose: Clear the lockout on an account that has been locked by repeated failed sign-in attempts.

Actors: Admin

Input Parameters:

- `accountRole : AccountRole`
- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.UnlockAccount` (POST).
- Appears in the *MANAGE TEACHER ACCOUNT* module of the use case diagram.

A-018 SET ACCOUNT ACTIVE

Use Case Name: SET ACCOUNT ACTIVE

Purpose: Activate or deactivate an account without deleting it, so a person can be kept out of the system while their records survive.

Actors: Admin

Input Parameters:

- `accountRole : AccountRole`
- `id : int`
- `isActive : bool`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.SetAccountActive (POST)`.
- Appears in the *MANAGE TEACHER ACCOUNT* module of the use case diagram.

MANAGE STUDENT ACCOUNT AdminController

System Use Case:



Written Use Case:

A-019 **VIEW STUDENTS**

Use Case Name: VIEW STUDENTS

Purpose: List the students the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Students (GET)`.
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

A-020 CREATE STUDENT

Use Case Name: CREATE STUDENT

Purpose: Record a new student account in the system.

Actors: Admin

Input Parameters:

- student : Student

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateStudent` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

A-021 UPDATE STUDENT

Use Case Name: UPDATE STUDENT

Purpose: Amend the stored details of an existing student account.

Actors: Admin

Input Parameters:

- student : Student
- newPassword : string?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateStudent` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

A-022 DELETE STUDENT

Use Case Name: DELETE STUDENT

Purpose: Remove a student account from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteStudent` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

A-023 BULK CREATE STUDENTS

Use Case Name: BULK CREATE STUDENTS

Purpose: Create many student accounts in one operation from pasted or uploaded CSV rows.

Actors: Admin

Input Parameters:

- bulkFirstNames : List<string>?
- bulkLastNames : List<string>?
- bulkUserNames : List<string>?
- bulkPasswords : List<string>?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through ApplicationDbContext.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by AdminController.BulkCreateStudents (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.
- Pulls in **BULK PREVIEW CSV** (<<include>>).

A-024 **BULK PREVIEW CSV**

Use Case Name: BULK PREVIEW CSV

Purpose: Parse the submitted CSV and show what would be created, so mistakes are caught before any account exists.

Actors: Admin, None; this behaviour runs inside **BULK CREATE STUDENTS**

Input Parameters:

- `classId : int`
- `file : IFormFile?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.
- **BULK CREATE STUDENTS** has reached the point where this is always performed.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.BulkPreviewCsv` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.
- Drawn as <<include>> from **BULK CREATE STUDENTS**.

MANAGE COMPUTER PROFILE AdminController

System Use Case:



Written Use Case:

A-025 **VIEW COMPUTERS**

Use Case Name: VIEW COMPUTERS

Purpose: List the computers the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by AdminController.Computers (GET).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

A-026 **CREATE COMPUTER**

Use Case Name: CREATE COMPUTER

Purpose: Record a new workstation profile in the system.

Actors: Admin

Input Parameters:

- computer : Computer

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

A-027 UPDATE COMPUTER

Use Case Name: UPDATE COMPUTER

Purpose: Amend the stored details of an existing workstation profile.

Actors: Admin

Input Parameters:

- computer : Computer

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

A-028 DELETE COMPUTER

Use Case Name: DELETE COMPUTER

Purpose: Remove a workstation profile from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

A-029 **ASSIGN COMPUTER**

Use Case Name: ASSIGN COMPUTER

Purpose: Bind a workstation to a student so the workstation is recognised when that student signs in at it.

Actors: Admin

Input Parameters:

- `studentId : int`
- `computerId : int?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.AssignComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

A-030 COMPUTER HISTORY

Use Case Name: COMPUTER HISTORY

Purpose: Show the recorded status changes for a workstation, and who made each one.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ComputerHistory` (GET).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

MANAGE CLASS `AdminController`

System Use Case:



Written Use Case:

A-031 **VIEW CLASSES**

Use Case Name: VIEW CLASSES

Purpose: List the classes the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Classes` (GET).
- Appears in the *MANAGE CLASS* module of the use case diagram.

A-032 **CREATE CLASS**

Use Case Name: CREATE CLASS

Purpose: Record a new class in the system.

Actors: Admin

Input Parameters:

- `cls` : Class

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

A-033 **UPDATE CLASS**

Use Case Name: UPDATE CLASS

Purpose: Amend the stored details of an existing class.

Actors: Admin

Input Parameters:

- `cls` : Class

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

A-034 **DELETE CLASS**

Use Case Name: DELETE CLASS

Purpose: Remove a class from the system.

Actors: Admin

Input Parameters:

- `classId : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

A-035 **ASSIGN TEACHER**

Use Case Name: ASSIGN TEACHER

Purpose: Put a teacher in charge of a class.

Actors: Admin

Input Parameters:

- `classId : int`
- `teacherId : int?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.AssignTeacher` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

A-036 **ARCHIVE CLASS**

Use Case Name: ARCHIVE CLASS

Purpose: Take a class out of active use while keeping its roster and records.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ArchiveClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

MANAGE CLASS ROSTER `AdminController`

System Use Case:



Written Use Case:

A-037 CLASS DETAILS

Use Case Name: CLASS DETAILS

Purpose: Show one class with its roster and the students enrolled in it.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ClassDetails` (GET).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

A-038 ENROLL STUDENT

Use Case Name: ENROLL STUDENT

Purpose: Add an existing student to a class roster.

Actors: Admin

Input Parameters:

- `classId` : int
- `studentId` : int
- `moveStudent` : bool (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.EnrollStudent` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

A-039 ENROLL STUDENTS

Use Case Name: ENROLL STUDENTS

Purpose: Add several existing students to a class roster in one operation.

Actors: Admin

Input Parameters:

- `classId : int`
- `studentIds : List<int>?`
- `moveStudent : bool` (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.EnrollStudents` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

A-040 **ADD STUDENT TO CLASS**

Use Case Name: ADD STUDENT TO CLASS

Purpose: Create a new student account and place it on a class roster in one step.

Actors: Admin

Input Parameters:

- `classId : int`
- `firstName : string`
- `lastName : string`
- `username : string?`
- `password : string?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.AddStudentToClass` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

A-041 **ASSIGN STUDENT TO CLASS**

Use Case Name: ASSIGN STUDENT TO CLASS

Purpose: Set the primary class a student belongs to.

Actors: Admin

Input Parameters:

- `studentId : int`
- `classId : int?`
- `moveStudent : bool` (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.AssignStudentToClass` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

A-042 REMOVE STUDENT

Use Case Name: REMOVE STUDENT

Purpose: Take a student off a class roster while leaving the student account intact.

Actors: Admin

Input Parameters:

- `classId : int`
- `studentId : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.RemoveStudent` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

MANAGE RESTRICTION RULE AdminController

System Use Case:



Written Use Case:

A-043 **VIEW RESTRICTIONS**

Use Case Name: VIEW RESTRICTIONS

Purpose: List the restrictions the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Restrictions (GET)`.
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

A-044 CREATE RESTRICTION

Use Case Name: CREATE RESTRICTION

Purpose: Record a new restriction rule in the system.

Actors: Admin

Input Parameters:

- rule : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateRestriction` (POST).
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

A-045 UPDATE RESTRICTION

Use Case Name: UPDATE RESTRICTION

Purpose: Amend the stored details of an existing restriction rule.

Actors: Admin

Input Parameters:

- `input : RestrictionRule`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateRestriction` (POST).
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

A-046 DELETE RESTRICTION

Use Case Name: DELETE RESTRICTION

Purpose: Remove a restriction rule from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteRestriction` (POST).
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

MANAGE BLACKLIST AND WHITELIST AdminController

System Use Case:



Written Use Case:

A-047 **VIEW BLACKLISTS**

Use Case Name: VIEW BLACKLISTS

Purpose: List the blacklists the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Blacklists (GET)`.
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

A-048 VIEW WHITELISTS

Use Case Name: VIEW WHITELISTS

Purpose: List the whitelists the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Whitelists (GET)`.
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

A-049 CREATE BLACKLIST

Use Case Name: CREATE BLACKLIST

Purpose: Record a new blacklist entry in the system.

Actors: Admin

Input Parameters:

- `RestrictionRuleId` — bound from the submitted form
- `RuleType` — bound from the submitted form
- `Target` — bound from the submitted form
- `Description` — bound from the submitted form
- `IsGlobal` — bound from the submitted form
- `IsActive` — bound from the submitted form
- `item : BlacklistItem`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateBlacklist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

A-050 UPDATE BLACKLIST

Use Case Name: UPDATE BLACKLIST

Purpose: Amend the stored details of an existing blacklist entry.

Actors: Admin

Input Parameters:

- `input : BlacklistItem`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateBlacklist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

A-051 **DELETE BLACKLIST**

Use Case Name: DELETE BLACKLIST

Purpose: Remove a blacklist entry from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteBlacklist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

A-052 **CREATE WHITELIST**

Use Case Name: CREATE WHITELIST

Purpose: Record a new whitelist entry in the system.

Actors: Admin

Input Parameters:

- rule : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateWhitelist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

A-053 UPDATE WHITELIST

Use Case Name: UPDATE WHITELIST

Purpose: Amend the stored details of an existing whitelist entry.

Actors: Admin

Input Parameters:

- RuleType — bound from the submitted form
- Target — bound from the submitted form
- Description — bound from the submitted form
- IsGlobal — bound from the submitted form
- IsActive — bound from the submitted form
- rule : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateWhitelist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

MANAGE CATEGORY AdminController

System Use Case:



Written Use Case:

A-054 **CREATE APPLICATION CATEGORY**

Use Case Name: CREATE APPLICATION CATEGORY

Purpose: Record a new application category in the system.

Actors: Admin

Input Parameters:

- category : ApplicationCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through ApplicationDbContext.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by AdminController.CreateApplicationCategory (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

A-055 UPDATE APPLICATION CATEGORY

Use Case Name: UPDATE APPLICATION CATEGORY

Purpose: Amend the stored details of an existing application category.

Actors: Admin

Input Parameters:

- input : ApplicationCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through ApplicationDbContext.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by AdminController.UpdateApplicationCategory (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

A-056 DELETE APPLICATION CATEGORY

Use Case Name: DELETE APPLICATION CATEGORY

Purpose: Remove a application category from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteApplicationCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

A-057 CREATE WEBSITE CATEGORY

Use Case Name: CREATE WEBSITE CATEGORY

Purpose: Record a new website category in the system.

Actors: Admin

Input Parameters:

- category : WebsiteCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateWebsiteCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

A-058 UPDATE WEBSITE CATEGORY

Use Case Name: UPDATE WEBSITE CATEGORY

Purpose: Amend the stored details of an existing website category.

Actors: Admin

Input Parameters:

- input : WebsiteCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateWebsiteCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

A-059 DELETE WEBSITE CATEGORY

Use Case Name: DELETE WEBSITE CATEGORY

Purpose: Remove a website category from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteWebsiteCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

MANAGE SESSION RULE AdminController

System Use Case:



Written Use Case:

A-060 SESSION RULES

Use Case Name: SESSION RULES

Purpose: List the session rules the signed-in user is allowed to see.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.SessionRules` (GET).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

A-061 CREATE SESSION RULE

Use Case Name: CREATE SESSION RULE

Purpose: Record a new session rule in the system.

Actors: Admin

Input Parameters:

- rule : SessionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateSessionRule` (POST).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

A-062 UPDATE SESSION RULE

Use Case Name: UPDATE SESSION RULE

Purpose: Amend the stored details of an existing session rule.

Actors: Admin

Input Parameters:

- input : SessionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through ApplicationDbContext.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by AdminController.UpdateSessionRule (POST).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

A-063 DELETE SESSION RULE

Use Case Name: DELETE SESSION RULE

Purpose: Remove a session rule from the system.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteSessionRule` (POST).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

MANAGE ROLE AND PERMISSION AdminController

System Use Case:



Written Use Case:

A-064 **VIEW ROLES**

Use Case Name: VIEW ROLES

Purpose: Show the seeded roles and the permissions attached to them.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Roles (GET)`.
- Appears in the *MANAGE ROLE AND PERMISSION* module of the use case diagram.

A-065 **CREATE ROLE**

Use Case Name: CREATE ROLE

Purpose: Add a role to the seeded reference data.

Actors: Admin

Input Parameters:

- role : Role

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateRole` (POST).
- Appears in the *MANAGE ROLE AND PERMISSION* module of the use case diagram.

A-066 DELETE ROLE

Use Case Name: DELETE ROLE

Purpose: Remove a role from the seeded reference data.

Actors: Admin

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteRole` (POST).
- Appears in the *MANAGE ROLE AND PERMISSION* module of the use case diagram.

CONTROL LABORATORY SESSION AdminController

System Use Case:



Written Use Case:

A-067 PAUSE ALL SESSIONS

Use Case Name: PAUSE ALL SESSIONS

Purpose: Pause every active laboratory session at once, freezing the timers across the room.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.PauseAllSessions` (POST).
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.

A-068 RESUME ALL SESSIONS

Use Case Name: RESUME ALL SESSIONS

Purpose: Resume every paused laboratory session at once.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.ResumeAllSessions` (POST).
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.

A-069 **END ALL SESSIONS**

Use Case Name: END ALL SESSIONS

Purpose: End every active laboratory session at once and tell the workstations.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.EndAllSessions` (POST).
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.
- Pulls in **NOTIFY STATES ASYNC** (<<include>>).

A-070 NOTIFY STATES ASYNC

Use Case Name: NOTIFY STATES ASYNC

Purpose: Push the new session state to every affected workstation so clients stop their timers rather than waiting to notice.

Actors: Admin, None; this behaviour runs inside **END ALL SESSIONS**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **END ALL SESSIONS** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `NotifyStatesAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `NotifyStatesAsync`.
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.
- Drawn as <<include>> from **END ALL SESSIONS**.

VIEW REPORTS AND LOGS AdminController

System Use Case:



Written Use Case:

A-071 **VIEW REPORTS**

Use Case Name: VIEW REPORTS

Purpose: Show the laboratory reports an administrator uses for oversight.

Actors: Admin

Input Parameters:

- from : DateTime?
- to : DateTime?
- classId : int? (optional)
- station : string? (optional)
- page : int (optional)
- pageSize : int (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.Reports (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Pulls in **EXPORT REPORTS CSV** (<<extend>>), **EXPORT ATTENDANCE CSV** (<<extend>>), **EXPORT USAGE CSV** (<<extend>>), **EXPORT REMOTE COMMANDS CSV** (<<extend>>).

A-072 **AUDIT LOGS**

Use Case Name: AUDIT LOGS

Purpose: Show the audit trail of administrative actions.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.AuditLogs (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Pulls in **EXPORT AUDIT CSV** (<<extend>>).

A-073 **SYSTEM LOGS**

Use Case Name: SYSTEM LOGS

Purpose: Show the technical log the server writes.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.SystemLogs (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Pulls in **EXPORT SYSTEM LOGS CSV** (<<extend>>).

A-074 **EXPORT REPORTS CSV**

Use Case Name: EXPORT REPORTS CSV

Purpose: Produce the reports view as a CSV file the user can download.

Actors: Admin, None; this behaviour runs inside **VIEW REPORTS**

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- classId : int? (optional)
- station : string? (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- The record named by the identifier exists.
- **VIEW REPORTS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ExportReportsCsv` (GET).
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Drawn as <<extend>> to **VIEW REPORTS**.

A-075 **EXPORT ATTENDANCE CSV**

Use Case Name: EXPORT ATTENDANCE CSV

Purpose: Produce the attendance view as a CSV file the user can download.

Actors: Admin, None; this behaviour runs inside **VIEW REPORTS**

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- classId : int? (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- The record named by the identifier exists.
- **VIEW REPORTS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ExportAttendanceCsv (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Drawn as <<extend>> to **VIEW REPORTS**.

A-076 **EXPORT USAGE CSV**

Use Case Name: EXPORT USAGE CSV

Purpose: Produce the usage view as a CSV file the user can download.

Actors: Admin, None; this behaviour runs inside **VIEW REPORTS**

Input Parameters:

- from : DateTime?
- to : DateTime?

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- **VIEW REPORTS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.ExportUsageCsv (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Drawn as <<extend>> to **VIEW REPORTS**.

A-077 **EXPORT REMOTE COMMANDS CSV**

Use Case Name: EXPORT REMOTE COMMANDS CSV

Purpose: Produce the remote commands view as a CSV file the user can download.

Actors: Admin, None; this behaviour runs inside **VIEW REPORTS**

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- teacherId : int? (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- The record named by the identifier exists.
- **VIEW REPORTS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ExportRemoteCommandsCsv (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Drawn as <<extend>> to **VIEW REPORTS**.

A-078 **EXPORT AUDIT CSV**

Use Case Name: EXPORT AUDIT CSV

Purpose: Produce the audit view as a CSV file the user can download.

Actors: Admin, None; this behaviour runs inside **AUDIT LOGS**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- **AUDIT LOGS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.ExportAuditCsv (GET)`.
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Drawn as <<extend>> to **AUDIT LOGS**.

A-079 **EXPORT SYSTEM LOGS CSV**

Use Case Name: EXPORT SYSTEM LOGS CSV

Purpose: Produce the system logs view as a CSV file the user can download.

Actors: Admin, None; this behaviour runs inside **SYSTEM LOGS**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher.
- **SYSTEM LOGS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.ExportSystemLogsCsv` (GET).
- Appears in the *VIEW REPORTS AND LOGS* module of the use case diagram.
- Drawn as <<extend>> to **SYSTEM LOGS**.

MANAGE DATABASE `AdminDatabaseController`

System Use Case:



Written Use Case:

A-080 DATABASE INDEX

Use Case Name: DATABASE INDEX

Purpose: Show database health: file size, integrity check, applied and pending migrations, and the backups on disk.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminDatabaseController.Index (GET)`.
- Appears in the *MANAGE DATABASE* module of the use case diagram.

A-081 **CREATE BACKUP**

Use Case Name: CREATE BACKUP

Purpose: Take a backup copy of the SQLite database file and store it on the server.

Actors: Admin

Input Parameters:

- label : string?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminDatabaseController.CreateBackup` (POST).
- Appears in the *MANAGE DATABASE* module of the use case diagram.

A-082 **VALIDATE BACKUP**

Use Case Name: VALIDATE BACKUP

Purpose: Check that a backup file is a readable, intact database before anybody relies on it.

Actors: Admin

Input Parameters:

- backupFileName : string

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminDatabaseController.ValidateBackup` (POST).
- Appears in the *MANAGE DATABASE* module of the use case diagram.

A-083 **STAGE RESTORE**

Use Case Name: STAGE RESTORE

Purpose: Stage a backup so the server restores it on the next restart, rather than swapping the file underneath a running system.

Actors: Admin

Input Parameters:

- backupFileName : string
- confirmation : string?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminDatabaseController.StageRestore` (POST).
- Appears in the *MANAGE DATABASE* module of the use case diagram.
- Pulls in **STAGE RESTORE ASYNC** (<<include>>).

A-084 **STAGE RESTORE ASYNC**

Use Case Name: STAGE RESTORE ASYNC

Purpose: Take a safety backup of the current database and mark the chosen backup for restore at next start.

Actors: Admin, None; this behaviour runs inside **STAGE RESTORE**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **STAGE RESTORE** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `StageRestoreAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `StageRestoreAsync`.
- Appears in the *MANAGE DATABASE* module of the use case diagram.
- Drawn as <<include>> from **STAGE RESTORE**.

MANAGE DEPLOYMENT `AdminDeploymentController`

System Use Case:



Written Use Case:

A-085 DEPLOYMENT INDEX

Use Case Name: DEPLOYMENT INDEX

Purpose: Show the deployment hub: release version, installer and certificate state, and the endpoint clients should use.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminDeploymentController.Index (GET)`.
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.
- Pulls in **GET STATUS ASYNC** (<<include>>).

A-086 **DOWNLOAD INSTALLER**

Use Case Name: DOWNLOAD INSTALLER

Purpose: Download the client installer for deployment to a workstation.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminDeploymentController.Installer (GET)`.
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.

A-087 **DOWNLOAD MANIFEST**

Use Case Name: DOWNLOAD MANIFEST

Purpose: Download the release manifest listing the files and their hashes.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminDeploymentController.Manifest (GET)`.
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.

A-088 ROOT CERTIFICATE

Use Case Name: ROOT CERTIFICATE

Purpose: Download the root certificate a workstation must trust to reach the server over HTTPS.

Actors: Admin

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminDeploymentController.RootCertificate (GET)`.
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.

A-089 CREATE BUNDLE

Use Case Name: CREATE BUNDLE

Purpose: Build and download an offline client bundle for a workstation with no access to the server yet.

Actors: Admin

Input Parameters:

- endpoint : string

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Admin opens the page and CAMS confirms the role on the authentication cookie.
2. The Admin fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminDeploymentController.Bundle` (POST).
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.
- Pulls in **CREATE BUNDLE ASYNC** (<<include>>).

A-090 GET STATUS ASYNC

Use Case Name: GET STATUS ASYNC

Purpose: Gather the deployment state: release version, file hashes, certificate and endpoint.

Actors: Admin, None; this behaviour runs inside **DEPLOYMENT INDEX**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **DEPLOYMENT INDEX** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `GetStatusAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `GetStatusAsync`.
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.
- Drawn as <<include>> from **DEPLOYMENT INDEX**.

A-091 **CREATE BUNDLE ASYNC**

Use Case Name: CREATE BUNDLE ASYNC

Purpose: Assemble an offline installer bundle carrying the installer, the root certificate and the server endpoint.

Actors: Admin, None; this behaviour runs inside **CREATE BUNDLE**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **CREATE BUNDLE** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `CreateBundleAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.


Additional Remarks:

- Implemented by `CreateBundleAsync`.
- Appears in the *MANAGE DEPLOYMENT* module of the use case diagram.
- Drawn as <<include>> from **CREATE BUNDLE**.

Teacher

PROCESS LOG IN AccountController

System Use Case:



Written Use Case:

T-092 LOGIN USER

Use Case Name: LOGIN USER

Purpose: Let a person sign in to the CAMS web portal with a username and password, and place them in the part of the system their role allows.

Actors: Teacher

Input Parameters:

- username : string
- password : string

Output Parameters:

- An authentication cookie carrying the account role as a claim, and a redirect to the landing page for that role.

Pre-Condition:

- None. This is the sign-in endpoint and is reachable without an account session; the CAMS server must be running and reachable.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the CAMS sign-in page.
2. The Teacher enters a username and a password and submits the form.
3. The server validates the antiforgery token that accompanied the form.
4. The server checks the credentials against each account table in turn and finds the matching account.
5. The server confirms the account is active and not locked out.
6. The server issues an authentication cookie carrying the role as a claim.
7. The Teacher is redirected to the landing page for that role.

Exception Scenario:

- **The username matches no account** — the page reports that the sign-in failed, without saying which half was wrong.
- **The password does not match the stored hash** — the failed-attempt counter is raised and the same message is shown.
- **The account is locked out** — the sign-in is refused until the lockout expires, even with the right password.
- **The account is deactivated** — the sign-in is refused and the person is told to contact an administrator.

Additional Remarks:

- Implemented by `AccountController.Login (POST)`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.

- Pulls in **LOGIN ASYNC** (<<include>>).

T-093 **LOGOUT USER**

Use Case Name: LOGOUT USER

Purpose: End the signed-in session and clear the authentication cookie, so the next visitor to the browser starts as an anonymous user.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The authentication cookie is cleared and the browser is returned to the sign-in page.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher chooses to sign out.
2. The server closes any lab session the account still has open.
3. The server clears the authentication cookie.
4. The browser is returned to the sign-in page as an anonymous visitor.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AccountController.Logout` (POST).
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Pulls in **LOGOUT ASYNC** (<<include>>).

T-094 **LOGIN ASYNC**

Use Case Name: LOGIN ASYNC

Purpose: Check the supplied password against the stored hash, confirm the account is active and not locked out, and decide which of the three account tables the person belongs to.

Actors: Teacher, None; this behaviour runs inside **LOGIN USER**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A `LoginResult` naming the role, the account id and the display name, or a result saying the credentials were rejected.

Pre-Condition:

- The sign-in use case has supplied a username and a password.
- **LOGIN USER** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The sign-in use case passes the username, the password, the workstation name and the caller address.
2. The service looks the username up in the administrator, teacher and student tables.
3. The stored hash is verified against the supplied password.
4. The active flag and the lockout expiry are checked.
5. On success the failed-attempt counter is cleared and the role and account id are returned; on failure the counter is raised.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `LoginAsync`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Drawn as <<include>> from **LOGIN USER**.

T-095 **LOGOUT ASYNC**

Use Case Name: LOGOUT ASYNC

Purpose: Close any lab session the student still has open and record the sign-out.

Actors: Teacher, None; this behaviour runs inside **LOGOUT USER**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **LOGOUT USER** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `LogoutAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `LogoutAsync`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Drawn as <<include>> from **LOGOUT USER**.

MANAGE OWN ACCOUNT `TeacherController`

System Use Case:



Written Use Case:

T-096 **VIEW SETTINGS**

Use Case Name: VIEW SETTINGS

Purpose: Show the settings page for the signed-in user.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Settings (GET)`.
- Appears in the *MANAGE OWN ACCOUNT* module of the use case diagram.

T-097 **CHANGE PASSWORD**

Use Case Name: CHANGE PASSWORD

Purpose: Let the signed-in user replace their own password after proving they know the current one.

Actors: Teacher

Input Parameters:

- input : PasswordChangeInput

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.ChangePassword` (POST).
- Appears in the *MANAGE OWN ACCOUNT* module of the use case diagram.
- Pulls in **CHANGE TEACHER PASSWORD ASYNC** (<<include>>).

T-098 **CHANGE TEACHER PASSWORD ASYNC**

Use Case Name: CHANGE TEACHER PASSWORD ASYNC

Purpose: Verify the current password and replace the stored hash for a teacher account.

Actors: Teacher, None; this behaviour runs inside **CHANGE PASSWORD**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **CHANGE PASSWORD** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `ChangeTeacherPasswordAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `ChangeTeacherPasswordAsync`.
- Appears in the *MANAGE OWN ACCOUNT* module of the use case diagram.
- Drawn as <<include>> from **CHANGE PASSWORD**.

MANAGE PEER TEACHER ACCOUNT `AdminController`

System Use Case:



Written Use Case:

T-099 **VIEW TEACHERS**

Use Case Name: VIEW TEACHERS

Purpose: List the teachers the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Teachers (GET)`.
- Appears in the *MANAGE PEER TEACHER ACCOUNT* module of the use case diagram.

T-100 **CREATE TEACHER**

Use Case Name: CREATE TEACHER

Purpose: Record a new teacher account in the system.

Actors: Teacher

Input Parameters:

- teacher : Teacher

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateTeacher` (POST).
- Appears in the *MANAGE PEER TEACHER ACCOUNT* module of the use case diagram.

T-101 UPDATE TEACHER

Use Case Name: UPDATE TEACHER

Purpose: Amend the stored details of an existing teacher account.

Actors: Teacher

Input Parameters:

- teacher : Teacher
- newPassword : string?

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateTeacher` (POST).
- Appears in the *MANAGE PEER TEACHER ACCOUNT* module of the use case diagram.

T-102 DELETE TEACHER

Use Case Name: DELETE TEACHER

Purpose: Remove a teacher account from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteTeacher` (POST).
- Appears in the *MANAGE PEER TEACHER ACCOUNT* module of the use case diagram.

T-103 UNLOCK ACCOUNT

Use Case Name: UNLOCK ACCOUNT

Purpose: Clear the lockout on an account that has been locked by repeated failed sign-in attempts.

Actors: Teacher

Input Parameters:

- `accountRole : AccountRole`
- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.UnlockAccount` (POST).
- Appears in the *MANAGE PEER TEACHER ACCOUNT* module of the use case diagram.

T-104 SET ACCOUNT ACTIVE

Use Case Name: SET ACCOUNT ACTIVE

Purpose: Activate or deactivate an account without deleting it, so a person can be kept out of the system while their records survive.

Actors: Teacher

Input Parameters:

- `accountRole : AccountRole`
- `id : int`
- `isActive : bool`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.SetAccountActive (POST)`.
- Appears in the *MANAGE PEER TEACHER ACCOUNT* module of the use case diagram.

MANAGE STUDENT ACCOUNT TeacherController

System Use Case:



Written Use Case:

T-105 **VIEW STUDENTS**

Use Case Name: VIEW STUDENTS

Purpose: List the students the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- `search : string?` (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Students` (GET).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

T-106 CREATE STUDENT

Use Case Name: CREATE STUDENT

Purpose: Record a new student account in the system.

Actors: Teacher

Input Parameters:

- student : Student
- classId : int? (optional)
- search : string? (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.CreateStudent` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

T-107 UPDATE STUDENT

Use Case Name: UPDATE STUDENT

Purpose: Amend the stored details of an existing student account.

Actors: Teacher

Input Parameters:

- student : Student
- newPassword : string?
- search : string? (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.UpdateStudent` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

T-108 DELETE STUDENT

Use Case Name: DELETE STUDENT

Purpose: Remove a student account from the system.

Actors: Teacher

Input Parameters:

- `studentId : int`
- `search : string?` (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `TeacherController.DeleteStudent` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

T-109 BULK ADD STUDENTS

Use Case Name: BULK ADD STUDENTS

Purpose: Create many student accounts at once and enrol them into a class in the same operation.

Actors: Teacher

Input Parameters:

- `classId : int`
- `bulkFirstNames : List<string>?`
- `bulkLastNames : List<string>?`
- `bulkUserNames : List<string>?`
- `bulkPasswords : List<string>?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.BulkAddStudents` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

- Pulls in **BULK PREVIEW CSV** (<<include>>).

T-110 **BULK PREVIEW CSV**

Use Case Name: BULK PREVIEW CSV

Purpose: Parse the submitted CSV and show what would be created, so mistakes are caught before any account exists.

Actors: Teacher, None; this behaviour runs inside **BULK ADD STUDENTS**

Input Parameters:

- `classId : int`
- `file : IFormFile?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.
- **BULK ADD STUDENTS** has reached the point where this is always performed.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.BulkPreviewCsv` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.
- Drawn as <<include>> from **BULK ADD STUDENTS**.

MANAGE COMPUTER PROFILE AdminController

System Use Case:



Written Use Case:

T-111 VIEW COMPUTERS

Use Case Name: VIEW COMPUTERS

Purpose: List the computers the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by AdminController.Computers (GET).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

T-112 CREATE COMPUTER

Use Case Name: CREATE COMPUTER

Purpose: Record a new workstation profile in the system.

Actors: Teacher

Input Parameters:

- computer : Computer

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

T-113 UPDATE COMPUTER

Use Case Name: UPDATE COMPUTER

Purpose: Amend the stored details of an existing workstation profile.

Actors: Teacher

Input Parameters:

- computer : Computer

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

T-114 DELETE COMPUTER

Use Case Name: DELETE COMPUTER

Purpose: Remove a workstation profile from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

T-115 **ASSIGN COMPUTER**

Use Case Name: ASSIGN COMPUTER

Purpose: Bind a workstation to a student so the workstation is recognised when that student signs in at it.

Actors: Teacher

Input Parameters:

- `studentId : int`
- `computerId : int?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.AssignComputer` (POST).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

T-116 COMPUTER HISTORY

Use Case Name: COMPUTER HISTORY

Purpose: Show the recorded status changes for a workstation, and who made each one.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `AdminController.ComputerHistory` (GET).
- Appears in the *MANAGE COMPUTER PROFILE* module of the use case diagram.

MANAGE CLASS `TeacherController`

System Use Case:



Written Use Case:

T-117 **VIEW CLASSES**

Use Case Name: VIEW CLASSES

Purpose: List the classes the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Classes (GET)`.
- Appears in the *MANAGE CLASS* module of the use case diagram.

T-118 **CREATE CLASS**

Use Case Name: CREATE CLASS

Purpose: Record a new class in the system.

Actors: Teacher

Input Parameters:

- `cls` : Class

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.CreateClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

T-119 UPDATE CLASS

Use Case Name: UPDATE CLASS

Purpose: Amend the stored details of an existing class.

Actors: Teacher

Input Parameters:

- `cls` : Class

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.UpdateClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

T-120 DELETE CLASS

Use Case Name: DELETE CLASS

Purpose: Remove a class from the system.

Actors: Teacher

Input Parameters:

- `classId : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `TeacherController.DeleteClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

T-121 **ASSIGN TEACHER**

Use Case Name: ASSIGN TEACHER

Purpose: Put a teacher in charge of a class.

Actors: Teacher

Input Parameters:

- `classId : int`
- `teacherId : int?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.AssignTeacher` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

T-122 **ARCHIVE CLASS**

Use Case Name: ARCHIVE CLASS

Purpose: Take a class out of active use while keeping its roster and records.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.ArchiveClass` (POST).
- Appears in the *MANAGE CLASS* module of the use case diagram.

MANAGE CLASS ROSTER `TeacherController`

System Use Case:



Written Use Case:

T-123 CLASS DETAILS

Use Case Name: CLASS DETAILS

Purpose: Show one class with its roster and the students enrolled in it.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.ClassDetails (GET)`.
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

T-124 **ENROLL STUDENT**

Use Case Name: ENROLL STUDENT

Purpose: Add an existing student to a class roster.

Actors: Teacher

Input Parameters:

- `classId` : int
- `studentId` : int
- `moveStudent` : bool (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.EnrollStudent` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

T-125 ENROLL STUDENTS

Use Case Name: ENROLL STUDENTS

Purpose: Add several existing students to a class roster in one operation.

Actors: Teacher

Input Parameters:

- `classId : int`
- `studentIds : List<int>?`
- `moveStudent : bool` (optional)

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.EnrollStudents` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

T-126 **ADD STUDENT TO CLASS**

Use Case Name: ADD STUDENT TO CLASS

Purpose: Create a new student account and place it on a class roster in one step.

Actors: Teacher

Input Parameters:

- `classId : int`
- `firstName : string`
- `lastName : string`
- `username : string?`
- `password : string?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.AddStudentToClass` (POST).
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

T-127 REMOVE STUDENT

Use Case Name: REMOVE STUDENT

Purpose: Take a student off a class roster while leaving the student account intact.

Actors: Teacher

Input Parameters:

- `classId : int`
- `studentId : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.RemoveStudent (POST)`.
- Appears in the *MANAGE CLASS ROSTER* module of the use case diagram.

MANAGE RESTRICTION RULE TeacherController

System Use Case:



Written Use Case:

T-128 VIEW RESTRICTIONS

Use Case Name: VIEW RESTRICTIONS

Purpose: List the restrictions the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Restrictions (GET)`.
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

T-129 CREATE RESTRICTION

Use Case Name: CREATE RESTRICTION

Purpose: Record a new restriction rule in the system.

Actors: Teacher

Input Parameters:

- rule : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.CreateRestriction` (POST).
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

T-130 UPDATE RESTRICTION

Use Case Name: UPDATE RESTRICTION

Purpose: Amend the stored details of an existing restriction rule.

Actors: Teacher

Input Parameters:

- input : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.UpdateRestriction` (POST).
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

T-131 DELETE RESTRICTION

Use Case Name: DELETE RESTRICTION

Purpose: Remove a restriction rule from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `TeacherController.DeleteRestriction` (POST).
- Appears in the *MANAGE RESTRICTION RULE* module of the use case diagram.

MANAGE BLACKLIST AND WHITELIST AdminController

System Use Case:



Written Use Case:

T-132 VIEW BLACKLISTS

Use Case Name: VIEW BLACKLISTS

Purpose: List the blacklists the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Blacklists (GET)`.
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

T-133 VIEW WHITELISTS

Use Case Name: VIEW WHITELISTS

Purpose: List the whitelists the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Whitelists (GET)`.
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

T-134 CREATE BLACKLIST

Use Case Name: CREATE BLACKLIST

Purpose: Record a new blacklist entry in the system.

Actors: Teacher

Input Parameters:

- `RestrictionRuleId` — bound from the submitted form
- `RuleType` — bound from the submitted form
- `Target` — bound from the submitted form
- `Description` — bound from the submitted form
- `IsGlobal` — bound from the submitted form
- `IsActive` — bound from the submitted form
- `item : BlacklistItem`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateBlacklist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

T-135 UPDATE BLACKLIST

Use Case Name: UPDATE BLACKLIST

Purpose: Amend the stored details of an existing blacklist entry.

Actors: Teacher

Input Parameters:

- input : BlacklistItem

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateBlacklist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

T-136 DELETE BLACKLIST

Use Case Name: DELETE BLACKLIST

Purpose: Remove a blacklist entry from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteBlacklist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

T-137 CREATE WHITELIST

Use Case Name: CREATE WHITELIST

Purpose: Record a new whitelist entry in the system.

Actors: Teacher

Input Parameters:

- rule : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateWhitelist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

T-138 UPDATE WHITELIST

Use Case Name: UPDATE WHITELIST

Purpose: Amend the stored details of an existing whitelist entry.

Actors: Teacher

Input Parameters:

- RuleType — bound from the submitted form
- Target — bound from the submitted form
- Description — bound from the submitted form
- IsGlobal — bound from the submitted form
- IsActive — bound from the submitted form
- rule : RestrictionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateWhitelist` (POST).
- Appears in the *MANAGE BLACKLIST AND WHITELIST* module of the use case diagram.

MANAGE CATEGORY AdminController

System Use Case:



Written Use Case:

T-139 CREATE APPLICATION CATEGORY

Use Case Name: CREATE APPLICATION CATEGORY

Purpose: Record a new application category in the system.

Actors: Teacher

Input Parameters:

- category : ApplicationCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through ApplicationDbContext.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by AdminController.CreateApplicationCategory (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

T-140 UPDATE APPLICATION CATEGORY

Use Case Name: UPDATE APPLICATION CATEGORY

Purpose: Amend the stored details of an existing application category.

Actors: Teacher

Input Parameters:

- input : ApplicationCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through ApplicationDbContext.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by AdminController.UpdateApplicationCategory (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

T-141 DELETE APPLICATION CATEGORY

Use Case Name: DELETE APPLICATION CATEGORY

Purpose: Remove a application category from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteApplicationCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

T-142 CREATE WEBSITE CATEGORY

Use Case Name: CREATE WEBSITE CATEGORY

Purpose: Record a new website category in the system.

Actors: Teacher

Input Parameters:

- category : WebsiteCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateWebsiteCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

T-143 UPDATE WEBSITE CATEGORY

Use Case Name: UPDATE WEBSITE CATEGORY

Purpose: Amend the stored details of an existing website category.

Actors: Teacher

Input Parameters:

- input : WebsiteCategory

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateWebsiteCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

T-144 **DELETE WEBSITE CATEGORY**

Use Case Name: DELETE WEBSITE CATEGORY

Purpose: Remove a website category from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries `[TeacherSharedAction]`; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteWebsiteCategory` (POST).
- Appears in the *MANAGE CATEGORY* module of the use case diagram.

MANAGE SESSION RULE AdminController

System Use Case:



Written Use Case:

T-145 **SESSION RULES**

Use Case Name: SESSION RULES

Purpose: List the session rules the signed-in user is allowed to see.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.SessionRules (GET)`.
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

T-146 CREATE SESSION RULE

Use Case Name: CREATE SESSION RULE

Purpose: Record a new session rule in the system.

Actors: Teacher

Input Parameters:

- rule : SessionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.CreateSessionRule` (POST).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

T-147 UPDATE SESSION RULE

Use Case Name: UPDATE SESSION RULE

Purpose: Amend the stored details of an existing session rule.

Actors: Teacher

Input Parameters:

- input : SessionRule

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AdminController.UpdateSessionRule` (POST).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

T-148 DELETE SESSION RULE

Use Case Name: DELETE SESSION RULE

Purpose: Remove a session rule from the system.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The record is still referenced** — the deletion is refused rather than leaving dangling references.

Additional Remarks:

- Implemented by `AdminController.DeleteSessionRule` (POST).
- Appears in the *MANAGE SESSION RULE* module of the use case diagram.

CONTROL LABORATORY SESSION TeacherController

System Use Case:



Written Use Case:

T-149 GLOBAL START SESSION

Use Case Name: GLOBAL START SESSION

Purpose: Start a laboratory-wide session so every connected workstation begins at the same moment.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.GlobalStartSession` (POST).
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.

T-150 GLOBAL PAUSE SESSION

Use Case Name: GLOBAL PAUSE SESSION

Purpose: Pause the laboratory-wide session for the whole room.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.GlobalPauseSession` (POST).
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.

T-151 GLOBAL END SESSION

Use Case Name: GLOBAL END SESSION

Purpose: End the laboratory-wide session for the whole room.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.GlobalEndSession` (POST).
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.
- Pulls in **NOTIFY STATES ASYNC** (<<include>>).

T-152 GLOBAL SESSION STATE

Use Case Name: GLOBAL SESSION STATE

Purpose: Report the current laboratory-wide session state so the page can show the right timer and controls.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.GlobalSessionState (GET)`.
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.

T-153 NOTIFY STATES ASYNC

Use Case Name: NOTIFY STATES ASYNC

Purpose: Push the new session state to every affected workstation so clients stop their timers rather than waiting to notice.

Actors: Teacher, None; this behaviour runs inside **GLOBAL END SESSION**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **GLOBAL END SESSION** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `NotifyStatesAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `NotifyStatesAsync`.
- Appears in the *CONTROL LABORATORY SESSION* module of the use case diagram.
- Drawn as <<include>> from **GLOBAL END SESSION**.

CONTROL STUDENT SESSION TeacherController

System Use Case:



Written Use Case:

T-154 **VIEW SESSIONS**

Use Case Name: VIEW SESSIONS

Purpose: List the lab sessions the teacher may act on.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Sessions (GET)`.
- Appears in the *CONTROL STUDENT SESSION* module of the use case diagram.

T-155 **START SESSION**

Use Case Name: START SESSION

Purpose: Open a lab session for one student at one workstation under a chosen session rule.

Actors: Teacher

Input Parameters:

- `studentId : int`
- `computerId : int?`
- `sessionRuleId : int?`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.StartSession` (POST).
- Appears in the *CONTROL STUDENT SESSION* module of the use case diagram.
- Pulls in **ENSURE STUDENT SESSION ASYNC** (<<include>>).

T-156 TOGGLE PAUSE

Use Case Name: TOGGLE PAUSE

Purpose: Pause a running session, or resume a paused one, accumulating the paused time so it is not charged against the limit.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.TogglePause` (POST).
- Appears in the *CONTROL STUDENT SESSION* module of the use case diagram.

T-157 **END SESSION**

Use Case Name: END SESSION

Purpose: Close one student lab session and record its end time.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.EndSession` (POST).
- Appears in the *CONTROL STUDENT SESSION* module of the use case diagram.

T-158 **ENSURE STUDENT SESSION ASYNC**

Use Case Name: ENSURE STUDENT SESSION ASYNC

Purpose: Find the student a session, creating one if none is open, and apply the governing session rule to it.

Actors: Teacher, None; this behaviour runs inside **START SESSION**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **START SESSION** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `EnsureStudentSessionAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `EnsureStudentSessionAsync`.
- Appears in the *CONTROL STUDENT SESSION* module of the use case diagram.
- Drawn as `<<include>>` from **START SESSION**.
- Pulls in **END EXPIRED SESSIONS ASYNC** (`<<extend>>`).

T-159 **END EXPIRED SESSIONS ASYNC**

Use Case Name: END EXPIRED SESSIONS ASYNC

Purpose: Close sessions that have run past the limit their session rule sets, without anyone having to intervene.

Actors: Teacher, None; this behaviour runs inside **ENSURE STUDENT SESSION ASYNC**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **ENSURE STUDENT SESSION ASYNC** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `EndExpiredSessionsAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `EndExpiredSessionsAsync`.
- Appears in the *CONTROL STUDENT SESSION* module of the use case diagram.
- Drawn as <<extend>> to **ENSURE STUDENT SESSION ASYNC**.

MONITOR STUDENT SCREEN TeacherController + Hub

System Use Case:



Written Use Case:

T-160 OPEN MONITORING

Use Case Name: OPEN MONITORING

Purpose: Open the live monitoring wall showing every connected student workstation.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Monitoring (GET)`.
- Appears in the *MONITOR STUDENT SCREEN* module of the use case diagram.
- Pulls in **SEND SCREEN FRAME** (<<include>>).

T-161 **MONITORING INDEX**

Use Case Name: MONITORING INDEX

Purpose: Serve the monitoring surface the live screen grid is built on.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as an administrator or a teacher. A teacher reaches this action only because it carries [TeacherSharedAction]; the teacher account must also be active.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `AdminController.Index (GET)`.
- Appears in the *MONITOR STUDENT SCREEN* module of the use case diagram.

T-162 **LIVE STATE**

Use Case Name: LIVE STATE

Purpose: Report the current state of every connected workstation so the monitoring page can refresh without reloading.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.LiveState (GET)`.
- Appears in the *MONITOR STUDENT SCREEN* module of the use case diagram.

T-163 **SEND SCREEN FRAME**

Use Case Name: SEND SCREEN FRAME

Purpose: Send one captured frame of the workstation screen to the watching teacher.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- frame : ScreenFrameMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **OPEN MONITORING** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `SendScreenFrame` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.SendScreenFrame (GET)`.
- Appears in the *MONITOR STUDENT SCREEN* module of the use case diagram.
- Drawn as <<include>> from **OPEN MONITORING**.

CONTROL STUDENT WORKSTATION RemoteMonitoringHub

System Use Case:



Written Use Case:

T-164 **START REMOTE CONTROL**

Use Case Name: START REMOTE CONTROL

Purpose: Take keyboard and mouse control of a student workstation, with the client showing that remote control is active.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A `RemoteCommandResult` stating whether the workstation accepted the command, returned to the caller over SignalR.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `StartRemoteControl` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.StartRemoteControl` (GET).
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.
- Pulls in **SEND REMOTE INPUT** (<<include>>).

T-165 **STOP REMOTE CONTROL**

Use Case Name: STOP REMOTE CONTROL

Purpose: Hand control of the workstation back to the student.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A `RemoteCommandResult` stating whether the workstation accepted the command, returned to the caller over SignalR.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `StopRemoteControl` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.StopRemoteControl (GET)`.
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-166 LOCK STUDENT

Use Case Name: LOCK STUDENT

Purpose: Lock a student workstation so the student cannot use it until it is unlocked.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `LockStudent` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.LockStudent` (GET).
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-167 UNLOCK STUDENT

Use Case Name: UNLOCK STUDENT

Purpose: Release the CAMS lock on a student workstation.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `UnlockStudent` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.UnlockStudent (GET)`.
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-168 **FORCE LOGOUT**

Use Case Name: FORCE LOGOUT

Purpose: Sign a student out of the workstation from the teacher console.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `ForceLogout` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.ForceLogout` (GET).
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-169 SHUTDOWN STUDENT

Use Case Name: SHUTDOWN STUDENT

Purpose: Shut a student workstation down remotely.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `ShutdownStudent` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.ShutdownStudent` (GET).
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-170 RESTART STUDENT

Use Case Name: RESTART STUDENT

Purpose: Restart a student workstation remotely.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `RestartStudent` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.RestartStudent` (GET).
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-171 BULK LOCK STUDENTS

Use Case Name: BULK LOCK STUDENTS

Purpose: Lock several student workstations in one action.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionIds : List<string>`

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `BulkLockStudents` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.BulkLockStudents (GET)`.
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-172 **BULK FORCE LOGOUT STUDENTS**

Use Case Name: BULK FORCE LOGOUT STUDENTS

Purpose: Sign several students out of their workstations in one action.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionIds : List<string>`

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `BulkForceLogoutStudents` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.BulkForceLogoutStudents (GET)`.
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.

T-173 **SEND REMOTE INPUT**

Use Case Name: SEND REMOTE INPUT

Purpose: Deliver one keyboard or mouse event to the workstation under remote control.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string
- `input` : RemoteInputMessage

Output Parameters:

- A `RemoteCommandResult` stating whether the workstation accepted the command, returned to the caller over SignalR.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.
- **START REMOTE CONTROL** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `SendRemoteInput` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.
6. The command is written to the remote command log.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.SendRemoteInput (GET)`.
- Appears in the *CONTROL STUDENT WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **START REMOTE CONTROL**.

SEND MESSAGE TO STUDENT `RemoteMonitoringHub`

System Use Case:



Written Use Case:

T-174 **SEND NOTIFICATION**

Use Case Name: SEND NOTIFICATION

Purpose: Send a message to connected students that appears on their workstation.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- notification : NotificationMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `SendNotification` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.SendNotification (GET)`.
- Appears in the *SEND MESSAGE TO STUDENT* module of the use case diagram.

T-175 **SEND WARNING POPUP**

Use Case Name: SEND WARNING POPUP

Purpose: Send a warning dialog to one student, shown on top of whatever they are doing.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `targetConnectionId` : string
- `warning` : NotificationMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- The record named by the identifier exists.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `SendWarningPopup` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.SendWarningPopup` (GET).
- Appears in the *SEND MESSAGE TO STUDENT* module of the use case diagram.

T-176 **BROADCAST SCREEN**

Use Case Name: BROADCAST SCREEN

Purpose: Put the teacher screen on every connected student workstation.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- `frameBase64` : string

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `BroadcastScreen` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.BroadcastScreen (GET)`.
- Appears in the *SEND MESSAGE TO STUDENT* module of the use case diagram.

T-177 **STOP BROADCAST**

Use Case Name: STOP BROADCAST

Purpose: Stop the teacher screen broadcast and return the workstations to the student view.

Actors: Teacher, The CAMS client on the target workstation

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Teacher triggers the command from the monitoring console.
2. The browser invokes `StopBroadcast` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.StopBroadcast (GET)`.
- Appears in the *SEND MESSAGE TO STUDENT* module of the use case diagram.

MANAGE MONITORING ALERT `TeacherController`

System Use Case:



Written Use Case:

T-178 **VIEW ALERTS**

Use Case Name: VIEW ALERTS

Purpose: List the monitoring alerts raised for the classes the teacher is responsible for.

Actors: Teacher

Input Parameters:

- filter : AlertListFilter

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by TeacherController.Alerts (GET).
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.

T-179 **ALERT HISTORY**

Use Case Name: ALERT HISTORY

Purpose: Show alerts that have already been acted on, with who acted and when.

Actors: Teacher

Input Parameters:

- `id : int`

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.AlertHistory (GET)`.
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.
- Pulls in **EXPORT ALERTS CSV** (<<extend>>).

T-180 OPEN ALERT COUNT

Use Case Name: OPEN ALERT COUNT

Purpose: Report how many alerts are still open, for the badge on the navigation bar.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.OpenAlertCount (GET)`.
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.

T-181 **ACKNOWLEDGE ALERT**

Use Case Name: ACKNOWLEDGE ALERT

Purpose: Mark one alert as seen and being handled.

Actors: Teacher

Input Parameters:

- `id : int`
- `acknowledged : bool`
- `filter : AlertListFilter`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.AcknowledgeAlert` (POST).
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.

T-182 BULK ACKNOWLEDGE ALERTS

Use Case Name: BULK ACKNOWLEDGE ALERTS

Purpose: Acknowledge several alerts in one action.

Actors: Teacher

Input Parameters:

- `alertIds : List<int>?`
- `filter : AlertListFilter`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.BulkAcknowledgeAlerts` (POST).
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.

T-183 BULK DISMISS ALERTS

Use Case Name: BULK DISMISS ALERTS

Purpose: Dismiss several alerts in one action.

Actors: Teacher

Input Parameters:

- `alertIds : List<int>?`
- `reason : string?`
- `filter : AlertListFilter`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.BulkDismissAlerts` (POST).
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.

T-184 BULK REOPEN ALERTS

Use Case Name: BULK REOPEN ALERTS

Purpose: Reopen several alerts that were closed too early.

Actors: Teacher

Input Parameters:

- `alertIds : List<int>?`
- `filter : AlertListFilter`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The Teacher fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `TeacherController.BulkReopenAlerts` (POST).
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.

T-185 **EXPORT ALERTS CSV**

Use Case Name: EXPORT ALERTS CSV

Purpose: Produce the alerts view as a CSV file the user can download.

Actors: Teacher, None; this behaviour runs inside **ALERT HISTORY**

Input Parameters:

- filter : AlertListFilter

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- **ALERT HISTORY** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.ExportAlertsCsv` (GET).
- Appears in the *MANAGE MONITORING ALERT* module of the use case diagram.
- Drawn as <<extend>> to **ALERT HISTORY**.

VIEW TEACHER RECORDS `TeacherController`

System Use Case:



Written Use Case:

T-186 **VIEW DASHBOARD**

Use Case Name: VIEW DASHBOARD

Purpose: Show the teacher landing page with the state of the laboratory at a glance.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Dashboard (GET)`.
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.

T-187 **VIEW RECORDS**

Use Case Name: VIEW RECORDS

Purpose: Show captured application and website activity for the teacher's students.

Actors: Teacher

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.Records (GET)`.
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Pulls in **EXPORT RECORDS CSV** (<<extend>>).

T-188 CLASS ANALYTICS

Use Case Name: CLASS ANALYTICS

Purpose: Show usage patterns for a class rather than for one student.

Actors: Teacher

Input Parameters:

- `id : int`
- `from : DateTime?` (optional)
- `to : DateTime?` (optional)
- `station : string?` (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.ClassAnalytics` (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.

T-189 LAB UTILIZATION

Use Case Name: LAB UTILIZATION

Purpose: Show how heavily the laboratory workstations are being used over time.

Actors: Teacher

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- station : string? (optional)
- classId : int? (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.LabUtilization (GET)`.
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.

T-190 UNIFIED TIMELINE

Use Case Name: UNIFIED TIMELINE

Purpose: Show one student's activity as a single timeline across applications, websites and idle periods.

Actors: Teacher

Input Parameters:

- `from : DateTime?` (optional)
- `to : DateTime?` (optional)
- `studentId : int?` (optional)
- `classId : int?` (optional)
- `station : string?` (optional)
- `source : string?` (optional)
- `eventType : string?` (optional)
- `page : int` (optional)
- `pageSize : int` (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.UnifiedTimeline (GET)`.
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.

T-191 **ACTIVITY TIMELINE**

Use Case Name: ACTIVITY TIMELINE

Purpose: Serve the timeline data the unified timeline view is drawn from.

Actors: Teacher

Input Parameters:

- `id : int`
- `from : DateTime?` (optional)
- `to : DateTime?` (optional)
- `page : int` (optional)
- `pageSize : int` (optional)
- `eventType : string?` (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.ActivityTimeline` (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.

T-192 BROWSER MONITORING HISTORY

Use Case Name: BROWSER MONITORING HISTORY

Purpose: Show the record of browser activity captured from the workstations.

Actors: Teacher

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- browser : string? (optional)
- mode : string? (optional)
- page : int (optional)
- pageSize : int (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by TeacherController.BrowserMonitoringHistory (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Pulls in **EXPORT BROWSER MONITORING CSV** (<<extend>>).

T-193 REMOTE HISTORY

Use Case Name: REMOTE HISTORY

Purpose: Show which remote commands were issued, by whom, and against which workstation.

Actors: Teacher

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- command : string? (optional)
- studentId : string? (optional)
- page : int (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by TeacherController.RemoteHistory (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Pulls in **EXPORT REMOTE HISTORY CSV** (<<extend>>).

T-194 STUDENT DETAILS

Use Case Name: STUDENT DETAILS

Purpose: Show one student in full: account, class, sessions and captured activity.

Actors: Teacher

Input Parameters:

- `id : int`
- `from : DateTime?` (optional)
- `to : DateTime?` (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.StudentDetails (GET)`.
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Pulls in **EXPORT STUDENT ANALYTICS CSV** (<<extend>>).

T-195 **EXPORT RECORDS CSV**

Use Case Name: EXPORT RECORDS CSV

Purpose: Produce the records view as a CSV file the user can download.

Actors: Teacher, None; this behaviour runs inside **VIEW RECORDS**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- **VIEW RECORDS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `TeacherController.ExportRecordsCsv` (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Drawn as <<extend>> to **VIEW RECORDS**.

T-196 **EXPORT REMOTE HISTORY CSV**

Use Case Name: EXPORT REMOTE HISTORY CSV

Purpose: Produce the remote history view as a CSV file the user can download.

Actors: Teacher, None; this behaviour runs inside **REMOTE HISTORY**

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- command : string? (optional)
- studentId : string? (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.
- **REMOTE HISTORY** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `TeacherController.ExportRemoteHistoryCsv` (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Drawn as <<extend>> to **REMOTE HISTORY**.

T-197 **EXPORT BROWSER MONITORING CSV**

Use Case Name: EXPORT BROWSER MONITORING CSV

Purpose: Produce the browser monitoring view as a CSV file the user can download.

Actors: Teacher, None; this behaviour runs inside **BROWSER MONITORING HISTORY**

Input Parameters:

- from : DateTime? (optional)
- to : DateTime? (optional)
- browser : string? (optional)
- mode : string? (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- **BROWSER MONITORING HISTORY** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by TeacherController.ExportBrowserMonitoringCsv (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Drawn as <<extend>> to **BROWSER MONITORING HISTORY**.

T-198 **EXPORT STUDENT ANALYTICS CSV**

Use Case Name: EXPORT STUDENT ANALYTICS CSV

Purpose: Produce the student analytics view as a CSV file the user can download.

Actors: Teacher, None; this behaviour runs inside **STUDENT DETAILS**

Input Parameters:

- `id : int`
- `from : DateTime?` (optional)
- `to : DateTime?` (optional)

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a teacher.
- The record named by the identifier exists.
- **STUDENT DETAILS** has reached the point where this is optionally performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Teacher opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.


Additional Remarks:

- Implemented by `TeacherController.ExportStudentAnalyticsCsv` (GET).
- Appears in the *VIEW TEACHER RECORDS* module of the use case diagram.
- Drawn as <<extend>> to **STUDENT DETAILS**.

Student

PROCESS LOG IN AccountController

System Use Case:



Written Use Case:

S-199 LOGIN USER

Use Case Name: LOGIN USER

Purpose: Let a person sign in to the CAMS web portal with a username and password, and place them in the part of the system their role allows.

Actors: Student

Input Parameters:

- username : string
- password : string

Output Parameters:

- An authentication cookie carrying the account role as a claim, and a redirect to the landing page for that role.

Pre-Condition:

- None. This is the sign-in endpoint and is reachable without an account session; the CAMS server must be running and reachable.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Student opens the CAMS sign-in page.
2. The Student enters a username and a password and submits the form.
3. The server validates the antiforgery token that accompanied the form.
4. The server checks the credentials against each account table in turn and finds the matching account.
5. The server confirms the account is active and not locked out.
6. The server issues an authentication cookie carrying the role as a claim.
7. The Student is redirected to the landing page for that role.

Exception Scenario:

- **The username matches no account** — the page reports that the sign-in failed, without saying which half was wrong.
- **The password does not match the stored hash** — the failed-attempt counter is raised and the same message is shown.
- **The account is locked out** — the sign-in is refused until the lockout expires, even with the right password.
- **The account is deactivated** — the sign-in is refused and the person is told to contact an administrator.

Additional Remarks:

- Implemented by `AccountController.Login` (POST).
- Appears in the *PROCESS LOG IN* module of the use case diagram.

- Pulls in **LOGIN ASYNC** (<<include>>).

S-200 **LOGOUT USER**

Use Case Name: LOGOUT USER

Purpose: End the signed-in session and clear the authentication cookie, so the next visitor to the browser starts as an anonymous user.

Actors: Student

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The authentication cookie is cleared and the browser is returned to the sign-in page.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Student chooses to sign out.
2. The server closes any lab session the account still has open.
3. The server clears the authentication cookie.
4. The browser is returned to the sign-in page as an anonymous visitor.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `AccountController.Logout` (POST).
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Pulls in **LOGOUT ASYNC** (<<include>>).

S-201 **LOGIN ASYNC**

Use Case Name: LOGIN ASYNC

Purpose: Check the supplied password against the stored hash, confirm the account is active and not locked out, and decide which of the three account tables the person belongs to.

Actors: Student, None; this behaviour runs inside **LOGIN USER**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A `LoginResult` naming the role, the account id and the display name, or a result saying the credentials were rejected.

Pre-Condition:

- The sign-in use case has supplied a username and a password.
- **LOGIN USER** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The sign-in use case passes the username, the password, the workstation name and the caller address.
2. The service looks the username up in the administrator, teacher and student tables.
3. The stored hash is verified against the supplied password.
4. The active flag and the lockout expiry are checked.
5. On success the failed-attempt counter is cleared and the role and account id are returned; on failure the counter is raised.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `LoginAsync`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Drawn as <<include>> from **LOGIN USER**.

S-202 **LOGOUT ASYNC**

Use Case Name: LOGOUT ASYNC

Purpose: Close any lab session the student still has open and record the sign-out.

Actors: Student, None; this behaviour runs inside **LOGOUT USER**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **LOGOUT USER** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `LogoutAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `LogoutAsync`.
- Appears in the *PROCESS LOG IN* module of the use case diagram.
- Drawn as <<include>> from **LOGOUT USER**.

LOG IN AT WORKSTATION `ClientAuthController`

System Use Case:



Written Use Case:

S-203 CLIENT LOGIN

Use Case Name: CLIENT LOGIN

Purpose: Let a student sign in from the CAMS client installed on a laboratory workstation, binding the sign-in to the machine the student is sitting at.

Actors: Student

Input Parameters:

- request : StudentClientLoginRequest

Output Parameters:

- A StudentClientLoginResponse carrying the student identity, the workstation registration and the session state.

Pre-Condition:

- None. The client reaches this before any session exists. The workstation must have found the server and must trust the CAMS root certificate.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The CAMS client finds the server on the laboratory network.
2. The student enters a username and a password in the client.
3. The client posts the credentials together with the name of the workstation.
4. The server verifies the credentials and confirms the account is a student that is active and not locked out.
5. The server registers the workstation against the student, reassigning it if it was held by someone else who is no longer using it.
6. The client receives the session details and the monitored session begins.

Exception Scenario:

- **No server was found on the network** — the client reports that it cannot reach CAMS and offers the endpoint to be entered by hand.
- **The workstation is already held by another active session** — the sign-in is refused rather than displacing the student using it.
- **The account is not a student** — the client refuses the sign-in; teacher and administrator accounts use the web portal.

Additional Remarks:

- Implemented by ClientAuthController.Login (POST).
- Appears in the *LOG IN AT WORKSTATION* module of the use case diagram.
- Pulls in **DEPLOYMENT PING** (<<include>>), **LOGIN ASYNC** (<<include>>).

S-204 CLIENT LOGOUT

Use Case Name: CLIENT LOGOUT

Purpose: End the workstation session from the client, releasing the workstation so another student may sign in to it.

Actors: Student

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- Confirmation that the session was closed and the workstation released.

Pre-Condition:

- The caller is signed in as a student.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The student signs out from the CAMS client.
2. The server ends the lab session and records its end time.
3. The workstation is released so another student may sign in at it.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `ClientAuthController.Logout` (POST).
- Appears in the *LOG IN AT WORKSTATION* module of the use case diagram.

S-205 DEPLOYMENT PING

Use Case Name: DEPLOYMENT PING

Purpose: Answer the discovery request a client broadcasts while looking for the CAMS server on the laboratory network.

Actors: Student, None; this behaviour runs inside **CLIENT LOGIN**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The server endpoint a client should connect to.

Pre-Condition:

- None. The endpoint answers an unauthenticated broadcast, so a client can find the server before it has credentials.
- **CLIENT LOGIN** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. A CAMS client broadcasts on the laboratory network looking for a server.
2. The server answers with the endpoint the client should use.
3. The client stores the endpoint and proceeds to sign in.

Exception Scenario:

- **The broadcast does not reach the server** — no answer is returned and the client falls back to a configured endpoint.

Additional Remarks:

- Implemented by `DeploymentPingController.Get (GET)`.
- Appears in the *LOG IN AT WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **CLIENT LOGIN**.

S-206 LOGIN ASYNC

Use Case Name: LOGIN ASYNC

Purpose: Check the supplied password against the stored hash, confirm the account is active and not locked out, and decide which of the three account tables the person belongs to.

Actors: Student, None; this behaviour runs inside **CLIENT LOGIN**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A `LoginResult` naming the role, the account id and the display name, or a result saying the credentials were rejected.

Pre-Condition:

- The sign-in use case has supplied a username and a password.
- **CLIENT LOGIN** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The sign-in use case passes the username, the password, the workstation name and the caller address.
2. The service looks the username up in the administrator, teacher and student tables.
3. The stored hash is verified against the supplied password.
4. The active flag and the lockout expiry are checked.
5. On success the failed-attempt counter is cleared and the role and account id are returned; on failure the counter is raised.

Exception Scenario:


- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `LoginAsync`.
- Appears in the *LOG IN AT WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **CLIENT LOGIN**.

WORK AT MONITORED WORKSTATION RemoteMonitoringHub

System Use Case:



Written Use Case:

S-207 **FETCH RESTRICTIONS**

Use Case Name: FETCH RESTRICTIONS

Purpose: Give the client the restriction rules that apply to the student signed in at that workstation.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes `FetchRestrictions` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.FetchRestrictions (GET)`.
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Pulls in **REPORT ACTIVE APP** (<<include>>), **REPORT WEBSITE ACTIVITY** (<<include>>), **REPORT IDLE STATUS** (<<include>>), **REPORT BROWSER MONITORING STATUS** (<<include>>), **REPORT TELEMETRY BATCH** (<<include>>), **REPORT INFRACTION** (<<extend>>).

S-208 **REPORT ACTIVE APP**

Use Case Name: REPORT ACTIVE APP

Purpose: Report which application is in the foreground on the workstation.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- app : ActiveAppMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **FETCH RESTRICTIONS** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes ReportActiveApp on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by RemoteMonitoringHub.ReportActiveApp (GET).
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **FETCH RESTRICTIONS**.

S-209 **REPORT WEBSITE ACTIVITY**

Use Case Name: REPORT WEBSITE ACTIVITY

Purpose: Report the website the student is viewing in the browser.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- website : WebsiteActivityMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **FETCH RESTRICTIONS** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes ReportWebsiteActivity on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by RemoteMonitoringHub.ReportWebsiteActivity (GET).
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **FETCH RESTRICTIONS**.

S-210 **REPORT IDLE STATUS**

Use Case Name: REPORT IDLE STATUS

Purpose: Report whether the workstation has gone idle.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- status : IdleStatusMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **FETCH RESTRICTIONS** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes ReportIdleStatus on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by RemoteMonitoringHub.ReportIdleStatus (GET).
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **FETCH RESTRICTIONS**.

S-211 REPORT BROWSER MONITORING STATUS

Use Case Name: REPORT BROWSER MONITORING STATUS

Purpose: Report whether browser monitoring is working on the workstation.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- status : BrowserMonitoringStatusMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **FETCH RESTRICTIONS** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes ReportBrowserMonitoringStatus on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by RemoteMonitoringHub.ReportBrowserMonitoringStatus (GET).
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **FETCH RESTRICTIONS**.

S-212 **REPORT TELEMETRY BATCH**

Use Case Name: REPORT TELEMETRY BATCH

Purpose: Send a batch of buffered telemetry, so a brief disconnection does not lose the record.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- batch : TelemetryBatchMessage

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **FETCH RESTRICTIONS** has reached the point where this is always performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes ReportTelemetryBatch on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by RemoteMonitoringHub.ReportTelemetryBatch (GET).
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Drawn as <<include>> from **FETCH RESTRICTIONS**.

S-213 REPORT INFRACTION

Use Case Name: REPORT INFRACTION

Purpose: Report that the student tried to open something a restriction rule blocks.

Actors: Student, The CAMS client on the target workstation

Input Parameters:

- `infraction : InfractionMessage`

Output Parameters:

- A SignalR message delivered to the target workstation or group; no HTTP response.

Pre-Condition:

- The caller is signed in.
- **FETCH RESTRICTIONS** has reached the point where this is optionally performed.

Post-Condition:

- The workstation has acted on the command and the console shows its new state.

Successful Scenario:

1. The Student triggers the command from the monitoring console.
2. The browser invokes `ReportInfraction` on the SignalR hub over the open connection.
3. The server checks the caller's role and resolves the target connection.
4. The server relays the instruction to the workstation client.
5. The client carries it out and the console reflects the new state.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **The workstation is not connected** — the command cannot be delivered and the console reports the workstation as offline.

Additional Remarks:

- Implemented by `RemoteMonitoringHub.ReportInfraction (GET)`.
- Appears in the *WORK AT MONITORED WORKSTATION* module of the use case diagram.
- Drawn as <<extend>> to **FETCH RESTRICTIONS**.

VIEW STUDENT SESSION `StudentController`

System Use Case:



Written Use Case:

S-214 **VIEW STUDENT HOME**

Use Case Name: VIEW STUDENT HOME

Purpose: Show the student portal home with the current session state and timer.

Actors: Student

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a student.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Student opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `StudentController.Index (GET)`.
- Appears in the *VIEW STUDENT SESSION* module of the use case diagram.

MANAGE STUDENT ALERT `StudentController`

System Use Case:



Written Use Case:

S-215 **VIEW ALERTS**

Use Case Name: VIEW ALERTS

Purpose: List the monitoring alerts raised for the classes the teacher is responsible for.

Actors: Student

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a student.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Student opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `StudentController.Alerts (GET)`.
- Appears in the *MANAGE STUDENT ALERT* module of the use case diagram.

S-216 MARK READ

Use Case Name: MARK READ

Purpose: Let a student mark one of their own alerts as read.

Actors: Student

Input Parameters:

- `id : int`

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a student.
- The record named by the identifier exists.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Student opens the page and CAMS confirms the role on the authentication cookie.
2. The Student fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:


- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.
- **The identifier matches no record** — the action reports that the record was not found and makes no change.

Additional Remarks:

- Implemented by `StudentController.MarkRead` (POST).
- Appears in the *MANAGE STUDENT ALERT* module of the use case diagram.

MANAGE STUDENT ACCOUNT `StudentController`

System Use Case:



Written Use Case:

S-217 VIEW SETTINGS

Use Case Name: VIEW SETTINGS

Purpose: Show the settings page for the signed-in user.

Actors: Student

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The rendered page, or a JSON payload where the caller is the page's own script.

Pre-Condition:

- The caller is signed in as a student.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The Student opens the page and CAMS confirms the role on the authentication cookie.
2. The server reads the records the caller is entitled to see.
3. The page renders with those records.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.

Additional Remarks:

- Implemented by `StudentController.Settings (GET)`.
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.

S-218 RESET PASSWORD

Use Case Name: RESET PASSWORD

Purpose: Let a student replace their own password from the student portal.

Actors: Student

Input Parameters:

- input : PasswordChangeInput

Output Parameters:

- A redirect back to the listing page, carrying a success or failure message for display.

Pre-Condition:

- The caller is signed in as a student.

Post-Condition:

- The change is committed to the database and visible to the next read.
- The caller sees the outcome reported on the page they return to.

Successful Scenario:

1. The Student opens the page and CAMS confirms the role on the authentication cookie.
2. The Student fills the form and submits it.
3. The server validates the antiforgery token that accompanied the form.
4. The server validates the submitted values against the model rules.
5. The change is written to the database through `ApplicationDbContext`.
6. The server redirects back to the listing, where the result is shown.

Exception Scenario:

- **Not signed in or wrong role** — the request is refused and the caller is sent to the access denied page.
- **Missing or stale antiforgery token** — the submission is rejected and must be retried from a freshly loaded form.
- **Validation fails** — the form is redisplayed with the offending fields marked and nothing is written.

Additional Remarks:

- Implemented by `StudentController.ResetPassword` (POST).
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.
- Pulls in **CHANGE STUDENT PASSWORD ASYNC** (<<include>>).

S-219 **CHANGE STUDENT PASSWORD ASYNC**

Use Case Name: CHANGE STUDENT PASSWORD ASYNC

Purpose: Verify the current password and replace the stored hash for a student account.

Actors: Student, None; this behaviour runs inside **RESET PASSWORD**

Input Parameters:

- None beyond the signed-in identity carried on the authentication cookie.

Output Parameters:

- The behaviour completes and its effect is visible to the use case that includes it.

Pre-Condition:

- The caller is signed in.
- **RESET PASSWORD** has reached the point where this is always performed.

Post-Condition:

- The caller has the requested information. Nothing in the database has changed.

Successful Scenario:

1. The including use case reaches the point where this behaviour is required.
2. The server runs `ChangeStudentPasswordAsync` and applies its result.
3. Control returns to the including use case, which continues.

Exception Scenario:

- The behaviour fails and the including use case reports the failure rather than continuing as if it had succeeded.

Additional Remarks:

- Implemented by `ChangeStudentPasswordAsync`.
- Appears in the *MANAGE STUDENT ACCOUNT* module of the use case diagram.
- Drawn as <<include>> from **RESET PASSWORD**.