

GATE-EC2023

Jay Vikrant EE22BTECH11025

Q65EC.2023: The frequency of occurrence of 8 symbols (a-h) is shown in the table below. A symbol is chosen and it is determined by asking a series of “yes/no” questions which are assumed to be truthfully answered. The average number of questions when asked in the most efficient sequence, to determine the chosen symbol, is


Symbols	Frequency of occurrence
a	$\frac{1}{2}$
b	$\frac{1}{4}$
c	$\frac{1}{8}$
d	$\frac{1}{16}$
e	$\frac{1}{32}$
f	$\frac{1}{64}$
g	$\frac{1}{128}$
h	$\frac{1}{128}$

Solution:

Parameter	Value	Description
X	$1 \leq X \leq 8$	number of symbols
l	2	base of algorithm
$H(X)$	$\sum_i p_X(i) \log_l \left(\frac{1}{p_X(i)} \right)$	average number of question

$$\begin{aligned}
 H(X) &= \sum_i p_X(i) \log_b \left(\frac{1}{p_X(i)} \right) \quad (1) \\
 &= \frac{1}{2} \log_2 (2) + \frac{1}{4} \log_2 (4) + \dots + \frac{1}{128} \log_2 (128) \quad (2) \\
 &= 0.5 + 0.5 + 0.375 + \dots + 0.0078125 \quad (3) \\
 &= 1.984375 \quad (4)
 \end{aligned}$$

Now, finding the average using Huffman code,



Using the above binary table following code is generated;

Symbols	Frequency	Code	Size
a	$\frac{1}{2}$	1	0.5
b	$\frac{1}{4}$	01	0.25
c	$\frac{1}{8}$	001	0.125
d	$\frac{1}{16}$	0001	0.0625
e	$\frac{1}{32}$	00001	0.03125
f	$\frac{1}{64}$	000001	0.015625
g	$\frac{1}{128}$	0000001	0.0078125
h	$\frac{1}{128}$	0000000	0.0078125

TABLE 0
HUFFMAN TABLE

The average number of question = Weighted path length = 1.9844