



Performance Portability in Practice

John Pennycook and Jason Sewall, Intel Corporation

Acknowledgements:

Doug Jacobsen, Google Tom Deakin and Simon McIntosh-Smith, University of Bristol






What is "Performance Portability"?

"A measurement of an application's performance efficiency for a given problem that can be executed correctly on all platforms in a given set."

$$\Phi(a,p,H) = \begin{cases} \frac{|H|}{\sum_{i \in H} \frac{1}{e_i(a,p)}} & \text{if } i \text{ is supported } \forall i \in H \\ 0 & \text{otherwise} \end{cases}$$

- Enables objective comparisons of implementations, algorithms, etc
- See our publications for more detail:
 - "Implications of a Metric for Performance Portability"
 - "Navigating Performance, Portability and Productivity"



An "efficiency cascade" plot, highlighting performance trends across platforms of interest. Plot your own using these scripts.





What About Productivity?

- Per-platform code increases developer effort:
 - Initial development
 - Debugging
 - Maintenance
- We measure this via "Code Divergence":

Codebase 1


```
shared.cpp:
void whereami()
{
#ifdef CPU
   printf("CPU\n");
#else
   printf("GPU\n");
#endif
}
8 lines - 6 shared lines
8 lines
```

Codebase 2

```
cpu.cpp:
void whereami()
{
  printf("CPU\n");
}

gpu.cpp:
void whereami()
{
  printf("GPU\n");
}

8 lines - 0 shared lines
8 lines
= 1.0
```




A dendrogram clustering platforms by "code divergence". Plot your own using our <u>Code Base Investigator</u> tool.





Setting Goals and Tracking Progress

- Trade-offs abound:
 - Abstraction ⇒ Higher Convergence
 - Specialization ⇒ Lower Convergence
 - Optimization ⇒ Higher Performance
- SYCL provides tools to help us manage these trade-offs
- But we must set our own goals (and manage our expectations!)







Device Queries

 Queries allow applications to inspect where they're running and dynamically adapt to the capabilities available.

```
sycl::queue q(sycl::default_selector{});
sycl::device d = q.get_device();
// Process input in the largest chunks we can allocate
uint64_t chunk_size = d.get_info<sycl::info::device::max_mem_alloc_size>();
// Prefer double precision if it's supported
if (d.has(sycl::aspect::fp64)) {
  run<double>(chunk_size);
} else {
  run<float>(chunk_size);
}
```

Many queries available, e.g.: cache size, work-group and sub-group sizes, availability
of scratchpad memory, atomics capabilities





Device Selectors

• Heterogeneous nodes may contain a mix of accelerators; device selectors provide a powerful mechanism to help you quickly select the best.

```
struct MySelector : sycl::device selector {
  // SYCL 2020 allows this to be a lambda
  int operator()(const sycl::device& d) const {
    int score = 0;
    if (not d.has(sycl::aspect::fp64)) {
      score = -1;
    } // Return negative if required features are not supported
    else if (d.has(sycl::aspect::gpu)) {
      score = 1;
    } // Return a higher score for GPU devices
    std::cout << "Scoring: " << d.get info<sycl::info::device::name>() << " " << score << std::endl;</pre>
    return score;
};
int main() {
  // Create a queue associated with the selected device
  sycl::queue q(MySelector{});
  std::cout << "Selected: " << q.get_device().get_info<sycl::info::device::name>() << std::endl;</pre>
```





Subdevices (e.g. NUMA Domains)

```
using namespace sycl::info;
constexpr auto by affinity domain = partition property::partition by affinity domain;
auto has numa domains = [=](sycl::device &d) {
 auto props = d.get info<device::partition properties>();
 auto domains = d.get info<device::partition affinity domains>();
 bool by_affinity = std::find(props.begin(), props.end(), by_affinity_domain) != props.end();
 bool by numa = std::find(domains.begin(), domains.end(),
                          partition affinity domain::numa) != domains.end();
return by_affinity && by numa;
// Try to split selected device into sub-devices along NUMA boundaries
sycl::device root = sycl::device(sycl::default selector{});
std::vector<sycl::device> devices;
if (has numa domains(root)) {
  devices = root.create sub devices<by affinity domain>(partition affinity domain::numa);
else {
 devices = std::vector<sycl::device>{root};
std::cout << "Split " << root.get info<device::name>() << " into " << devices.size()</pre>
          << " NUMA domains." << std::endl;</pre>
```





Specialization Constants

```
q.submit([&](auto &h) {
 h.template set specialization constant<BLOCKSIZE>(blocksize);
 h.parallel for(nd range<2>({(size t)N,(size t)M},{blocksize,blocksize}),
     [=](nd item<2> it, kernel handler kh) {
         const auto BS = kh.template get specialization constant<BLOCKSIZE>();
         auto id = it.get group().get id();
         const int i = id[1]*BS;
         const int j = id[0]*BS;
         if(BS == 4) {
           do_block_static<4>(it, i, j, M, N, K, C, A, B);
         else if(BS == 8) {
           do_block_static<8>(it, i, j, M, N, K, C, A, B);
         else if(BS == 16) {
           do_block_static<16>(it, i, j, M, N, K, C, A, B);
         else {
           do block dyn(BS, it, i, j, M, N, K, C, A, B);
      });
  }).wait();
```

- JIT compilation-enabled optimization tool
- Set dynamically in handler
- Act as constant during JIT lowering





Group Algorithms

- Syntax and semantics based on ISO C++ algorithms
 - any_of, all_of, none_of, shift_left, shift_right, reduce, exclusive_scan, inclusive_scan
 - SYCL specific: permute, select





DPC++ Extension: invoke_simd

Exploring ways to provide interoperability between SPMD and SIMD programming

```
int popcount(sycl::ext::oneapi::experimental::simd_mask<bool, 8> mask) {
  // Utilize SIMD APIs with no SPMD equivalent, e.g., popcount
  return sycl::ext::oneapi::experimental::popcount(mask);
q.parallel for(sycl::nd range<1>{N},
               sycl::nd_item<1> it) [[sycl::reqd_sub_group_size(8)]] {
  // Express algorithm in SPMD where convenient
  bool cond = (it.get_local_id() % 2);
  // Pass control to explicitly vectorized SIMD function
  sycl::sub group sg = it.get sub group();
  int ct = sycl::ext::oneapi::experimental::invoke_simd(sg, popcount, cond);
  // Resume SPMD coding
```





Summary and Call to Action

- SYCL exposes many features to help us achieve our desired balance of performance, portability and productivity
- Achieving high levels of performance (portability) may require non-trivial effort; what is "acceptable" effort is subjective
- Help us improve SYCL and implementations:
 - SYCL Specification: https://github.com/KhronosGroup/SYCL-Docs
 - Intel DPC++: https://github.com/intel/llvm
 - TODO: LINKS FROM CODEPLAY, XILINX, AKSEL HERE?