OPERATING SYSTEMS

Lab Assignment-1

Adarsh Kumar Sharma 2301420058

Experiment Title: Process Creation and Management Using Python OS Module

Task 1: Process Creation Utility

INPUT-

```
import os
import sys
def main():
    trv:
        N = int(input("Enter thr number of child processes: "))
    except ValueError:
        print("Please enter a valid integer.")
        sys.exit(1)
    print(f"Parent process PID: {os.getpid()} creating {N} child processes...\n")
    for i in range(N):
        pid = os.fork()
        if pid == 0:
            print(f"Child {i+1}: PID = {os.getpid()}, Parent PID = {os.getppid()}, Message = Hello from chld {i+1}")
            os._exit(0)
            continue
    for i in range(N):
        pid, status = os.wait()
        print(f"Parent: Child with PID = {pid} finished with status{status}")
if __name__ == "__main__":
    main()
```

```
Enter thr number of child processes: 3

Parent process PID: 10039 creating 3 child processes...

Child 1: PID = 10061, Parent PID = 10039, Message = Hello from chld 1

Child 2: PID = 10064, Parent PID = 10039, Message = Hello from chld 2

Parent: Child with PID = 10061 finished with status0

Child 3: PID = 10065, Parent PID = 10039, Message = Hello from chld 3

Parent: Child with PID = 10064 finished with status0

Parent: Child with PID = 10065 finished with status0
```

Task 2: Command Execution Using exec()

```
import os
import sys
def create_children_with_exec(n, command):
   children_pids = []
   for i in range(n):
       try:
          pid = os.fork()
      except OSError as e:
          print(f"Fork failed: {e}", file=sys.stderr)
          sys.exit(1)
       if pid == 0:
          print(f"\\n[Child {i+1}] PID={os.getpid()}, Parent PID={os.getppid()}, executing command: {' '.join(command)}\\n")
              os.execvp(command[\emptyset], command)
          except FileNotFoundError:
              print(f"Command not found: {command[0]}", file=sys.stderr)
              os._exit(1)
          children_pids.append(pid)
   for _ in children_pids:
      pid, status = os.wait()
       if os.WIFEXITED(status):
          print(f"[Parent] Child PID={pid} exited with status {os.WEXITSTATUS(status)}")
          print(f"[Parent] Child PID={pid} terminated abnormally")
def main():
    try:
         n = int(input("Enter the number of child processes: "))
         if n <= 0:
              print("Number of processes must be positive.")
              return
    except ValueError:
         print("Invalid input. Please enter an integer.")
    command = input("Enter the Linux command to execute (e.g., 'ls -1'): ").split()
    print(f"\n[Parent]\ PID=\{os.getpid()\}\ creating\ \{n\}\ children\ to\ run:\ \{'\ '.join(command)\}\n"\}
    create_children_with_exec(n, command)
if __name__ == "__main__":
    main()
```

```
Enter the number of child processes: 4
Enter the Linux command to execute (e.g., 'ls -l'): ls
[Parent] PID=13071 creating 4 children to run: 1s
[Child 1] PID=13136, Parent PID=13071, executing command: 1s
[Child 2] PID=13137, Parent PID=13071, executing command: 1s
[Child 3] PID=13138, Parent PID=13071, executing command: ls
                    forky.py
Desktop
          even.py
                                            Pictures
                                                      Videos
                                            Public
Documents fork1.py Music
Downloads fork2.py os_alltasks_submission Templates
[Child 4] PID=13139, Parent PID=13071, executing command: 1s
[Parent] Child PID=13136 exited with status 0
Desktop
          even.py forky.py
                                            Pictures
                                                      Videos
Documents fork1.py Music
                                            Public
Downloads fork2.py os_alltasks_submission Templates
[Parent] Child PID=13137 exited with status 0
Desktop
          even.py forky.py
                                            Pictures
                                                      Videos
Documents fork1.py Music
                                            Public
Downloads fork2.py os_alltasks_submission Templates
[Parent] Child PID=13138 exited with status 0
          even.py forky.py
                                            Pictures
                                                      Videos
Desktop
Documents fork1.py Music
                                            Public
Downloads fork2.py os_alltasks_submission Templates
[Parent] Child PID=13139 exited with status 0
```

Task 3: Zombie & Orphan Processes

```
import os
import time
def zombie_process():
   pid = os.fork()
   if pid == 0:
        print(f"[Child] PID={os.getpid()}, Parent PID={os.getppid()} -> Exiting now.")
       os._exit(0)
   else:
        print(f"[Parent] PID={os.getpid()}, created child PID={pid}")
        print("[Parent] Not calling wait(), sleeping... Run 'ps -el | grep defunct' to see zombie.")
        time.sleep(30)
def orphan_process():
    pid = os.fork()
    if pid == 0:
        print(f"[Child] PID={os.getpid()}, Parent PID={os.getppid()} -> Sleeping...")
        time.sleep(20)
       print(f"[Child] PID={os.getpid()}, New Parent PID={os.getppid()} -> I am orphaned.")
    else:
       print(f"[Parent] PID={os.getpid()}, created child PID={pid} -> Exiting immediately.")
       os._exit(0)
if __name__ == "__main__":
    print("\n=== Task 3: Zombie & Orphan Processes ===")
   print("1. Zombie process demo")
   print("2. Orphan process demo")
   choice = input("Enter choice: ")
   if choice == "1":
       zombie_process()
   elif choice == "2":
       orphan_process()
   else:
        print("Invalid choice.")
```

```
=== Task 3: Zombie & Orphan Processes ===

1. Zombie process demo

2. Orphan process demo

Enter choice: 1

[Parent] PID=1909, created child PID=1990

[Parent] Not calling wait(), sleeping... Run 'ps -el | grep defunct' to see zombie.

[Child] PID=1990, Parent PID=1909 -> Exiting now.
```

```
import os
def inspect_process(pid):
   status_file = f"/proc/{pid}/status"
   exe_file = f"/proc/{pid}/exe"
   fd dir = f"/proc/{pid}/fd"
   try:
       with open(status_file, "r") as f:
           name, state, vm_size = None, None, None
           for line in f:
               if line.startswith("Name:"):
                   name = line.split()[1]
               elif line.startswith("State:"):
                   state = " ".join(line.split()[1:])
               elif line.startswith("VmSize:"):
                   vm_size = " ".join(line.split()[1:])
           print(f"Process Name : {name}")
           print(f"Process State: {state}")
           print(f"Memory Usage : {vm_size}")
       try:
           exe_path = os.readlink(exe_file)
           print(f"Executable : {exe path}")
       except FileNotFoundError:
           print("Executable : [Not available]")
         try:
             fds = os.listdir(fd_dir)
             print(f"Open FDs : {len(fds)}")
             for fd in fds:
                 try:
                     target = os.readlink(os.path.join(fd_dir, fd))
                     print(f" FD {fd} -> {target}")
                 except OSError:
                     print(f" FD {fd} -> [unavailable]")
        except FileNotFoundError:
            print("Open FDs
                                : [Not available]")
    except FileNotFoundError:
         print(f"Process with PID {pid} does not exist.")
if __name__ == "__main__":
    pid = input("Enter PID to inspect: ")
    if pid.isdigit():
        inspect_process(pid)
         print("Invalid PID")
```

```
Enter PID to inspect: 8165
Process Name : systemd-udevd
Process State: S (sleeping)
Memory Usage : 35684 kB
```



INPUT

```
import os
import time
import multiprocessing as mp
def cpu_worker(nice_value, duration):
    try:
       new_nice = os.nice(nice_value)
    except Exception as e:
       print(f"PID={os.getpid()} | Error setting nice({nice_value}): {e}")
        return
   pid = os.getpid()
    start = time.time()
   count = 0
    while time.time() - start < duration:</pre>
        count += 1
   print(f"PID={pid} | Requested nice={nice_value} | "
          f"Actual nice={new_nice} | Iterations={count}")
if __name__ == "__main__":
    duration = 5
   nice_values = [0, 5, 10, 15]
    procs = []
    for n in nice_values:
        p = mp.Process(target=cpu_worker, args=(n, duration))
       p.start()
       procs.append(p)
    for p in procs:
       p.join()
```

```
PID=76505 | Requested nice=0 | Actual nice=0 | Iterations=12944342
PID=76506 | Requested nice=5 | Actual nice=5 | Iterations=9200200
PID=76507 | Requested nice=10 | Actual nice=10 | Iterations=3130143
PID=76508 | Requested nice=15 | Actual nice=15 | Iterations=1047727
```