

# Implementation of a new infrared sea surface emissivity model in the Community Radiative Transfer Model (CRTM)

Paul F. van Delst<sup>a</sup>, Nicholas R. Nalli<sup>b</sup>, and John C. Derber<sup>c</sup>

a. SAIC, NOAA/NWS/NCEP/EMC, Joint Center for Satellite Data Assimilation

b. PSGS Inc., NOAA/NESDIS/STAR


c. NOAA/NWS/NCEP/EMC, Joint Center for Satellite Data Assimilation

Submitted for the 2<sup>nd</sup> Workshop on Remote Sensing and Modeling of Surface Properties.

The CRTM is used in the NCEP/EMC<sup>1</sup> data assimilation systems to simulate satellite radiance observations. The current infrared (IR) sea surface emissivity model component of the CRTM has been in use since 2006 and is based on Wu and Smith [1997] in which the reflected sea surface emission is taken into account.

Recent work [Hanafin and Minnett, 2005, Nalli et al., 2008a,b] has shown that this methodology will underestimate the effective emissivity at larger zenith angles due to the quasi-specular reflection of downwelling atmospheric radiance into the sensor field-of-view. A comparison of computed emissivities for a large view angle is shown in figure 1. The difference between the Wu-Smith and Nalli model emissivities in the longwave IR window region (800-950cm<sup>-1</sup>) is around 0.01, or 1%. For blackbody emission at typical sea surface temperatures, this is roughly equivalent to a brightness temperature error of 0.7K. When the reflected downwelling atmospheric radiation is included, this error reduces to a still significant 0.5K [Wu and Smith, 1996].

The impact of the new IR sea surface emissivity model in the data assimilation system at NCEP/EMC will be evaluated. In addition, because the CRTM IR sea surface emissivity models are implemented via look-up-tables as functions of frequency, wind speed and view angle, interpolation artifacts in the adjoint model will be described.



**Figure 1:** Comparison of Wu-Smith emissivities with that of Nalli using Cox and Munk [1954] (CM) and Ebuchi and Kizu [2002] (EK) wave slope statistics for a wind speed of 6ms<sup>-1</sup> and zenith angle of 60°.

## References

- C. Cox and W. Munk. Measurements of the roughness of the sea surface from photographs of the sun's glitter. *J. Opt. Soc. Am.*, 44:838–850, 1954.

---

<sup>1</sup>National Centers for Environmental Prediction/Environmental Modeling Center

- N. Ebuchi and S. Kizu. Probability distribution of surface wave slope derived using sun glitter images from geostationary meteorological satellite and surface vector winds from scatterometers. *J. Oceanography*, 58(3): 477–486, 2002.
- J.A. Hanafin and P.J. Minnett. Measurements of the infrared emissivity of a wind-roughened sea surface. *Appl. Opt.*, 44(3):398–411, 2005.
- N.R. Nalli, P.J. Minnett, and P. van Delst. Emissivity and reflection model for calculating unpolarized isotropic water surface-leaving radiance in the infrared. 1: Theoretical development and calculations. *Appl. Opt.*, 47(21):3701–3721, 2008a.
- N.R. Nalli, P.J. Minnett, E. Maddy, W.W. McMillan, and M.D. Goldberg. Emissivity and reflection model for calculating unpolarized isotropic water surface-leaving radiance in the infrared. 2: Validation using Fourier transform spectrometers. *Appl. Opt.*, 47(25):4694–4671, 2008b.
- X. Wu and W.L. Smith. Sensitivity of sea surface temperature retrieval to sea surface emissivity. *ACTA Meteorol. Sinica*, 10(3):376–383, 1996.
- X. Wu and W.L. Smith. Emissivity of rough sea surface for 8-13 $\mu$ m: modeling and verification. *Appl. Opt.*, 36(12):2609–2619, 1997.