IPO

HW1:

INPUT: Integer mark.

PROCESSING: Reject marks outside 0 to 100 and classify grades according to the range of the marks.

OUTPUT: Print the grade of the mark.

Why validation comes before grade thresholds?

According to my code, I have set the first “if” condition to check whether value is between 0 to 100. Therefore, it will check the validity of the input mark before grade thresholds.

HW2:

INPUT: Integer year.

PROCESSING: Check whether the year is positive, divisible by 400, or divisible by 4 but not by 100.

OUTPUT: Print “Invalid” , “Leap year” or “Common year”.

HW3:

INPUT: Integer age and student status as a word (yes or no).

PROCESSING: Accept ages 0 to 120. Reject any other age or status. Compare status ignoring case. Every process being done to determine the ticket price.

OUTPUT: Print ticket price.

HW4:

INPUT: Two double values and an operator character.

PROCESSING: Use classic switch to calculate the result. Then, check whether both values can be divided by zero or there is another operator.

OUTPUT: Calculate the results, print out the results and check whether a value can be divided by zero or there is an invalid operator.

HW5:

INPUT: Two single-word names.

PROCESSING: Check whether names are equal ignoring case or they are in lexicographic order ignoring case.

OUTPUT: Print the names according to lexicographic order ignoring case comparing the result with zero.

HW6:

INPUT: Two integers a and b.

PROCESSING: Choose smaller integer value and check whether it is odd or even value.

OUTPUT: Print the smaller number and its parity.

Explain what happens when both values are equal.

It is still going to display the values and classify the parity based on its number.