Assignments

1. Write a scala program which produces all values from an Array after removing duplicates
2. Create a map of prices for number of shopping items you want .now create another map from it with same key but price reduce by 10 %
3. Write a function minmax(values : Array[Int]) which return a pair of minimum and maximum values of an array
4. Repeat the above exercise as procedure which print the min and max values of an array

1.

```
scala>  val arr = Array(1, 2, 3, 2, 4, 1, 5)
val arr: Array[Int] = Array(1, 2, 3, 2, 4, 1, 5)

scala> val res = arr.distinct
val res: Array[Int] = Array(1, 2, 3, 4, 5)

scala> res.foreach(println)
1
2
3
4
5
```

2 . scala>

```
       val items = Map(
     |     "Rice" -> 60,
     |     "Milk" -> 50,
     |     "Bread" -> 40,
     |     "Sugar" -> 45,
     |     "Eggs" -> 70
     |   )
val items: scala.collection.immutable.Map[String,Int] = HashMap(Sugar -> 45, Milk -> 50,
Rice -> 60, Eggs -> 70, Bread -> 40)

scala> val discountedItems = items.map { case (item, price) =>
     |     (item, price * 0.9)
     |   }
val discountedItems: scala.collection.immutable.Map[String,Double] = HashMap(Sugar ->
40.5, Milk -> 45.0, Rice -> 54.0, Eggs -> 63.0, Bread -> 36.0)

scala> print(items)
HashMap(Sugar -> 45, Milk -> 50, Rice -> 60, Eggs -> 70, Bread -> 40)
scala> print(discountedItems)
HashMap(Sugar -> 40.5, Milk -> 45.0, Rice -> 54.0, Eggs -> 63.0, Bread -> 36.0)
```

3. def minmax(values: Array[Int]): (Int, Int) = {

```
val min = values.min
val max = values.max
(min, max)
}

def main(args: Array[String]): Unit = {
val arr = Array(4, 7, 1, 9, 3)

val result = minmax(arr)

println("Minimum: " + result._1)
println("Maximum: " + result._2)
}
```

4 . def minmax(values: Array[Int]): Unit = {

```
val min = values.min
val max = values.max

println("Minimum value: " + min)
println("Maximum value: " + max)
}

def main(args: Array[String]): Unit = {
val arr = Array(4, 7, 1, 9, 3)

minmax(arr)
}
```