

## Experiment – 2

Student Name: ADITYA SHARMA

UID: 24BAI70379

Branch: CSE-AIML

Section/Group: 24AIT\_KRG-1\_A

th

Semester: 5

Date of Performance: 17/7/26

Subject Name: ADBMS

Subject Code: 24CSP-310

(A)

A university administration requires an analytical performance report for each academic unit. Write a PostgreSQL solution to calculate the average marks scored by students grouped by their respective departments. The solution must join the student profile, course subjects, and grade marks tables, returning a breakdown sorted by the highest average marks down to the lowest.

Solution:

```
CREATE TABLE Departments (  
    dept_id INT PRIMARY KEY,  
    dept_name VARCHAR(50) NOT NULL  
);
```

```
CREATE TABLE Students (  
    student_id INT PRIMARY KEY,  
    student_name VARCHAR(50) NOT NULL,  
    dept_id INT REFERENCES Departments(dept_id)  
);
```

```
CREATE TABLE Subjects (  
    subject_id INT PRIMARY KEY,  
    subject_name VARCHAR(50) NOT NULL  
);
```

```
CREATE TABLE Marks (  
    student_id INT REFERENCES Students(student_id),  
    subject_id INT REFERENCES Subjects(subject_id),  
    marks_scored INT NOT NULL,  
    PRIMARY KEY (student_id, subject_id)  
);
```

```
INSERT INTO Departments (dept_id, dept_name) VALUES  
(1, 'Computer Science'),  
(2, 'Mathematics');
```

```
INSERT INTO Students (student_id, student_name, dept_id) VALUES
```

```
(101, 'Alex', 1),  
(102, 'Bella', 1),  
(103, 'Charlie', 2);
```

```
INSERT INTO Subjects (subject_id, subject_name) VALUES  
(501, 'Data Structures'),  
(502, 'Calculus');
```

```
INSERT INTO Marks (student_id, subject_id, marks_scored) VALUES  
(101, 501, 85),  
(101, 502, 90),  
(102, 501, 75),  
(103, 502, 95);
```

```
SELECT D.DEPT_NAME AS DEPARTMENT, ROUND(AVG(M.MARKS_SCORED), 2) AS AVERAGE_MARKS  
FROM DEPARTMENTS AS D  
JOIN STUDENTS AS S  
ON S.DEPT_ID = D.DEPT_ID  
JOIN MARKS AS M  
ON M.STUDENT_ID = S.STUDENT_ID  
GROUP BY D.DEPT_NAME  
ORDER BY AVERAGE_MARKS DESC;
```

(B)

Solution:

```
CREATE TABLE A  
(  
    EmpID INT,  
    Ename VARCHAR(50),  
    Salary INT  
);
```

```
CREATE TABLE B  
(  
    EmpID INT,  
    Ename VARCHAR(50),  
    Salary INT  
);
```

```
INSERT INTO A (EmpID, Ename, Salary)  
VALUES  
(1, 'AA', 1000),  
(2, 'BB', 300);
```

```
INSERT INTO B (EmpID, Ename, Salary)  
VALUES
```

```
(2, 'BB', 400),  
(3, 'CC', 100);
```

```
SELECT EMPID, MIN(ENAME) AS ENAME, MIN(SALARY) AS SALARY  
FROM(  
    SELECT * FROM A  
    UNION ALL  
    SELECT * FROM B  
)  
GROUP BY EMPID  
ORDER BY EMPID;
```

(C)

A multinational organization maintains separate records for employee information and department details. The management wants to identify the employees who receive the highest salary within their respective departments for an annual performance report.

If more than one employee earns the same highest salary in a department, all such employees should be included in the report. The final output should display the Department Name, Employee Name, and Salary, arranged in ascending order of department name.

Note: The employee and department information are maintained in separate normalized tables.

Solution:

(a)

```
CREATE TABLE Department  
(  
    id INT PRIMARY KEY,  
    dept_name VARCHAR(50)  
);
```

```
CREATE TABLE Employee  
(  
    id INT PRIMARY KEY,  
    name VARCHAR(50),  
    salary INT,  
    department_id INT,  
    FOREIGN KEY(department_id)  
    REFERENCES Department(id)  
);
```

```
INSERT INTO Department
```

```
VALUES  
(1,'IT'),  
(2,'SALES');
```

```
INSERT INTO Employee  
VALUES  
(1,'JOE',70000,1),  
(2,'JIM',90000,1),  
(3,'HENRY',80000,2),  
(4,'SAM',60000,2),  
(5,'MAX',90000,1);
```

```
SELECT D.DEPT_NAME, E.NAME, E.SALARY  
FROM EMPLOYEE AS E  
JOIN DEPARTMENT AS D  
ON E.DEPARTMENT_ID = D.ID  
WHERE E.SALARY IN(  
    SELECT MAX(SALARY)  
    FROM EMPLOYEE AS E1  
    WHERE E1.DEPARTMENT_ID = E.DEPARTMENT_ID  
)  
ORDER BY DEPT_NAME;
```

```
(b)  
SELECT D.DEPT_NAME, E.NAME, E.SALARY  
FROM EMPLOYEE AS E  
JOIN DEPARTMENT AS D  
ON E.DEPARTMENT_ID = D.ID  
WHERE E.SALARY IN(  
    SELECT MAX(SALARY)  
    FROM EMPLOYEE AS E1  
    WHERE E1.DEPARTMENT_ID = E.DEPARTMENT_ID  
    AND E1.SALARY NOT IN(  
        SELECT MAX(SALARY)  
        FROM EMPLOYEE AS E2  
        WHERE E2.DEPARTMENT_ID = E1.DEPARTMENT_ID  
    )  
)  
ORDER BY DEPT_NAME;
```