

Assignment 1

Adam Livingston

University Of Arizona

CYBV 454 MALWARE THREATS & ANALYSIS

Professor Galde

31 Jan 2023

LAB 3-1

- LAB03-01.exe : d537acb8f56a1ce206bc35cf8ff959c0




Figure 1: Virus Total Findings for file Lab03-01.exe.

Virus Total found 66 matching signatures for Trojan (possibly backdoor) malware for the file Lab03-01.exe (Figure1). It has a compilation timestamp of 06 Jan 2008 at 14:51:31 UTC (Figure 2). It appears to only import Kernel32.dll, suggesting it manipulates memory, files, and other hardware (Figure 2). Under the “Behavior” tab, the malware reportedly has indicators of privilege escalation and defense evasion (Figure 3). It is also reported that it has the capability to perform DNS (Figure 4). Based on the fact that this malware had the name of “backdoor” in the initial findings along with its network connection capabilities, it is reasonable to assume that this malware is in fact a back door.

Header					
Target Machine	Intel 386 or later processors and compatible processors				
Compilation Timestamp	2008-01-06 14:51:31 UTC				
Entry Point	520				
Contained Sections	2				
Sections					
Name	Virtual Address	Virtual Size	Raw Size	Entropy	MD5
.text	512	104	512	0.82	9e59
.data	1024	5775	6144	6.4	8dc0
Imports					
+ kernel32.dll					

Figure 2: Virus Total Compilation Timestamp and .dll imports for Lab03-01.exe

Privilege Escalation	TA0004
Process Injection	T1055
① Spawns processes	
Defense Evasion	TA0005
Masquerading	T1036
① Creates files inside the system directory	
Process Injection	T1055
① Spawns processes	
Virtualization/Sandbox Evasion	T1497
① Checks if the current process is being debugged	

Figure 3: Virus Total behavior for Lab03-01.exe




Figure 4: Virus Total network behavior for Lab03-01.exe

LAB 3-1**LAB 3-1 Question 1****What are this malware's imports and strings?**

After analysis with Dependencies and PEiD, the malware appears to be packed. Figure 5 shows that there is an output from PEiD of “PEEncrypt 3.1 Final -> Junkcode” and the only import is kernel32.dll. Using PView, we see that the only imports within the address table are ExitProcess and kernel32.dll (Figure 6). Without any additional imports, it is difficult to predict the purpose of this malware. A strings analysis with BinText showed some interesting imports. There are calls to modify the registry key, “SOFTWARE\Classes\http\shell\open\commandV”, which, according to Microsoft, is where one would add an http subkey to the registry (Figure 7). We even see the string, “CONNECT %s:%iHTTP/1.0”. Based on the initial analysis on VirusTotal, this malware most likely uses this registry key to create a shell. This shell would then be used over port 80 by the malicious actor to create a TCP connection and access the user’s system.




Figure 5: Evidence of packing for Lab03-01.exe




Figure 6: More evidence of packing for Lab03-01.exe





Figure 7: More evidence of packing for Lab03-01.exe

LAB 3-1 Question 2

What are the malware's host-based indicators?

One host-based indicator to look for would be the creation of the object, "WinVMX32" which would be located in the registry within "SOFTWARE\Microsoft\Windows\CurrentVersion\Run" (Figure 8). This object would be a good indicator that a machine has been infected with malware and there would be a good probability that this object is located in the Windows\system32 folder as many malware that imports kernel32.dll make modifications to that folder or attempt to access it.



00000000163C	00000040163C	0	www.practicalmalwareanalysis.com
0000000016D4	0000004016D4	0	admin
0000000016E2	0000004016E2	0	VideoDriver
0000000016F1	0000004016F1	0	WinVMX32-
0000000016FD	0000004016FD	0	vmx32to64.exe
000000001735	000000401735	0	SOFTWARE\Microsoft\Windows\CurrentVersion\Run
0000000018E5	0000004018E5	0	SOFTWARE\Microsoft\Windows\CurrentVersion\Explorer\Shell Folders
000000001943	000000401943	0	AppData
00000000004D	00000040004D	0	!This program cannot be run in DOS mode.
0000000001A8	0000004001A8	0	.text
0000000001D0	0000004001D0	0	.data


Figure 8: WinVMX32 registry creation by Lab03-01.exe

LAB 3-1 Question 3

Are there any useful network-based signatures for this malware? If so, what are they?


Because we identified in VirusTotal and our strings analysis that this malware most likely connects over http and makes DNS calls, a netcat listener was established on port 80 and port 53. This was done in conjunction with active monitoring on AupdateDNS, procmon, and Wireshark. When Lab03-01.exe was ran, Process Explorer briefly showed the process and then showed “WerFault.exe” (the Windows Problem Reporting Application) which was confirmed in abundance in the Process Monitor Capture (Figure 9). This happened despite the fact that no GUI-based error reporting message was created and therefore can most likely be attributed to Lab03-01.exe. This also happened when the malware was ran without the use of AupdateDNS and on both occasions, Netcat did not pick up any traffic on ports 80 and 53. There some specific instances of WerFault.exe occurring on network-based .dlls showed failed attempts at using Ws2_32.dll (Figure 10). Procmon did not show any events that coincided with setting registry values or writing to files (Figure 11).

Beginning the suspect that the malware and/or the host the malware intends to connect to may be defunct, the malware was uploaded to app.any.run to test it in a different OS environment. It showed that the malware did not run. (Figure 12). The online sandbox did not show any network callouts or file modifications.



Time	Process Name	PID	Operation	Path	Result	Detail
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\System32\ntdll.dll	SUCCESS	Image Base: 0x7ff...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\ntdll.dll	SUCCESS	Image Base: 0x775...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\System32\wow64.dll	SUCCESS	Image Base: 0x7ff...
4:43:59.4073893 PM	WerFault.exe	7796	Load Image	C:\Windows\System32\wow64win.dll	SUCCESS	Image Base: 0x7ff...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\System32\wow64cpu.dll	SUCCESS	Image Base: 0x775...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\kernel32.dll	SUCCESS	Image Base: 0x75c...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\KernelBase.dll	SUCCESS	Image Base: 0x75e...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\msvcrt.dll	SUCCESS	Image Base: 0x774...
4:43:5...	WerFault.exe	7796	Thread Create		SUCCESS	Thread ID: 8108
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\combase.dll	SUCCESS	Image Base: 0x760...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\urlbase.dll	SUCCESS	Image Base: 0x764...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\iprct4.dll	SUCCESS	Image Base: 0x772...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\oleaut32.dll	SUCCESS	Image Base: 0x766...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\ole32.dll	SUCCESS	Image Base: 0x765...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\ole32.dll	SUCCESS	Image Base: 0x766...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\ole32.dll	SUCCESS	Image Base: 0x755...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\ole32.dll	SUCCESS	Image Base: 0x755...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\ole32.dll	SUCCESS	Image Base: 0x755...
4:43:5...	WerFault.exe	7796	Thread Create		SUCCESS	Thread ID: 6080
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\bcrypt.dll	SUCCESS	Image Base: 0x773...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\bcrypt.dll	SUCCESS	Image Base: 0x753...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\cryptsp.dll	SUCCESS	Image Base: 0x753...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\wer.dll	SUCCESS	Image Base: 0x751...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\dbghelp.dll	SUCCESS	Image Base: 0x750...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\powrprof.dll	SUCCESS	Image Base: 0x752...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\Faultrep.dll	SUCCESS	Image Base: 0x74f...
4:43:5...	WerFault.exe	7796	Thread Create		SUCCESS	Thread ID: 7004
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\dbgcore.dll	SUCCESS	Image Base: 0x74f...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\umpdc.dll	SUCCESS	Image Base: 0x752...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\WinSxS\x86_microsoft.win...	SUCCESS	Image Base: 0x713...
4:43:5...	WerFault.exe	7796	Load Image	C:\Windows\SysWOW64\gdi32.dll	SUCCESS	Image Base: 0x755...

Figure 9: Lots of error messages generated after running Lab03-01.exe



Time of Day	Process Name	PID	Operation	Path
4:44:00.0287124 PM	svchost.exe	8008	Load Image	C:\Windows\System32\ws2_32.dll
4:44:00.0292635 PM	svchost.exe	8008	QueryNameInfo...	C:\Windows\System32\ws2_32.dll
4:44:00.0360309 PM	svchost.exe	8008	RegQueryValue	HKLM\System\CurrentControlSet\Services\WinSock2\Parameters\Ws2_32NumHandleBuckets
4:44:00.0360364 PM	svchost.exe	8008	RegQueryValue	HKLM\System\CurrentControlSet\Services\WinSock2\Parameters\Ws2_32SpinCount
4:44:00.4830447 PM	WerFault.exe	2120	Load Image	C:\Windows\SysWOW64\ws2_32.dll
4:44:00.4834596 PM	WerFault.exe	2120	QueryNameInfo...	C:\Windows\SysWOW64\ws2_32.dll
4:44:00.4872717 PM	WerFault.exe	2120	RegQueryValue	HKLM\System\CurrentControlSet\Services\WinSock2\Parameters\Ws2_32NumHandleBuckets
4:44:00.4872770 PM	WerFault.exe	2120	RegQueryValue	HKLM\System\CurrentControlSet\Services\WinSock2\Parameters\Ws2_32SpinCount

Figure 10: ws2_32.dll failures after running Lab03-01.exe




Figure 11: RegSetValue and WriteFile operations by Lab03-01.exe exclude all events.




Figure 12: app.any.run screenshot for Lab03-01.exe not responding.

LAB 3-2

- LAB03-02.dll : 84882c9d43e23d63b82004fae74ebb61




Figure 13: Virus Total Findings for file Lab03-02.dll.

Virus Total found 56 matching signatures for Trojan malware for the file Lab03-02.dll with indications that it could be a backdoor (Figure 13). It has a compilation timestamp of 28 Sep 2010 at 01:00:25 UTC (Figure 14). It appears to import Kernel32.dll and advapi32.dll suggesting it manipulates memory, files, and other hardware. The additional import of wininet.dll suggests that it has the ability to configure ports and protocols in conjunction with Ws2_32.dll. (Figure 15). Under the “Behavior” tab, it is noted that the malware schedules a task and found a very long command line which indicates that the file may be encrypted or packed. It also executes commands using a shell (Figure 16). It has other indicators of persistence, privilege escalation, and defense evasion (Figure 17). It is also reported that the file has network calls, performing DNS lookups, using HTTPS, and potentially downloading/writing to files (Figure 18). VirusTotal also notes that the malware may be obfuscated (Figure 19).

Header	
Target Machine	Intel 386 or later processors and compatible processors
Compilation Timestamp	2010-09-28 01:00:25 UTC
Entry Point	20045
Contained Sections	4

Figure 14: Virus Total Timestamp for file Lab03-02.dll.

Imports	
+	ADVAPI32.dll
+	KERNEL32.dll
+	MSVCRT.dll
+	WS2_32.dll
+	WININET.dll

Figure 15: Virus Total Imports for Lab03-02.dll.

Execution TA0002	
Command and Scripting Interpreter T1059	
① Very long cmdline option found, this is very uncommon (may be encrypted or packed)	
Execution TA0002	
Windows Command Shell T1059.003	
① Execute shell command and capture output	
Shared Modules T1129	
① Link function at runtime on Windows	
Service Execution T1569.002	
① Create service	
① Persist via Windows service	
Persistence TA0003	
Windows Service T1543.003	
① Create service	
① Persist via Windows service	
① Delete service	

Figure 16: Virus Total Behavior for file Lab03-02.dll.




Figure 17: Virus Total Behavior for file Lab03-02.dll.




Figure 18: Virus Total C&C for file Lab03-02.dll.





Figure 19: Virus Total indications of obfuscation for Lab03-02.dll.

LAB 3-2**LAB 3-2 Question 1****How can you get this malware to install itself?**

The native program in Windows environments, “rundll32.exe” provides user a method to manually run .dll files using the syntax, “C:\>rundll32.exe <dllName>.dll, Export arguments” on the command line. To get it to install, the rundll32.exe is also used but with the syntax “C:\>rundll32.exe <dllName>.dll, Install”. This syntax is used to install a dll if the dll file has an “install” export, which Lab03-02.dll was confirmed as having after viewing it in PEview under the “EXPORT Address Table” (Figure 20). We also notice in Figure 20 that the export of “installA” was included in this table. This argument was also passed in rundll32.exe when installing the malware on a virtual machine in addition to the “install”



pFile	Data	Description	Value
00004D28	00004706	Function RVA	0001 Install
00004D2C	00003196	Function RVA	0002 ServiceMain
00004D30	00004B18	Function RVA	0003 UninstallService
00004D34	00004B0B	Function RVA	0004 installA
00004D38	00004C2B	Function RVA	0005 uninstallA

Figure 20: “Install” and “installA” exports included in Lab03-02.dll.

LAB 3-2 Question 2**How would you get this malware to run after installation?**

After installing the malware by finding the proper export argument in PEview, a string analysis was conducted in order to find any clues of what the proper commands are to get it to run. There are numerous functions that the malware imports that suggest manipulation of services. From

these services, it can be deduced that registry values will be altered, services will be created, and some networking functions over HTTP will be used.

000000004932	000010005532	0	Isntera
00000000493E	00001000553E	0	SetLastError
00000000494E	00001000554E	0	OutputDebugStringA
0000000049C2	0000100055C2	0	KERNEL32.dll
0000000049D2	0000100055D2	0	RegisterServiceCtrlHandlerA
0000000049F0	0000100055F0	0	RegSetValueExA
000000004A02	000010005602	0	RegCreateKeyA
000000004A12	000010005612	0	CloseServiceHandle
000000004A28	000010005628	0	CreateServiceA
000000004A3A	00001000563A	0	OpenSCManagerA
000000004A4C	00001000564C	0	RegCloseKey
000000004A5A	00001000565A	0	RegQueryValueExA
000000004A6E	00001000566E	0	RegOpenKeyExA
000000004A7E	00001000567E	0	DeleteService
000000004A8E	00001000568E	0	OpenServiceA
000000004A9E	00001000569E	0	SetServiceStatus
000000004AB0	0000100056B0	0	ADVAPI32.dll
000000004AC0	0000100056C0	0	WSASocketA
000000004ACC	0000100056CC	0	WS_32.dll
000000004ADA	0000100056DA	0	InternetReadFile
000000004AEE	0000100056EE	0	HttpQueryInfoA
000000004B00	000010005700	0	HttpSendRequestA
000000004B14	000010005714	0	HttpOpenRequestA
000000004B28	000010005728	0	InternetConnectA
000000004B3C	00001000573C	0	InternetOpenA
000000004B4C	00001000574C	0	InternetCloseHandle
000000004B60	000010005760	0	WININET.dll
000000004B6E	00001000576E	0	memset
000000004B78	000010005778	0	wcstombs
000000004B84	000010005784	0	strncpy
000000004B8E	00001000578E	0	strcat
000000004B98	000010005798	0	strcpy

Figure 21: Lab03-02.dll imported functions.

Some more notable features on the string analysis are “serve.html”, “IPRIP”, and calls to edit registry keys (Figures 22 and 23). To figure out how to run this malware, RegShot and Process Monitor will be used to verify the changes the malware makes during installation.

000000004D95	000010005995	0	installA
000000004D9E	00001000599E	0	uninstallA
000000004E10	000010006010	0	Y29ubmVjdA==
000000004E28	000010006028	0	practicalmalwareanalysis.com
000000004E68	000010006068	0	serve.html
000000004EB8	0000100060B8	0	dW5zdXBwb3J0
000000004EC8	0000100060C8	0	c2xIZXA=
000000004EDC	0000100060DC	0	cXVpdA==
000000004EEC	0000100060EC	0	Windows XP 6.11
000000004F04	000010006104	0	CreateProcessA
000000004F14	000010006114	0	kernel32.dll
000000004F38	000010006138	0	HTTP/1.1
000000004F44	000010006144	0	%s %s
000000004F4C	00001000614C	0	1234567890123456
000000004F74	000010006174	0	getfile
000000004F7C	00001000617C	0	cmd.exe /c
000000004F8C	00001000618C	0	ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz
000000005000	000010006200	0	DependOnService

Figure 22: Lab03-02.dll serve.html.

A	000000005208	000010006408	0	You specify service name not in Svchost\services, must be one of
A	000000005254	000010006454	0	RegQueryValueEx(Svchost\services)
A	000000005278	000010006478	0	services
A	000000005280	000010006480	0	RegOpenKeyEx(\\.\) KEY_QUERY_VALUE success.
A	0000000052AC	0000100064AC	0	RegOpenKeyEx(\\.\) KEY_QUERY_VALUE error.
A	0000000052D8	0000100064D8	0	SOFTWARE\Microsoft\Windows NT\CurrentVersion\Svchost
A	000000005310	000010006510	0	IPRIP
A	000000005318	000010006518	0	uninstall success
A	00000000532C	00001000652C	0	OpenService(\\.\) error 2
A	000000005344	000010006544	0	OpenService(\\.\) error 1
A	00000000535C	00001000655C	0	uninstall is starting
A	000000005388	000010006588	0	.?AVtype_info@@
A	000000005408	000010012008	0	080@0
A	000000005411	000010012011	0	0m0r0

Figure 23: Lab03-02.dll IPRIP.

Within a Windows 10 VM Windows, installing Lab03-02.dll did not produce any viable results.

Regshot showed failed registry edits and, like Lab03-01.exe, Process Monitor noted multiple

instances of WerFault.exe. A Windows 7 VM (app.any.run) also produced the same output as

Lab03-01.exe with an error message stating that the file stopped working but did note that

malicious activity was detected by WerFault.exe due to the creation of mutexes (Figure 24). This

necessitated an attempt to install the .dll on a WindowsXP machine.

[404] WerFault.exe C:\Windows\system32\WerFault.exe

Put the slider in the desired position or select the desired segment by yourself ?

7.151 s +15 ms 65.254 s

Time	Operation	Type	Name	Status
+15 ms	Open	Event	HookSwitchHookEnabledEvent	0xC0000034
+15 ms	Create	Mutex	Local\WERReportingForProcess2308	0x00000000
+15 ms	Open	Event	HookSwitchHookEnabledEvent	0xC0000034
+15 ms	Create	Mutex	Local\WERReportingForProcess2308	0x00000000
+31 ms	Open	Event	2308-AppRecorderEnabled	0xC0000034
+31 ms	Open	Event	2308-AppRecorderEnabled	0xC0000034
+46 ms	Create	Event	DbgEngEvent_00000194	0x00000000
+46 ms	Create	Event	DbgEngEvent_00000194	0x00000000
+62 ms	Create	Mutex	Global\cbab6005-a107-11ed-80da-12a9866c77de	0x00000000
+62 ms	Create	Mutex	Global\cbab6005-a107-11ed-80da-12a9866c77de	0x00000000
+93 ms	Open	Event	\Sessions\1\BaseNamedObjects\ThemeLoadedEvent	0x00000000
+93 ms	Open	Event	\Sessions\1\BaseNamedObjects\ThemeLoadedEvent	0x00000000

Figure 24: app.any.run report of Lab03-02.dll.

After installing the malware on a Windows XP VM, the results provided more indications of the changes it made. Regshot captured key and value additions to the registry with they keyword of IPRIP which was identified in the strings analysis (Figure 25). Additionally, Process Monitor identified similar activity in the registry (Figure 26). Paying close attention to the Regshot capture in Figure 25, there is a path set to the “svchost.exe” application which can be reasonably deduced that svchost.exe is the application used by the malware to perform its function. This would require installing the malware as a service by using the command, “rundll32.exe Lab03-02.dll, installA IPRIP” since IPRIP is an executable .dll file. It can then be run with the command “net start IPRIP”.

```

Regshot 1.9.0 x86 ANSI
Comments:
Datetime: 2023/2/1 01:54:12 , 2023/2/1 01:56:43
Computer: JOHN33-PC , JOHN33-PC
Username: John , John

-----
Keys added: 6
-----
HKLM\SYSTEM\ControlSet001\Services\IPRIP
HKLM\SYSTEM\ControlSet001\Services\IPRIP\Parameters
HKLM\SYSTEM\ControlSet001\Services\IPRIP\Security
HKLM\SYSTEM\CurrentControlSet\Services\IPRIP
HKLM\SYSTEM\CurrentControlSet\Services\IPRIP\Parameters
HKLM\SYSTEM\CurrentControlSet\Services\IPRIP\Security
-----
Values added: 21
-----
HKLM\SYSTEM\ControlSet001\Services\IPRIP\Type: 0x00000020
HKLM\SYSTEM\ControlSet001\Services\IPRIP\Start: 0x00000002
HKLM\SYSTEM\ControlSet001\Services\IPRIP\ErrorControl: 0x00000001
HKLM\SYSTEM\ControlSet001\Services\IPRIP\ImagePath: "%SystemRoot%\System32\svchost.exe -k netsvcs"
HKLM\SYSTEM\ControlSet001\Services\IPRIP\DisplayName: "Intranet Network Awareness (INA+)"
HKLM\SYSTEM\ControlSet001\Services\IPRIP\ObjectName: "LocalSystem"
HKLM\SYSTEM\ControlSet001\Services\IPRIP>Description: "depends INA+, collects and stores network configuration and l
HKLM\SYSTEM\ControlSet001\Services\IPRIP\DependOnService: 52 70 63 53 73 00 00
HKLM\SYSTEM\ControlSet001\Services\IPRIP\Parameters\ServiceDll: "C:\documents and settings\John\Desktop\Lab03-02.dll"
HKLM\SYSTEM\ControlSet001\Services\IPRIP\Security\security: 01 00 14 80 90 00 00 00 9c 00 00 00 14 00 00 00 30 00 00
HKLM\SYSTEM\CurrentControlSet\Services\IPRIP\Type: 0x00000020

```

Figure 25: Regshot results after installing Lab03-02.dll.

Process Monitor - C:\Class\Noriben\Noriben_08_Jun_18_13_53_54_291000.pml				
File Edit Event Filter Tools Options Help				
Time ...	Process Name	PID	Operation	Path
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\Type
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\Start
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\ErrorControl
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\ImagePath
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\DisplayName
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\Security\security
6:56:1...	services.exe	556	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\ObjectName
6:56:1...	services.exe	556	RegFlushKey	HKLM\System\CurrentControlSet\Services\IPRIP
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\ImagePath
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP>Description
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\DisplayName
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\ErrorControl
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\ObjectName
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\Start
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\Type
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\Parameters\ServiceDll
6:56:1...	rundll32.exe	3596	RegSetValue	HKLM\System\CurrentControlSet\Services\IPRIP\DependOnService

Figure 26: Process Monitor results after installing Lab03-02.dll.

LAB 3-2 Question 3

How can you find the process under which this malware is running?

After installing the malware with run32dll.exe and running the command “net start IPRIP,”

Process Monitor and Wireshark captures were made. Process Monitor captured that Lab03-02.dll

used the process svchost.exe (Figure 27). A brief check in Process Explorer revealed that IPRIP was indeed running under this process (Figure 28).

7:30:5...	Procmon.exe	3300	CreateFile	C:\WINDOWS\system32\winmgmt.dll
7:30:5...	Procmon.exe	3300	CloseFile	C:\WINDOWS\system32\shimeng.dll
7:30:5...	Procmon.exe	3300	CreateFile	C:\WINDOWS\system32\ndptsp.tsp
7:30:5...	svchost.exe	892	CreateFile	C:\Documents and Settings\John\Desktop\Lab03-02.dll
7:30:5...	svchost.exe	892	CloseFile	C:\Documents and Settings\John\Desktop\Lab03-02.dll
7:30:5...	Procmon.exe	3300	CloseFile	C:\WINDOWS\system32\ndptsp.tsp
7:30:5...	Procmon.exe	3300	CreateFile	C:\WINDOWS\AppPatch\AcGenral.dll

Figure 27: Lab03-02.dll uses svchost.exe.




Figure 28: IPRIP being used under svchost.exe.

LAB 3-2 Question 4

Which filters could you set in order to use procmon to glean information?

Because the malware runs under the process svchost.exe, Process Explorer gives us the PID of svchost.exe that IPRIP is being used under as 892. That filter can be applied to procmon as well

CYBV 454 Assignment 2 LIVINGSTON

as any other useful information to narrow down the breadth of services that svchost.exe runs, such as the path containing “Lab03-02” (Figure 29).





Figure 29: Process Monitor Filters.

LAB 3-2 Question 5

What are the malware’s host-based indicators?

It would be very suspicious to have svchost running the IPRIP service as it has been used, according to bleepingcomputer.com, as a backdoor by other malware in the past (Figure 30). The malware embeds itself in the windows registry under:

HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\IPRIP\ Parameters\ServiceDll. The data in ServiceDll shows the name of the file and having ServiceDll data values set is a good host-based indicator of infection (Figure 31). Additionally, when the same path was inspected on an uninfected Windows 10 machine, the IPRIP service did not exist under that path (Figure 32). The mere existence of IPRIP would be a good host-based indicator of infection.



Name	IPRIP
Filename	ipripst.dll
Command	C:\Windows\System32\ipripst.dll
Description	Added by the W32/Mofei-W backdoor worm.
File Location	%System%

Figure 31: IPRIP has been used by malware.




Figure 31: Lab03-02.dll located in the registry.




Figure 31: Path to IPRIP service does not exist in an uninfected machine's registry.

LAB 3-2 Question 6

Are there any useful network-based signatures for this malware?

The only useful network-based signature that this malware provided was that, every so often, the malware makes a DNS callout to the website, "practicalmalwareanalysis.com" (Figure 32). The network administrator for an enterprise should add this domain to the block list.

ApateDNS		
Capture Window		DNS Hex View
Time	Domain Requested	DNS Returned
20:02:38	practicalmalwareanalysis.com	FOUND

Figure 32: Callout to practicalmalwareanalysis.com.

LAB 3-3

- LAB03-03.exe : e2bf42217a67e46433da8b6f4507219e




Figure 33: Virus Total Findings for file Lab03-03.exe.

Virus Total found 59 matching signatures for Trojan malware with potential explorer hijack functionality for the file Lab03-03.exe (Figure 33). It has a compilation timestamp of 08 Apr 2011 at 17:54:23 UTC (Figure 34). It appears to only import Kernel32.dll suggesting it manipulates memory, files, and other hardware (Figure 35). Under the “Behavior” tab, it is noted that the malware executes by using process hollowing and attempting to dynamically load functions (Figure 36). It has indicators of privilege escalation and defense evasion (Figures 36 and 37). Noting that it has input capture characteristics, it is possible that this malware is a keylogger, sending the inputs back to a Command and Control host since it performs DNS lookups (Figure 38).

Header	
Target Machine	Intel 386 or later processors and compatible processors
Compilation Timestamp	2011-04-08 17:54:23 UTC
Entry Point	6875
Contained Sections	4

Figure 34: Virus Total Compilation Timestamp for file Lab03-03.exe.

Imports	
+	KERNEL32.dll

Figure 35: Virus Total Import for file Lab03-03.exe

Execution	TA0002
Shared Modules	T1129
⚠ Sample uses process hollowing technique	
Execution	TA0002
Shared Modules	T1129
⚠ The process tried to load dynamically one or more functions.	
Execution	TA0002
Shared Modules	T1129
① Parse PE header	
① Link function at runtime on Windows	
Privilege Escalation	TA0004
Process Injection	T1055
⚠ Allocates memory in foreign processes	
⚠ Injects a PE file into a foreign processes	
⚠ Writes to foreign memory regions	
⚠ Sample uses process hollowing technique	
① Creates a process in suspended mode (likely to inject code)	
① Spawns processes	

Figure 36: Virus Total behavior for file Lab03-03.exe.




Figure 37: Virus Total behavior for file Lab03-03.exe.





Figure 38: Virus Total C&C for file Lab03-03.exe.

LAB 3-3**LAB 3-3 Question 1****What do you notice when monitoring this malware with Process Explorer?**

To first get an indication of what the malware would look like in process explorer, Process Monitor was used to create a capture first. From the capture, the process that would be used by the malware, and therefore the process to look for in Process Explorer, would be svchost.exe (Figure 39). This is confirmed by examining a svchost.exe instance in Process Explorer and that it is accessing the current directory where the malware is stored (Figure 40).



8:31:2...	Procmon.exe	3340	Thread Create	
8:31:2...	Procmon.exe	3940	Thread Create	
8:31:2...	Explorer.EXE	1472	Process Create	C:\Labs\BinaryCollection\Chapter_3L\Lab03-03.exe
8:31:2...	Lab03-03.exe	232	Process Start	
8:31:2...	Lab03-03.exe	232	Thread Create	
8:31:2...	csrss.exe	488	Thread Create	
8:31:2...	Lab03-03.exe	232	Process Create	C:\WINDOWS\system32\svchost.exe
8:31:2...	svchost.exe	252	Process Start	
8:31:2...	svchost.exe	252	Thread Create	
8:31:2...	Lab03-03.exe	232	Process Exit	

Figure 39: Lab03-03.exe uses svchost.exe to run.




Figure 40: svchost.exe running in the malware's directory.

LAB 3-3 Question 2

Can you identify any live memory modifications?

In the “Properties” window of svchost.exe running the malware, the “Strings” tab offers an option to view not only the image of the running process, but also the memory. The process has multiple printable strings that are suspicious in the memory. There is a reference to a suspicious URL of practicalmalwareanalysis.log as well as what appears to be keyboard inputs of “[SHIFT]”, “[BACKSPACE]”, etc. (Figure 41). This string pattern is highly suggestive of the malware being a keylogger, a potential behavior characteristic identified by Virus Total. To test this, the svchost.exe PID of 252 was added as a filter into procmon and some text was typed into a notepad document. The PID captured every keystroke and stored it in the directory from which the malware was running (Figure 42).




Figure 41: Lab03-03.exe memory strings.




Figure 42: Lab03-03.exe stores keystrokes in a .txt file in its directory.

LAB 3-3 Question 3

What are the malware's host-based indicators?

For this particular malware, the most noticeable host-based indicator was the generation of a .txt file titled, "practicalmalwareanalysis.log." The presence of a file of this extension and name on a host system would not only be indicative of infection, but also help point to the directory in which the malware is installed (Figure 43). If the malware was modified in any way to change the name or location of which the directory is stored, then using procmon to monitor svchost.exe PIDs while simultaneously pressing buttons on the keyboard to live-capture memory. The malware was tested by entering strings in a .txt file and randomly on the screen, both of which were captured by the malware.




Figure 43: *practicalmalwareanalysis.log* is stored in the directory of the malware.

LAB 3-3 Question 4

What is the purpose of this program?

It is extraordinarily clear that this malware is a keylogger. However, procmon did not detect any attempts to send that information to a remote host (Figure 44). This would lead to the reasonable assumption that someone with malicious intent on capturing the keystrokes of a user would have access to the machine of that user. This would then mean that those two individuals likely live in close proximity, if not cohabitate with each other. Likely, a keylogger of this type would be used by a jealous, malicious, or otherwise ill-intended person trying to spy on their significant other.




Figure 44: *Lab03-03.exe* did not have any network traffic.

LAB 3-4

- LAB03-04.exe : b94af4a4d4af6eac81fc135abda1c40c




Figure 45: Virus Total Findings for file Lab03-04.exe.

Virus Total found 50 matching signatures for Trojan malware for the file Lab03-04.exe (Figure 45). It has a compilation timestamp of 18 Oct 2011 at 18:46:44UTC (Figure 46). It appears to import Kernel32.dll and advapi32.dll, suggesting it manipulates memory, files, and other hardware as well as the potential to edit the registry. The additional imports of shell32.dll and ws2_32.dll suggest that it possibly opens a shell and connects to the internet, allowing for a remote domain or host to upload or even remotely connect to the infected machine (Figure 47). Under the “Behavior” tab, it is noted that the malware has other indicators of persistence and privilege escalation, as well as creating a process that is likely to inject code (Figure 48). Noting that it has input capture characteristics, it is possible that this malware has characteristics of a keylogger and has some functionality to perform downloads and file writing (Figure 49).

Header	
Target Machine	Intel 386 or later processors and compatible processors
Compilation Timestamp	2011-10-18 18:46:44 UTC
Entry Point	14486
Contained Sections	3

Figure 46: Virus Total compilation timestamp for file Lab03-04.exe.

Imports	
+	ADVAPI32.dll
+	SHELL32.dll
+	KERNEL32.dll
+	WS2_32.dll

Figure 47: Virus Total imports for file Lab03-04.exe.

Execution	TA0002
Service Execution	T1569.002
① Create service	
① Modify service	
① Persist via Windows service	
Persistence	TA0003
Windows Service	T1543.003
① Create service	
① Modify service	
① Persist via Windows service	
① Delete service	
Privilege Escalation	TA0004
Process Injection	T1055
① Spawns processes	
① Creates a process in suspended mode (likely to inject code)	

Figure 48: Virus Total behavior for file Lab03-04.exe.



Figure 49: Virus Total input capture and C&C for file Lab03-04.exe.

LAB 3-4**LAB 3-4 Question 1****What happens when you run this file?**

While conducting a static analysis, some strings contained within the file suggested that this malware potentially has the ability to download and upload files with a potential domain of www.practicalmalwareanalysis.com. Combined with the string of “HTTP/1.0”, it is likely that this malware is a backdoor (Figure 50).

A	00000000B034	00000040B034	0	CompareStringW
A	00000000B046	00000040B046	0	CompareStringW
A	00000000B058	00000040B058	0	SetEnvironmentVariableA
A	00000000C030	00000040C030	0	Configuration
A	00000000C040	00000040C040	0	SOFTWARE\Microsoft\XPS
A	00000000C058	00000040C058	0	\kernel32.dll
A	00000000C070	00000040C070	0	HTTP/1.0
A	00000000C098	00000040C098	0	NOTHING
A	00000000C0AC	00000040C0AC	0	DOWNLOAD
A	00000000C0B8	00000040C0B8	0	UPLOAD
A	00000000C0C4	00000040C0C4	0	SLEEP
A	00000000C0CC	00000040C0CC	0	cmd.exe
A	00000000C0D4	00000040C0D4	0	>> NUL
A	00000000C0DC	00000040C0DC	0	/c del
A	00000000C0E8	00000040C0E8	0	http://www.practicalmalwareanalysis.com
A	00000000C118	00000040C118	0	Manager Service
A	00000000C134	00000040C134	0	%SYSTEMROOT%\system32\
A	00000000C14C	00000040C14C	0	k:%s h:%s p:%s per:%s
U	00000000B1F0	00000040B1F0	0	(null)
A	00000000004D	00000040004D	0	!This program cannot be run in DOS mode.
A	0000000000BE	0000004000BE	0	6KRich

Figure 50: BinText strings for Lab03-04.exe.

To dynamically analyze the malware when it is run, instances of both procmon and Process Explorer were set up in order to capture any output that would provide clues that would lead to the purpose of this malware. Additionally, because of the potential for this malware to act as a backdoor, UpdatedDNS was set up in order to capture any outbound traffic.

When the malware was run, Lab03-04.exe deleted itself from the directory it was in and did not end up in the Recycle Bin. In procmon, a process was created by Lab03-04.exe with a PID of

8996 (Figure 51). Filtering procmon by that PID, a cmd.exe process was created that shows how the file deleted itself (Figure 52).




Figure 51: Created PID of 8996 by Lab03-04.exe.




Figure 52: How Lab03-04.exe deleted itself.

LAB 3-4 Question 2

What is causing the roadblock in dynamic analysis?

When a search of PID 8996 is conducted in Process Explorer, no results come back which indicate that the malware is not actively running on the machine (Figure 53). Furthermore, there

aren't any network-based indicators that this malware is attempting to conduct. The fact that the malware deleted itself presents a roadblock that the VM needs to be reset to the previous snapshot if further dynamic or static analyses are conducted. However, the malware does not delete duplicates of itself and only deletes the .exe file that was run by the user. Without more advanced knowledge on how to analyze malware, especially with increasing complexity, the roadblocks are not the tools nor the malware. The roadblock is the skill of the analyst.




Figure 53: Lab03-04.exe is not actively running.

LAB 3-4 Question 3

Are there other ways to run this program?

Without further knowledge of how to run a self-deleting piece of malware in order to view its effects on a sandbox environment, I cannot think of anything. I am excited to learn more on how to overcome this type of challenge and perform an even more thorough analysis. The book teases more advanced dynamic analysis techniques in the future and infers solutions to the self-deleting-malware problem.