


Helper Classes

***Kristine Middlemiss**, Senior Developer Consultant
Autodesk Developer Network (ADN)*

Autodesk®

Agenda

- API Command Utilities
- Error Handling and Debugging
- DAG Hierarchy



API Command Utilities



Utilities API: MGlobal

- Query and set global settings (time, z-up, selection masks, etc..)
- Query what is selected or highlighted
- Display command warnings and errors
- Interaction with script languages

Utilities API: MGlobal

- Query and set global settings (time, z-up, selection masks, etc..)
 - MGlobal::mayaState(MStatus * returnStatus)
 - MGlobal::viewFrame (const MTime & time)
 - MGlobal::setSelectionMode (MGlobal::MSelectionMode mode)
 - MGlobal::setYAxisUp (bool rotateView)
 - Etc...

MGlobal & Selection List

- MSelectionList: class representing a list of MObjects
 - Used for more than just what is selected, e.g.
 - Highlight list
 - Query / Modify list membership
- MItSelectionList: class for iterating over the items in an MSelectionList. A filter can be specified so that only those items of interest on a selection list can be obtained.

```
MGlobal::getActiveSelectionList(MSelectionList &dest);
```

```
MGlobal::getSelectionListByName ( const MString & name, MSelectionList & list )
```

```
MGlobal::setActiveSelectionList( const MSelectionList & src,  
                                MGlobal::ListAdjustment )
```

MGlobal Selection

- `MGlobal::select (const MDagPath & object, MGlobal::ListAdjustment listAdjustment)`
add an object to the active selection list without creating an `MSelectionList` first
- `MGlobal::selectByName(const MString & name, MGlobal::ListAdjustment listAdjustment)`
finds all objects matching a pattern and adds them to the active selection list
- `MGlobal::setActiveSelectionList (const MSelectionList & src, MGlobal::ListAdjustment)`
Set the active selection list. The selection items on the given list will update the contents of the active selection list as indicated by the `listAdjustment` parameter.
- `MGlobal::selectCommand (const MSelectionList & src, MGlobal::ListAdjustment)`
Set the active selection list, by calling the built in Maya select command
- `MStatus MGlobal::selectFromScreen (const short & x_pos, const short & y_pos, MGlobal::ListAdjustment, MGlobal::SelectionMethod)`
Perform click-pick type selection. If an object intersects the click point then it is selected according to `listAdjustment`.

Utilities API: MGlobal

- Display error/warning messages or general information to the user for custom command

```
void MGlobal::displayInfo ( const MString & theMessage )
```

```
void MGlobal::displayWarning ( const MString & theWarning )
```

```
void MGlobal::displayError ( const MString & theError )
```


Utilities API: MGlobal

- Execute MEL script:

```
MGlobal::executeCommand(const MString &command)  
MGlobal::sourceFile
```

- Execute Python Command:

```
MGlobal::executePythonCommand (const MString &command)
```

```
# execute MEL command to create a nurbs sphere  
OpenMaya.Mglobal.executeCommand( "sphere" );
```

```
# execute the specified mel script  
OpenMaya.MGlobal.sourceFile( "C:\\MyScripts\\testScript.mel" );
```

```
#execute python command to create a poly cube  
OpenMaya.MGlobal.executePythonCommand ( "polyCube( sx=10, sy=15, sz=5, h=20 )" )
```

Error Handling and Debugging



Error checking: MStatus

- We have removed the MStatus class.
- Python exceptions (try and except) must be used instead of MStatus.
- 3 Special cases:
 - Hardcoded Maya API class for status codes:

`OpenMaya.MStatus.kSuccess` - The operation was successful

`OpenMaya.MStatus.kFailure` - The operation failed

`OpenMaya.MStatus.kUnknownParameter` - Returned by `MPxNode::compute` for unrecognized plugs

OpenMaya Status Codes

- Python API does not contain MStatus
- Any method that would have returned a non-success
- MStatus will raise an exception instead
- Provides error checking that is more natural in Python


```
try:
```

```
    mplugin.registerNode( kPluginNodeTypeName, sineNodeId,  
                          nodeCreator, nodeInitializer )
```

```
except:
```

```
    sys.stderr.write( "Failed to register node: %s" %  
                      kPluginNodeTypeName )  
    raise
```

DAG Hierarchy




DAG (Directed Acyclic Graph)

- DAG Nodes are just DG Nodes!
- Parenting are not dependency graph connections
- DAG hierarchy
 - Node types containing transformation info:
 - joints (MFn::kJoint)
 - transforms (MFn::kTransform)
 - Other typical node types in a skeletal hierarchy:
 - shapes (nurbs, polys, ...)
 - locators (MFn::kLocator)
 - Ik (MFn::ikHandle, MFn::ikEffector)


DAG Hierarchy

- An Example: sphere




DAG Hierarchy

- A more complex example: skeleton hierarchy



DAG Hierarchy

- A more complex example: skeleton hierarchy



hip

spine

shoulder

arm



hand

Instancing

- A node may have more than one parent
- A dagPath is used to identify instances


group1|pCube1|pCubeShape1

group1|pCube2|pCubeShape1



Dag Paths

- used to find world space transformations
- used to traverse up and down hierarchy
- node names need not be unique if dagPaths are different (MDagPath fullPathName, partialPathName)




MObject VS. MDagPath

Many of the Maya API accept/return a MObject or a MDagPath

- A MDagPath is a handle describing a path to a node
- A MObject is a wrapper around a pointer to the internal Maya object
 - Generic class (represents all node / attribute)
 - Use apiType() / hasFn() to determine what it is or what you can do with it
 - Use isNull() to determine if it is a valid MObject
 - Do not store MObject

Important API methods

- Traversal : MltDag iterator class
- Depth in hierarchy: MDagPath::length, MltDag::depth
- Getting the parent: MDagPath::pop
- Local matrix: MFnTransform::transformation
- World matrix: MDagPath::inclusiveMatrix, MDagPath::exclusiveMatrix ...



Workshop Session



Example: dagInfo

- In this exercise, we will implement a custom command dagInfo. For all the selected DAG nodes in the scene, it will print out the instance information, dag path and also inclusive and exclusive matrix.
- Important Classes: MFnDagNode, MDagPath MMatrix, MGlobal, MItSelectionList

Autodesk