SPRING-BOOT

Q.1 What is Spring-Boot?

→ Spring boot is a java framework that is used to create standalone applications and micro services.

Q.2. Dependencies -

→ parent dependency

```
<parent>
        <groupId>      </groupId>
        <artifactId> spring-boot-starter-parent </artifactId>
</parent>  <version> 2.1.2.release </version>
<dependencies>
<dependency>
        <artifactId> spring-boot-starter-web </artiId>
</dependency>
<dependency>
  <artifactId> spring-boot-devtools </artiId>
</depend>
<dependency>
  <artifactId> My-connector-sql-connector </artifactId>
<dependency>
</dependencies>
```

Q.3. Annotation used in starter class?
-> @SpringBootApplication - It is a combination of 3 annotations
  -> @SpringBootConfiguration
  @EnableAutoConfiguration
  @ComponentScan

Q4 How to run spring-boot-application?
-> Using SpringApplication.run(ORSProject-10Application.class, args);

Q5 layers in Springboot?
1. Data access layer (DAO)
2. Business layer (Service)
3. Controller layer
4. Presentation layer

Q.6 DESIGN PATTERNS?
1. DTO (Data transfer object) -
It is used to transfer data between layer component of a applicat
2. DAO design Pattern (Data access object) -
It is used to separate the data access logic from business logic.
Classes that communicates with database follows DAO DP.
3. Session Facade -
-> Single gateway for multiple sub systems.
4. Bridge D.P. -
-> followed on service & DAO layer.
5. observer D.P. -
-> DAO layer: Bridge DP, DTO DP, DAO DP.
-> Service layer: Bridge DP, DTO DP, Session facade

Q7. what is IOC?
-> Inversion of control provides dependency injection and creates bean.

Q8. How we created non-bussiness PK?
-> @Id
  @GeneratedValue(generator = "PK")
  @GenericGenerator(name = "PK", strategy = "native")
  @Column(name = "ID", nullable = false, unique = true)
@Id marks as primary key.
@GeneratedValue & @genericGenerator with strategy "native"



tell Hb. to let the db itself auto-generate the Id.
(like auto-increment in MySQL)

→ nullable = false, unique = true every record must have an ID and no two records can share one.

Q. HTTP status codes?

→
- 200 - OK (success)
- 400 - resource not found
- 401 - unauthorised
- 500 - server error

Q what we did to connect backend with frontends?

→ frontend to backend - Ajax calling
backend to frontend - CORS Mapping

Q. How we did Cors Mapping?

```
@Bean
    public WebMvcConfigurer corsConfig() {
        WebMvcConfigurer w = new WebMvcConfigurer() {
    @Override
    public void addCorsMappings(CorsRegistry registry) {
      registry.addMapping("/**")
      .allowedOrigins("http://localhost:4200")
      .allowedMethods("Get", "Post", "Put", "Delete", "OPTIONS")
      .allowedHeaders("*")
      .allowCredentials(true);
    }
};  return w;
```

Q. JWTUtil is used for?
→ To generate token & Validate.

Q. what is JWTRequestFilter does?
→ Validates token on every request.

Q. what is API?
→ applications that communicates using JSON are called restful web services.

Q what is JPA?
→ JPA stands for Java Persistence API. It is a specification that def
Set of interfaces and rules for db operations in java.
Q. what is entity manager? (Manage objects) (called entities).
→ entity manager is used to manage entity & database interaction with a

Q. what is JWT?
→ JWT stands for JSON web Token and It is used for authenticat
and authorisation in modern application. It is stateless & secure
→ JWT Token consist of - Header, Payload and Signature.
→ Header Contains Meta information
- Algorithm → HS256 (HMAC + SHA-256)
type - Token

→ Payload. Contains claims (data)
eg - UserId, role etc, Basically → actual information
→ Signature is consist of header + Payload + Secret key
- ensures integrity + authencity.

Q why JWT instead of session?
→ No need to store session in server memory
easy to scale across multiple servers, secure & light weight.
Q what is HS-256?
→ It is hashing algorithym that converts data into fixed size i.e 256 bit
HMAC + SHA = 256
HMAC = Hash-based message authentication code
SHA-256 = secure Hash algorithm (256 bit → 32 bytes)
Q Behaviour of Token?
→ Cannot be manually destroyed.
But can expire (exp claim)
used in HTTP requests (usually in headers)

8954666711

Page

Q what is HMAC?

→ HMAC is mechanism that uses a hashing algorythm & adds a secret key on top of hashing

SHA-256 → Creates hash

HMAC → secures it with secret key

RESULT → signature

Q WebSecurityConfig extends?

→ WebSecurityConfigurerAdapter.

ANGULAR

Q.1. what is angular?

→ Angular is a typescript based frontend framework that is used to create single page application.

Q.2. default files available in angular project?

→ app.component.html
app.component.ts
app.component.spec.ts
app.component.css
app.module.ts
app.routing.module.ts

Q.3. what is AJAX calling? what we did for AJAX calling?

→ AJAX (Asynchronous Javascript and xml) is a technique used in web application development to send and receive a data from a server without reloading the entire web page.

1. we imported http client in app.module.ts
2. then hamne httpservice me get aur post method banaya h.
3. usme httpclient ki get and post method ko return karaa h.

Q.4. what is single page application?

→ SPA is a web application that load a single HTML page and dynamically updates content without reloading the page.

Q5 Arrays in App.module.ts?
-> 1. Declarations (to declare components)
2. imports (imports libraries)
3. Providers (service declare karne ke liye)
4. bootstrap

Q.6 decorators used in app.module.ts?
-> @ngModule

Q7. what is pipe?
-> Pipes transformed displayed value in desired Format.

Q.8 How to Create angular build?
-> ng build --base-href /orsproject10-ui/

Q9. what are angular directives?
-> a way to control HTML dynamically.
*ngIf -> show/hide element
*ngFor -> loop through data
*ngSwitch -> switch cases

Q.10. what is key method contained in the observable object returned by the HttpClient.get() or post() methods in angular?
-> subscribe() method

Q11. How many Callback method are passed to subscribe() method?
-> 3
1. success Callback
2. fail Callback
3. complete callback

Q.12. The failure Callback of the subscribe() method in angular is called:
-> 1.) A 404 (not found) response is returned
2). There is a network failure.

Q.13. what is observable object?
-> observable object in angular handles realtime data. It basically observes & answer when we subscribe to it using subs. method.

Q.14 <Router-outlet> tag kya karta h?
-> Components ki routing ko enable karta hai.

Q.15 what is callback?

-> Function as a parameter is called callback function.

Q.16 @viewchildren kya karta hai?

-> used to point more than one element in HTML.

Q.17 what is internationalisation?

-> internationalisation (often written as i18n) is the process of making your application support multiple languages & regions so users see content in their preferred language & format.

Q.18 what is httpclient? in angular?

-> Httpclient is a service provided by angular to interact with REST APIs.

Q.19 what is subscribe method?

Subscribe() is used to execute the HTTP request & handle the response.

get() -> fetch data

post() -> send data

1. what is Httpclient in angular?

-> Httpclient is an angular service used to communicate with backened APIs. It helps sends HTTP requests like get, post, Put & delete and handle reponses easily.

2. Why does Httpclient return an observable instead of data?
→ HTTP Client returns an observable because API calls are asynch
data does come immediately. So, observables allow angular
handle future data efficiently.

3. what happens if we don't use subscribe()?
→ If you don't call subscribe(), the HTTP request will not execute
observables are lazy. meaning nothing happens until you subsc

4. what is the purpose of subscribe()?
→ subscribe() is used to execute the HTTP request & handle the respo
errors, and completion ~~of~~ of the request.

5. what are the Callbacks in subscribe()?
→ subscribe() can take 3 callbacks.
next → called when data is received successfully.
error → called when an error occurs. (404, 500, network issue)
complete → called when the request finishes.

6. what is the difference betn get() & post()?
→ get() → used to fetch data from the server.
post() → send data to server.

7. Can, we handle errors globally in angular?
yes, using http interceptors, we can handle errors globally instead of
writing error logic in every subscribe().

8. what is typesafety in httpclient?
→ Type safety means defining the expected data type:
this.http.get<User[]>(url);
This helps avoid runtime errors & improves codes quality.

9. ~~Can we~~ Is httpClient used in real world projects?
yes, http client is used in almost every angular applicat'n for API
Communicat'n in enterprise systems.

10. Can we avoid subscribe() in angular?
yes, in some cases using async pipe in templates can automatically
subscribe() & unsubscribe.

PROJECT-10 FLOWS

Q.1. Dashboard kyu open ho raha hai?

→ {

Path: '' '',

Pathmatch: "Full",

redirectTo: 'dashboard'

},

Q.2. Header aur Footer ko kaise include kara hai?

→ Humne dashboard.component.html par navbar and Footer ke selector ko call kiya hai.

Q.3. Login ki link par click karne par kya hota h?

→ sabse pehle humne navbar.component.html pe login ki link banayi h <a [routerLink] = "['/login']">.Login

→ request jayegi app.routing.module.ts par

→ Routing me path match hua.

→ login component call hua.

→ waha se request gyi login.comp.ts par

→ and login.component.html open ho gya

Q.4 Input validations kaise perform ho rhe hai?

→ humne login.component.html par sign-In ka button banaya h.

→ click event par humne signIn() ke function ko call kiya h.

→ request gyi login.component.ts par

→ SignIn() function me humne HttpService ki post method ka use login ki api ko hit kiya hai saath me body.data bheja hai.
→ request gayi loginCtl par.
→ uski login method call hui.
→ @RequestBody se humne request ka data body me nikala h
→ @Valid se humne input validations ko enable kiya hai.
→ usko BindingResult ke object bindingResult me hold kiya hai
→ humne baseCtl ki validate method ko call kiya hai & usme binding result ko pass kiya hai.
→ validate method me humne condition di hai, ki bindingResult hasErrors() true h to humne success ko false kiya hai.
→ and res.addInputErrors(errors) me errors ko pass kiya hai & response ko return karaya hai.
→ angular me humne callback function ka use karke response ko get kiya h.
→ body.error ko true kiya h
→ and result.inputerror ko body.inputerror me hold karke interpolation se html par Print karya hai.

Q5. Login Ka Flow?
→ humne login.component.html par SignIn ka button banaya hai.
→ click event par humne SignIn() ke function ko call kiya hai.
→ request gayi login.component.~~html~~ ts par
→ uha par signIn() function me humne http service ki Post method ka use karke login ki API ko hit kiya saath me body.data bheja h.
→ request gayi loginCtl par.
→ uski login method call hui.
→ uha par @RequestBody se humne request ka data body me nikala h.
→ getDTO method se body ke data ko dto me transfer kaiya h
→ fir userService ki authenticate method ko call kiya h
→ agar user authenticate hota h to return me hume USERDTO milega
→ If UserDTO is not Null then humne success ko true kiya h.
→ res.addData me DTO ko pass kiya and response ko return karaya h
→ angular me humne callback function se response ko get kiya h
→ navigate by URL se dashboard par redirect kiya h.

Q. SignUp Ka Flow?

→ humne login.component.html par humne signup ka button banaya h.
→ click event par humne SignUp ke function ko call kiya h.
→ request gyi login.component.ts.
→ humne SignUp() function me http service ki post method ka use karke humne API ko call kiya h aur sath me form.data bheja h.
→ request gyi loginCtl par. loginCtl ki signUp() call hui.
→ @RequestBody se humne request ka data form me nikala h
→ uske baad humne getDTO method se Form ka data dto me transfer kiya h.
→ UserService ki register method call ki h usme DTO pass kiya h
→ humne res.set success ko true kiya h.
→ and res.add message me "User Registered Successfully" pass kiya h & response ko return karaya h.
→ angular me humne response ko callback function se get kiya h and interpolation se html par print karaya h.

Q. Business Validations kese perform ho rhe h?

→ user.component.html par save ka button banaya hai.
→ click event par submit function ko call kiya h.
→ request gayi user.component.ts par
→ submit function me humne http service ki post method ka use karke save/signUp/login ki api ko hit kiya h sath me form.data bheja h.
→ request gyi UserCtl/LoginCtl par
→ uski save/login/signUp method call hui.
→ @RequestBody se humne request.ka data.ko form me nikala hai.

LOGIN:

→ humne UserService ki authenticate method ko call kiya h jisme boorm.getloginId & boorm.getPassword Pass kiya h.
→ return me humko userDTO mila.
→ agar UserDTO null h to humne success ko false kiya h & res.addMessage me "Invalid loginId & Password" pass kiya h
→ response ko return kara h.

SIGN UP / ADD:

→ Service ki bindbyloginId method ko call kiya h jisme boorm.getlogin pass kiya h
→ return me humko userDTO milega jisko humne existDTO me hold karaya h
→ agar existDTO not null h to humne success ko false kiya h & res. add Message me humne "loginId already exists" Pass kiya h.
→ response ko return kara h.

UPDATE:

→ getDTO method se humne boorm ke data ko DTO me transfer kiya h.
→ humne service ki bindbylogin chalayi usme dto.getlogin pass kiya.
→ return me humko existDTO mila then humne check kia - ifb existDTO not null h and existDTO.getId not equal h to dto.getId ke.
→ success ko false kiya h & res. add message me "loginId already exists" pass kiya h & response return kara h.

Angular:

→ callback funct" se response ko get kiya h.
→ boorm. error ko true kia h and
→ res. result message ko boorm. message me set kiya.
→ interpolation ki help se html par print karaya h.

LIST FLOW

-> Navbar.comp.html par humne userlist ki link banayi h.
-> request gayi app-routing.module.ts k pass, Uha par path match hua. and user-list.component.ts call hua.
-> Vha par search function call hua
-> search functn me humne http service ki post method ka use karke search ki api ko hit kiya h & sath me body.search param ko bheja h.
-> request gayi userCtl par
-> UserCtl ki search method call hui.
-> Usne humne userservice ki search method ko call kiya.
-> usme humne DTO, pageNo & pagesize pass kiya
-> return me hunko list mili.
-> fir humne res.setSuccess ko true kiya
-> res.addData me list pass kardi
-> and response ko return kar diya.
-> humne resp. ko callback functn get kar liya.
-> res.result.data to body.list me hold kiya.
-> and user list component.html par *ngFor loop ka use karke list ko iterate kara diya, interpolatn ki help se print kara diya.

Reset Ka Flow?

-> User list comp.html. par humne reset ka button banaya h and click event par humne reset functn ko call kiya h
-> Reset ke function me humne location.reload kar diya.

Q.3. Annotation used in ...

LOGIN:

→ NEW Ka Flow.

- humne user list component.html par new ka button banaya h.
- click event par humne forward function ko call kiya h jisme hum user pass kiya h and router ki navigate by URL ka use karke redirect karaya h.

→ NEXT Ka Flow.

- click event par next function ko call kiya h
- form.pageNo ko ++ kiya h.
- and search ko function ko call kar diya h.

→ PREVIOUS Ka Flow

- same as next Ka Flow.

Q. PREVIOUS And Next ko disable kese kiya h?

→ Previous;

[disabled] = "form.pageNo == 0"

next:

[disabled] = "form.nextListSize == 0"

Q. SEARCH Ka Flow?

1. Humne input field banayi hai.
   <input type="text" name="firstName" [(ngModel)] = "form.searchParams.firstName"
2. search ka button banaya h & click event par search function ko call kiya h.
3. Uha par humne http service. ki post method ka use karke search ki api ko hit kiya h aur sath me form. search param bheja h.
4. request gyi userCtl par
5. search method call hui. Uha par humne @RequestBody se humne request ka data form me nikala h. humne getDTO method se form ka data dto me transfer kiya h.
6. User service. ki search method ko call kiya h jisme dto, pageNo, pageSize ko pass kiya h.
7. humne dao me getwhereclause method banayi hai jisme humne cond^n di h. ib dto.getFirstName() != null & dto.getfirstName.length() > 0 to humne conditions.add(CriteriaBuilder.like(qRoot.get("firstName")) + "%"));
   (qRoot.get("firstName"), dto.getfirst() + "%");

Q. Checkbox kese banaye hai?

-> selectall;

<input type="checkbox" (change)="checkUncheckAll($event)" />

input type me checkbox liya h and change event par checkuncheck all function ko call kiya hai.

Niche wale checkbox;

<input type="checkbox" (change)="checklistUpdate()".[id]="m.id">

input type me checkbox and change event me checklistupdate ko call kiya h.

Q Humne checkUncheckAll($event) me kya kiah

Ans -> checkUncheckAll(event:any) {

Const checked = event.target.checked;

this.checkboxes.forEach(cb => cb.nativeElement.checked = checked);

agar event.target.checked h to humne checkboxes k upar foreach loop laga kar saare native elements ko checked kar diya.

Q.3. Annotation used in starter class?
→ @SpringBootApplication
→ @Sno in -

Q. Humne checklistUpdate() me kya kiya h?
→ checklistUpdate() {
Const totalChecked = this.checkboxes.filter(cb =>
cb.nativeElement.checked).length;
this.isMasterSel = totalChecked === this.boerm.list.length;

→ Humne checkboxes ke upar filter apply kiya h.
and native element checked ki length agar humari list ki length ke equal aatih to upar wala checkbox checked ho jayega.

Q.18 Delete par 'select atleast one record' kese aa rha h?
1→ humne input me checkbox liya h & change event par checklistupdate() ko call kiyah.
2. Humne property binding se id ko bind kar rakha h [id] = "m.id"
3. Humne userlist.comp.html par delete ka button banaya h
4. and click event par deleteMany ke function ko call kiya h.
5. deleteMany funct" me humne deleteRecordlist naam ki blank list le rakhih and bir humne checkboxes par for each loop apply kiah.
6. agar native Element checked h to humne nativeElement.id ko deleteRecordList me push kar diya h
7 bir check kiya ki deleteRecordlist ki length agar equals to 0 h to humne boerm.error ko true kiya h deleteRecordlist.length == 0.
8. and boerm.message me "select atleast one record" set kiya

DELETE API → http://localhost:8081/User/deleteMany/1,2,3?pageNo=0
SEARCH API → http://localhost:8081/User/search/0

Q. DELETE ka flow?

→ input me checkbox diya h and change event par checklistupdate() ko call kiya h.

→ property binding se id ko bind kar rakha h [id] = "m.id"

→ fir humne delete ka button banaya h.

→ and click event par deleteMany ke function ko call kiya h.

→ deleteMany funct^{n} me humne deleteRecordListnaam ki blankList le rakhi h.

→ fir humne checkboxes par for each loop apply kiya h

→ agar nativeElement checked h to humne nativeElement.id ko deleteRecordList me push kar diya h

→ agar deleteRecordlist.length > 0 to humne form.pageNo ko 0 set kiya h

→ http service ki post method ka use karke delete ki api ko hit kiya h

→ sath me search param ko bheja h

→ then request jayegi UserCtl ki deleteMany method par

→ uha par @PathVariable se ids ko get karke long type ke array me hold karaya h

→ fir for each loop laga kar ids ko iterate karke service ki delete method se delete karaya h

→ res. setSuccess ko true kara h

→ & res.message me "user deleted successfully" set kiya h

→ angular me response ko get kiya h

→ res.result.message ko form.message me hold kara ke interpolation ki help se print kara h.

Q. PRELOAD ke liye kya kiya h (dynamic)?

→ humne Preload function banaya h.
→ http service ki get method ka use karke preload ki API hit kiya h.
→ request gyi userctl ki preload method par.
→ Uha par humne roleservice ki search method ko call kiya h.
→ usme humne dto me null, PageNo me 0 and PageSize me 0 pass kiya h.
→ return me hume list mili.
→ success ko true kiya h.
→ res.add result me key me rolelist likha h and value me rolelist ka object pass kiya h & response ko return kiya h.
→ res.result.rolelist ko boorm.preload me hold kiya h.
→ callback funct^n se resp. ko get kiya h.
→ res.result.rolelist ko boorm.preload me hold kiya h.
→ humne select & option tag ka use karke "ngFor loop lagaya h jisme value me obj.key pass kiya h & obj..value ko display karaya h.

Q2) EDIT Ka bolo?

→ userlist comp.html par humne edit ki link banayi h.
→ click event par forward funct^n ko call kiya h. usme humne value me /user/m.id pass kiya h (click) = "forward('/user/'+m.id)"
→ request gayi app-routing.module.ts par
→ Uha path match hua
→ Path match par user.comp.ts call hua
→ Uha par humne activated route ki help se path variable se id ko get kiya h
→ display method call ki
→ display method me humne http service ki get method ka use karke get ki api ko hit kiya h & sath me path variable me boorm.data.id bheji h
→ request gyi userctl ki get method me
→ humne @ Pathvariable se path variable ko long type ki id me hold karaya h and fir humne user service ki findById ko call kiya
→ DTO return kiya. & res.set success ko true kiya.
→ res.add Data me DTO pass karke resp. ko return karaya.
→ callback funct^n ka use karke humne resp. ko get kiya
→ res.result.data ko humne boorm.data me hold karaya
→ two way data binding ki help se data ko print karaya.

Q Front Controller ke liye kya kiya h?
-> ek class @@. banayi h FC.
-> humne HandlerInterceptor Adaptor ko extend kara h
-> prehandle() method ko override kiya h.
-> Humne httpsession ka object banaya h.
-> $session.getattribute se humne userContext ko get kiya h.
-> agar userContext null to humne response.setContent Type me humne ("application/json") likha h.
-> response.setStatus(HttpServletResponse.SC_UnAuthorized); likha h
-> & printwriter ka object bana kar response ko write kar diya
-> success ko false kar diya
-> & error me "oops! your session has been expired" karke return kar diya
-> starter class me corsConfig kiya & usme humne addinterceptors me FrontCtl ko add kar diya.
-> angular me humne httpservice banayih
-> usne get & post method me agar respons FAIL milta h to humne usko handle kiya h.
-> usse phle humne local storage ko clear kiya & navigate by URL se login par redirect kar diya h along with message.
-> fir us msg ko get kiya & form.message me hold karaya.
-> interpolation ki help print kara liya.

Q. Image display karne ke liye kya kia h?
-> humne user list.comp.ts par humne ek image ka column banaya h
-> Wha par humne img tag ka use karke src me image ki api ko hit kiya h

Q.3. Annotation used in starter class.?
→ @SpringBootApplication - It is
→ @SpringBootConfiguration

Q. Image upload ke liye kya kiya h?
→ input field banayi h.
<input type="file" name="imageId" (change)="onFileSelect($event)"
accept="image/*">
→ change event par onFileSelect function ko call kiya h.
→ save ka button banaya h jisme hume click event me submit function call kiya h.
→ submit funct^n me humne uploadFile() function ko call kiya h.
→ uha sbse pehle humne FormData ka object banaya h.
→ formData.append me humne key me "file" pass kiya & value me fileToUpload formData.append('file', this.fileToUpload);
→ uha par http client ki Post method ka use karke profilePic ki API ko hit kiya h along with formdata
→ request gayi userCtl ki uploadPic method par
→ uha par @PathVariable se userId get kari
→ & @requestParam se file ko get karke MultipartFile ke object me hold karaya.
→ then hume attachmentService ki save method ka use karke image ko add kiya h & userservice ki update method ka use karke imageId ko update kiya h.

Q. Humne JWT kese configure kiya h?
→ humne 4 classes banayi h.-
1. JWT Request Filter
2. JWT Util
3. web security Config
4. JWT User Details Service

application.properties me 2 properties define kari hai.
jwt.secret = RAYS
jwt.expiration = 3600000

- hum login karenge to DTO agar not null h authenticat^n k bad to humne jwtUtil.generateToken(dto.getId(), dto.getLogin(), dto.getRoleName()); kara h
- return me hume ko string type ka token mila
- res.addResult("token", token);

Q26 token validation ke liye kya kiah?

-> JWT RequestFilter class banayih
-> Usko OncePerRequestFilter se extend karaya h.
-> uski doFilterInternal() method ko override kiya h.
-> request.getHeader se authorization ko get kiya h.
-> usko humne authorizationHeader me hold karaya h.
-> condition lagayi h agar authorisation header not null ho & starts with Bearer ho to hum substring(7) method ka use karke aage ke 7 letters ko remove kar diya h
-> return me humko token mil gaya h.
-> Jwt Util ~~method~~ ki validate method ka use karke token ko validate karaya h
-> agar validate ho gya to code aage bad jaega.
-> agar validate nhi hua to humne exception raise kari h
-> humne auth service banayi h & exception ko catch kiya h
-> login comp. par navigate by url se bhej diya h & sath me queryparam me msg bhej diya h
-> msg ko get karke form.message me set karaya h & interpolation se print karaya h.

Q.27 signUp & login par token check hoga ki nahi?

-> nhi hoga
kyNki humne WebSecurity Config me antMatchers me "/Auth/**", "/User/profilePic/**" pass kara h.
inpar token verify nhi hoga.

Q.3. Annotation used in stret

-> @Sprin...

Q. Token kha kha par check hoga?

-> everywhere except "/Auth/**", "/User/ProfilePic/**"

Q. Har request par JWTRequestFilter kyu call hoga?

-> kyunki humne WebSecurity config me addFilterBefore me jwtRequestFilter pass kar rakha h.

-> Spring security ka filter apply hone se phle jwtrequestfilter apply hoga.

Q. JWT ke liye angular me kya kia h?

-> auth service banayi h jo ki interceptor h

-> ye local storage se token ko get karti h

-> agar token exist karta h humne request ki cloning kari h. clone() method se.

-> setHeaders me authorization me token pass kiya h.

Q. Internationalisation ke liye kya kia h?

-> sabse phle humne 2 module ko install kiye h

"@ngx-translate/core":
@ngx-translate/http-loader

-> app.module.ts me function banaya h httploaderfactory

-> ye humko Translate HTTPLoader ka object return karta h

-> humne imports me Translate module ko import kiya h

-> & loader me

provider: TranslateLoader
useFactory: HTTPLoaderFactory
deps: [HttpClient]

-> Uske baad me humne 2 files banayi h assets me en.json & hi.json

-> navbar.comp.html par humne dropdown banayi h select & option tag ka use kare

-> change event par humne changeLocale() function ko call kiya h

-> changeLocale() function me humne translate.use me locale pass kiya h

-> then humne translate pipe ka use kiya h.