

EXTENDED DEMOGRAPHY AMXEDITOR – PLUGIN

EXTENDED DEMOGRAPHY	1
1. Introduction.....	2
2. AD_Reference Table.....	4
3. New Messages on AD_Message Table.	6
4. Fields Added on C_Country Table.	7
5. Capture Sequence on Table C_Country.	8
6. New Table C_Community	9
7. New Tables C_Municipality and C_Parish	11
8. Fields Added on C_Region Table.	14
9. Fields Added on C_Location.	16
10. Country-Community-Region-Municipality-Parish Window.....	17
11. Business Partner Location Extended Example.	19
A1. Plugin Installation.....	21

Author : Luis Amesty Linares
Madrid, Spain August 2015
Revision December 2019
luisamesty@gmail.com



1. Introduction.

This Plugin is related to Demographic Aspects on Idempiere ERP. It is well known that on some countries there is a political division with concepts that go beyond country, region and city.

For example, in Spain we talk about Communities, they are related to Group of Provinces that keeps Local Government. They also have a political division for Provinces called Municipalities (Municipality-*Municipio*).

Another example is Venezuela, they have a political division for Provinces (*Estados*) called Municipalities (Municipality-*Municipio*) and a Municipality is also divided on Parishes (Parish-*Parroquia*). Particularity Main Mail office in Venezuela has published a new rule indicating the way postal address is to be written:

La dirección postal ahora se escribe así:	
NOMBRE Y APELLIDO	
DEPARTAMENTO / CARGO	Quando la correspondencia va dirigida a una empresa colocar nombre de la unidad administrativa (gerencia, división, departamento, sección) o a cargo de la persona a quien va dirigido el envío.
LOCALIDAD	Sector, Avenida, calle, carrera, vereda, aldea, barrio, callejón, pasaje, asentamiento, caserio, terraza, urbanización, escalera, esquina, ciudadelita, hacienda, parque residencial, residencias, entre otros.
INMUEBLE	Nombre o número, edificio, bloque, casa, quinta, piso, torre, apartamento, oficina, local, consultorio, entre otros.
PARROQUIA	
MUNICIPIO	
CIUDAD O PUEBLO	
ESTADO	
PAÍS	Si la correspondencia es internacional.
ZONA POSTAL	Vigente en Venezuela.

Communities, Region, Municipality and Parish, can be use for statistic and BI analysis on Sales, Cost, Personnel and other type of transaction results.

Postal Codes is another concern to be covered in future on this plugin, because a default value can be obtained from Region, Provinces, Municipality and Parish. Also Street Names provides a rule for finding zip codes.

In order to accomplish what have been explained before, some tables have to be modified, and some others tables have to be added to implement the new Window and plugin.

Tables	
Modify	Add
<i>C_Country</i> (2)	<i>C_Municipality</i>
<i>AD_Message</i> (1)	<i>C_Parish</i>
<i>C_Location</i> (2)	<i>C_Zipcode</i>
<i>C_Region</i> (2)	<i>C_Community</i>
<i>AD_Reference</i> (1)	

(1) Add New Records (2) Add New Fields

I have been working with Idempiere since version 1.0c, before I made some test on Adempiere 3.70. I have migrated my old Visual FoxPro application with one of my customers using Idempiere 2.1 in VENEZUELA.

A list of Lectures and References related with this Material. Some information, procedures, code and data taken from:

Wiki Page: **Developing plug-ins without affecting the trunk**

http://wiki.idempiere.org/en/Developing_plug-ins_without_affecting_the_trunk

Jan Thielemann Videos in special:

Developing iDempiere 2.0 - Custom Editors (IEditorFactory and IDisplayTypeFactory)

<https://www.youtube.com/watch?v=jVhKnFzsMZo>

DCS-ERP Repository from Orlando Curieles.

https://bitbucket.org/dcs_bitbucket/

Initial Venezuelan Demography.

Redhuan Daniel Oon (red1) Repository.

<https://bitbucket.org/red1/>

Ghintech Location.

<https://bitbucket.org/ghintech/com.ghintech.location>

Carlos Ruiz (CarlosRuiz_globalqss)

https://bitbucket.org/CarlosRuiz_globalqss/

Plugin Source code, documentation and jar files are located on github.com repository:

<https://github.com/luisamesty/Amerpsoft-iDempiere-community>

You may clone it with git:

\$ git clone <https://github.com/luisamesty/Amerpsoft-iDempiere-community>

I really appreciate all material, readings and information provided by forum, wiki pages and repositories. This was my first little contribution to the group and I hope it will be useful to you.

2. AD_Reference Table.

AD_Reference Table, it is an Application Dictionary's Table that contains all Small List arrays associated with fields, where it is necessary to select from Short Length Selection List. It is used instead of a Table. Normally Tables are used when Selection contains Large List Counts of records.

When defining Tables on Application Dictionary, *AD_Reference* table is used for selection of Field Type on Table's Columns. For example, we can see records among others:

Name	Description
....
Image	Binary Image Data
Integer	10 Digit numeric
List	Reference List
Location (Address)	Location/Address
<u>LocationExtended</u>	<u>Location Extended /Address with Parish and Municipality</u>

Location Reference Type is related with Address Fields, normally associated with *C_Location* table records thru *C_Location_ID* field. This reference selects the type of editor associated with the Table's Field on AD Model. For example:

Integer: is associated with a plain integer number editor.

Date: is associated with a Date Format (MM/DD/YYYY) editor.

Location: is associated with Address Location Field (see Figure 2.1)

Figure 2.1

LocationExtended Is the name of the new reference to be added to Application Dictionary in order to run Plugin. It must be defined exactly with this name, because plugin code will find on *AD_Reference* table as it.


When Plugin be completed and running, it can be associated to the *C_Location_ID* field on *C_BPartnerLocation* Table to a *LocationExtended* reference, the address form will be presented as figure 2.2:

The screenshot displays a form titled 'Address*' with various input fields. On the left side, there are labels for 'Phone', 'Fax', 'Sales Region', and 'Customer Address ID'. The main form area contains the following fields: 'Country' (set to 'Venezuela'), 'Region/State' (set to 'Zulia'), 'City' (set to 'Maracaibo'), 'Municipality of Re', 'Parish', 'Address 1' (containing 'Av 3F Calle 75'), 'Address 2', 'Address 3', 'Address 4', and 'ZIP'. A red arrow points from the text 'New Fields' to the 'Parish' field. At the bottom right of the form, there is a 'Map' button and two icons: a green checkmark and a red X.

Figure 2.2

3. New Messages on AD_Message Table.

New Messages translations are required to be presented on Plugin Forms. Add new messages Community, Municipality, Parish and Zipcode, and their respective translation to your Localization Language. It must be done using AD window Message: (See examples)



Entity Type: AMERP Localiza... x

Message

Data requested

Client* System Organization* *

Search Key Municipality

☒ Active

Entity Type* AMERP Localization

Message Type* Information

Message Text* Municipality


Message Tip

Translation

2 Records

	Message	Language	Active	Translated	Message Text
<input type="checkbox"/>	Municipality	Spanish (Colombia)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Municipio
<input type="checkbox"/>	Municipality	Spanish (Venezuela)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Municipio

Figure 3.1



Entity Type: AMERP Localiza... x

Message

Data requested

Client* System Organization* *

Search Key Parish

☒ Active

Entity Type* AMERP Localization

Message Type* Information

Message Text* Parish

Message Tip

Translation

2 Records

	Message	Language	Active	Translated	Message Text
<input type="checkbox"/>	Parish	Spanish (Colombia)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Parroquia
<input type="checkbox"/>	Parish	Spanish (Venezuela)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Parroquia

Figure 3.2

4. Fields Added on C_Country Table.

C_Country table contains Records for Countries. Some fields have been added to this table, and they have to be done using Application Dictionary. The fields added are:

System Element	DB Column Name	Description
CountryCode3 (*)	CountryCode3	Country Code 3 Digits Standard
HasCommunity	HasCommunity	Country is divided in Communities Y-N
HasMunicipality	HasMunicipality	Country Regions are divided in Municipalities Y-N
HasParish	HasParish	Country Regions are divided in Municipalities and Parish Y-N

In some Countries the appropriate translation for Region differs, for example:

Colombia: *Departamento*.

Venezuela: *Estado*.

USA: *Estado*.

España: *Provincia*.

Take note for this, when create Field Elements and their translation:

(*) For CountryCode3 inclusion, see Script 'amxeditor.sql', included on Sources.

5. Capture Sequence on Table C_Country.

Capture Sequence indicates the order on which Address Fields are presented to the user when creating or modifying address fields (Location or LocationExtended).

Tokens are surrounded by @ character.

For example:

@CO@ @R@ @C@ @A1@ @A2@ @A3@ @A4@ @P@

Available Tokens:

CO: Country

R: Region

C: City

A1, A2, A3, A4: Four Address Lines.

P: Postal Code

Added Tokens to Plugin:

MU: Municipality

PA: Parish

Idempiere Administrator could change this Value in order to modify the Form's Field Sequence on Window's Address Fields.

Recommended sequence:

@CO@ @A1@ @A2@ @A3@ @A4@ @P@ @R@ @C@ @MU@ @PA@

Mandatory Fields can be identified by the symbol '!'.
For example:

@CO@ @A1!@ @A2!@ @A3@ @A4@ @P@ @R!@ @C!@ @MU@ @PA@

Address 1, Address 2, Region, City are Mandatory Fields.

6. New Table C_Community

C_Community Table contains the Community Political Territorial Division of the Country. As it will be used for Key reference on *C_Region* table, at least one record for each Country must be created. A SQL file is provided (See amxeditor.sql).

Create Table using PostgreSQL pgAdmin3 app, with this Script:

```
/* CREATE TABLE c_community (COUNTRY'S COMMUNITIES ) */
CREATE TABLE "adempiere"."c_community" (
  "c_community_id" NUMERIC(10,0) NOT NULL,
  "ad_client_id" NUMERIC(10,0) NOT NULL,
  "ad_org_id" NUMERIC(10,0) NOT NULL,
  "isactive" CHAR(1) DEFAULT 'Y'::bpchar NOT NULL,
  "created" TIMESTAMP WITHOUT TIME ZONE DEFAULT now() NOT NULL,
  "createdby" NUMERIC(10,0) NOT NULL,
  "updated" TIMESTAMP WITHOUT TIME ZONE DEFAULT now() NOT NULL,
  "updatedby" NUMERIC(10,0) NOT NULL,
  "name" VARCHAR(60) NOT NULL,
  "description" VARCHAR(255),
  "c_country_id" NUMERIC(10,0) NOT NULL,
  "isdefault" CHAR(1) DEFAULT 'N'::bpchar,
  CONSTRAINT "c_community_pkey" PRIMARY KEY("c_community_id"),
  CONSTRAINT "c_community_isactive_check" CHECK (isactive = ANY (ARRAY['Y'::bpchar, 'N'::bpchar])),
  CONSTRAINT "c_community_isdefault_check" CHECK (isdefault = ANY (ARRAY['Y'::bpchar, 'N'::bpchar])),
  CONSTRAINT "c_communityclient" FOREIGN KEY ("ad_client_id")
    REFERENCES "adempiere"."ad_client"("ad_client_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "c_communityorg" FOREIGN KEY ("ad_org_id")
    REFERENCES "adempiere"."ad_org"("ad_org_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "ccountry_cregion" FOREIGN KEY ("c_country_id")
    REFERENCES "adempiere"."c_country"("c_country_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED
) WITHOUT OIDS;
```

See Application Dictionary Window for Table C_Community:



Table > Column▼

<input type="checkbox"/>	Table	DB Column Name	Reference	Reference Key	Length	Mandatory	Updatable
<input type="checkbox"/>	C_Community_Community	AD_Client_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	AD_Org_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	C_Community_ID	ID		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	C_Community_UU	String		36	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	C_Country_ID	Table	C_Country	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	Created	Date+Time		29	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	CreatedBy	Table	AD_User	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	Description	String		255	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	IsActive	Yes-No		1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	IsDefault	Yes-No		1	<input type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	Name	String		60	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	Updated	Date+Time		29	<input checked="" type="checkbox"/>	<input type="checkbox"/>
<input type="checkbox"/>	C_Community_Community	UpdatedBy	Table	AD_User	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>

See Script 'amxeditor.sql', included on Sources.

7. New Tables C_Municipality and C_Parish

Some countries divide Region on Municipality entities.
This is the Script for create the table.

```

--- C_Municipality TABLE (c_municipality)
CREATE TABLE "adempiere"."c_municipality" (
  "c_municipality_id" NUMERIC(10,0) NOT NULL,
  "ad_client_id" NUMERIC(10,0) NOT NULL,
  "ad_org_id" NUMERIC(10,0) NOT NULL,
  "isactive" CHAR(1) DEFAULT 'Y'::bpchar NOT NULL,
  "created" TIMESTAMP WITHOUT TIME ZONE DEFAULT now() NOT NULL,
  "createdby" NUMERIC(10,0) NOT NULL,
  "updated" TIMESTAMP WITHOUT TIME ZONE DEFAULT now() NOT NULL,
  "updatedby" NUMERIC(10,0) NOT NULL,
  "name" VARCHAR(60) NOT NULL,
  "capital" VARCHAR(60) NOT NULL,
  "c_country_id" NUMERIC(10,0),
  "c_region_id" NUMERIC(10,0),
  "isdefault" CHAR(1) DEFAULT 'Y'::bpchar,
  CONSTRAINT "c_municipality_pkey" PRIMARY KEY("c_municipality_id"),
  CONSTRAINT "c_municipality_isactive_check" CHECK (isactive = ANY (ARRAY['Y'::bpchar, 'N'::bpchar])),
  CONSTRAINT "c_municipalityclient" FOREIGN KEY ("ad_client_id")
    REFERENCES "adempiere"."ad_client"("ad_client_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "c_municipalityorg" FOREIGN KEY ("ad_org_id")
    REFERENCES "adempiere"."ad_org"("ad_org_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "ccountry_cmunicipality" FOREIGN KEY ("c_country_id")
    REFERENCES "adempiere"."c_country"("c_country_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "cregion_cmunicipality" FOREIGN KEY ("c_region_id")
    REFERENCES "adempiere"."c_region"("c_region_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED
) WITHOUT OIDS;

```

Note:
PRIMARY KEY for C_Municipality Table is c_municipality_id.

Some countries also, divide Municipality on Parish entities.

This is the Script for create the table.



```

CREATE TABLE "adempiere"."c_parish" (
  "c_parish_id" NUMERIC(10,0) NOT NULL,
  "ad_client_id" NUMERIC(10,0) NOT NULL,
  "ad_org_id" NUMERIC(10,0) NOT NULL,
  "isactive" CHAR(1) DEFAULT 'Y'::bpchar NOT NULL,
  "created" TIMESTAMP WITHOUT TIME ZONE DEFAULT now() NOT NULL,
  "createdby" NUMERIC(10,0) NOT NULL,
  "updated" TIMESTAMP WITHOUT TIME ZONE DEFAULT now() NOT NULL,
  "updatedby" NUMERIC(10,0) NOT NULL,
  "name" VARCHAR(60) NOT NULL,
  "c_country_id" NUMERIC(10,0) NOT NULL,
  "c_region_id" NUMERIC(10,0) NOT NULL,
  "c_municipality_id" NUMERIC(10,0) NOT NULL,
  "isdefault" CHAR(1) DEFAULT 'N'::bpchar,
  CONSTRAINT "c_parish_pkey" PRIMARY KEY("c_parish_id"),
  CONSTRAINT "c_parish_isactive_check" CHECK (isactive = ANY (ARRAY['Y'::bpchar, 'N'::bpchar])),
  CONSTRAINT "c_parishclient" FOREIGN KEY ("ad_client_id")
    REFERENCES "adempiere"."ad_client"("ad_client_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "c_parishorg" FOREIGN KEY ("ad_org_id")
    REFERENCES "adempiere"."ad_org"("ad_org_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "ccountry_cparish" FOREIGN KEY ("c_country_id")
    REFERENCES "adempiere"."c_country"("c_country_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "cmunicipality_cparish" FOREIGN KEY ("c_municipality_id")
    REFERENCES "adempiere"."c_municipality"("c_municipality_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED,
  CONSTRAINT "cregion_cparish" FOREIGN KEY ("c_region_id")
    REFERENCES "adempiere"."c_region"("c_region_id")
    ON DELETE NO ACTION
    ON UPDATE NO ACTION
    DEFERRABLE
    INITIALLY DEFERRED
) WITHOUT OIDS;

```

Note:


PRIMARY KEY for C_Parish Table is c_parish_id.



Finally take care of Adequate Name and Description on AD using Upper and Lower Cases on AD Tables.


C_Municipality Table looks like this on AD:

[Table](#) > [Column](#)▼

<input type="checkbox"/>	Table	DB Column Name	Reference	Reference Key	Length	Mandatory	Updatable	
<input checked="" type="checkbox"/>	 C_Municipality_C_Municipality	AD_Client_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	AD_Org_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	C_Country_ID	Table	C_Country	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	C_Municipality_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	C_Municipality_UU	String		36	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	C_Region_ID	Table	C_Region	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	Created	Date+Time		29	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	CreatedBy	Table	AD_User	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	IsActive	Yes-No		1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	IsDefault	Yes-No		1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	Name	String		60	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	Updated	Date+Time		29	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	UpdatedBy	Table	AD_User	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Municipality_C_Municipality	capital	String		60	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	

C_Parish Table looks like this on AD:

[Table](#) > [Column](#)▼

<input type="checkbox"/>	Table	DB Column Name	Reference	Reference Key	Length	Mandatory	Updatable	S
<input checked="" type="checkbox"/>	 C_Parish_C_Parish	AD_Client_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	AD_Org_ID	Table Direct		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	C_Country_ID	Table	C_Country	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	C_Municipality_ID	Table		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	C_Parish_ID	ID		10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	C_Parish_UU	String		36	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	C_Region_ID	Table	C_Region	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	Created	Date+Time		29	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	CreatedBy	Table	AD_User	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	IsActive	Yes-No		1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	IsDefault	Yes-No		1	<input type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	Name	String		60	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	Updated	Date+Time		29	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
<input type="checkbox"/>	C_Parish_C_Parish	UpdatedBy	Table	AD_User	10	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

8. Fields Added on C_Region Table.

The table *C_Region* is the second level on demographic structure. On this new proposal *C_Community* is the New second level, nevertheless in order to be compatible with Standard Address structure on Idempiere, Community and Region are both Second Level, but on *C_Region* table a Community ID has to be indicated if Idempiere Administrator desire to use it.

See Figure 8.1 For the New Demographic Structure of Plugin:





Figure 8.1
(*) Future Development

A new Field (*C_Community_ID*) is added to *C_Region* Table. This Field Accept Null values, because some country may not use this feature. See Figure 8.2.

Figure 8.2

A new Validation Rule is created in order to accept only Communities from selected Country.
See figure 8.3.



The screenshot shows the 'Validation' configuration window in the AMERP application. The window has a green title bar with various icons. The main area is white and contains the following fields:

- Client***: System
- Organization***: *
- Name***: C_Community of Country
- Description**: (empty)
- Active**: ☒
- Entity Type***: AMERP Localization
- Type***: SQL
- Validation code**: C_Community.C_Country_ID=@C_Country_ID@

Figure 8.3

9. Fields Added on C_Location.

C_Location Table contains the all addresses included on Business Partners, Employees, Warehouses, Organization Info, and any other table containing **Location** or **LocationExtended** Reference Fields.

New fields added are *C_Municipality_ID* and *C_Parish_ID*, both have been mentioned before. See Figures 9.1 and 9.2 for AD window on Table *C_Location*.

The screenshot shows the 'Table > Column' configuration window for the *C_Location* table. The 'System Element' is set to *C_Municipality_ID*. The 'DB Column Name' is *C_Municipality_ID*, and the 'Name' is *C_Municipality*. The 'Reference' is set to 'Table' with 'Reference Key' as *C_Municipality_ID* and 'Constraint Name' as *c_municipality_location*. The 'Constraint Type' is 'No Action'. The 'Length' is 10. The 'Active' checkbox is checked. The 'Version' is 0.00. The 'Always Updatable' checkbox is checked. The 'Synchronize Column' button is visible.

Figure 9.1.

The screenshot shows the 'Table > Column' configuration window for the *C_Location* table. The 'System Element' is set to *C_Parish_ID*. The 'DB Column Name' is *C_Parish_ID*, and the 'Name' is *C_Parish*. The 'Reference' is set to 'Table' with 'Reference Key' as *C_Parish_ID* and 'Constraint Name' as *c_parish_location*. The 'Constraint Type' is 'Do Not Create'. The 'Length' is 10. The 'Active' checkbox is checked. The 'Version' is 0.00. The 'Always Updatable' checkbox is checked. The 'Synchronize Column' button is visible.

Figure 9.2

Both Fields may contain Null values in order to be compatible with Idempiere Address Standard.

Field *C_City_ID* may contain Null Value, because some Country can be configured with 'Allow Cities out of List' feature. A City String Field is Provided for Storing values when this happens.

10. Country-Community-Region-Municipality-Parish Window.

Finally a New Window is created to perform extended address and Demographic Structure for the Countries. It has tried to develop the window so that it can be used as Standard Country-Region-City one. But also the Idempiere Administrator can perform the construction of new Communities, Municipalities and Parishes.

It is shown below the main Window, and will explain some fields that has to be set for Country in order to perform adequate update of actual Demographic Structure.

The screenshot displays the 'Country' configuration window in the Idempiere Administrator. The 'Client' is set to 'System' and 'Organization' is marked with an asterisk. The 'Name' field contains 'United States' and the 'Description' is 'United States of America'. The 'ISO Country Code' is 'US' and 'Country Code 3' is empty. The 'Region' is set to 'State'. A red arrow points to a group of four checked checkboxes: 'Country has Region', 'Country has Community', 'Regions has Municipality', and 'Municipality has Parish', which are collectively labeled 'New Checks'. Other fields include 'Address Print Format' (@C@, @R@ @P@), 'Capture Sequence' (@A1@ @A2@ @A3@ @A4@ @C@, @R@ @P@ @CO@), 'Phone Format' ((000) 000-0000), 'Postal Code Format' (empty), 'Additional Postal Format' (empty), 'Currency' (USD), 'Language' (English (USA)), 'Bank Account No Format' (empty), 'Bank Routing No Format' (empty), 'Local Address Format' (empty), 'Reverse Local Address Lines' (unchecked), and 'Use Postcode Lookup' (unchecked). The bottom of the window shows a tabbed interface with 'Community' selected, and a status bar indicating '0 Records'.

Figure 10.1

New Fields Added:

- Country has Region
- Country has Community
- Regions has Municipality
- Municipality has Parish

Idempiere Administrator may perform Community input through database, but just in case it is necessary to include the new Country's Communities using the Window, the '*Country has Community*' check has to be set in order to have Community Tab available and then include Communities.

After completing income communities, regions have to be associated with their respective communities. In order to do this job, Idempiere Administrator has to deselect '*Country has Community*' check in order to have Standard Region Tab available. Having this Region Tab Visible, Regions can be updated in order to set Community associated with them. See Figure 10.2 and 10.3.

Country

Data required

Client* System Organization* *

Name* United States

Description* United States of America

ISO Country Code* US Country Code 3 Region State

Has Community Check Deselected

☒ Country has Region

☐ Country has Community

☒ Allow Cities out of List

Address Print Format* @C@, @R@ @P@

Capture Sequence* @A1@ @A2@ @A3@ @A4@ @C@, @R@ @P@ @CO@

Phone Format* (000) 000-0000

Postal Code Format

Additional Postal Format

Currency* USD

Language* English (USA)

☐ Reverse Local Address Lines

☐ Use Postcode Lookup

Region Tab

Region City Region Translation City Region Translation Country Translation

51 Records

Client	Country	Name	Description	Active	Default	Community
System	United States	CT	Connecticut	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Community Unit
System	United States	CA	California	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	MA	Massachusetts	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	ME	Maine	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	NH	New Hampshire	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	RI	Rhode Island	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	NY	New York	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	NJ	New Jersey	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	PA	Pennsylvania	<input checked="" type="checkbox"/>	<input type="checkbox"/>	
System	United States	VA	Virginia	<input checked="" type="checkbox"/>	<input type="checkbox"/>	

Figure 10.2

Home Country Community Region Mu...

Country > Region

Client* System Organization* *

Country* United States

Community

Name* Community United States

Description* Connecticut

☐ Default

☒ Active

Figure 10.3

Complete Community association for all Regions and then set again 'Country has Community' Check. Community Tab will be visible again and Idempiere Administrator can perform Extended Demography Structure.

Community -> Region -> (Municipality – City) → Parish

11. Business Partner Location Extended Example.

Once Plugin is installed as it is shown on A1 section, some AD modifications must be done before changes been observed. One example is Business Partner Address, on Business Partner Location Tab.

Get into Idempiere as System Administrator and locate Business Partner Location Table: *C_BParter_Location*.




Figure 11.1

Modify *C_location_ID* Field, and set Reference as LocationExtended, as it was explained on Chapter 2.




Figure 11.2

Now, you may test plugin. Get into Idempiere as SuperUser and Garden World; go to Business Partner Windows, and Location Tab. Modify Country to which was selected on Chapter 5, like Venezuela. For this example Capture Sequence was set as:

@CO@ @A1@ @A2@ @A3@ @A4@ @P@ @R@ @C@ @MU@ @PA@

Figure 11.3 shows changes observed on




Figure 11.3

A1. Plugin Installation.

You must follow indicated procedure as idempiere versión.

For Version 7.1 and up

Follow these steps:

1. Pack-In AMERPSOFT Editor – Step 1.zip
2. Pack-In AMERPSOFT Editor – Step 2.zip
3. Pack-In AMERPSOFT Editor – Step 3.zip
4. Set es_VE as System language
5. Create Language extension for es_VE or xx_XX
6. Add country code 3 digits
7. Pack IN Venezuela Extended Demography
8. Install Plugin using Apache Felix Web Console
9. Restart Server
10. Modify C_BPartner_Location Table
11. Modify Country Record

For Version 6.2

Follow these steps:

12. Pack-In AMERPSOFT Editor 6.2 – Step 1.zip
13. Pack-In AMERPSOFT Editor 6.2 – Step 2.zip
14. Pack-In AMERPSOFT Editor 6.2 – Step 3.zip
15. Set es_VE as System language
16. Create Language extension for es_VE or xx_XX
17. Add country code 3 digits
18. Pack IN Venezuela Extended Demography
19. Install Plugin using Apache Felix Web Console
20. Restart Server
21. Modify C_BPartner_Location Table
22. Modify Country Record

For Version 2.1 to 5.1:

Follow these steps:

23. Pack-In AMERP amxeditor.zip
24. Set es_VE as System language
25. Create Language extension for es_VE or xx_XX
26. Add country code 3 digits
27. Pack IN Venezuela Extended Demography
28. Install Plugin using Apache Felix Web Console
29. Restart Server
30. Modify C_BPartner_Location Table
31. Modify Country Record

1. Pack IN AMERPSOFT Editor – Step (1-2-3).zip

Download:

AMERPSOFT Editor – Step 1.zip


AMERPSOFT Editor – Step 2.zip

AMERPSOFT Editor – Step 3.zip

from repository:

<https://github.com/luisamesty/Amerpsoft-iDempiere-community/tree/master/org.amerpsoft.com.idempiere.editors-com/install>

Create Pack In record and Attach: ‘AMERPSOFT Editor – Step 1.zip’



The screenshot shows a web application window titled 'Pack In: AMERPSOFT Editor - ...'. The interface includes a toolbar with various icons for navigation and editing. The main form area is titled 'PackIn' and contains the following fields:

- Client***: A dropdown menu with 'System' selected.
- Organization***: A dropdown menu with a single asterisk (*) selected.
- Name***: A text input field containing 'AMERPSOFT Editor - Step 1'.
- Created**: Two input fields showing '12/15/2019' and '12:05:43 PM'.
- Date Processed**: Two input fields showing '12/15/2019' and '12:06:33 PM'.
- Process Message**: A text area containing 'Processed=110 Un-Resolved=0'.
- PackIn**: A button at the bottom of the form.

Pack In ‘*AMERPSOFT Editor – Step 1.zip*’

Repeat Steps for:

AMERPSOFT Editor – Step 2.zip

AMERPSOFT Editor – Step 3.zip

2. Set es_VE as System language

Login idempiere as System in English

Go to Menu: /System Admin/General Rules/System Rules/Language

On Window Language: Locate es_VE or your preferred Language xx_XX

Language es_VE

On Window Language: Check System Language


On Window Language: Execute 'Language Maintenance' Process

3. Create Language extension for es_VE or xx_XX

Download '**Create_language_from_es_CO_to_es_VE.sql**' Script from Repository
<https://github.com/luisamesty/Amerpsoft-iDempiere-community/tree/master/org.amerpsoft.com.idempiere.editors-com/documentation>

Execute Query from PostgreSQL environment

You may edit this Query for your favourite Language xx_XX




4. Add country code 3 digits

(This is already done by plugin Install on AMERP SOFT Editor – Step 2.zip Pack In)

Download Script '**Create_Country_codes_3_digit.sql**' from Repository
 Execute Query from PostgreSQL environment



This Fill CountryCode3 Fields on **C_Country** Table



```


747
748 INSERT INTO "adempiere"."c_country2" ("countrycode", "countrycode3", "countryid", "name", "detalle1",
749 VALUES ('ZA', 'ZAF', '710', 'Sudáfrica', '', '', 0);
750
751 INSERT INTO "adempiere"."c_country2" ("countrycode", "countrycode3", "countryid", "name", "detalle1",
752 VALUES ('ZM', 'ZMB', '894', 'Zambia', '', '', 0);
753
754 INSERT INTO "adempiere"."c_country2" ("countrycode", "countrycode3", "countryid", "name", "detalle1",
755 VALUES ('ZW', 'ZWE', '716', 'Zimbabue', '', '', 0);
756
757 /* Reemplaza el codigo de tres digitos en la tabla c_country */
758 update adempiere.c_country
759 set countrycode3=(
760 select adempiere.c_country2.countrycode3
761 from adempiere.c_country2
762 where adempiere.c_country.countrycode=adempiere.c_country2.countrycode );
763 /* Venezuela (339) hasRegion='Y' */
764 update adempiere.c_country set hasregion = 'Y' where c_country_id= 339;
765
766 /* Elimina la tabla c_country2 */
767 DROP TABLE "adempiere"."c_country2" ;
  
```

5. Pack IN Venezuela Extended Demography

Download '**AMERPSOFT Demografia Venezolana.zip**' from repository:

<https://github.com/luisamesty/Amerpsft-iDempiere-community/tree/master/org.amerpsft.com.idempiere.editors-com/install>

Create Pack In record and Attach: '**AMERPSOFT Demografia Venezolana.zip**'



Home | Pack In: AMERPSOFT Editor -... | Pack In: AMERPSOFT Demograf...

Pack In

Client: System Organization: *

Name: AMERPSOFT Demografia Venezolana


Created: 12/15/2019 12:38:34 PM

Date Processed: 12/15/2019 12:39:35 PM

Process Message: Processed=1861 Un-Resolved=0

Pack In

Pack In '**AMERPSOFT Demografia Venezolana.zip**'



Attach '*AMERPSOFT Demografia Venezolana.zip*' file


You may look at '*GeografiaVenezolanaCompleta.sql*'
And make your Country Extended Demography Pack In.

6. Install Plugin using Apache Felix Web Console


Download '*org.amerpsoft.com.idempiere.editors-com_7.1.0.201912142214.jar*'
from repository (Version should be different):

https://github.com/luisamesty/Amerpsoft-iDempiere-community/blob/master/org.amerpsoft.com.idempiere.p2.site/target/repository/plugins/org.amerpsoft.com.idempiere.editors-com_7.1.0.201912142214.jar

May be another version, check last one.



Verify plugin is updated and running.



7. Restart Server

You must restart Idempiere Server in order to accomplish the changes.

8. Modify C_BPartner_Location Table

Login idempiere as System in English

Go to Menu: /Application Dictionary/ Table and Column

On Window Table and Column: Locate C_BPartner_Location Table

On Tab Column: Locate C_Location_ID Field

Change Reference to '*LocationExtended*'

The screenshot shows the 'Table and Column: Partner Location' window. The 'System Element' field is set to 'C_Location_ID'. The 'Reference' dropdown menu is highlighted with a red box and set to 'LocationExtended'. Other fields include 'Client' (System), 'Table' (C_BPartner_Location_Partner Location), 'Entity Type' (Dictionary), 'Name' (Address), 'Description' (Location or Address), and 'Comment/Help' (The Location / Address field defines the location of an entity.).

9. Modify Country Record

Login idempiere as System in English

Go to Menu: /System Admin/General Rules/System Rules/Country Community ...

This is the new window for Country Maintenance added from plugin.

Check:

- Country has Community
- Country Regions has Municipality
- Country Municipality has Parish

Modify Capture Sequence as explained on Chapter 5:

@CO@ @A1!@ @A2@ @A3@ @A4@ @R!@ @MU@ @PA@ @C@, @P@

This sequence indicates plugin order on Field capture.

Country

Client: System Organization:

Name: Venezuela

Description: Venezuela

ISO Country Code: VE Country Code 3: VEN

☒ Country has Region Region:

☒ Country has Community ☒ Country Regions has Municipality ☒ Country Municipality has Parish

☒ Allow Cities out of List

Address Print Format: @C@, @P@

Capture Sequence: @CO@ @A1@ @A2@ @A3@ @A4@ @R1@ @MU@ @PA@ @C@, @P@

Phone Format:

Postal Code Format: Additional Postal code:

Capture Sequence