



# Case 1

00 Classes for Life Support Metrics



- Can you create a C++ class Metric that holds CPR metrics? here is an overview of common CPR metrics:



## Gemini came up with:

- Some pro's and con's

```
class Metric {
public:
    // Ventilation Metrics
    int ventilationVolume; // in mL (milliliters)
    int ventilationRate;   // breaths per minute
    int ventilationPauses; // duration in seconds


    // Compression Metrics
    double compressionFraction; // percentage of time spent on compressions
    int compressionDepth;       // in mm (millimeters)
    int compressionRate;        // compressions per minute
    double compressionDutyCycle; // percentage of compression cycle spent compressing

    // Other Metrics (Potentially)
    int ventilationCompressionRatio; // e.g., 30:2 for adults
    // You could add more as needed, like:
    // - Finger positioning details (if represented numerically)
    // - Chest recoil assessment (if quantifiable)
    // - Chest wall contact information (if quantifiable)

    // Constructor
    Metric() :
        ventilationVolume(0),
        ventilationRate(0),
        ventilationPauses(0),
        compressionFraction(0.0),
        compressionDepth(0),
        compressionRate(0),
        compressionDutyCycle(0.0),
        ventilationCompressionRatio(0) {}

    // You might add other constructors or methods
    // for setting/getting individual metrics,
    // calculating derived metrics, etc.
};
```

- Ok but I want a SOLID compatible version of course. Compressions, Ventilations should be children of Metric. A compression should have a "depth" in mm and a recoil also in mm.





# Gemini came up with:

- Some pro's and con's

```
#include <string>

class Metric { // Base class, could be abstract if you don't want to inherit
public:
    virtual std::string getType() const = 0; // To identify the type of metric
    // ... other common metric properties or methods if any
};

class Compressions : public Metric {
public:
    int depth; // in mm
    int recoil; // in mm (assuming you want to track recoil distance)
    // ... other compression-specific metrics (rate, fraction, etc.)

    std::string getType() const override {
        return "Compressions";
    }
};

class Ventilations : public Metric {
public:
    int volume; // in mL
    int rate;    // breaths per minute
    int pauses; // duration in seconds
    // ... other ventilation-specific metrics

    std::string getType() const override {
        return "Ventilations";
    }
};

// ... (Rest of your code, potentially using these classes)
```

- SOLID Compliance
  - SRP: Each class now has a more focused responsibility (base class for general concept, child classes for specific metrics).
  - OCP: If you need to add new metric types in the future (e.g., AirwayManagement), you can create a new child class without modifying existing ones.

# Case 2

## Sensor Library



# LLM (Gemini) cue

- Can you help writing an Arduino library for my vl6180x sensor in C++

# Gemini came up with:

- Some pro's and con's

```
#ifndef VL6180X_h
#define VL6180X_h

#include "Arduino.h"
#include <Wire.h> // Assuming I2C communication

class VL6180X {
public:
    VL6180X(uint8_t address = 0x29); // Default I2C address

    // Initialization and configuration
    bool begin();
    bool init();
    bool configureDefault();

    // Range measurement
    uint8_t readRangeSingle();
    uint8_t readRangeContinuous();

    // Additional functions for other sensor features
    // (e.g., ambient light, proximity, interrupt configuration, etc.)

private:
    uint8_t _address;
    TwoWire *_i2c;

    // Helper functions for reading/writing registers
    uint8_t readReg(uint16_t reg);
    void writeReg(uint16_t reg, uint8_t value);
    void writeReg16Bit(uint16_t reg, uint16_t value);
};

#endif
```

## Gemini came up with:

- Where did gemini get it's inspiration from?
- Which principle is again violated in the begin() method?

```
#include "VL6180X.h"
```

```
// Constructor
```

```
VL6180X::VL6180X(uint8_t address) {  
    _address = address;  
    _i2c = &Wire; // Using the default Wire instance  
}
```

```
// Initialization and configuration functions
```

```
bool VL6180X::begin() {  
    _i2c->begin();  
    // Check sensor ID or other initialization steps  
    return true; // Or false if initialization fails  
}
```

```
// (Add implementations for init(), configureDefault(), readRange(),  
// readRangeContinuous(), and other helper functions based on t
```

```
// Register read/write helper functions
```

```
uint8_t VL6180X::readReg(uint16_t reg) {  
    _i2c->beginTransaction(_address);  
    _i2c->write(reg >> 8); // MSB  
    _i2c->write(reg & 0xFF); // LSB  
    _i2c->endTransmission();  
  
    _i2c->requestFrom(_address, (uint8_t)1);  
    return _i2c->read();  
}
```

```
// ... (Implement writeReg, writeReg16Bit similarly)
```

# LLM (Gemini) cue

- It would be better to do `_i2c->begin()`; of course as it is not really the responsibility of VL6180X to do this.

**Gemini came up with:**

```
#include "VL6180X.h"

// Constructor
VL6180X::VL6180X(uint8_t address) {
    _address = address;
    _i2c = &Wire; // Using the default Wire instance
}

// Initialization and configuration functions
bool VL6180X::begin() {
    // _i2c->begin(); // Removed

    // Check sensor ID or other initialization steps
    return true; // Or false if initialization fails
}

// (Add implementations for init(), configureDefault(), readRangeContinuous(), and other helper functions based on the VL6180X datasheet)

// Register read/write helper functions
uint8_t VL6180X::readReg(uint16_t reg) {
    _i2c->beginTransaction(_address);
    _i2c->write(reg >> 8); // MSB
    _i2c->write(reg & 0xFF); // LSB
    _i2c->endTransmission();

    _i2c->requestFrom(_address, (uint8_t)1);
    return _i2c->read();
}
```

# LLM (Gemini) cue

- ok great can you give me the entire implementation including the register calls?
- can you also implement readReg, writeReg, writeReg16Bit



## Gemini came up with:

```
#include "VL6180X.h"
```

```
// ... (Rest of the code remains the same)
```

```
// Register read/write helper functions
```

```
uint8_t VL6180X::readReg(uint16_t reg) {  
    _i2c->beginTransaction(_address);  
    _i2c->write(reg >> 8); // MSB  
    _i2c->write(reg & 0xFF); // LSB  
    _i2c->endTransmission();  
  
    _i2c->requestFrom(_address, (uint8_t)1);  
    return _i2c->read();  
}
```

```
void VL6180X::writeReg(uint16_t reg, uint8_t value) {  
    _i2c->beginTransaction(_address);  
    _i2c->write(reg >> 8); // MSB  
    _i2c->write(reg & 0xFF); // LSB  
    _i2c->write(value);  
    _i2c->endTransmission();  
}
```

```
void VL6180X::writeReg16Bit(uint16_t reg, uint16_t value) {  
    _i2c->beginTransaction(_address);  
    _i2c->write(reg >> 8); // MSB  
    _i2c->write(reg & 0xFF); // LSB  
    _i2c->write(value >> 8); // MSB of value  
    _i2c->write(value & 0xFF); // LSB of value  
    _i2c->endTransmission();  
}
```



# LLM (Gemini) cue

## (Refactoring)

- Ok great, can you also improve it using good programming principles while keeping in mind that it is an embedded project so balance it between SOLID and efficiency.

## Gemini came up with:

- (That saves us a lot of trouble...)

```
bool VL6180X::init() {
    // Mandatory register settings (refer to datasheet for details)
    writeRegister(0x0207, 0x01);
    writeRegister(0x0208, 0x01);
    writeRegister(0x0096, 0x00);
    writeRegister(0x0097, 0xfd);
    writeRegister(0x00e3, 0x00);
    writeRegister(0x00e4, 0x04);
    writeRegister(0x00e5, 0x02);
    writeRegister(0x00e6, 0x01);
    writeRegister(0x00e7, 0x03);
    writeRegister(0x00f5, 0x02);
    writeRegister(0x00d9, 0x05);
    writeRegister(0x00db, 0xce);
    writeRegister(0x00dc, 0x03);
    writeRegister(0x00dd, 0xf8);
    writeRegister(0x009f, 0x00);
    writeRegister(0x00a3, 0x3c);
    writeRegister(0x00b7, 0x00);
    writeRegister(0x00bb, 0x3c);
    writeRegister(0x00b2, 0x09);
    writeRegister(0x00ca, 0x09);
    writeRegister(0x0198, 0x01);
    writeRegister(0x01b0, 0x17);
    writeRegister(0x01ad, 0x00);
    writeRegister(0x00ff, 0x05);
    writeRegister(0x0100, 0x05);
    writeRegister(0x0199, 0x05);
    writeRegister(0x01a6, 0x1b);
    writeRegister(0x01ac, 0x3e);
    writeRegister(0x01a7, 0x1f);
    writeRegister(0x0030, 0x00);

    return true;
}
```

Gemini came up with:

```
#ifndef VL6180X_h
#define VL6180X_h

#include "Arduino.h"
#include <Wire.h>

class VL6180X {
public:
    // Constructor with optional I2C address and Wire instance
    VL6180X(uint8_t address = 0x29, TwoWire *wire = &Wire);

    bool begin();
    bool init();
    bool configureDefault();

    uint8_t readRangeSingle();
    // Additional functions for other features

private:
    uint8_t _address;
    TwoWire *_i2c;

    // Encapsulate register access for better maintainability
    uint8_t readRegister(uint16_t reg);
    void writeRegister(uint16_t reg, uint8_t value);
    void writeRegister16Bit(uint16_t reg, uint16_t value);

    // Constants for register addresses (consider using enums for c
    static const uint16_t IDENTIFICATION__MODEL_ID = 0x0000;
    // ... other register addresses
};

#endif
```

Gemini came up with:

```
#include "VL6180X.h"

// Constructor
VL6180X::VL6180X(uint8_t address, TwoWire *wire) :
    _address(address),
    _i2c(wire)
{}

bool VL6180X::begin() {
    // Check sensor ID
    if (readRegister(IDENTIFICATION__MODEL_ID) != 0xB4) {
        return false;
    }
    return true;
}

// ... (Implement other functions, using readRegister, writeRegister, etc.)

// Encapsulated register access functions
uint8_t VL6180X::readRegister(uint16_t reg) {
    _i2c->beginTransaction(_address);
    _i2c->write(reg >> 8);
    _i2c->write(reg & 0xFF);
    _i2c->endTransmission();

    _i2c->requestFrom(_address, (uint8_t)1);
    return _i2c->read();
}

// ... (Implement writeRegister, writeRegister16Bit similarly)
```



# LLM (Gemini) - Comments

Use them to learn, check and recheck the reasoning...

Key Improvements:

- **Dependency Injection:** The constructor now allows injecting a TwoWire instance, making the library more testable and adaptable to different I2C setups.
- **Encapsulation:** Register access is encapsulated within private functions (readRegister, writeRegister, writeRegister16Bit), promoting maintainability and potential future changes to the communication protocol.
- **Constants/Enums:** Using constants or enums for register addresses improves code readability and reduces the risk of errors.
- **Initialization List:** The constructor uses an initialization list for member variables, which can be more efficient in some cases.

# LLM (Gemini) - Comments

Use them to learn, check and recheck the reasoning...

Balancing SOLID and Efficiency:

- **Single Responsibility Principle:** Each function has a clear purpose (e.g., `begin()` for initialization, `readRangeSingle()` for range measurement).
- **Open/Closed Principle:** The library is open for extension (adding new functions) but closed for modification (core functionality remains stable).
- **Dependency Inversion:** The library depends on abstractions (`TwoWire`) rather than concrete implementations.
- **Efficiency:** We avoid excessive abstraction or complex inheritance hierarchies that might introduce overhead in an embedded environment.

**Gemini came up with:**

```
bool VL6180X::configureDefault() {
    // Recommended register settings (refer to datasheet)
    writeRegister16Bit(SYSRANGE__MAX_CONVERGENCE_TIME, 0x0010); // 16ms
    writeRegister(SYSRANGE__VHV_REPEAT, 0xFF);
    writeRegister(SYSRANGE__INTERMEASUREMENT_PERIOD, 0x09); // 100ms

    // Further configuration based on your application

    return true;
}

uint8_t VL6180X::readRangeSingle() {
    writeRegister(SYSRANGE__START, 0x01); // Start single shot mode

    // Poll for completion
    delay(10); // Adjust delay based on measurement time
    while ((readRegister(RESULT__INTERRUPT_STATUS_GPIO) & 0x07) == 0);

    uint8_t range = readRegister(RESULT__RANGE_VAL);
    writeRegister(SYSTEM__INTERRUPT_CLEAR, 0x01); // Clear interrupt

    return range;
}

uint8_t VL6180X::readRangeContinuous() {
    writeRegister(SYSRANGE__START, 0x03); // Start continuous mode

    // Poll for new data ready
    delay(10); // Adjust delay based on measurement time
    while ((readRegister(RESULT__INTERRUPT_STATUS_GPIO) & 0x07) == 0);

    uint8_t range = readRegister(RESULT__RANGE_VAL);
    writeRegister(SYSTEM__INTERRUPT_CLEAR, 0x01); // Clear interrupt

    return range;
}
```



## Gemini came up with:

```
// Encapsulated register access functions
uint8_t VL6180X::readRegister(uint16_t reg) {
    _i2c->beginTransaction(_address);
    _i2c->write(reg >> 8);
    _i2c->write(reg & 0xFF);
    _i2c->endTransmission();

    _i2c->requestFrom(_address, (uint8_t)1);
    return _i2c->read();
}

void VL6180X::writeRegister(uint16_t reg, uint8_t value) {
    _i2c->beginTransaction(_address);
    _i2c->write(reg >> 8);
    _i2c->write(reg & 0xFF);
    _i2c->write(value);
    _i2c->endTransmission();
}

void VL6180X::writeRegister16Bit(uint16_t reg, uint16_t value) {
    _i2c->beginTransaction(_address);
    _i2c->write(reg >> 8);
    _i2c->write(reg & 0xFF);
    _i2c->write(value >> 8);
    _i2c->write(value & 0xFF);
    _i2c->endTransmission();
}
```

# LLM (Gemini) - Key Points

Use them to learn, check and recheck the reasoning...

- **Register Addresses:** The register addresses are defined as constants at the beginning of the .cpp file for better readability and maintainability.
- **init():** This function performs the mandatory register settings as per the datasheet.
- **configureDefault():** This function sets up the recommended register settings. You can customize it further based on your application's requirements.
- **readRangeSingle():** This function triggers a single range measurement and returns the result.
- **readRangeContinuous():** This function starts continuous range measurements and returns the latest available result.
- **Helper Functions:** The readRegister, writeRegister, and writeRegister16Bit functions encapsulate the I2C communication for register access.

# LLM (Gemini) - Remember

## Some advice...

- **Datasheet:** Always refer to the VL6180X datasheet for the most accurate and up-to-date register information.
- **Error Handling:** Consider adding error handling to the register access functions and other critical parts of the library for robustness.
- **Additional Features:** Implement functions for other sensor features like ambient light sensing, proximity detection, and interrupt handling as needed.
- **Optimization:** You might need to optimize the code further for performance or power consumption, especially in resource-constrained embedded systems.