Task 4 — Steepest local search with candidate moves

- 160296: Paweł Laszczyk
- 160314: Ashley Jurga

Solver revision: `75ec58b` (branch `task4-fixes`)
Source code link: GitHub
Instances: `TSPA.csv`, `TSPB.csv` — 200 nodes each
Methods: `RandomSolution` (baseline), full-neighbourhood steepest local search with a random start (reference), and the same search restricted to candidate lists with `k = 10` and `k = 13`
Previous methods: the same methods as in Report 3, registered in the same extended benchmark run for consistent timings; the algorithms are unchanged.

---

1. The problem

The problem is the same as in Tasks 1–3. Each instance has `N` points with coordinates and a **cost**. We select exactly

```
M = ceil(N / 2) = 100
```

points and put them in a closed tour. The objective is

```
objective = tour length + cost of the selected nodes
```

and lower is better. Distances are Euclidean and rounded to the nearest integer, so all objective values are integers. A solution is stored as the list of selected nodes in visit order; the last node connects back to the first one.

Task 4 changes the neighbourhood, not the objective. The local search from Task 3 checks every inter-route exchange and every 2-opt move. Candidate moves check only a small part of that neighbourhood, chosen by a heuristic. The goal is to keep most of the quality while evaluating far fewer moves.

2. Methods

2.1 Candidate lists

For every node `i` we build a list `C[i]` of `k` other nodes. The nodes are sorted by

```
score[i][j] = dist[i][j] + cost[j]
```

and the `k` smallest are kept. The cost term matters: a cheap node is more attractive than an expensive one at the same distance. The lists are built once per instance and do not change during the search.

```
BuildCandidates(instance, k):
    for i ← 0 to N-1:
        for j ← 0 to N-1:
            score[i][j] ← dist[i][j] + cost[j]

        order ← [0, 1, ..., N-1]
        sort order by score[i][order[a]] ascending

        C[i] ← []
        for v in order:
            if v ≠ i:
                C[i].append(v)
                if len(C[i]) = k:
                    break

    return C
```

The lists are directed: `v` can be in `C[i]` even when `i` is not in `C[v]`. The iterators below read the list of every selected node; section 2.6 explains what this misses for inter-route moves.

2.2 Inter-route moves through candidate edges

An inter-route move replaces one selected node with one unselected node. In the full neighbourhood every pair `(position, unselected node)` is checked. In the candidate version we only check moves that create a candidate edge.

Suppose the tour contains `old` and `new` is in `C[old]`. To create the edge `(old, new)`, we can replace one of the two neighbours of `old`:

- replace the predecessor `prev` of `old`, creating `prevPrev → new → old`;
- replace the successor `next` of `old`, creating `old → new → nextNext`.

Both moves are checked. The delta includes the node costs, because one selected node leaves and one unselected node enters.

```
InterRouteIterator(path, C, selected):
    m ← len(path)

    for i ← 0 to m-1:
        old      ← path[i]
        prev     ← path[(i-1+m) mod m]
        prevPrev ← path[(i-2+m) mod m]
        next     ← path[(i+1) mod m]
        nextNext ← path[(i+2) mod m]

        for new in C[old]:
            if selected[new]:
                continue

            # Replace prev with new.
            Δprev ← cost[new] + dist[prevPrev][new] + dist[new][old]
                    − cost[prev] − dist[prevPrev][prev] − dist[prev][old]
            yield (replace position (i-1+m) mod m with new, Δprev)

            # Replace next with new.
            Δnext ← cost[new] + dist[old][new] + dist[new][nextNext]
                    − cost[next] − dist[old][next] − dist[next][nextNext]
            yield (replace position (i+1) mod m with new, Δnext)
```

`selected[new]` is a boolean array, so the membership test is O(1). A replacement can be generated twice, once from each neighbour of the replaced position. The two yields have the same delta, so the search removes the duplicate (section 2.4).

2.3 Intra-route moves through candidate edges

The intra-route move is a 2-opt exchange. For edges `(a, aNext)` and `(b, bNext)`, it removes them, adds `(a, b)` and `(aNext, bNext)`, and reverses the segment between the removed edges. No node enters or leaves, so node costs cancel and the delta contains only distances.

For a candidate edge `(old, new)` there are two such moves. If `i` is the position of `old` and `j` is the position of `new`, they remove the edges **after** both nodes or the edges **before** both nodes.

```
IntraRouteIterator(path, C, pos):
    m ← len(path)

    for i ← 0 to m-1:
        old ← path[i]

        for new in C[old]:
            j ← pos[new]
            if j = -1:
                continue                        # new is not selected
            if j = (i-1+m) mod m or j = (i+1) mod m:
                continue                        # the nodes are adjacent

            YieldTwoOpt(i, j)
            YieldTwoOpt((i-1+m) mod m, (j-1+m) mod m)

YieldTwoOpt(e1, e2):
    if e1 > e2:
        swap e1, e2
    if e2 - e1 < 2 or (e1 = 0 and e2 = m-1):
        return                                  # adjacent edges or wrap-around pair

    a     ← path[e1]
    aNext ← path[(e1+1) mod m]
    b     ← path[e2]
    bNext ← path[(e2+1) mod m]

    Δ ← −dist[a][aNext] − dist[b][bNext]
        + dist[a][b] + dist[aNext][bNext]

    yield (reverse segment e1+1 .. e2, Δ)
```

`pos[new]` is the position of `new`, or `-1` when it is not selected, so both the membership test and the position lookup are O(1). The first call removes the edges after `old` and `new`, the second removes the edges before them. The `e2 - e1 < 2` check skips adjacent edges, and `e1 = 0 and e2 = m-1` skips the wrap-around pair `(v0, v1)` and `(v_{m-1}, v0)`, which share node `v0` and cannot be used for a 2-opt move.

2.4 Steepest search with candidate lists

This is normal steepest descent, but the neighbourhood is the candidate set. One iteration checks all candidate inter-route moves and all candidate 2-opt moves, keeps the best delta, and applies it if it is negative. If nothing improves, the search stops.

The tour is kept in a fixed-size array. Two arrays are maintained with it:

- `selected[v]` — whether `v` is in the tour;
- `pos[v]` — its position in the tour, or `-1` when it is not selected.

They are updated after every accepted move, so the iterators never scan the path. Duplicate moves are removed with generation stamps.

```
SteepestCandidates(path, C):
    x ← copy(path)
    m ← len(x)

    for v ← 0 to N-1:
        selected[v] ← false
        pos[v]      ← -1
    for i ← 0 to m-1:
        selected[x[i]] ← true
        pos[x[i]]      ← i

    generation ← 0
    repeat:
        generation ← generation + 1
        bestDelta  ← 0
        bestMove   ← none

        for each (q, new, Δ) from InterRouteIterator(x, C, selected):
            if seenInter[q][new] = generation:
                continue
            seenInter[q][new] ← generation
            if Δ < bestDelta:
                bestDelta ← Δ
                bestMove  ← (replace x[q] with new)

        for each (e1, e2, Δ) from IntraRouteIterator(x, C, pos):
            if seenIntra[e1][e2] = generation:
                continue
            seenIntra[e1][e2] ← generation
            if Δ < bestDelta:
                bestDelta ← Δ
                bestMove  ← (reverse x[e1+1 .. e2])

        if bestDelta ≥ 0:
            return x

        apply bestMove
        update selected and pos
```

The comparison is strict, and `bestDelta` starts at zero, so only improving moves are accepted. Ties go to the first move in the fixed iteration order. Candidate lists are not updated during the search, and no delta is reused from a previous iteration.

2.5 The full-neighbourhood reference

The reference is the steepest edge-exchange search from Task 3 with a random start. It uses the same deltas but checks every move.

```
SteepestFull(path):
    x ← copy(path)
    m ← len(x)

    repeat:
        bestDelta ← 0
        bestMove  ← none

        used[v] ← false for all v
        for v in x:
            used[v] ← true
        unused ← [v | used[v] = false]

        # All inter-route exchanges.
        for i ← 0 to m-1:
            old  ← x[i]
            prev ← x[(i-1+m) mod m]
            next ← x[(i+1) mod m]

            for new in unused:
                Δ ← cost[new] + dist[prev][new] + dist[new][next]
                    − cost[old] − dist[prev][old] − dist[old][next]
                if Δ < bestDelta:
                    bestDelta ← Δ
                    bestMove  ← (replace x[i] with new)

        # All 2-opt exchanges.
        for i ← 0 to m-1:
            for j ← i+2 to m-1:
                if i = 0 and j = m-1:
                    continue

                a     ← x[i]
                aNext ← x[(i+1) mod m]
                b     ← x[j]
                bNext ← x[(j+1) mod m]

                Δ ← dist[a][b] + dist[aNext][bNext]
                    − dist[a][aNext] − dist[b][bNext]
                if Δ < bestDelta:
                    bestDelta ← Δ
                    bestMove  ← (reverse x[i+1 .. j])

        if bestDelta ≥ 0:
            return x

        apply bestMove
```

One full iteration checks `M(N−M) = 10,000` inter-route moves and `M(M−3)/2 = 4,850` 2-opt moves, about 14,850 in total. A candidate iteration yields at most `2Mk` moves of each type (`4Mk` in total) before skips: for `k = 10` that is 2,000 per type and 4,000 in total, and for `k = 13` 2,600 per type and 5,200 in total. The real number is lower because many candidates are already selected and duplicates are removed.

2.6 What the restriction does, and what it does not do

Every candidate move also exists in the full neighbourhood, but not the other way round. A good move is invisible to the candidate search if it creates no candidate edge. This is the expected trade-off: fewer evaluations, but a risk of stopping in a worse local optimum.

The list is built from `dist + cost`. For an inter-route move that replaces `prev` by `new`, the true node-cost change is `cost[new] − cost[prev]`, but the candidate score only sees `cost[new]`. For a 2-opt move the node cost cancels completely. So the list is a heuristic ordering, not an exact ranking of the moves by their delta. Section 4.4 shows what this does on the two instances.

The lists are also directed. Because `dist + cost` is not symmetric, a pair can be a candidate edge from one side only. The intra-route iterator still sees both endpoints because both are selected and both are visited. The inter-route iterator only reads the selected node's list, so a swap whose candidate edge appears only in the unselected node's list is not generated. With a distance-only list this would not happen; it is a consequence of the cost-aware criterion.

3. Experiment setup

- `N = 200`, `M = 100`, two instances.
- **200 runs per method per instance.** Run `r` starts from `RandomSolution` with seed `r`, the same starts as in the Task 3 local search.
- 4 methods × 2 instances × 200 runs = **1600 solutions**: `RandomSolution` (baseline), full neighbourhood, 10 candidates, 13 candidates.
- Candidate lists are built once per instance before the timed loop, so their construction is not charged to the first run.
- Times are measured around the strategy call only. They come from one run of the program and vary between runs; only comparisons inside the same run are meaningful.
- The previous methods are registered together with the Task 4 methods in one extended benchmark run, so the timings in section 4.2 are directly comparable. Their objectives, components and tours are identical to Report 3's 200-run experiment.
- The extended timing table was produced with a temporary harness that registers the 16 Report 3 strategies (the four Task 1 constructions, the four Task 2 constructions and the eight from `task3.All()`) plus the two Task 4 candidate strategies in one `Benchmark` call. The repository's default `go run .` runs the Task 4 subset; the algorithms are unchanged.
- The sweep in section 4.5 uses the same 200 runs and adds `k = 5, 8, 20, 30, 50`.

To reproduce:

```
go run . -json results_task4.json
go run . -candidates 5,8,10,13,20,30,50 -json results_task4_sweep.json
python3 tools/check_with_excel.py results_task4.json \
    --out report/excel_check_task4.json
python3 tools/make_report_task4.py results_task4.json \
    --sweep results_task4_sweep.json \
    --excel-check report/excel_check_task4.json
```

`make_report_task4.py` produces the Task 4 tables and figures only. The extended timing table in section 4.2 was produced by the temporary all-method harness described above; the repository's default `go run .` runs the Task 4 subset. The algorithms and the solutions are unchanged.

4. Results

4.1 Objective values

Method	TSPA.csv av (min–max)	TSPB.csv av (min–max)
RandomSolution	261,353.1 (238,111 – 291,409)	207,261.0 (186,229 – 225,881)

Method	TSPA.csv av (min–max)	TSPB.csv av (min–max)
RandomStartSteepestEdges	76,168.9 (73,580 – 80,490)	52,662.4 (50,328 – 55,056)
RandomStartSteepestEdges10Candidates	80,218.4 (75,324 – 85,156)	52,723.0 (50,441 – 55,895)
RandomStartSteepestEdges13Candidates	78,345.8 (75,325 – 83,113)	52,600.8 (50,394 – 55,062)
ExtendEnd	87,476.6 (84,362 – 90,075)	59,397.3 (56,007 – 63,166)
ExtendAny	74,347.0 (72,328 – 77,022)	59,475.5 (52,915 – 66,164)
GreedyCycle	73,793.4 (72,590 – 75,281)	59,649.9 (55,655 – 63,734)
RegretOnlyExtendAny	122,860.7 (111,527 – 133,181)	74,763.4 (69,032 – 80,767)
RegretOnlyGreedyCycle	123,320.3 (112,410 – 135,431)	74,458.2 (69,474 – 79,437)
RegretWeightedExtendAny	75,561.2 (72,419 – 78,504)	55,698.3 (50,485 – 61,406)
RegretWeightedGreedyCycle	73,335.3 (72,011 – 76,027)	57,905.2 (52,860 – 63,406)
RandomStartSteepestNodes	89,797.9 (83,476 – 99,440)	66,139.6 (60,091 – 72,562)
GreedyStartSteepestNodes	72,998.0 (71,994 – 75,688)	57,536.9 (52,669 – 62,998)
GreedyStartSteepestEdges	72,978.7 (71,994 – 75,204)	57,145.6 (52,512 – 62,301)
RandomStartGreedyNodes	87,245.0 (80,056 – 94,234)	62,985.8 (58,118 – 69,313)
GreedyStartGreedyNodes	72,997.2 (71,996 – 75,688)	57,538.7 (52,510 – 62,933)
RandomStartGreedyEdges	75,524.3 (73,376 – 78,145)	51,869.9 (49,932 – 54,790)
GreedyStartGreedyEdges	72,947.1 (71,996 – 75,204)	57,213.5 (52,545 – 62,475)

The first four rows are the Task 4 methods. The remaining rows are the previous methods from the same extended run, included for context. The best previous averages are 72,947.1 on TSPA (`GreedyStartGreedyEdges`) and 51,869.9 on TSPB (`RandomStartGreedyEdges`).

`RandomSolution` is only a baseline. Its average is 261,353 on TSPA and 207,261 on TSPB, about 3.4 and 3.9 times the full-neighbourhood averages. It is kept in the tables to show the scale but is not used in the plots.

The two instances behave differently:

- **TSPA.** 10 candidates are 4,049.5 worse on average (+5.32%) than the full search, 13 candidates are 2,176.9 worse (+2.86%). The 10-candidate search loses all 200 paired runs; the 13-candidate search wins 11 and loses 189.
- **TSPB.** 10 candidates are only 60.5 worse (+0.11%) than the full search, and 13 candidates are 61.6 *better* (−0.12%). The paired results are almost even: 96/103/1 and 107/90/3.

The best single solutions show the same. On TSPA the full search reaches 73,580, while the candidate searches stop at 75,324 and 75,325. On TSPB the best solutions are 50,328, 50,441 and 50,394, so the candidate searches are within 113 units of the full search.

4.2 Running times

Method	TSPA.csv av (min–max)	TSPB.csv av (min–max)
RandomSolution	0.01 ms (0.01 – 0.55)	0.01 ms (0.01 – 0.02)
RandomStartSteepestEdges	8.31 ms (6.99 – 10.07)	8.34 ms (7.22 – 10.35)
RandomStartSteepestEdges10Candidates	1.54 ms (1.33 – 4.02)	1.58 ms (1.35 – 3.42)
RandomStartSteepestEdges13Candidates	2.06 ms (1.75 – 3.81)	2.05 ms (1.74 – 3.74)
ExtendEnd	0.02 ms (0.01 – 0.05)	0.02 ms (0.01 – 0.03)

Method	TSPA.csv av (min–max)	TSPB.csv av (min–max)
ExtendAny	2.01 ms (1.92 – 2.99)	2.03 ms (1.93 – 2.84)
GreedyCycle	2.06 ms (1.94 – 3.04)	2.01 ms (1.93 – 2.96)
RegretOnlyExtendAny	2.28 ms (2.16 – 3.27)	2.27 ms (2.15 – 3.39)
RegretOnlyGreedyCycle	2.21 ms (1.97 – 3.43)	2.18 ms (1.95 – 3.21)
RegretWeightedExtendAny	2.29 ms (2.13 – 3.32)	2.29 ms (2.08 – 3.28)
RegretWeightedGreedyCycle	2.29 ms (2.15 – 3.57)	2.26 ms (2.09 – 3.27)
RandomStartSteepestNodes	11.57 ms (8.94 – 22.75)	11.40 ms (9.50 – 15.60)
GreedyStartSteepestNodes	2.59 ms (2.25 – 3.94)	2.72 ms (2.28 – 3.91)
GreedyStartSteepestEdges	2.51 ms (2.23 – 3.71)	2.87 ms (2.34 – 3.85)
RandomStartGreedyNodes	5.53 ms (2.94 – 8.07)	5.21 ms (2.82 – 10.79)
GreedyStartGreedyNodes	2.50 ms (2.26 – 3.73)	2.49 ms (2.24 – 3.58)
RandomStartGreedyEdges	4.16 ms (2.16 – 7.11)	3.89 ms (2.01 – 6.89)
GreedyStartGreedyEdges	2.48 ms (2.24 – 3.75)	2.55 ms (2.25 – 3.37)

The first four rows are the Task 4 methods; the remaining rows are the previous methods.

The candidate searches are about **5.3–5.4 times faster** than the full search with `k = 10` and about **4.0 times faster** with `k = 13`. The first run of a method is a bit slower (for example 4.02 ms against a median of 1.51 ms for `k = 10` on TSPA), probably because the first run pays for allocation and cache warm-up. `RandomSolution` is almost free (0.01 ms) and is only the baseline.

The speedup is not only from checking fewer moves. The iterators use O(1) `selected` and `pos` arrays and generation stamps for duplicates. A naive version that scans the path for every candidate, or evaluates the same move several times, can lose the whole advantage.

All times in table 4.2 come from one extended run that registers all 18 methods — the 16 from Report 3 plus the two Task 4 candidate strategies — in the same process, so they are directly comparable. Only times inside the extended run should be compared.

4.3 Paired comparisons

Every pair uses the same seed, so the difference is caused by the neighbourhood alone. Only the Task 4 methods are paired here: they share the same random starts and differ only in the candidate restriction. The previous methods are in the extended run, but they differ in more than the neighbourhood (and some use greedy starts), so they are not included in this paired comparison.

Instance	Comparison	Mean difference	Better / worse / tie (of 200)
TSPA.csv	10 candidates − full	+4,049.4	0 / 200 / 0
TSPA.csv	13 candidates − full	+2,176.9	11 / 189 / 0
TSPA.csv	13 candidates − 10 candidates	−1,872.5	177 / 23 / 0
TSPB.csv	10 candidates − full	+60.5	96 / 103 / 1
TSPB.csv	13 candidates − full	−61.6	107 / 90 / 3
TSPB.csv	13 candidates − 10 candidates	−122.2	104 / 93 / 3

On TSPA the restriction is a clear loss against the full search. On TSPB the candidate search is not simply worse: it reaches a different local optimum and wins 96–107 of 200 starts against the full search. A restricted neighbourhood can change the whole sequence of accepted moves, not only the first step.

4.4 Where the objective goes

Component averages are rounded, so they may not add exactly to the objective. The first four rows for each instance are the Task 4 methods; the remaining rows are the previous methods from the same extended run, included for context.

Instance	Method	Avg tour length	Avg node cost	Avg objective
TSPA.csv	RandomSolution	164,360.7	96,992.4	261,353.1
TSPA.csv	RandomStartSteepestEdges	23,040.2	53,128.7	76,168.9
TSPA.csv	RandomStartSteepestEdges10Candidates	23,663.5	56,554.8	80,218.4
TSPA.csv	RandomStartSteepestEdges13Candidates	23,358.0	54,987.9	78,345.8
TSPA.csv	ExtendEnd	33,641.8	53,834.8	87,476.6
TSPA.csv	ExtendAny	23,071.4	51,275.6	74,347.0
TSPA.csv	GreedyCycle	22,304.4	51,489.0	73,793.4
TSPA.csv	RegretOnlyExtendAny	22,557.7	100,303.0	122,860.7
TSPA.csv	RegretOnlyGreedyCycle	21,215.2	102,105.1	123,320.3
TSPA.csv	RegretWeightedExtendAny	23,352.2	52,209.0	75,561.2
TSPA.csv	RegretWeightedGreedyCycle	21,184.7	52,150.6	73,335.3
TSPA.csv	RandomStartSteepestNodes	37,458.6	52,339.2	89,797.9
TSPA.csv	GreedyStartSteepestNodes	21,139.4	51,858.6	72,998.0
TSPA.csv	GreedyStartSteepestEdges	21,121.6	51,857.1	72,978.7
TSPA.csv	RandomStartGreedyNodes	34,575.2	52,669.9	87,245.0
TSPA.csv	GreedyStartGreedyNodes	21,135.7	51,861.6	72,997.2
TSPA.csv	RandomStartGreedyEdges	22,737.3	52,787.0	75,524.3
TSPA.csv	GreedyStartGreedyEdges	21,092.9	51,854.2	72,947.1
TSPB.csv	RandomSolution	155,274.3	51,986.7	207,261.0
TSPB.csv	RandomStartSteepestEdges	20,847.6	31,814.8	52,662.4
TSPB.csv	RandomStartSteepestEdges10Candidates	21,074.1	31,648.9	52,723.0
TSPB.csv	RandomStartSteepestEdges13Candidates	20,884.4	31,716.4	52,600.8
TSPB.csv	ExtendEnd	26,882.0	32,515.3	59,397.3
TSPB.csv	ExtendAny	18,678.0	40,797.5	59,475.5
TSPB.csv	GreedyCycle	18,014.7	41,635.2	59,649.9
TSPB.csv	RegretOnlyExtendAny	22,584.5	52,178.9	74,763.4
TSPB.csv	RegretOnlyGreedyCycle	21,110.4	53,347.9	74,458.2
TSPB.csv	RegretWeightedExtendAny	20,849.9	34,848.4	55,698.3
TSPB.csv	RegretWeightedGreedyCycle	17,025.1	40,880.1	57,905.2
TSPB.csv	RandomStartSteepestNodes	35,185.3	30,954.3	66,139.6
TSPB.csv	GreedyStartSteepestNodes	17,100.1	40,436.8	57,536.9
TSPB.csv	GreedyStartSteepestEdges	16,704.9	40,440.7	57,145.6
TSPB.csv	RandomStartGreedyNodes	31,445.2	31,540.7	62,985.8
TSPB.csv	GreedyStartGreedyNodes	17,101.8	40,437.0	57,538.7
TSPB.csv	RandomStartGreedyEdges	20,884.6	30,985.3	51,869.9

Instance	Method	Avg tour length	Avg node cost	Avg objective
TSPB.csv	GreedyStartGreedyEdges	16,772.7	40,440.8	57,213.5

The best previous averages are 72,947.1 on TSPA (`GreedyStartGreedyEdges`) and 51,869.9 on TSPB (`RandomStartGreedyEdges`); the candidate searches are a faster restricted version of the full steepest search, not the best overall method.

The random baseline is far behind, mostly because its tour is much longer: 164,361 against 23,040 on TSPA and 155,274 against 20,848 on TSPB.

On TSPA the candidate searches lose on both parts compared with the full search. With `k = 10` the tour is 623 longer and the nodes cost 3,426 more; with `k = 13` the tour is 318 longer and the nodes cost 1,859 more. The restricted search ends in a worse basin, and the cost-aware list does not make up for the missing moves.

On TSPB the parts move in opposite directions compared with the full search. With `k = 10` the search saves 166 on nodes but pays 227 more for the tour (net +61). With `k = 13` it saves 98 on nodes and pays 37 more for the tour (net −62). The list shifts the selection towards cheaper nodes, and the tour grows only a little.


The instance's node costs average 971 (sd 568) on TSPA and 519 (sd 287) on TSPB. The cost term therefore has a larger effect on the candidate ordering on TSPA, while the 2-opt delta is cost-blind and the inter-route criterion ignores the cost of the node that leaves. This is the likely reason for the TSPA deterioration. The experiment does not separate these effects.

4.5 Candidate-list size

The choice `k = 13` is not special. The table below runs the same search for several list sizes; the full-neighbourhood row is the reference.

k	TSPA avg objective	TSPB avg objective	TSPA ms/run	TSPB ms/run
full	76,168.9	52,662.4	8.01	7.98
5	86,525.6	54,185.8	0.80	0.74
8	82,638.2	52,961.8	1.21	1.21
10	80,218.4	52,723.0	1.49	1.51
13	78,345.8	52,600.8	1.98	1.99
20	76,432.7	52,668.6	3.14	3.06
30	76,093.9	52,688.9	4.73	4.60
50	76,150.6	52,668.0	7.99	7.76

Timings in this table come from the sweep run and differ slightly from section 4.2 because timing varies; the objectives are deterministic.





- **TSPA needs about 20–30 candidates.** At `k = 20` the average is 0.35% above the full search and the search is 2.5 times faster; at `k = 30` it is 0.10% below the full search and 1.7 times faster. The curve is still improving at 13.
- **TSPB is already fine with 10 candidates.** At `k = 10` the average is 0.11% above the full search and the search is 5.3 times faster. Larger lists change the average by less than 0.25% and only cost time.


So 13 is an awkward middle point: slower than 10 without closing the TSPA gap, and unnecessary on TSPB. For speed, 10 is the better choice on TSPB; for quality on TSPA, 20–30 is the useful range.


4.6 Pictures of the best solutions

Node colour is the node cost (light blue cheap, dark blue expensive) and the dark line is the closed tour. The first panel is the full-neighbourhood reference, the other two are the candidate searches. `RandomSolution` is left out of the plots because its objective is about three times larger and would make the panels hard to read; it is in the tables. The figures show only the Task 4 methods; the previous methods are in the tables.









On TSPA the candidate panels have more long edges and the selected nodes are on average more expensive, which matches section 4.4. On TSPB the three panels look close.

4.7 Best runs

The first four rows for each instance are the Task 4 methods. The remaining rows are the previous methods from the same extended run, included for context.

Instance	Method	Best objective	Run	Tour length	Node cost
TSPA.csv	RandomSolution	238,111	154	146,623	91,488
TSPA.csv	RandomStartSteepestEdges	73,580	171	21,726	51,854
TSPA.csv	RandomStartSteepestEdges10Candidates	75,324	70	22,896	52,428
TSPA.csv	RandomStartSteepestEdges13Candidates	75,325	15	22,694	52,631
TSPA.csv	ExtendEnd	84,362	54	31,319	53,043
TSPA.csv	ExtendAny	72,328	11	21,816	50,512
TSPA.csv	GreedyCycle	72,590	31	21,570	51,020
TSPA.csv	RegretOnlyExtendAny	111,527	85	19,974	91,553

Instance	Method	Best objective	Run	Tour length	Node cost
TSPA.csv	RegretOnlyGreedyCycle	112,410	31	21,509	90,901
TSPA.csv	RegretWeightedExtendAny	72,419	69	20,127	52,292
TSPA.csv	RegretWeightedGreedyCycle	72,011	31	20,248	51,763
TSPA.csv	RandomStartSteepestNodes	83,476	94	32,174	51,302
TSPA.csv	GreedyStartSteepestNodes	71,994	126	20,157	51,837
TSPA.csv	GreedyStartSteepestEdges	71,994	126	20,157	51,837
TSPA.csv	RandomStartGreedyNodes	80,056	63	27,207	52,849
TSPA.csv	GreedyStartGreedyNodes	71,996	31	20,233	51,763
TSPA.csv	RandomStartGreedyEdges	73,376	19	21,634	51,742
TSPA.csv	GreedyStartGreedyEdges	71,996	31	20,233	51,763
TSPB.csv	RandomSolution	186,229	165	132,442	53,787
TSPB.csv	RandomStartSteepestEdges	50,328	101	20,812	29,516
TSPB.csv	RandomStartSteepestEdges10Candidates	50,441	149	21,229	29,212
TSPB.csv	RandomStartSteepestEdges13Candidates	50,394	149	20,711	29,683
TSPB.csv	ExtendEnd	56,007	32	24,632	31,375
TSPB.csv	ExtendAny	52,915	50	20,068	32,847
TSPB.csv	GreedyCycle	55,655	174	19,634	36,021
TSPB.csv	RegretOnlyExtendAny	69,032	185	21,267	47,765
TSPB.csv	RegretOnlyGreedyCycle	69,474	169	21,486	47,988
TSPB.csv	RegretWeightedExtendAny	50,485	192	18,835	31,650
TSPB.csv	RegretWeightedGreedyCycle	52,860	5	16,480	36,380
TSPB.csv	RandomStartSteepestNodes	60,091	191	29,813	30,278
TSPB.csv	GreedyStartSteepestNodes	52,669	5	16,589	36,080
TSPB.csv	GreedyStartSteepestEdges	52,512	17	17,298	35,214
TSPB.csv	RandomStartGreedyNodes	58,118	97	24,165	33,953
TSPB.csv	GreedyStartGreedyNodes	52,510	175	17,010	35,500
TSPB.csv	RandomStartGreedyEdges	49,932	105	18,676	31,256
TSPB.csv	GreedyStartGreedyEdges	52,545	175	16,391	36,154

For context, the best previous run is 71,994 on TSPA (`GreedyStartSteepestNodes` and `GreedyStartSteepestEdges`) and 49,932 on TSPB (`RandomStartGreedyEdges`).

The Task 4 tours are in `results_task4.json`; the previous methods' tours are in Report 3's `results.json`. `go run .` prints the best tour of every Task 4 method, and the run column identifies the random start.

5. Solution checker

All 1600 runs were checked with the course-provided **`Solution checker.xlsx`** through `tools/check_with_excel.py`. The workbook writes the tour into `F3:F102`, uses `LOOKUP` to fetch the coordinates and costs, computes the rounded edges in `J3:J102` (`F103 = F3` closes the cycle), and reports the node cost in `I2`, the tour length in `J2` and the objective in `K2`. The script only checks that the tour has exactly `M = 100` distinct in-range ids and reads those cells back from a temporary copy, so the provided file is not modified.

Instance	Method	Runs checked	Feasible	Objective matches	Components match
TSPA.csv	RandomSolution	200	200/200	200/200	200/200
TSPA.csv	RandomStartSteepestEdges	200	200/200	200/200	200/200
TSPA.csv	RandomStartSteepestEdges10Candidates	200	200/200	200/200	200/200
TSPA.csv	RandomStartSteepestEdges13Candidates	200	200/200	200/200	200/200
TSPB.csv	RandomSolution	200	200/200	200/200	200/200
TSPB.csv	RandomStartSteepestEdges	200	200/200	200/200	200/200
TSPB.csv	RandomStartSteepestEdges10Candidates	200	200/200	200/200	200/200
TSPB.csv	RandomStartSteepestEdges13Candidates	200	200/200	200/200	200/200

1600 runs checked, 0 failures.

The extended run's 7200 solutions are identical to the solutions checked earlier: the 1600 Task 4 runs checked here and all 6400 Report 3 runs (the two baselines appear in both checks). The previous methods were therefore not rechecked again.

6. Source code

File	Contents
`solver/problem.go`	loading the instance, the distance matrix, `TourLength` / `NodesCost` / `Objective`
`solver/solver.go`	the `Strategy` interface, the optional `Preparer` interface and the benchmark loop
`task1/strategies.go`	`RandomSolution`, used for the starts and as the baseline
`task3/task3.go`	the full-neighbourhood steepest search
`task4/task4.go`	candidate lists, the candidate iterators and `improvePathSteepestWithCandidates`
`task4/strategies.go`	`CandidateSteepest`, which prepares the lists and runs the search
`main.go`	command line, the `-candidates` option, the table and the JSON export
`tools/check_with_excel.py`	drives `Solution checker.xlsx`
`tools/make_report_task4.py`	Task 4 figures and tables for this report
`tools/oeviz.py`	plotting helpers

The candidate search is one type, `CandidateSteepest`, with the list size `K` as a field. `Prepare` builds the lists before the timed loop and `Solve` runs the search. The `-candidates` flag makes the list size an experiment parameter, which is how the sweep in section 4.5 is produced without changing the code.

7. Conclusions

1. **Candidate moves give the expected speedup.** With `k = 10` the search is about 5.3–5.4 times faster than the full search in the same run, with `k = 13` about 4.0 times. Constant-time membership and position lookups and duplicate removal are needed; a naive implementation can lose the gain.
2. **The quality cost depends on the instance.** On TSPA 10 candidates are 5.32% worse than the full search and lose all 200 paired runs; 13 candidates are 2.86% worse and lose 189. On TSPB the differences are +0.11% and −0.12%, with almost even paired results.

3. `k = 13` **is not a special point.** TSPA needs about 20–30 candidates to recover the quality of the full search, while TSPB is already fine with 10. Thirteen is slower than 10 without closing the TSPA gap, and it is unnecessary on TSPB.
4. **A restricted neighbourhood is not simply worse.** On TSPB the candidate search wins 96–107 of 200 paired runs against the full search. It reaches a different local optimum, which can be better than the one found by the full search.
5. **The candidate criterion has limits.** The list uses `dist + cost`, but the 2-opt delta is cost-blind and the inter-route criterion ignores the cost of the node that leaves. On TSPA, where costs are larger, the search loses on both tour length and node cost compared with the full search. A criterion made for each move type, or learned from earlier solutions, could help.
6. **What to keep.** Candidate lists are useful when speed matters, especially on TSPB-like instances with 10 candidates. On TSPA-like instances, use 20–30 candidates or the full search within this steepest random-start family. If the goal is the best objective regardless of method, the best methods from Report 3 are `GreedyStartGreedyEdges` on TSPA (72,947.1) and `RandomStartGreedyEdges` on TSPB (51,869.9). The next step is to put candidate lists inside a higher-level method such as MSLS or ILS.