

# [Sightations](#) ← [A Computer Vision Blog](#)

- [Home](#)
- [About](#)
- [Contact](#)
- [Code](#)
- [Archive](#)
- 

## Calibrated Cameras and gluPerspective

June 18, 2013

After posting my last article [relating glFrustum to the intrinsic camera matrix](#), I received some emails asking how the (now deprecated) [gluPerspective](#) function relates to the intrinsic matrix. We can show a similar result with `gluPerspective` as we did with `glFrustum`, namely that it is the product of a `glOrtho` matrix and a (modified) intrinsic camera matrix, but in this case the intrinsic matrix has different constraints. I'll be re-using notation and concepts from the previous article, so if you aren't familiar with them, I recommend reading it first.

### Decomposing gluPerspective

The matrix generated by `gluPerspective` is

$$\begin{pmatrix} \frac{f}{\text{aspect}} & 0 & 0 & 0 \\ 0 & f & 0 & 0 \\ 0 & 0 & C' & D' \\ 0 & 0 & -1 & 0 \end{pmatrix}$$

where

$$\begin{aligned} f &= \cot(\text{fovy}/2) \\ C' &= -\frac{\text{far} + \text{near}}{\text{far} - \text{near}} \\ D' &= -\frac{2 \text{far} \text{near}}{\text{far} - \text{near}} \end{aligned}$$

Like with `glFrustum`, `gluPerspective` permits no axis skew, but it also restricts the viewing volume to be centered around the camera's principal (viewing) axis. This means that the principal point offsets  $x_0$  and  $y_0$  must be zero, *and* the matrix generated by `glOrtho` must be centered, i.e. bottom = -top and left = -right. The *Persp* matrix corresponding to the intrinsic matrix is:

$$\text{Persp} = \begin{pmatrix} \alpha & 0 & 0 & 0 \\ 0 & \beta & 0 & 0 \\ 0 & 0 & A & B \\ 0 & 0 & -1 & 0 \end{pmatrix}$$

where

$$A = near + far$$

$$B = near * far$$

and the *NDC* matrix is

$$NDC = \begin{pmatrix} \frac{2}{right-left} & 0 & 0 & t_x \\ 0 & \frac{2}{top-bottom} & 0 & t_y \\ 0 & 0 & -\frac{2}{far-near} & t_z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

$$= \begin{pmatrix} \frac{2}{width} & 0 & 0 & 0 \\ 0 & \frac{2}{height} & 0 & 0 \\ 0 & 0 & -\frac{2}{far-near} & t_z \\ 0 & 0 & 0 & 1 \end{pmatrix}$$

where

$$t_x = -\frac{right + left}{right - left}$$

$$t_y = -\frac{top + bottom}{top - bottom}$$

$$t_z = -\frac{far + near}{far - near}$$

It is easy to show that the product ( $NDC \times Persp$ ) is equivalent to the matrix generated by `gluPerspective(fovy, aspect, near, far)` with

$$fovy = 2 \arctan \left( \frac{height}{2\beta} \right)$$

$$aspect = \frac{\beta}{\alpha} \frac{width}{height}.$$

## glFrustum vs. gluPerspective

In my experience, the zero-skew assumption is usually reasonable, so `glFrustum` can provide a decent approximation to the full intrinsic matrix. However there is quite often a non-negligible principal point offset ( $\sim 2\%$  of the image size), even in high-quality cameras. For this reason, `gluPerspective` might be a good choice for quick-and-dirty demos, but for the most accurate simulation, you should use the full camera matrix [like I described previously](#).

Posted by [Kyle Simek](#)

[Dissecting the Camera Matrix, Part 3: The Intrinsic Matrix](#) → ← [Calibrated Cameras in OpenGL without glFrustum](#)

0 points

Tweet



0 Comments

Sightations

1 Login ▾

♥ Recommend

🐦 Tweet

f Share

Sort by Best ▾



Start the discussion...

LOG IN WITH

OR SIGN UP WITH DISQUS (?)

Name

Be the first to comment.

## ALSO ON SIGHTATIONS

**Q & A: Recovering pose of a calibrated camera - Algebraic vs. Geometric method?**

1 comment • 4 years ago



**dissertation writing service** — Learning this 3D points projections is ideal in math subject. It gives the easy way to determine the ...

**Dissecting the Camera Matrix, Part 2: The Extrinsic Matrix**

16 comments • 6 years ago



**Rajesh** — Hi, I am looking for a method to compute homography matrix between images(left & right) of stereo camera using ...

**Compiling ELSD (Ellipse and Line Segment Detector) on OS X**

4 comments • 5 years ago



**philip andrew** — Do you know anything better than elsd now?

**Calibrated Cameras in OpenGL without glFrustum**

21 comments • 6 years ago



**ksimek** — Thanks for the clarifying photos. Sorry, I misunderstood the scenario -- I thought your calibration image was larger ...

✉ Subscribe   Add Disqus to your siteAdd DisqusAdd   Disqus' Privacy PolicyPrivacy PolicyPrivacy Policy

Content by [Kyle Simek](#). Original design by [Mark Reid](#)  
([Some rights reserved](#)) Powered by [Jekyll](#)