



Javascript Events

Mouse Events

A mouse event is triggered when the user click some element, move the mouse pointer over an element, etc. Here're some most important mouse events and their event handler.

The Click Event (onclick)

The click event occurs when a user clicks on an element on a web page. Often, these are form elements and links. You can handle a click event with an **onclick** event handler.

Eg:

```
<button type="button" onclick="alert('You have clicked a button!');">Click Me</button>
```

The Mouseover Event (onmouseover)

The mouseover event occurs when a user moves the mouse pointer over an element.

You can handle the mouseover event with the **onmouseover** event handler. The following example will show you an alert message when you place mouse over the elements.

Eg:

```
<button type="button" onmouseover="alert('You have placed mouse pointer over a button!');">Place Mouse Over Me</button>
```

The Mouseout Event (onmouseout)

The mouseout event occurs when a user moves the mouse pointer outside of an element.

You can handle the mouseout event with the **onmouseout** event handler. The following example will show you an alert message when the mouseout event occurs.

Eg:

```
<button type="button" onmouseout="alert('You have moved out of the button!');">Place Mouse Inside Me and Move Out</button>
```

Keyboard Events

A keyboard event is fired when the user press or release a key on the keyboard. Here're some most important keyboard events and their event handler.

The Keydown Event (onkeydown)

The keydown event occurs when the user presses down a key on the keyboard.

You can handle the keydown event with the `onkeydown` event handler. The following example will show you an alert message when the keydown event occurs.

Eg:

```
<input type="text" onkeydown="alert('You have pressed a key inside text input!')">
```

The Keyup Event (onkeyup)

The keyup event occurs when the user releases a key on the keyboard.

You can handle the keyup event with the `onkeyup` event handler. The following example will show you an alert message when the keyup event occurs.

Eg;

```
<input type="text" onkeyup="alert('You have released a key inside text input!')">
```

The Keypress Event (onkeypress)

The keypress event occurs when a user presses down a key on the keyboard that has a character value associated with it. For example, keys like Ctrl, Shift, Alt, Esc, Arrow keys, etc. will not generate a `keypress` event, but will generate a `keydown` and `keyup` event.

You can handle the keypress event with the `onkeypress` event handler. The following example will show you an alert message when the keypress event occurs.

Eg:

```
<input type="text" onkeypress="alert('You have pressed a key inside text input!')">
```

Form Events

A form event is fired when a form control receive or loses focus or when the user modify a form control value such as by typing text in a text input, select any option in a select box etc. Here're some most important form events and their event handler.

The Focus Event (onfocus)

The focus event occurs when the user gives focus to an element on a web page.

You can handle the focus event with the `onfocus` event handler. The following example will highlight the background of text input in yellow color when it receives the focus.

Eg

```
</script> <input type="text" onfocus="highlightInput(this)"> <button  
type="button">Button</button>
```

The Blur Event (onblur)

The blur event occurs when the user takes the focus away from a form element or a window.

You can handle the blur event with the `onblur` event handler. The following example will show you an alert message when the text input element loses focus.

Eg

```
<input type="text" onblur="alert('Text input loses focus!')"> <button  
type="button">Submit</button>
```

To take the focus away from a form element first click inside of it then press the tab key on the keyboard, give focus on something else, or click outside of it.

The Change Event (onchange)

The change event occurs when a user changes the value of a form element.

You can handle the change event with the `onchange` event handler. The following example will show you an alert message when you change the option in the select box.

Eg

```
<select onchange="alert('You have changed the selection!');">
<option>Select</option> <option>Male</option> <option>Female</option>
</select>
```

The Submit Event (onsubmit)

The submit event only occurs when the user submits a form on a web page.

You can handle the submit event with the **onsubmit** event handler. The following example will show you an alert message while submitting the form to the server.

Eg:

```
<form action="action.php" method="post" onsubmit="alert('Form data will be
submitted to the server!');"> <label>First Name:</label> <input type="text"
name="first-name" required> <input type="submit" value="Submit"> </form>
```

Events are also triggered in situations when the page has loaded or when user resize the browser window, etc. Here're some most important document/window events and their event handler.

The Load Event (onload)

The load event occurs when a web page has finished loading in the web browser.

You can handle the load event with the **onload** event handler. The following example will show you an alert message as soon as the page finishes loading.

Eg:

```
<body onload="window.alert('Page is loaded successfully!');"> <h1>This is a
heading</h1> <p>This is paragraph of text.</p> </body>
```