113. Path Sum II

113 Path Sum II

- **Depth-first Search** + Tree

Description

Given a binary tree and a sum, find all root-to-leaf paths where each path's sum equals the given sum.

For example:

Given the below binary tree and `sum = 22`,



```
              5
             / \
            4   8
           /   / \
          11  13  4
         /  \    / \
        7    2  5   1
```

return

```
[
   [5,4,11,2],
   [5,8,4,5]
]
```

1. Thought line

2. Depth-first Search + Tree

```
/**
 * Definition for a binary tree node.
 * struct TreeNode {
 *     int val;
 *     TreeNode *left;
 *     TreeNode *right;
 *     TreeNode(int x) : val(x), left(NULL), right(NULL) {}
 * };
 */
class Solution {
private:
    void dfsSum(vector<vector<int>>& res, vector<int> temp, TreeNode* node, int sum, int tempSum){
        if (node == nullptr) return;
        tempSum += node->val;
        temp.push_back(node->val);
        if (!node->left && !node->right && tempSum == sum){
            res.push_back(temp);
            return;
        }
        dfsSum(res, temp, node->left, sum, tempSum);
```

```
        dfsSum(res, temp, node->right, sum, tempSum);
    }
public:
    vector<vector<int>> pathSum(TreeNode* root, int sum) {
        vector<vector<int>> res(0);
        dfsSum(res, {}, root, sum, 0);
        return res;
    }
};
```