

<code>R</code>	<code>touch</code>
<code>docker run -it --rm [USERNAME]</code>	<code>sudo apt update</code> AND <code>sudo apt upgrade</code>
<code>hostname</code>	<code>pwd</code>
<code>ls</code>	<code>rm</code>
<code>tldr</code>	<code>cat</code>

Updates the timestamp of a new file, or (if the file doesn't exist) creates a new file	Opens the R language computing environment
Performs a software update or upgrade	Launch a container from the image
Shows your present working directory	Name of computer you have a terminal/shell on
Removes or deletes a file	Lists files in a certain directory
Displays contents of a file	• "Too long didn't read" • Lists an abbreviated description of what a function does

<code>grep</code>	<code>apt OR brew</code>
<code>sudo</code>	<code>alias</code>
<code>unset</code>	<code>ssh</code>
<code>shasum</code>	<code>Git</code>
<code>GitHub</code>	<code>git init</code>

Allows you to install, update, or remove various applications	Extracts lines matching a text pattern (regular expression)
Make a short-hand macro for a longer command	• Allows you to run a command with elevated privileges • "Superuser do"
Creates a secure shell connection to a remote machine i.e. log in to a remote machine	Used to delete a function
A version control command line	FILL IN LATER
Used to create a repository	Online platform that utilizes Git to allow for collaboration on code

`git add AND git add .`

`git commit -m [MESSAGE]`

`git diff`

`git restore`

`git log OR git checkout`

`git config`

NOTE:

`git push`

`git pull`

Used to make a commit	• <code>git add</code> is used to add specified files to a repository • <code>git add .</code> is used to add ALL files to a repository
Restores to previous commit	Shows differences in every modified file
Allows for modifications of git configurations	Shows all changes that have ever happened to a repository
Pushes updates onto GitHub	<code>HEAD</code> in the context of Git is where things are at the moment
	Pulls updates from GitHub