

# Origami

**Computing Veechgroups of origamis**

1.0

26 February 2018

**Pascal Kattler**

**Sergio Siccha**

**Andrea Thevis**

**Pascal Kattler**

Email: [kattler@math.uni-sb.de](mailto:kattler@math.uni-sb.de)

Homepage: <http://www.math.uni-sb.de/ag/weitze/>

Address: AG Weitze-Schmithüsen  
FR 6.1 Mathematik  
Universität des Saarlandes  
D-66041 Saarbrücken

**Sergio Siccha**

Email: [siccha@mathb.rwth-aachen.de](mailto:siccha@mathb.rwth-aachen.de)

Homepage: <https://www.mathb.rwth-aachen.de/Mitarbeiter/siccha.php>

Address: Lehrstuhl B für Mathematik RWTH - Aachen  
Pontdriesch 10-16  
52062 Aachen  
Germany

**Andrea Thevis**

Email: [thevis@math.uni-sb.de](mailto:thevis@math.uni-sb.de)

Homepage: <http://www.math.uni-sb.de/ag/weitze/>

Address: AG Weitze-Schmithüsen  
FR 6.1 Mathematik  
Universität des Saarlandes  
D-66041 Saarbrücken

# Contents

<b>1</b>	<b>The Origami object</b>	<b>3</b>
1.1	The action on the Origami . . . . .	3
1.2	The Origami object . . . . .	3
<b>2</b>	<b>Introduction</b>	<b>6</b>
2.1	The Free Group . . . . .	6
	<b>Index</b>	<b>7</b>

# Chapter 1

## The Origami object

### 1.1 The action on the Origami

#### 1.1.1 ActionOfSl

▷ `ActionOfSl(word, Origami)` (function)

**Returns:** the Origami Object `word.Origami`

This lets act a word in the free group  $Group(S, T)$ , representing an element of  $Sl_2(\mathbb{Z})$  on an Origami and returns `word.Origami`.

#### 1.1.2 ActionOff2ViaCanonical

▷ `ActionOff2ViaCanonical(word, Origami)` (function)

**Returns:** the Origami Object `word.Origami`

This lets act a word in the free group  $Group(S, T)$ , representing an element of  $Sl_2(\mathbb{Z})$ , on an Origami and returns `word.Origami`. But in contrast to "ActionOfSl" the result is stored in the canonical representation.

#### 1.1.3 RightActionOff2ViaCanonical

▷ `RightActionOff2ViaCanonical(word, Origami)` (function)

**Returns:** the Origami Object `Origami.word`

This lets act a word in the free group  $Group(S, T)$  on an Origami from right and returns `Origami.word = word-1.Origami`, where the left action is the common action of  $Sl_2(\mathbb{Z})$  on 2 manifolds. This action has the same Veechgroup and orbits as the left action. In contrast to "ActionOfSl" the result is stored in the canonical representation.

### 1.2 The Origami object

#### 1.2.1 CanonicalOrigami

▷ `CanonicalOrigami(Origami)` (function)

**Returns:** An Origami

This calculates a canonical representation of an origami, represented as record `rec(d := *, x := *, y := *)`. Two origamis are equal if they are described by the same permutations in their canonical representation.

### 1.2.2 VerticalPerm (for IsOrigami)

▷ `VerticalPerm(Origami)` (attribute)  
**Returns:** a permutation  
 This returns the horizontal permutation  $\sigma_x$  of the Origami.

### 1.2.3 HorizontalPerm (for IsOrigami)

▷ `HorizontalPerm(Origami)` (attribute)  
**Returns:** a permutation  
 This returns the vertical permutation  $\sigma_y$  of the Origami.

### 1.2.4 DegreeOrigami (for IsOrigami)

▷ `DegreeOrigami(Origami)` (attribute)  
**Returns:** an integer  
 This returns the degree of an Origami.

### 1.2.5 Stratum (for IsOrigami)

▷ `Stratum(Origami)` (attribute)  
**Returns:** a list of integers  
 This calculates the stratum of an Origami. That is a list of the orders of the singularities.

### 1.2.6 VeechGroup (for IsOrigami)

▷ `VeechGroup(Origami)` (attribute)  
**Returns:** a ModularSubgroup object  
 This calculates the Veechgroup of an Origami. This is a subgroup of  $Sl_2(\mathbb{Z})$  of finite degree. The group is stored as ModularSubgroup from the ModularSubgroup package. The Veechgroup is represented as the coset permutations  $\sigma_S$  and  $\sigma_T$  with respect to the generators  $S$  and  $T$ . This means if  $i$  is the integer associated to the right coset  $G$  ( $\text{Cosets}(O) [i] \text{VeechGroup} = H$ ) then we have for the coset  $H$ , associated to  $\sigma_S(i)$ , that  $SG = H$ . Dito for  $\sigma_T$ .

### 1.2.7 Cosets (for IsOrigami)

▷ `Cosets(Origami)` (attribute)  
**Returns:** a list of words in the Free group, generated by  $S$  and  $T$ .  
 This Calculates the right cosets of the Veechgroup of an Origami.

### 1.2.8 Equals

▷ `Equals(Origami1, Origami2)` (function)  
**Returns:** true or false  
 This tests whether Origami1 is equal to Origami2 up to numbering of the squares.

### 1.2.9 ExampleOrigami

▷ `ExampleOrigami(d)` (function)

**Returns:** a random origami

This creates a random origami of degree d.

### 1.2.10 CalcVeechGroup

▷ `CalcVeechGroup(Origami)` (function)

**Returns:** A list with tree entrys

This function is used to calculate some attributes. It calculates the Veechgroup of a given origami and . the veechgroup is stored as ModularGroup Object from the ModularGroup package. The cosets of the veechgroup is stored in a list of words in the generators S and T of the matrix group  $SL_2(\mathbb{Z})$ .

### 1.2.11 CalcStratum

▷ `CalcStratum(Origami)` (function)

**Returns:** nothing

Calculates the stratum of an object and sets its attribute. The stratum is stored as list of integers.

### 1.2.12 ToRec

▷ `ToRec(Origami)` (function)

**Returns:** record of the form `rec(d := *, x := *, y := *)` Description This calculates a record representation for an origami object.

## Chapter 2

# Introduction

This package provides calculations with Origamis. An Origami can be obtained in the following way from two permutations  $\sigma_a, \sigma_b \in S_d$ . We take  $d$  Squares  $Q_1, \dots, Q_d$  and glue the lower side of  $Q_i$  to the upper side of  $Q_{\sigma_y(i)}$  and the right side of  $Q_i$  to the left side of  $Q_{\sigma_x(i)}$ . So in this Package we identify an Origami with a pair of permutations, which acts transitively on  $\{1 \dots d\}$  up to simultaneous conjugation. We store an Origami as Origami object. We are mainly interested in the Veechgroup of an Origami. It can be shown that the Veechgroup of an Origami is a subgroup of  $Sl_2(\mathbb{Z})$  of finite index. So we fix two generators

$$S = \begin{pmatrix} 0 & -1 \\ 1 & 0 \end{pmatrix}$$

and

$$T = \begin{pmatrix} 1 & 1 \\ 0 & 1 \end{pmatrix}.$$

### 2.1 The Free Group

In this package we fix the Free Group  $F$  generated by  $S$  and  $T$ .

# Index

ActionOfF2ViaCanonical, 3

ActionOfSl, 3

CalcStratum, 5

CalcVeechGroup, 5

CanonicalOrigami, 3

Cosets

for IsOrigami, 4

DegreeOrigami

for IsOrigami, 4

Equals, 4

ExampleOrigami, 5

HorizontalPerm

for IsOrigami, 4

RightActionOfF2ViaCanonical, 3

Stratum

for IsOrigami, 4

ToRec, 5

VeechGroup

for IsOrigami, 4

VerticalPerm

for IsOrigami, 4