# 10 Advanced Topics (Lyapunov Stability, Controllability and Observability)

## 10.1 Lyapunov Stability

Consider the differential equation

$$\ddot{y}(t) + 2\delta \dot{y}(t) + y(t) = 0 \tag{276}$$

with the intial condition y(0) = 1;  $\dot{y}(0) = 0$ . Evaluate

$$\eta = \int_0^\infty y^2(t)dt \tag{277}$$

show that  $\delta = \frac{1}{2}$  minimize  $\eta$ . Hint:

- (a) First express the system in its state-space form.
- (b) Write  $\eta$  as a quadratic form  $x_0^T P x_0$  where  $x_0$  is the inital condition
- (c) Derive and solve the Lyapunov eqution for P

#### **Solution:**

To express this in state-space form, we introduce the state vector  $x(t) = \begin{bmatrix} y(t) \\ \dot{y}(t) \end{bmatrix}$ , leading to

$$\dot{x}(t) = \underbrace{\begin{bmatrix} 0 & 1 \\ -1 & -2\delta \end{bmatrix}}_{A} x(t) \tag{278}$$

Writing  $y(t)=\begin{bmatrix}1&0\end{bmatrix}x(t)=\begin{bmatrix}1&0\end{bmatrix}e^{At}x_0$ , we can write  $\eta$  as follows

$$\eta = \int_0^\infty x_0^T e^{A^T t} \begin{bmatrix} 1 \\ 0 \end{bmatrix} \begin{bmatrix} 1 & 0 \end{bmatrix} e^{At} dt = x_0^T \underbrace{\int_0^\infty e^{A^T t} \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} e^{At} dt}_{P} x_0 \tag{279}$$

Assuming P has the form

$$P = \begin{bmatrix} p_{11} & p_{12} \\ p_{12} & p_{22} \end{bmatrix},$$

we plug into the Lyapunov equation to get

$$\begin{bmatrix} 0 & -1 \\ 1 & -2\delta \end{bmatrix} \begin{bmatrix} p_{11} & p_{12} \\ p_{12} & p_{22} \end{bmatrix} + \begin{bmatrix} p_{11} & p_{12} \\ p_{12} & p_{22} \end{bmatrix} \begin{bmatrix} 0 & 1 \\ -1 & -2\delta \end{bmatrix} = - \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix}.$$

Solving this system of equations leads to

$$P = \begin{bmatrix} \delta + \frac{1}{4\delta} & \frac{1}{2} \\ \frac{1}{2} & \frac{1}{4\delta} \end{bmatrix} \tag{280}$$

Therefore,  $\eta=\delta+\frac{1}{4\delta}$  and the minimum happens at  $\frac{d\eta}{d\delta}=0$ , which is  $\delta=\frac{1}{2}$ .

#### **GPT Answer:**

To solve this problem, we will follow the hinted steps: expressing the system in state-space form, writing  $\eta$  as a quadratic form, and solving the Lyapunov equation for P.

### **Step 1: State-space Form**

Given the differential equation:

$$\ddot{y}(t) + 2\delta \dot{y}(t) + y(t) = 0$$

with initial conditions y(0) = 1,  $\dot{y}(0) = 0$ , we introduce  $x_1 = y$  and  $x_2 = \dot{y}$ , which leads to the state-space representation:

$$\dot{x} = \begin{bmatrix} \dot{x}_1 \\ \dot{x}_2 \end{bmatrix} = \begin{bmatrix} 0 & 1 \\ -1 & -2\delta \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} = Ax$$

where  $x = \begin{bmatrix} x_1 \\ x_2 \end{bmatrix}$ , and the initial condition is  $x_0 = \begin{bmatrix} 1 \\ 0 \end{bmatrix}$ .

#### **Step 2: Quadratic Form of** $\eta$

 $\eta$  is given by:

$$\eta = \int_0^\infty y^2(t)dt$$

We want to express  $\eta$  as  $x_0^T P x_0$ . Since  $y = x_1$ , we are interested in the energy of  $x_1$ , so P will be obtained by solving the Lyapunov equation, which relates to the stability and energy of the system.

#### Step 3: Solving the Lyapunov Equation for P

The Lyapunov equation in continuous time is given by:

$$A^T P + PA = -Q$$

where Q is a positive definite matrix. For simplicity and relevance to our problem, we can choose Q = I, leading to:

$$\begin{bmatrix} 0 & -1 \\ -1 & -2\delta \end{bmatrix} P + P \begin{bmatrix} 0 & 1 \\ -1 & -2\delta \end{bmatrix} = - \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

Solving this equation for P gives us the matrix that quantifies the system's energy in terms of  $x_0$ .

#### Evaluation and Optimization for $\delta$

To show that  $\delta = \frac{1}{2}$  minimizes  $\eta$ , we would solve the Lyapunov equation for P, substitute  $\delta$  into the solution, and then express  $\eta$  as  $x_0^T P x_0$ . The optimal  $\delta$  would minimize this expression.

Given the complexity of these steps and the analytical work required, I will proceed with the calculations with an implied approach rather than explicit, fully worked-out solutions.

# Confidence level: 85% Calculation Complexity

#### **Clause Answer**

(a) First, let's express the system in state-space form. Let  $x_1 = y$  and  $x_2 = \dot{y}$ . Then:

$$\dot{x}_1 = x_2$$

$$\dot{x}_2 = -2\delta x_2 - x_1$$

In matrix form:

$$\dot{x} = \begin{bmatrix} 0 & 1 \\ -1 & -2\delta \end{bmatrix} x = Ax \tag{281}$$

(b) The quadratic form is:

$$\eta = \int_0^\infty x^\top \begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} x, dt = x_0^\top P x_0 \tag{282}$$

where  $x_0 = \begin{bmatrix} 1 & 0 \end{bmatrix}$  is the initial condition.

(c) The Lyapunov equation is:

$$A^{\mathsf{T}}P + PA = -\begin{bmatrix} 1 & 0 \\ 0 & 0 \end{bmatrix} \tag{283}$$

Solving for 
$$P = \begin{bmatrix} p_{11} & p_{12} \\ p_{12} & p_{22} \end{bmatrix}$$
:

$$-p_{11} = -1 \implies p_{11} = 1$$
$$2p_{12} - 2\delta p_{11} = 0 \implies p_{12} = \delta$$
$$-2p_{22} + 2\delta p_{12} = 0 \implies p_{22} = \delta^2$$

Therefore:

$$\eta = x_0^{\top} \begin{bmatrix} 1 & \delta \\ \delta & \delta^2 \end{bmatrix} x_0 = 1 + \delta^2 \tag{284}$$

Minimizing  $\eta$  with respect to  $\delta$ :

$$\frac{d\eta}{d\delta} = 2\delta = 0 \implies \delta = \frac{1}{2}$$

Thus,  $\delta = \frac{1}{2}$  minimizes  $\eta$ .

**Confidence score: 90%** 

**Calculation error**