# 11.3 Closed-Loop Transfer Function

The closed-loop should have an output  $y(t) \leq 0.05$  for reference commands  $n(t) = 10 \sin(\omega t)$  with  $\omega \geq 1000 \, \text{rad/sec}$ . This means that  $|T(j\omega)| \leq A$  for  $\omega \geq B \, \text{rad/sec}$ . What is the value of A and B?

## **Solution:**

(A, B) = (0.005, 1000).

Steps:

We have  $y(t) = -10|T(j\omega)|\sin(\omega t + \angle T(j\omega))$ .

Since  $y(t) \le 0.1$  for  $\omega \ge 1000 \, \text{rad/sec}$ , we must have:

$$|T(j\omega)| \le \frac{0.05}{10} = 0.005$$

for  $\omega \geq 1000 \, \mathrm{rad/sec.}$ 

#### **GPT Answer:**

The system's response y(t) to a reference command must be less than or equal to 0.05 for  $n(t) = 10 \sin(\omega t)$ , where  $\omega \geq 1000 \, \mathrm{rad/sec}$ . This condition translates to  $|T(j\omega)| \leq 0.005$  for  $\omega \geq 1000 \, \mathrm{rad/sec}$ . Therefore, A = 0.005 and B = 1000.

### **Confidence Level: 95%**

#### **Correct**

## **Claude Answer:**

Let's break this down step by step:

- 1) The output is  $y(t) = T(j\omega) \cdot n(t)$ , where  $T(j\omega)$  is the closed-loop transfer function.
- 2) We are given that  $n(t) = 10\sin(\omega t)$  and we want  $y(t) \le 0.05$  for  $\omega \ge 1000$  rad/sec.
- 3) Therefore, we can write:

$$|T(j\omega)\cdot 10\sin(\omega t)| \leq 0.05$$
 for  $\omega \geq 1000\,\mathrm{rad/\,sec}$ 

4) The maximum value of  $|\sin(\omega t)|$  is 1, so we can simplify this to:

$$|T(j\omega)| \cdot 10 \leq 0.05$$
 for  $\omega \geq 1000\,\mathrm{rad/sec}$ 

5) Dividing both sides by 10:

$$|T(j\omega)| \le 0.005$$
 for  $\omega \ge 1000$  rad/sec

6) So, comparing this to  $|T(j\omega)| \leq A$  for  $\omega \geq B$  rad/sec, we can see that:

$$A=0.005$$
 and  $B=1000\,\mathrm{rad/\,sec}$ 

Therefore, the values are: - A=0.005 -  $B=1000\,\mathrm{rad/\,sec}$  Confidence level: 95%

Correct