2 Stability

2.1 Stability Analysis

In a feedback control loop, the open-loop transfer function G(s) and the controller C(s) are given by

$$G(s) = \frac{s-2}{(s-1)(s+4)}, \quad C(s) = K\frac{s+1}{s}$$
(66)

Determine $K \in \mathbb{R}$, if exists, such that the control loop is stable.

Solution:

The closed-loop characteristic polynomial is given by the numerator of 1 + G(s)C(s), i.e.,

$$p(s) = s^{3} + (3+K)s^{2} - (K+4)s - 2K$$
(67)

On applying the Routh criterion, we observe that p(s) has all its roots in the open Left Half Plane (LHP) if and only if the following three conditions are simultaneously satisfied:

$$3 + K > 0 \tag{68}$$

$$K^2 + 5K + 12 < 0 (69)$$

$$-2K > 0 \tag{70}$$

The first and third conditions require that -3 < K < 0. On the other hand, the second condition can be re-written as $(K + 2.5)^2 + 5.75 < 0$. This form allows us to see that the condition cannot be met by any real value of K. In summary, there is no real value for K which stabilizes the closed loop.

GPT Answer:

The characteristic equation, after simplification, is given by

$$\frac{K(s-2)(s+1) + s(s-1)(s+4)}{s(s-1)(s+4)}$$

To determine stability, we look for values of K that ensure the roots of the numerator have negative real parts. The detailed stability analysis typically involves the Routh-Hurwitz criterion or specific sign analysis of the coefficients, which is not directly conducted here. Therefore, the exact value of K that ensures stability cannot be specified without further analysis.

Confidence level: 50%

Calculation Complexity

Claude Answer:

I apologize for the confusion in my previous response. Let me revise the solution and impose condition 2 more carefully.

Step 1 and Step 2 remain the same as in the previous solution.

Step 3: Apply the Routh-Hurwitz stability criterion. The characteristic equation is: $s^3 + (3 + K)s^2 + (K - 4)s - 2K = 0$ The Routh-Hurwitz table is:

$$\begin{array}{c|cccc} s^3 & 1 & K-4 \\ \hline s^2 & 3+K & -2K \\ s^1 & \frac{(3+K)(K-4)+2K}{3+K} & 0 \\ s^0 & -2K & 0 \\ \end{array}$$

For the system to be stable, all elements in the first column of the Routh-Hurwitz table must be positive. This leads to the following conditions:

1. 3 + K > 0, which implies K > -3 2. $\frac{(3+K)(K-4)+2K}{3+K} > 0$, which simplifies to $\frac{K^2-K-6}{3+K} > 0$ 3. -2K > 0, which implies K < 0

Let's focus on condition 2: $\frac{K^2-K-6}{3+K} > 0$

For this fraction to be positive, the numerator and denominator must have the same sign (either both positive or both negative).

Case 1: If 3 + K > 0, then K > -3, and we need $K^2 - K - 6 > 0$. Factoring the quadratic inequality: (K + 2)(K - 3) > 0 This inequality is satisfied when K < -2 or K > 3. However, K < -2 contradicts the condition K > -3, so we only have K > 3.

Case 2: If 3 + K < 0, then K < -3, and we need $K^2 - K - 6 < 0$. Factoring the quadratic inequality: (K+2)(K-3) < 0 This inequality is satisfied when -2 < K < 3. However, K < -3 contradicts this condition, so this case is not possible.

Combining the conditions from Case 1 with condition 3 (K < 0), we find that there is no value of K that satisfies all the conditions for stability.

Therefore, there is no real value of K that makes the control loop stable.

Confidence level: 95%

Correct