

7.5 Phase-Lag Controller

Consider the following system:

$$G(s) = \frac{10}{s(s+2)(s+5)}$$

Design a Phase-Lag controller such that it meets the following design specifications:


$$\zeta \geq 0.6, \quad e_{ss}|_{\text{ramp}} \leq 0.1$$

Solution :


Since transient response improvement is not aimed, we may use a static controller to satisfy the damping ratio requirement. Let $K = 0.7$; then, the closed-loop system has dominant roots at: $s = -0.8 \pm j0.8 (\zeta = 0.7)$. The characteristic polynomial is factored as:

$$\Delta(s) = (s + 5.38)(s^2 + 1.62s + 1.3)$$

Next, the velocity error constant is evaluated as: $K_v = 0.7$. In order to raise $K_v > 10$, we consider a phase-lag controller: $K(s) = \frac{s+0.02}{s+0.0012}$, where $\angle K(s_1) = -0.3^\circ$. The compensated system has: $K_v = 11.67$; hence $e_{ss}|_{\text{ramp}} \leq 0.1$. The ramp response of the closed-loop system is plotted to confirm the results.



(a) Root locus plot for phase-lag design



(b) Closed-loop system response

Figure 16: Root locus and response of the systems

With the addition of the phase-lag controller, the closed-loop transfer function is given as:

$$T(s) = \frac{7(s + 0.02)}{(s + 0.0202)(s + 5.38)(s^2 + 1.61s + 1.29)}$$

The closed-loop root at $s = -0.0202$ is almost canceled by the presence of the zero at $s = -0.02$. Hence, the slow mode $e^{-0.0202t}$ has a very small coefficient and only minimally affects the system response. The dominant closed-loop roots are also minimally affected.

GPT Answer :

To design a Phase-Lag controller for the given system $G(s) = \frac{10}{s(s+2)(s+5)}$ that meets the design specifications of $\zeta \geq 0.6$ and a steady-state error for a ramp input, $e_{ss}|_{\text{ramp}} \leq 0.1$, we must consider both the damping ratio (ζ) requirement for transient response and the steady-state error requirement for a ramp input.

The damping ratio ζ affects the transient response of the system. A higher ζ means less oscillation. To ensure the system has a damping ratio of at least 0.6, we look at the system's open-loop transfer function and its influence on the closed-loop system's poles. The Phase-Lag controller won't significantly alter the peak time or overshoot, as its primary function is to improve steady-state error, but it can impact the system damping. For this requirement, we might primarily adjust our system through the choice of compensator placement to ensure we're influencing the system's natural frequency and damping ratio appropriately, but let's focus on the second requirement for the design specifics of the Phase-Lag controller.

The steady-state error for a ramp input can be directly influenced by adding a pole at the origin or close to the origin, effectively increasing the system's type. The original system has a type 1 system (single integrator), and the steady-state error for a ramp input e_{ss} is given by $\frac{1}{K_v}$, where K_v is the velocity error constant. For a ramp input, to achieve $e_{ss} \leq 0.1$, we need $K_v \geq 10$.

The velocity error constant K_v of the open-loop transfer function $G(s)C(s)$ is given by the limit $\lim_{s \rightarrow 0} s \cdot G(s)C(s)$. For the given system, without the controller, $K_v = \lim_{s \rightarrow 0} s \cdot \frac{10}{s(s+2)(s+5)} = \frac{10}{10} = 1$, which is not sufficient.

A Phase-Lag controller, which generally has the form $C(s) = K \frac{1+T_l s}{1+\alpha T_l s}$ where $\alpha > 1$ and $T_l > 0$, can be used to increase the system's low-frequency gain without significantly affecting its high-frequency gain, thus increasing K_v .

To design such a controller to meet $K_v \geq 10$, we need to increase the low-frequency gain of the system by a factor of 10. The design of a Phase-Lag controller involves selecting α , T_l , and K to shape the frequency response appropriately while satisfying both the transient and steady-state specifications.

Given the specifics of the problem, the exact values for α , T_l , and K depend on detailed calculations involving the root locus or frequency response analysis to ensure both transient and steady-state requirements are met. Without performing these detailed calculations, the specific values for the Phase-Lag controller cannot be determined directly from the given information.

Confidence Level: 60%

Did not solve

Claude Answer :

To design a Phase-Lag controller that meets the given specifications, we need to follow these steps:

Step 1: Determine the steady-state error for a ramp input without the controller.

$$e_{ss}|_{\text{ramp}} = \frac{1}{\lim_{s \rightarrow 0} sG(s)} = \frac{1}{\lim_{s \rightarrow 0} s \cdot \frac{10}{s(s+2)(s+5)}} = \frac{1}{\lim_{s \rightarrow 0} \frac{10}{(s+2)(s+5)}} = \frac{1}{\frac{10}{2 \cdot 5}} = 0.5$$

Step 2: Calculate the required velocity error constant (K_v) to meet the steady-state error specification.

$$e_{ss}|_{\text{ramp}} = \frac{1}{K_v} \leq 0.1 \quad \Rightarrow \quad K_v \geq 10$$

Step 3: Design the Phase-Lag controller to achieve the required K_v and damping ratio. Let the Phase-Lag controller be:

$$G_c(s) = \frac{K(s+z)}{s+p}, \quad \text{where } z < p$$

The closed-loop transfer function with the controller is:

$$\frac{C(s)}{R(s)} = \frac{10K(s+z)}{s(s+p)(s+2)(s+5) + 10K(s+z)}$$

To meet the damping ratio requirement, we can use the dominant pole design method. Let the dominant poles be:

$$s_{1,2} = -\zeta\omega_n \pm j\omega_n\sqrt{1-\zeta^2}$$

For $\zeta = 0.6$ and assuming $\omega_n = 5$ (chosen to be close to the slowest pole of the original system), we get:

$$s_{1,2} = -3 \pm j4$$

Equating the denominator of the closed-loop transfer function with the desired characteristic equation:

$$s(s+p)(s+2)(s+5) + 10K(s+z) = (s+3+j4)(s+3-j4)(s+p)(s+2)$$

Comparing coefficients and solving for K and z , we get:

$$K = 2.5, \quad z = 0.5$$

The Phase-Lag controller is:

$$G_c(s) = \frac{2.5(s+0.5)}{s+p}, \quad \text{where } p > 0.5$$

We can choose $p = 1$ to ensure that $z < p$.

Therefore, the designed Phase-Lag controller is:

$$G_c(s) = \frac{2.5(s + 0.5)}{s + 1}$$

Confidence level: 90/100

Confidence Level: 60%

Did not solve