

{EPITECH}

TIME MANAGER

< API />



TIME MANAGER

Gotham City Hall wants to deploy the application on several platforms (mainly computers and different types of terminals). It is also considering a mobile version.

The goal of this project is to create a platform-independent API for exchanging and storing data.



Before you start, make sure you have **finished** and **assimilated all the concepts** covered in the Bootstrap.



The goal of this project is to get an API, and only an API. We do not want a front-end (HTML, JS). Use the right flags when creating!

Here is the list of mandatory schemas for your application :

```
users = {
  "username": "string - required - can't be null",
  "email":    "string - required - can't be null - X@X.X",
}

clocks = {
  "time":     "datetime - required - can't be null",
  "status":   "boolean - required - true ( when clock'in) - can't be null",
  "user":     "user - required - can't be null"
}

workingtime = {
  "start":    "datetime - required - can't be null - YYYY-MM-DD HH:mm:ss",
  "end":      "datetime - required - can't be null - YYYY-MM-DD HH:mm:ss",
  "user":     "user - required - can't be null"
}
```



Nothing fancy here, only obvious points. Obviously, you can add some more schemas and check the accuracy of your database after your migration.

Concerning the CRUD, here is a list of demanded endpoints

✓ USER

- a GET method : <http://localhost:4000/api/users?email=XXX&username=YYY>
- a GET method : <http://localhost:4000/api/users/:userID>
- a POST method : <http://localhost:4000/api/users>
- a PUT method : <http://localhost:4000/api/users/:userID>
- a DELETE method : <http://localhost:4000/api/users/:userID>

✓ WORKING TIME

- a GET (ALL) method : <http://localhost:4000/api/workingtime/:userID?start=XXX&end=YYY>
- a GET (ONE) method : <http://localhost:4000/api/workingtime/:userID/:id>
- a POST method : <http://localhost:4000/api/workingtime/:userID>
- a PUT method : <http://localhost:4000/api/workingtime/:id>
- a DELETE method : <http://localhost:4000/api/workingtime/:id>

✓ CLOCKING

- a GET method : <http://localhost:4000/api/clocks/:userID>
- a POST method : <http://localhost:4000/api/clocks/:userID>



The [POST](#) endpoint of this part handles both the departure and the arrival of the users; think hard about your route!



Be rigorous! Check carefully the accuracy of your database after your migration, and test extensively your different endpoints with [Postman](#)



Respect carefully the subject nomenclature for schemas and endpoints.

v 2.0.1

{EPITECH}