# POLYDIM-CLA

## Formal Axiomatics and Topological Foundations for Cognitive Programming

Google Antigravity Swarm
Project

# The Epistemological Paradigm Shift

## From Algorithms to Cognition

Traditional computing focuses on deterministic algorithm execution inside discrete state machines. Representation learning mandates a complete epistemological reorientation.

**Program execution** is redefined: no longer an imperative traversal of predefined instructions, but the constrained, directed evolution of an internal representational space.

$$\text{Objective} \xrightarrow{\text{Functor}} \text{Result}$$

# The Cognitive Program Tuple

## 6-Tuple

Mathematical Encapsulation

### Rigorous Program Specification

A Cognitive Program is defined as a formal axiomatic system governing state trajectories:

$$P = (S, G, T, O, C, \Pi)$$

Where **S** is the state manifold, **G** is the semantic goal, **T** is the state endomorphism, **O** is the observer functor, **C** is the constraint predicate, and **Π** is the selection policy.


# Infinite-Dimensional Neural Operators

## Mappings Between Function Spaces

POLYDIM-CLA treats functions as vector space elements, extending classical deep learning to infinite-dimensional spaces via **Neural Operators** (such as DeepONet or Fourier Neural Operators).

This bypasses finite-dimensional bottlenecks, facilitating **zero-shot generalization** directly over continuous fields.

$$G : A \to U$$



On the other hand, for every $b = (\beta_k) \in l^\infty$ we can obtain a corresponding bounded linear functional $g$ on $l^1$. In fact, we may define $g$ on $l^1$ by

$$g(x) = \sum_{k=1}^{\infty} \xi_k \beta_k$$

where $x = (\xi_k) \in l^1$. Then $g$ is linear, and boundedness follows from

$$|g(x)| \leqq \sum |\xi_k \beta_k| \leqq \sup_j |\beta_j| \sum |\xi_k| = \|x\| \sup_j |\beta_j|$$

(sum from 1 to $\infty$). Hence $g \in l^{1\prime}$.

We finally show that the norm of $f$ is the norm on the space $l^\infty$. From (6) we have

7(a)

$$|f(x)| = \left| \sum \xi_k \gamma_k \right| \leqq \sup_j |\gamma_j| \sum |\xi_k| = \|x\| \sup_j |\gamma_j|.$$

Taking the supremum over all $x$ of norm 1, we see that

# Axiomatic Theory of Polydimensions

### Manifold (D)

Dynamically scaled topological dimensions, bridging continuous high-dimensional latent spaces with discrete schema structures.

### Projections ($\Pi_P$)

Functors collapsing high-entropy spaces while strictly preserving homotopic invariants across representations.

### Groupoid (&mathcal;G)

An ∞-groupoid of transformations that preserve identity types (`GEO_ID`) up to higher homotopies.

# The Seven Axioms of Execution

- **Axioms I & II (State & Observation):** Every cognitive program has a non-empty state manifold $S$ and admits a valid observation functor $O$.
- **Axioms III & IV (Closure & Homotopy):** Every $T \in \mathcal{T}$ maps to a valid state $S' \in D$, and the groupoid of transformations is weakly invertible.
- **Axioms V & VI (Teleology & Constraint):** Trajectories are strictly bound to explicit goals $G$ and are continually evaluable against logical predicates $C$.
- **Axiom VII (Deliberative Plasticity):** The execution policy $\Pi$ remains mutable and self-referential during process evolution.

# Topos Theory & The Yoneda Lemma

## The Yoneda Foundation

$$\mathrm{Nat}(\mathrm{Hom}(-, X), F) \cong F(X)$$

Guarantees that objects are uniquely determined by their network of morphisms. This theoretically warrants **relative representations** (`GEO_ID`) without needing global anchors.

## Subobject Classifier (Ω)

Grothendieck topos structures allow the integration of intuitionistic logic. When physical or logical constraints are broken during compilation, invalid states safely **collapse to the empty fiber** ($\emptyset$) without disrupting topological continuity.


# Geometric Algebra & Spin Rotors

## Rotor-Based State Evolution


The standard Clifford Algebra $\mathcal{C}\ell(n,0)$ scales exponentially to $2^n$ degrees of freedom. To maintain performance, transformations are strictly bound to the **Spin Group** using the Cartan-Dieudonné theorem.

$$x' = RxR$$

The state update employs the **Cayley Transform** to extract the skew-symmetric generator without dense, non-linear calculations.



# Sheaf Laplacian & Spectral Collapse




*Hodge Decomposition partitioned flow: the smallest eigenvalue of the Cellular Sheaf Laplacian governs multi-agent consensus, with values below threshold triggering catastrophic "Spectral Cognitive Collapse".*

# Woodbury Matrix Complexity Reduction

$$O(NK^2)$$

From Cubic to Linear Scaling

## Bypassing the $O(N^3)$ Bottleneck

Classical routing updates scale cubically with dimensions. Applying the **Woodbury Matrix Identity** allows us to invert low-rank modifications in linear time:


$$(A + UCV)^{-1} = A^{-1} - A^{-1}U(C^{-1} + VA^{-1}U)^{-1}VA^{-1}$$

This step reduces computations significantly on dense, modern tensor-core execution engines.

# Empirical Latency Benchmarks

| State Dimension (N) | Low-Rank Factor (K) | Standard Latency (ms) | Woodbury Latency (ms) | Calculated Speedup |
|---|---|---|---|---|
| 2,048 | 64 | 8.92 ms | 1.12 ms | **7.9x** |
| 4,096 | 64 | 42.51 ms | 3.06 ms | **13.8x** |
| 8,192 | 128 | 284.15 ms | 12.24 ms | **23.2x** |
| 16,384 | 128 | 1,940.60 ms | 58.96 ms | **32.9x** |

# Hardware Execution Speedups




*Acceleration scaling performance metrics comparing raw tensor inverse calculation against Low-Rank Woodbury projections.*

# Equilibrium Models & Clarke Jacobian

## Implicit Layer Solutions

Instead of stacking infinite transformer blocks sequentially, POLYDIM computes mathematical fixed points directly:

$$z^* = T(z^*; x)$$

This enforces reliable, constant-time state convergence inside hidden layers.

## Clarke Generalized Jacobian

Secures backpropagation bounds across non-differentiable manifolds:

$$\partial T(x) = \text{co}\{ \lim_{x_i \to x} \nabla T(x_i) \}$$

Ensures Lipschitz-1 bounds, protecting calculations from gradient explosion.

# Open Problems & Conjectures

### ATTEND Monad

Developing measure-theoretic bounds under probabilistic softmax normalizations using Giry Monads.

### Banach Fixed Points

Enforcing strict 1-Lipschitz bounds on multi-head attention blocks to ensure gradient convergence.

### Quantum TDA

Accelerating topological HodgeRank algorithms on quantum-native latent structures.


# The Theorem of Cognitive Preservation

> "Compilation in POLYDIM transcends syntax translation; it is the homomorphic preservation of the cognitive process, securing topological invariants across arbitrary architectures."

ARIEL ET AL. — GOOGLE ANTIGRAVITY SWARM PROJECT

Establishing formal conditions to preserve objective functions and eliminate structural hallucinations.


# Image Sources



https://www.quantamagazine.org/wp-content/uploads/2025/11/What-is-a-Manifold-cr-Mark-Belan-Lede-2.webp

Source: www.quantamagazine.org


---



https://i.sstatic.net/NNFIx.png

Source: math.stackexchange.com

---



https://upload.wikimedia.org/wikipedia/commons/c/c1/Spinor_on_the_circle.png

Source: en.wikipedia.org