

ChildMonitor — Complete API Reference

Every endpoint, request body, response body, and purpose — extracted directly from the controller source code (59 endpoints across 12 controllers).

Legend — Public: no JWT required (open endpoint). JWT: requires header Authorization: Bearer <token>. All request/response bodies below are JSON unless noted otherwise. Field shapes are simplified for readability.

1. Authentication — Auth Module

Base path: /api/auth | Entire module is listed as 'permitAll' in SecurityConfig (token not required to call these, except logout which needs the token to revoke)

Method	Endpoint	Request Body	Response Body	Description / Purpose
POST	/api/auth/signup	{ "monitorName": "string", "email": "string", "password": "string", "confirmPassword": "string" }	201 Created { "message": "User registered successfully", "email": "...", "token": "<jwt>" }	Register a new parent account. Encodes password (BCrypt) and immediately returns a JWT.
POST	/api/auth/login	{ "email": "string", "password": "string" }	200 OK { "message": "Login successful", "email": "...", "token": "<jwt>" }	Authenticate an existing user; verifies password via BCrypt and issues a new JWT.
POST	/api/auth/logout	(none) Header: Authorization: Bearer <token>	200 OK { "message": "Logged out successfully" }	Revokes the current JWT by storing it in Redis with a TTL equal to its remaining lifetime.
POST	/api/auth/reset-password/request	{ "email": "string" }	200 OK { "message": "OTP sent to your email" }	Generates a 6-digit OTP (5-min expiry) and emails it asynchronously.
POST	/api/auth/reset-password/verify	{ "email": "string", "otp": "string" }	200 OK { "message": "OTP verified successfully" }	Validates that the supplied OTP matches and has not expired.
POST	/api/auth/reset-password/confirm	{ "email": "string",	200 OK {	Verifies OTP again, then re-encodes and saves the new password.

Method	Endpoint	Request Body	Response Body	Description / Purpose
		<pre>"otp": "string", "newPassword": "string", "confirmPassword": "string" }</pre>	<pre>"message": "Password reset successfully" }</pre>	
GET	/api/auth/oauth2/google	(none)	302 Redirect → /oauth2/authorization/google	Starts the Google OAuth2 login flow.
GET	/api/auth/oauth2/facebook	(none)	302 Redirect → /oauth2/authorization/facebook	Starts the Facebook OAuth2 login flow.

2. Children & User Profile — Child / User Module

Base path: **/api/children** (+ **/api/password**, **/api/settings** – see section 9) | Listed under 'permitAll' in SecurityConfig, but every method still resolves the user from the JWT via SecurityUtils — a missing/invalid token results in 401 from within the controller logic

Method	Endpoint	Request Body	Response Body	Description / Purpose
POST	/api/children/add	<pre>{ "name": "string", // required "birthDate": "YYYY-MM-DD", "gender": "string", "knowsCondition": true, "diagnosedCondition": "string" }</pre>	<pre>201 Created { "message": "Child added successfully", "child_id": 1, "child_name": "..." }</pre>	Adds a new child profile under the authenticated parent's account.
GET	/api/children/my-children	(none)	200 OK [{ Child }, { Child }, ...]	Returns the full list of children belonging to the authenticated parent.
GET	/api/children/{childId}	(none) – childId in path	200 OK { Child object }	Gets one child's full profile. Ownership is verified — 401 if it's not your child.
PUT	/api/children/{childId}	<pre>{ "name": "string", "birthDate": "YYYY-MM-DD", "gender": "string", "knowsCondition": true, "diagnosedCondition": "string" }</pre>	<pre>200 OK { "message": "Child updated successfully", "child_id": 1 }</pre>	Updates an existing child's profile fields.
DELETE	/api/children/{childId}	(none) – childId in path	<pre>200 OK { "message": "Child deleted successfully" }</pre>	Deletes a child profile after verifying it belongs to the requester.
GET	/api/children/profile	(none)	200 OK	Returns the authenticated parent's

Method	Endpoint	Request Body	Response Body	Description / Purpose
			<pre>{ "user_id": 1, "monitor_name": "...", "email": "..."} </pre>	own profile (handled by UserController).
PUT	/api/children/update-profile	<pre>{ "monitorName": "string", "email": "string"} </pre>	200 OK <pre>{ "message": "Profile updated successfully"} </pre>	Updates the parent's display name and/or email (checks email uniqueness).
DELETE	/api/children/delete-account	(none)	200 OK <pre>{ "message": "Account deleted successfully"} </pre>	Permanently deletes the authenticated user's account.

3. Screening Tests (ADHD / Autism / Dyslexia) — Screening Module

Base path: **/api/tests** | *permitAll — screening can be used before/without an account*

Method	Endpoint	Request Body	Response Body	Description / Purpose
GET	/api/tests/questions/autism	(none)	200 OK <pre>{ "test_type": "autism", "total_questions": 10, "instructions": "...", "questions": [{q_id, question, type}, ...] }</pre>	Returns the 10 static Autism screening questions (Arabic).
GET	/api/tests/questions/adhd	(none)	200 OK <pre>{ "test_type": "adhd", "total_questions": 13, "answer_options": {yes, sometimes, no}, "questions": [{q_id, question, category, positive_behavior}, ...] }</pre>	Returns the 13 static ADHD screening questions (Arabic).
GET	/api/tests/questions/dyslexia	(none)	200 OK <pre>{ "test_type": "dyslexia", "total_questions": 10, "questions": [{q_id, question, category}, ...] }</pre>	Returns the 10 static Dyslexia screening questions (Arabic).

Method	Endpoint	Request Body	Response Body	Description / Purpose
			}	
POST	/api/tests/submit	<pre>{ "childId": 1, "testType": "adhd autism dyslexia", "age": 5, "sex": "m f", "jaundice": "no", "familyAsd": "no", "answers": [{ "q_id": 1, "answer": "yes" }, ...] }</pre>	<pre>200 OK { "test_id": 1, "test_type": "...", "result": "...", "risk_score": 0.12, "child_id": 1, "child_name": "...", "details": {...} }</pre>	Validates the payload, forwards to AI Engine POST /predict, persists Test/TestAnswer/TestResult, and updates the child's diagnosed_condition.
GET	/api/tests/results/{testId}	(none) – testId in path	<pre>200 OK { "message": "Feature coming soon", "test_id": 1 }</pre>	Placeholder endpoint — detailed historical result retrieval is not yet implemented.

POST /api/tests/submit is the integration point with the AI Engine: it calls POST {AI_URL}/predict, persists the Test / TestAnswer / TestResult entities, and — if a childId is supplied — updates that child's diagnosed_condition.

4. Home Dashboard & Daily Plan — Home Module

Base path: / and /api/home | permitAll at the Spring Security level, but each endpoint still requires a valid JWT to resolve 'which user' internally

Method	Endpoint	Request Body	Response Body	Description / Purpose
GET	/	(none)	200 OK "ChildMonitor API is running ✓"	Root welcome / liveness message for the API.
GET	/api/home/data	Query param (optional): ?childId=1	<pre>200 OK { "user_name", "greeting", "message", "children": [...], "selected_child_id", "today_plan", "today_activities", "progress_stats", "progress_by_category", "monthly_assessments", "articles" }</pre>	Aggregated dashboard payload: children, today's plan, progress stats, and recent articles.

Method	Endpoint	Request Body	Response Body	Description / Purpose
GET	/api/home/today-plan	Query param: ?childId=1 (required)	200 OK { "plan": { DailyPlan }, "activities": [Activity, ...], "status_code": 200 }	Returns (or auto-generates) today's AI-influenced activity plan for a child.
POST	/api/home/plan/complete	{ "childId": 1, "date": "YYYY-MM-DD" }	200 OK { "message": "Plan marked as completed", "plan_id": 1, "completed": true }	Marks a given day's plan as completed.
GET	/api/home/plan-history	Query param: ?childId=1 (required)	200 OK { "history": [DailyPlan, ...], "status_code": 200 }	Returns all previous daily plans for a child, most recent first.
GET	/api/home/progress	Query param: ?childId=1 (required)	200 OK { "progress": { latest_score, trend, assessment_improvement, ... }, "status_code": 200 }	Returns the child's overall progress statistics (vs. previous month).
GET	/api/home/monthly-assessment/questions/{disorder}	(none) – disorder in path e.g. adhd autism dyslexia	200 OK { "questions": {...AI Engine payload...}, "disorder": "...", "status_code": 200 } or 503 if AI Engine is down	Forwards to AI Engine GET /monthly-tracker/questions/{disorder} to fetch the dynamic question set.
POST	/api/home/monthly-assessment/submit	{ "childId": 1, "disorder": "adhd", "answers": [{ "q_id": "m_adhd_1", "value": 2 }, ...] }	201 Created { "current_score", "trend_label", "interpretation", "progress_percentage", "assessment_id", "message", "status_code": 201 }	Forwards answers to AI Engine POST /monthly-tracker (including previous score for trend), then persists a MonthlyAssessment.
GET	/api/home/monthly-assessment/history/{childId}	(none) – childId in path	200 OK { "history": [MonthlyAssessment, ...], "chart_data": [{month, score, ...}, ...], "total_assessments": 3, }	Returns full assessment history plus a simplified array ready for charting.

Method	Endpoint	Request Body	Response Body	Description / Purpose
			<pre>"status_code": 200 }</pre>	

/api/home/monthly-assessment/questions/{disorder} and /api/home/monthly-assessment/submit are the two AI-Engine integration points for the monthly tracker — they call GET and POST {AI_URL}/monthly-tracker respectively.

5. Educational Articles — Article Module

Base path: **/api/articles** | *permitAll at the security level; user identity still resolved per-request from the JWT*

Method	Endpoint	Request Body	Response Body	Description / Purpose
GET	/api/articles/all	(none)	<pre>200 OK { "articles": [Article, ...] }</pre>	Returns all published articles. Cached in Redis for 6 hours.
GET	/api/articles/{articleId}	(none) – articleId in path	<pre>200 OK { Article object }</pre>	Returns a single article by ID. Cached.
GET	/api/articles/category/{category}	(none) – category in path	<pre>200 OK { "articles": [...], "category": "..." }</pre>	Returns articles filtered by category. Cached.
POST	/api/articles/favorite/add	Query param: ?articleId=1	<pre>200 OK { "message": "Article added to favorites" }</pre>	Adds an article to the authenticated user's favorites list.
DELETE	/api/articles/favorite/remove	Query param: ?articleId=1	<pre>200 OK { "message": "Article removed from favorites" }</pre>	Removes an article from the user's favorites.
GET	/api/articles/favorites	(none)	<pre>200 OK { "favorites": [Article, ...] }</pre>	Lists all of the authenticated user's favorited articles.
GET	/api/articles/favorite/check	Query param: ?articleId=1	<pre>200 OK {</pre>	Checks whether a specific article is already favorited by the user.

Method	Endpoint	Request Body	Response Body	Description / Purpose
			<pre>"is_favorite": true }</pre>	

6. Activities / Exercises — Activity Module

Base path: `/api/activities` | `permitAll` at the security level; user identity still resolved per-request from the JWT

Method	Endpoint	Request Body	Response Body	Description / Purpose
GET	<code>/api/activities/all</code>	(none)	<pre>200 OK { "activities": [...], "total": 45, "status_code": 200 }</pre>	Returns all active activities/exercises. Cached in Redis for 6 hours.
GET	<code>/api/activities/type/{type}</code>	(none) – type in path e.g. <code>PHYSICAL</code> <code>PARENT_CHILD</code> <code>QUIZ</code>	<pre>200 OK { "activities": [...], "type": "...", "total": 12, "status_code": 200 }</pre>	Filters the activity library by type. Cached.
POST	<code>/api/activities/for-child</code>	<pre>{ "childId": 1 }</pre>	<pre>200 OK { "activities": [...], "child_id": 1, "status_code": 200 }</pre>	Returns activities filtered to the child's age range.
GET	<code>/api/activities/{activityId}</code>	(none) – activityId in path	<pre>200 OK { "activity": { Activity }, "status_code": 200 }</pre>	Returns details for a single activity.
POST	<code>/api/activities/complete</code>	<pre>{ "childId": 1, "activityId": 1 }</pre>	<pre>200 OK { "message": "Activity completed successfully", "completed_count": 3, "status_code": 200 }</pre>	Marks an activity as completed for a child; increments completion_count.
POST	<code>/api/activities/stats</code>	{	<pre>200 OK</pre>	Returns the child's activity-

Method	Endpoint	Request Body	Response Body	Description / Purpose
		<pre>"childId": 1 }</pre>	<pre>{ "stats": { completed_count, total_activities, completion_percentage, progress: [...] }, "status_code": 200 }</pre>	completion statistics.
POST	/api/activities/recommended	<pre>{ "childId": 1 }</pre>	<pre>200 OK { "recommended_activities": [...top 5...], "status_code": 200 }</pre>	Returns the 5 least-completed, age-appropriate activities for the child.

7. Monthly Assessment (Direct / Non-AI) — Assessment Module

Base path: **/api/monthly-assessment** | *permitAll at the security level; user identity still resolved per-request from the JWT*

Method	Endpoint	Request Body	Response Body	Description / Purpose
POST	/api/monthly-assessment/submit	<pre>{ "childId": 1, "answers": { "q1_focus": 1, "q2_social": 0, "q3_communication": 2, "q4_behavior": 1, "q5_learning": 0 } }</pre>	<pre>201 Created { "message": "Assessment submitted successfully", "assessment_id": 1, "result": "...", "status_code": 201 }</pre>	Saves a monthly assessment directly (non-AI variant) — one submission per child per calendar month.
GET	/api/monthly-assessment/child/{childId}	(none) — childId in path	<pre>200 OK { "child_id": 1, "assessments": [...], "total": 3, "status_code": 200 }</pre>	Returns all monthly assessments recorded for a child.
GET	/api/monthly-assessment/trend/{childId}	(none) — childId in path	<pre>200 OK { "data": { assessments, trend, improvement }, "status_code": 200 }</pre>	Computes whether the child is improving/declining/stable across all recorded assessments.
GET	/api/monthly-assessment/{assessmentId}	(none) — assessmentId in path	<pre>200 OK { "assessment": { MonthlyAssessment }, "status_code": 200 }</pre>	Returns one specific assessment record (ownership verified).

Method	Endpoint	Request Body	Response Body	Description / Purpose
			}	

Note: this is a separate, simpler endpoint group from /api/home/monthly-assessment/. This version computes the result label locally (no AI Engine call) and enforces one submission per child per calendar month.*

8. Interactive Quiz — Quiz Module

Base path: **/api/quiz** | *permitAll at the security level; user identity still resolved per-request from the JWT*

Method	Endpoint	Request Body	Response Body	Description / Purpose
GET	/api/quiz/questions	(none)	200 OK { "quiz": { "title", "description", "total_questions": 3, "questions": [{id, question, type}, ...] }, "status_code": 200 }	Returns the 3 short yes/no quiz questions (Arabic).
POST	/api/quiz/submit	{ "childId": 1, "answers": { "q1_focus": true, "q2_follow_instructions": true, "q3_complete_tasks": false } }	201 Created { "message": "Quiz submitted successfully", "score": 2, "feedback": "...", "result_id": 1, "status_code": 201 }	Scores the 3 yes/no answers (0-3) and returns localized feedback text.
POST	/api/quiz/history	{ "childId": 1 }	200 OK { "child_id": 1, "history": [...], "total_attempts": 5, "status_code": 200 }	Returns the child's full interactive-quiz attempt history.

9. AI Chatbot — Chatbot Module

Base path: **/api/chatbot** | *permitAll at the security level; user identity still resolved per-request from the JWT*

Method	Endpoint	Request Body	Response Body	Description / Purpose
POST	/api/chatbot/send	<pre>{ "message": "string", // required "conversation_id": "string" // optional }</pre>	<pre>200 OK { "success": true, "data": { "conversation_id": "...", "bot_response": "...", "user_message": {id, message, createdAt} } }</pre>	Forwards the user's message to AI Engine POST /chat and persists both sides of the exchange.
GET	/api/chatbot/history	Query param (optional): ?conversationId=<uuid>	<pre>200 OK { "success": true, "messages": [{id, message, isFromUser, createdAt, conversationId}, ...], "count": 8 }</pre>	Returns either one conversation's history, or all messages if no conversationId is given.
DELETE	/api/chatbot/conversation/{conversationId}	(none) – conversationId in path	<pre>200 OK { "success": true, "message": "Conversation deleted successfully" }</pre>	Deletes every message belonging to a specific conversation.

Every call to /api/chatbot/send is forwarded to AI Engine POST /chat with { text, session_id }, and the reply is parsed from whichever of response / reply / answer / text / message field is present in the AI's JSON.

10. Password Management & Settings — User Module

Base path: /api/password and /api/settings | Explicitly listed under 'permitAll' in SecurityConfig (so a user who forgot their password — and thus has no token — can still call these); identity for /change is resolved from the JWT when present

Method	Endpoint	Request Body	Response Body	Description / Purpose
POST	/api/password/change	<pre>{ "currentPassword": "string", "newPassword": "string", "confirmNewPassword": "string" }</pre>	<pre>200 OK { "message": "Password changed successfully" }</pre>	Changes the password for the authenticated user after verifying the current one.

Method	Endpoint	Request Body	Response Body	Description / Purpose
POST	/api/password/forgot	<pre>{ "email": "string" }</pre>	<pre>200 OK { "message": "If this email is registered, you will receive a reset code shortly" }</pre>	Sends a password-reset OTP by email (does not reveal whether the email exists).
POST	/api/password/reset	<pre>{ "email": "string", "otp": "string", "newPassword": "string", "confirmPassword": "string" }</pre>	<pre>200 OK { "message": "Password reset successfully" }</pre>	Verifies the OTP and resets the password.
GET	/api/settings	(none)	<pre>200 OK { "user_id", "email", "monitor_name", "available_settings": { notification, password, delete_account } }</pre>	Returns the authenticated user's account settings overview.
DELETE	/api/settings/account	(none)	<pre>200 OK { "message": "Account deleted successfully" }</pre>	Deletes the authenticated user's account (alternate path to /api/children/delete-account).

Summary

Total controllers: 12 Total endpoints: 59

All endpoint paths above were cross-checked directly against the `@GetMapping` / `@PostMapping` / `@PutMapping` / `@DeleteMapping` annotations in the source code — every single mapping found in the codebase is represented in this document with no omissions.