


Taxa and metacoder: R packages for parsing, visualization, and manipulation of taxonomic data

Zachary Foster, Scott Chamberlain, Thomas Sharpton, and
Niklaus Grünwald


The challenges of taxonomic data



- ▶ Taxonomic data is hierarchical
- ▶ Associated with tabular data
- ▶ Can be names, classifications, or IDs
- ▶ Many different taxonomic systems
- ▶ Many different data formats
- ▶ Hierarchical visualization is difficult

Sources of taxonomic data

DNA sequence databases



Species occurrence databases



Museum records



Sources of taxonomic data: DNA sequences

NCBI GenBank

```
>AC073210.8 Homo sapiens BAC clone RP11-460N20 from 7, complete sequence  
AACGAACGCTGGCGGCATGCCTAACACATGCAAGTCGAACGAGACCTTCGGGTC...
```

UNITE

```
>SH099456.05FU_FJ357315_refs k__Fungi;p__Ascomycota;c__Dothideomycetes  
;o__Pleosporales;f__Pleosporaceae;g__Embellisia;s__Embellisia_planifunda  
GCTGGCGGCGTGCCTAACACATGTAAGTCGAACGGGACTGGGGGCAACTCCAGT...
```

RDP

```
>S000448483 Sparassis crispa; MBUH-PIRJ0&ILKKA94-1587/ss5  
Lineage=Root;rootrank;Fungi;domain;Basidiomycota;phylum;Agaricomycetes;  
class;Polyporales;order;Sparassidaceae;family;Sparassis;genus  
AGAGTTTGATCCTGGCTCAGATTGAACGCTGGCGGAATGCTTAACACATGAAAC...
```

SILVA

```
>GCVF01000431.1.2369 Bacteria;Proteobacteria;Gammaproteobacteria;  
Oceanospirillales;Alcanivoraceae;Alcanivorax;Thalassiosira rotula  
AGAGTTTGATCCTGGCTCAGGATGAACGCTGGCGGTATGCTTAACACATGCAAG...
```

Sources of taxonomic data: DNA sequences

NCBI GenBank

>AC073210.8 Homo sapiens BAC clone RP11-460N20 from 7, complete sequence
AACGAACGCTGGCGGCATGCCTAACACATGCAAGTCGAACGAGACCTTCGGGTC...

UNITE

>SH099456.05FU_FJ357315_refs k__Fungi;p__Ascomycota;c__Dothideomycetes
;o__Pleosporales;f__Pleosporaceae;g__Embellisia;s__Embellisia_planifunda
GCTGGCGGCGTGCCTAACACATGTAAGTCGAACGGGACTGGGGCAACTCCAGT...

RDP

>S000448483 Sparassis crispa; MBUH-PIRJ0&ILKKA94-1587/ss5
Lineage=Root;rootrank;Fungi;domain;Basidiomycota;phylum;Agaricomycetes;
class;Polyporales;order;Sparassidaceae;family;Sparassis;genus
AGAGTTTGATCCTGGCTCAGATTGAACGCTGGCGGAATGCTTAACACATGAAAC...

SILVA

>GCVF01000431.1.2369 Bacteria;Proteobacteria;Gammaproteobacteria;
Oceanospirillales;Alcanivoraceae;Alcanivorax;Thalassiosira rotula
AGAGTTTGATCCTGGCTCAGGATGAACGCTGGCGGTATGCTTAACACATGCAAG...

Sources of taxonomic data: Occurrence records

Global Biodiversity Information Facility : Archaea database

```
readr::read_tsv("datasets/gbif_archaea.csv")[4:8]
```

```
# A tibble: 19,013 x 5
```

	kingdom	phylum	class	order	family
	<chr>	<chr>	<chr>	<chr>	<chr>
1	Archaea	Euryarchaeota	Halobacteria	Halobacteriales	Halobacteriaceae
2	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
3	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
4	Archaea	Crenarchaeota	Thermoprotei	Desulfurococcales	Desulfurococcaceae
5	Archaea	Crenarchaeota	Thermoprotei	Desulfurococcales	Pyrodictiaceae
6	Archaea	Crenarchaeota	Thermoprotei	Thermoproteales	Thermoproteaceae
7	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
8	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
9	Archaea	Euryarchaeota	Halobacteria	Halobacteriales	Halobacteriaceae
10	Archaea	Euryarchaeota	Halobacteria	Halobacteriales	Halobacteriaceae

```
# ... with 19,003 more rows
```

Sources of taxonomic data: Museum records

Smithsonian Museum of Natural History: Mammal database

```
readr::read_csv("datasets/SNMNH.csv")[9]
```

```
# A tibble: 5,000 x 1
```

```
  `Name Hierarchy`
```

```
  <chr>
```

```
1 Abditomys latidens : Muridae : Rodentia : Mammalia : Chordata
```

```
2 Abrawayaomys ruschii : Cricetidae : Rodentia : Mammalia : Chordata
```

```
3 Abrawayaomys ruschii : Cricetidae : Rodentia : Mammalia : Chordata
```

```
4 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
5 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
6 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
7 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
8 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
9 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
10 Abrocoma bennettii bennettii : Abrocomidae : Rodentia : Mammalia : Chordata
```

```
# ... with 4,990 more rows
```

The taxa package


build **passing** codecov **87%** repo status **WIP** downloads **311/month** CRAN **0.2.1**

The taxa package is designed to be a solid foundation for using taxonomic data in R.

- ▶ R6 classes to hold taxa, taxonomies, and associated data
- ▶ Flexible parsers to convert raw data to these classes
- ▶ Dplyr-inspired functions to manipulate these classes
- ▶ Functions to get data associated with each taxon in a taxonomy


The metacoder package: visualization of taxon data

```
readr::read_tsv("datasets/gbif_archaea.csv") %>%  
  parse_tax_data(class_cols = 4:8) %>%  
  filter_taxa(taxon_names != "") %>%  
  heat_tree(node_label = taxon_names, node_color = n_obs,  
            node_size = n_obs, layout = "da")
```




Classes defined by taxa

Classes defined by taxa: Relationships



Classes defined by taxa: Relationships



Classes defined by taxa: The taxmap class

```
> ex_taxmap
```

```
<Taxmap>
```

```
17 taxa: b. Mammalia, c. Plantae, d. Felidae ... p. sapiens, q. lycopersicum, r. tuberosum
```

```
17 edges: NA->b, NA->c, b->d, b->e, b->f, c->g, d->h ... h->m, i->n, j->o, k->p, l->q, l->r
```

```
4 data sets:
```

```
info:
```

```
# A tibble: 6 x 4
```

```
  taxon_id name  n_legs dangerous
```

```
  <chr>    <chr>  <dbl> <lgl>
```

```
1 m      tiger    4. TRUE
```

```
2 n      cat      4. FALSE
```

```
3 o      mole     4. FALSE
```

```
# ... with 3 more rows
```

```
phylopic_ids: a named vector of 'character' with 6 items
```

```
  m. e148eabb-f138-43c6-b1e4-5cda2180485a ... r. 63604565-0406-460b-8cb8-1abe954b3f3a
```

```
foods: a list of 6 items named by taxa:
```

```
  m, n, o, p, q, r
```

```
abund:
```

```
# A tibble: 8 x 5
```

```
  taxon_id code  sample_id count taxon_index
```

```
  <chr>    <fct> <fct>    <dbl>    <int>
```

```
1 m      T    A        1.        1
```

```
2 n      C    A        2.        2
```

```
3 o      M    B        5.        3
```

```
# ... with 5 more rows
```

Parsing

Parsing

Input data format

	Simple	Embedded	Raw string
	<pre>> print(data) [1] "input_1" "input_2" [3] "input_3"</pre>	<pre>> print(data) x input y 1 a input_1 100 2 b input_2 200 3 c input_3 300</pre>	<pre>> print(data) [1] ">id:a-tax:input_1" [2] ">id:b-tax:input_2" [3] ">id:c-tax:input_3"</pre>
Classification Primates;Hominidae;Homo;sapiens	<pre>> print(data) [1] "Primates;Hominidae;Hom..." [2] "Primates;Haplorhini;Cr..." > parse_tax_data(data, class_sep = ";")</pre>	<pre>> print(data) x class y 1 a Primates;Hominidae;... 100 2 b Primates;Haplorhini... 200 > parse_tax_data(data, class_cols = "class", class_sep = ";")</pre>	<pre>> print(data) [1] ">id:a-tax:Primates;Hom..." [2] ">id:b-tax:Primates;Hap..." > extract_tax_data(data, regex = ">id:(.)-tax:(.)", key = c("info", "class"), class_sep = ";")</pre>
Taxon ID 9606	<pre>> print(data) [1] "9606" "100937" ... > lookup_tax_data(data, type = "taxon_id")</pre>	<pre>> print(data) x id y 1 a 9606 100 2 b 100937 200 > lookup_tax_data(data, type = "taxon_id", column = "id")</pre>	<pre>> print(data) [1] ">id:a-tax:9606" [2] ">id:b-tax:100937" > extract_tax_data(data, regex = ">id:(.)-tax:(.)", key = c("info", "taxon_id"), database = "ncbi")</pre>
Taxon name Homo sapiens	<pre>> print(data) [1] "Homo sapiens" [2] "Primates" ... > lookup_tax_data(data, type = "taxon_name")</pre>	<pre>> print(data) x name y 1 a Homo sapiens 100 2 b Primates 200 > lookup_tax_data(data, type = "taxon_name", column = "name")</pre>	<pre>> print(data) [1] ">id:a-tax:Homo sapiens" [2] ">id:b-tax:Primates" > extract_tax_data(data, regex = ">id:(.)-tax:(.)", key = c("info", "taxon_name"), database = "ncbi")</pre>
Sequence ID AC073210	<pre>> print(data) [1] "AC073210" "KC312885" ... > lookup_tax_data(data, type = "seq_id")</pre>	<pre>> print(data) x ncbi_id y 1 a AC073210 100 2 b KC312885 200 > lookup_tax_data(data, type = "seq_id", column = "ncbi_id")</pre>	<pre>> print(data) [1] ">id:a-tax:AC073210" [2] ">id:b-tax:KC312885" > extract_tax_data(data, regex = ">id:(.)-tax:(.)", key = c("info", "seq_id"), database = "ncbi")</pre>

Input type

Parsing: vectors of classifications

```
x <- c("Mammalia;Theria;Metatheria;Diprotodontia;Macropodiformes",  
      "Mammalia;Theria;Eutheria;Primates;Haplorrhini;Simiiformes")  
  
parse_tax_data(x, class_sep = ";")
```

<Taxmap>

9 taxa: b. Mammalia, c. Theria ... j. Simiiformes

9 edges: NA->b, b->c, c->d, c->e, d->f, e->g, f->h, g->i, i->j

1 data sets:

tax_data: a named vector of 'character' with 2 items

h. Mammalia;Theria;[truncated] ... j. Mammalia;Theria;[truncated]

0 functions:

Parsing: vectors of names

```
x <- c("Homo sapiens", "Macropus", "Chordata")  
  
lookup_tax_data(x, type = "taxon_name", database = "ncbi")
```

```
<Taxmap>  
35 taxa: 131567. cellular organisms ... 9606. Homo sapiens  
35 edges: NA->131567, 131567->2759 ... 207598->9605, 9605->9606  
2 data sets:  
  tax_data:  
    # A tibble: 35 x 4  
      taxon_id ncbi_name          ncbi_rank  ncbi_id  
    <chr>    <chr>          <chr>    <chr>  
1 131567    cellular organisms no rank    131567  
2 2759      Eukaryota          superkingdom 2759  
3 33154     Opisthokonta       no rank    33154  
# ... with 32 more rows  
  query_data: a named vector of 'character' with 3 items  
    9606. Homo sapiens, 9312. Macropus, 7711. Chordata  
0 functions:
```

Parsing: vectors of taxon or sequence IDs

Taxon IDs

```
x <- c("9606", "207598", "7711") # NCBI taxon IDs  
lookup_tax_data(x, type = "taxon_id", database = "ncbi")
```

Sequence IDs

```
x <- c("AC073210", "MG014608", "AE006468") # NCBI sequence IDs  
lookup_tax_data(x, type = "seq_id", database = "ncbi")
```

Parsing: tables

Global Biodiversity Information Facility : Archaea database

```
readr::read_tsv("datasets/gbif_archaea.csv")[4:8]
```

```
# A tibble: 19,013 x 5
```

	kingdom	phylum	class	order	family
	<chr>	<chr>	<chr>	<chr>	<chr>
1	Archaea	Euryarchaeota	Halobacteria	Halobacteriales	Halobacteriaceae
2	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
3	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
4	Archaea	Crenarchaeota	Thermoprotei	Desulfurococcales	Desulfurococcaceae
5	Archaea	Crenarchaeota	Thermoprotei	Desulfurococcales	Pyrodictiaceae
6	Archaea	Crenarchaeota	Thermoprotei	Thermoproteales	Thermoproteaceae
7	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
8	Archaea	Euryarchaeota	Thermococci	Thermococcales	Thermococcaceae
9	Archaea	Euryarchaeota	Halobacteria	Halobacteriales	Halobacteriaceae
10	Archaea	Euryarchaeota	Halobacteria	Halobacteriales	Halobacteriaceae

```
# ... with 19,003 more rows
```

Parsing: tables

```
x = readr::read_tsv("datasets/gbif_archaea.csv")  
  
parse_tax_data(x, class_cols = 4:8)
```

<Taxmap>

95 taxa: ab. Archaea, ac. Euryarchaeota ... dr. Methermicoccaceae

95 edges: NA->ab, ab->ac, ab->ad ... aw->dp, at->dq, ax->dr

1 data sets:

tax_data:

A tibble: 19,013 x 45

	taxon_id <chr>	gbifid <dbl>	datasetkey <chr>	occurrenceid <chr>	kingdom <chr>	phylum <chr>	class <chr>
1	br	1.84e9	3c6e7390~	D7C42A39-3A~	Archaea	Eurya~	Halo~
2	bs	1.83e9	863efcc4~	<NA>	Archaea	Eurya~	Ther~
3	bs	1.83e9	863efcc4~	<NA>	Archaea	Eurya~	Ther~

... with 1.901e+04 more rows, and 38 more variables:

order <chr>, family <chr>, genus <chr>, species <chr>,
infraspecific epithet <lg1>, taxonrank <chr>,
scientificname <chr>, countrycode <chr>, locality <chr>,
publishingorgkey <chr>, ...

0 functions:

Parsing: complex strings (NCBI Genbank)

```
x = c("AC073210.8 Homo sapiens BAC clone RP11-460N20 from 7, complete sequence"  
      "AE006468.2 Salmonella enterica subsp. enterica serovar Typhimurium",  
      "MG014608.1 Macropus fuliginosus Csflr gene, enhancer")  
  
extract_tax_data(x, database = "ncbi", regex = "([A-Z0-9.]+) (.+)",  
                 key = c(my_ncbi_id = "seq_id", my_desc = "info"))
```

<Taxmap>

46 taxa: 131567. cellular organisms ... 9606. Homo sapiens
46 edges: NA->131567, 131567->2759 ... 207598->9605, 9605->9606
2 data sets:

tax_data:

A tibble: 46 x 4

	taxon_id	ncbi_name	ncbi_rank	ncbi_id
	<chr>	<chr>	<chr>	<chr>
1	131567	cellular organisms	no rank	131567
2	2759	Eukaryota	superkingdom	2759
3	33154	Opisthokonta	no rank	33154

... with 43 more rows


query_data:

A tibble: 3 x 4

	taxon_id	my_ncbi_id	my_desc	input
	<chr>	<chr>	<chr>	<chr>
1	9606	AC073210.8	Homo sapiens BAC cl~	AC073210.8 Homo sap~
2	99287	AE006468.2	Salmonella enterica~	AE006468.2 Salmonel~


Taxon attributes

Taxon attributes: Taxonomy terminology




Taxon attributes: subtaxa and supertaxa


Subtaxa (recursive = T)




Supertaxa (recursive = T)



Subtaxa (recursive = F)




Supertaxa (recursive = F)




Taxon attributes: parts of a tree


Leaves




Stems



Roots



Internodes



Taxon attributes: functions

Ranks, names, and IDs

`taxon_names`, `taxon_ranks`, `taxon_ids`

Parts of the tree

`branches`, `internodes`, `leaves`, `roots`, `stems`, `supertaxa`,
`subtaxa`

Filtering helpers

`is_branch`, `is_internode`, `is_leaf`, `is_root`, `is_stem`

Numbers of supertaxa/subtaxa/data

`n_supertaxa`, `n_subtaxa`, `n_obs`, `n_supertaxa_1`,
`n_subtaxa_1`, `n_obs_1`

Taxon attributes: Ranks, names, and IDs

These are derived from the list of taxon objects.

```
taxon_names(ex_taxmap) %>% head
```

b	c	d	e	f
"Mammalia"	"Plantae"	"Felidae"	"Notoryctidae"	"Hominidae"
g				
"Solanaceae"				

```
taxon_ranks(ex_taxmap) %>% head
```

b	c	d	e	f	g
"class"	"kingdom"	"family"	"family"	"family"	"family"

```
taxon_ids(ex_taxmap) %>% head
```

b	c	d	e	f	g
"b"	"c"	"d"	"e"	"f"	"g"

Taxon attributes: subtaxa

These return a list of vectors named by taxon IDs.

```
subtaxa(ex_taxmap, value = "taxon_names")[1:3]
```

\$b

	d	h	m	i	n
	"Felidae"	"Panthera"	"tigris"	"Felis"	"catus"
	e	j	o	f	k
	"Notoryctidae"	"Notoryctes"	"typhlops"	"Hominidae"	"homo"
	p				
	"sapiens"				

\$c

	g	l	q	r
	"Solanaceae"	"Solanum"	"lycopersicum"	"tuberosum"

\$d

	h	m	i	n
	"Panthera"	"tigris"	"Felis"	"catus"

Taxon attributes: subtaxa

These return a list of vectors named by taxon IDs.

```
subtaxa(ex_taxmap, value = "taxon_names", recursive = FALSE)[1:3]
```

\$b

d	e	f
"Felidae"	"Notoryctidae"	"Hominidae"

\$c

g
"Solanaceae"

\$d

h	i
"Panthera"	"Felis"

Taxon attributes: counts

These return counts of things per taxon.

```
n_subtaxa(ex_taxmap)
```

	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r
	11	4	4	2	2	3	1	1	1	1	2	0	0	0	0	0	0

```
n_supertaxa(ex_taxmap)
```

	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r
	0	0	1	1	1	1	2	2	2	2	2	3	3	3	3	3	3

```
n_obs(ex_taxmap, "info")
```

	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r
	4	2	2	1	1	2	1	1	1	1	2	1	1	1	1	1	1

```
n_obs(ex_taxmap, "abund")
```

	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r
	8	0	4	2	2	0	2	2	2	2	0	2	2	2	2	0	0

Manipulating

Manipulating: example data

Here is the example object that will be used:


```
print(obj)
```

```
<Taxmap>
 17 taxa: b. Mammalia, c. Plantae ... q. lycopersicum, r. tuberosum
 17 edges: NA->b, NA->c, b->d, b->e ... j->o, k->p, l->q, l->r
 3 data sets:
   info:
     # A tibble: 6 x 4
       taxon_id name  n_legs dangerous
     <chr>    <chr> <dbl> <lgl>
 1 m        tiger    4. TRUE
 2 n         cat     4. FALSE
 3 o         mole     4. FALSE
     # ... with 3 more rows
 phylopic_ids: a named vector of 'character' with 6 items
    m. e148eabb-f138-43[truncated] ... r. 63604565-0406-46[truncated]
 foods: a list of 6 items named by taxa:
    m, n, o, p, q, r
 1 functions:
    reaction
```


Manipulating: example data

Here is the example object that will be used:

```
heat_tree(obj, node_label = taxon_names, layout = "da")
```



Manipulating: Subsetting the taxonomy

Subset taxonomy and user-defined data to one taxon:

```
filter_taxa(obj, taxon_names == "Plantae", subtaxa = TRUE)
```

<Taxmap>

5 taxa: c. Plantae, g. Solanaceae, l. Solanum, q. lycopersicum, r. tuberosum

5 edges: NA->c, c->g, g->l, l->q, l->r

3 data sets:

info:

A tibble: 2 x 4

taxon_id	name	n_legs	dangerous
----------	------	--------	-----------

<chr>	<chr>	<dbl>	<lgl>
-------	-------	-------	-------

1 q	tomato	0.	FALSE
-----	--------	----	-------

2 r	potato	0.	FALSE
-----	--------	----	-------

phylopic_ids: a named vector of 'character' with 2 items

q. b6400f39-345a-47[truncated] ... r. 63604565-0406-46[truncated]

foods: a list of 2 items named by taxa:

q, r


1 functions:

reaction

Manipulating: Subsetting the taxonomy

Subset taxonomy and user-defined data to one taxon:

```
filter_taxa(obj, taxon_names == "Plantae", subtaxa = TRUE) %>%  
  heat_tree(node_label = taxon_names, layout = "da")
```



Manipulating: Subsetting the taxonomy

Subset taxonomy to one rank:

```
filter_taxa(obj, taxon_ranks == "family", supertaxa = TRUE)
```

<Taxmap>

6 taxa: b. Mammalia, c. Plantae ... f. Hominidae, g. Solanaceae

6 edges: NA->b, NA->c, b->d, b->e, b->f, c->g

3 data sets:

info:

A tibble: 6 x 4

taxon_id	name	n_legs	dangerous
----------	------	--------	-----------

<chr>	<chr>	<dbl>	<lgl>
-------	-------	-------	-------

1 d	tiger	4.	TRUE
-----	-------	----	------

2 d	cat	4.	FALSE
-----	-----	----	-------

3 e	mole	4.	FALSE
-----	------	----	-------

... with 3 more rows

phylopic_ids: a named vector of 'character' with 6 items

d. e148eabb-f138-43[truncated] ... g. 63604565-0406-46[truncated]

foods: a list of 6 items named by taxa:

d, d, e, f, g, g


1 functions:

reaction

Manipulating: Subsetting the taxonomy

Subset taxonomy to one rank:

```
filter_taxa(obj, taxon_ranks == "family", supertaxa = TRUE) %>%  
  heat_tree(node_label = taxon_names, layout = "da")
```



Manipulating: Subsetting user data

Subset user-defined data and remove any taxa not in subset:

```
filter_obs(obj, "info", n_legs == 4, drop_taxa = TRUE)
```

<Taxmap>

9 taxa: b. Mammalia, d. Felidae ... n. catus, o. typhlops

9 edges: NA->b, b->d, b->e, d->h, d->i, e->j, h->m, i->n, j->o

3 data sets:

info:

A tibble: 3 x 4

taxon_id	name	n_legs	dangerous
----------	------	--------	-----------

<chr>	<chr>	<dbl>	<lgl>
-------	-------	-------	-------

1 m	tiger	4.	TRUE
-----	-------	----	------

2 n	cat	4.	FALSE
-----	-----	----	-------

3 o	mole	4.	FALSE
-----	------	----	-------

phylopic_ids: a named vector of 'character' with 3 items

m. e148eabb-f138-43[truncated] ... o. 11b783d5-af1c-4f[truncated]

foods: a list of 3 items named by taxa:

m, n, o


1 functions:

reaction

Manipulating: Subsetting user data

Subset data and remove any taxa not in subset:

```
filter_obs(obj, "info", n_legs == 4, drop_taxa = TRUE) %>%  
  heat_tree(node_label = taxon_names, layout = "da")
```



Manipulating: Adding user data

Add a column to a dataset:

```
mutate_obs(obj, "info", bipedal = n_legs == 2)
```

<Taxmap>

17 taxa: b. Mammalia, c. Plantae ... q. lycopersicum, r. tuberosum

17 edges: NA->b, NA->c, b->d, b->e ... j->o, k->p, l->q, l->r

3 data sets:

info:

A tibble: 6 x 5

taxon_id	name	n_legs	dangerous	bipedal
----------	------	--------	-----------	---------

<chr>	<chr>	<dbl>	<lgl>	<lgl>
-------	-------	-------	-------	-------

1 m	tiger	4.	TRUE	FALSE
-----	-------	----	------	-------

2 n	cat	4.	FALSE	FALSE
-----	-----	----	-------	-------

3 o	mole	4.	FALSE	FALSE
-----	------	----	-------	-------

... with 3 more rows

phylopic_ids: a named vector of 'character' with 6 items

m. e148eabb-f138-43[truncated] ... r. 63604565-0406-46[truncated]

foods: a list of 6 items named by taxa:

m, n, o, p, q, r

1 functions:

reaction

Acknowledgements



Oregon State
University



United States Department of Agriculture
Agricultural Research Service



Manipulating: values accessible to NSE


The following can be used in manipulation functions as if they were independent variables using Non-Standard Evaluation (NSE):

- ▶ Functions that return per-taxon information
- ▶ User-defined table columns
- ▶ User-defined vectors and lists
- ▶ User-defined functions

```
unnname(all_names(obj))
```

[1]	"taxon_names"	"taxon_ids"	"taxon_indexes"	"classifications"
[5]	"n_supertaxa"	"n_supertaxa_1"	"n_subtaxa"	"n_subtaxa_1"
[9]	"n_leaves"	"n_leaves_1"	"taxon_ranks"	"is_root"
[13]	"is_stem"	"is_branch"	"is_leaf"	"is_internode"
[17]	"n_obs"	"n_obs_1"	"name"	"n_legs"
[21]	"dangerous"	"phylopic_ids"	"foods"	"reaction"

Metacoder: visualization of taxonomic data



Metacoder: visualization of taxonomic data


Conosa




Radiolaria




Cercozoa



Dinophyta



Metazoa



Thanks for listening!

Questions?