

SAT-based planners

Dra. M^a Dolores Rodríguez Moreno

Objectives

Specific Objectives

- Encoding planning problems as satisfiability problems

Source

- Stuart Russell & Peter Norvig (2009). Artificial Intelligence: A Modern Approach. (3rd Edition). Ed. Pearsons
- License <https://creativecommons.org/licenses/by-nc-sa/2.0/>

Outline

- **Motivation**
- Overall approach
- Notation
- Example: GoTo
- SAT planners
- Conclusions

Motivation

- Propositional satisfiability: given a boolean formula
 - e.g., $(P \vee Q) \wedge (\neg Q \vee R \vee S) \wedge (\neg R \vee \neg P)$,
does there exist a model (an assignment of truth values to the propositions) that makes the formula true?
- This was the very first problem shown to be NP-complete
- Algorithms are known for solving all but a small subset in average-case polynomial time
- Therefore, try translating classical planning problems into satisfiability problems, and solving them that way

Outline

- Motivation
- **Overall approach**
- Notation
- Example: GoTo
- SAT planners
- Conclusions

Overall Approach

- A *bounded planning problem* is a pair (P, n) :
 - P is a planning problem; n is a positive integer
 - Any solution for P of length n is a solution for (P, n)
- Planning algorithm:
- Do iterative deepening like we did with Graphplan:
 - for $n = 0, 1, 2, \dots$,
 - encode (P, n) as a satisfiability problem Φ
 - if Φ is satisfiable, then
 - From the set of truth values that satisfies Φ , a solution plan can be constructed, so return it and exit

Outline

- Motivation
- Overall approach
- **Notation**
- Example: GoTo
- SAT planners
- Conclusions

Notation: propositions

- For satisfiability problems we need to use propositional logic
- Need to encode ground atoms into propositions
 - For set-theoretic planning we encoded predicates into propositions by rewriting them as shown here:
 - Predicate: $\text{at}(r1, \text{loc1})$
 - Proposition: $\text{at-}r1\text{-loc1}$
- For planning as satisfiability we'll do the same thing
 - But we won't bother to do a syntactic rewrite
 - Just use $\text{at}(r1, \text{loc1})$ itself as the proposition
- Also, we'll write plans starting at a_o rather than a_i
 - $\pi = \langle a_o, a_1, \dots, a_{n-1} \rangle$

Notation: fluents

- Proposition saying a particular predicate is true in a particular state
 - $\text{at}(\text{r1}, \text{loc1}, i)$ is a fluent that's true iff $\text{at}(\text{r1}, \text{loc1})$ is in s_i
 - We'll use l_i to denote the fluent for literal l in state s_i
 - e.g., if $l = \text{at}(\text{r1}, \text{loc1})$
then $l_i = \text{at}(\text{r1}, \text{loc1}, i)$
 - a_i is a fluent saying that a is the i th step of π
 - e.g., if $a = \text{GoTo}(\text{r1}, \text{loc2}, \text{loc1})$
then $a_i = \text{GoTo}(\text{r1}, \text{loc2}, \text{loc1}, i)$

Outline

- Motivation
- Overall approach
- Notation
- **Example: GoTo**
- SAT planners
- Conclusions

Example (I)

- Planning domain:
 - one robot $r1$
 - two adjacent locations $l1, l2$
 - one planning operator (to move the robot from one location to another)
- Encode (P, n) where $n = 1$
 1. Initial state: $\{at(r1, l1)\}$
Encoding: $at(r1, l1, 0) \wedge \neg at(r1, l2, 0)$
 2. Goal: $\{at(r1, l2)\}$
Encoding: $at(r1, l2, 1) \wedge \neg at(r1, l1, 1)$
 3. Operator: GoTo (see next slide)

Example (II)

- Operator: $\text{GoTo}(r, l, l')$
precond: $\text{at}(r, l)$
effects: $\text{at}(r, l'), \neg \text{at}(r, l)$

Encoding:

$\text{GoTo}(r1, l1, l2, 0) \Rightarrow \text{at}(r1, l1, 0) \wedge \text{at}(r1, l2, 1) \wedge \neg \text{at}(r1, l1, 1)$	} contradictions (easy to detect)
$\text{GoTo}(r1, l2, l1, 0) \Rightarrow \text{at}(r1, l2, 0) \wedge \text{at}(r1, l1, 1) \wedge \neg \text{at}(r1, l2, 1)$	
$\text{GoTo}(r1, l1, l1, 0) \Rightarrow \text{at}(r1, l1, 0) \wedge \text{at}(r1, l1, 1) \wedge \neg \text{at}(r1, l1, 1)$	
$\text{GoTo}(r1, l2, l2, 0) \Rightarrow \text{at}(r1, l2, 0) \wedge \text{at}(r1, l2, 1) \wedge \neg \text{at}(r1, l2, 1)$	
$\text{GoTo}(l1, r1, l2, 0) \Rightarrow \dots$	} nonsensical, and we can avoid generating them if we use data types like we did for state-variable representation
$\text{GoTo}(l2, l1, r1, 0) \Rightarrow \dots$	
$\text{GoTo}(l1, l2, r1, 0) \Rightarrow \dots$	
$\text{GoTo}(l2, l1, r1, 0) \Rightarrow \dots$	

- Operator: $\text{move}(r : \text{robot}, l : \text{location}, l' : \text{location})$
precond: $\text{at}(r, l)$
effects: $\text{at}(r, l'), \neg \text{at}(r, l)$

Example (III)

4. Complete-exclusion axiom:

$$\neg \text{GoTo}(r1, l1, l2, 0) \vee \neg \text{GoTo}(r1, l2, l1, 0)$$

5. Explanatory frame axioms:

$$\neg \text{at}(r1, l1, 0) \wedge \text{at}(r1, l1, 1) \Rightarrow \text{GoTo}(r1, l2, l1, 0)$$

$$\neg \text{at}(r1, l2, 0) \wedge \text{at}(r1, l2, 1) \Rightarrow \text{GoTo}(r1, l1, l2, 0)$$

$$\text{at}(r1, l1, 0) \wedge \neg \text{at}(r1, l1, 1) \Rightarrow \text{GoTo}(r1, l1, l2, 0)$$

$$\text{at}(r1, l2, 0) \wedge \neg \text{at}(r1, l2, 1) \Rightarrow \text{GoTo}(r1, l2, l1, 0)$$

Extracting a Plan

- Suppose we find an assignment of truth values that satisfies it
 - This means P has a solution of length n
- For $i=1, \dots, n$, there will be exactly one action a such that $a_i = true$
 - This is the i 'th action of the plan.
- The formula on the previous slide
 - It can be satisfied with $\text{GoTo}(r1, l1, l2, 0) = true$
 - Thus $\langle \text{GoTo}(r1, l1, l2, 0) \rangle$ is a solution for (P, I)
 - It's the only solution - no other way to satisfy it

Planning

- How to find an assignment of truth values that satisfies Φ ?
 - Use a satisfiability algorithm
- Example: the *DPLL* algorithm
 - First need to put Φ into conjunctive normal form
e.g., $\Phi = D \wedge (\neg D \vee A \vee \neg B) \wedge (\neg D \vee \neg A \vee \neg B) \wedge (\neg D \vee \neg A \vee B) \wedge A$
 - Write Φ as a set of *clauses* (disjuncts of literals)
 $\Phi = \{\{D\}, \{\neg D, A, \neg B\}, \{\neg D, \neg A, \neg B\}, \{\neg D, \neg A, B\}, \{A\}\}$
 - Some special cases:
 - If $\Phi = \emptyset$ then Φ is always *true*
 - If $\Phi = \{\dots, \emptyset, \dots\}$ then Φ is always *false* (hence unsatisfiable)
 - If Φ contains a *unit clause*, l , then l must be true in order to satisfy Φ

Outline

- Motivation
- Overall approach
- Notation
- Example: GoTo
- **SAT planners**
- Conclusions

SAT planners

- SATPLAN: builds a GP, translates manually the graph constraints to $\{\}$ axioms, then uses a SAT and if no solution is found \rightarrow length increases
- BLACKBOX: combines GP and SATPLAN
- LPSAT: uses a backtrack random algorithm with a new formalism (LCNF) that combines propositional logic with a set of metric constraints
- LPG
- ...

Outline

- Motivation
- Overall approach
- Notation
- Example: GoTo
- SAT planners
- **Conclusions**

Conclusion

- The philosophy of the algorithm is:
 - The planning problem is translated to CNF
 - Guess the length which aims to achieve the goal
 - A set of propositional clauses is generated to check the satisfiability
 - Apply algorithms for propositional logic (DPLL, WALSAT, LMTS-style)