Network Programming Lecture 01

Haitham A. El-Ghareeb

Faculty of Computers and Information Sciences Mansoura University Egypt helghareeb@mans.edu.eg

February 17, 2017

Contacts

about.me/helghareeb

Administrative

TCP/IP Network Stack

Understanding TCP/IP

Objectives of TCP/IP

Key characteristics of TCP/IP

Data Transmission

Data Transmission Layers

User Area

POSIX

Kernel Socket

TCP Control Block

TCP Frame Structure

IP Layer

Ethernet Layer

NIC

However

Next Week InchALLAH

Next Week InchALLAH

Homework

Homework

Administrative

Topics

- TCP/IP Suite Review
- Unix/Linux Networking Basics
- IP4 and IP6
- Socket Programming (C++/Python)
- Client Server Architecture Model
- Network Protocols and Services
- Network Routing Protocols
- SDN, NFV

Lab

- Unix/Linux Networking Basics
- Socket Programming (C++/Python)
- Packet Capturing and Analysis (tcpdump/wireshark)
- Packet Tracer
- Mininet

Administrative

References



Administrative

Marks

- 60 Marks Final Exam
- 10 Marks Oral Exam
- 10 Marks Midterm Exam
- 10 Marks Practical Exam
- 10 Marks Project
- 100 Marks Total

OFFICE HOURS

OPEN Most Days About 9 or 10 Occasionally as Early as 7, But SOME DAYS As Late As 12 or 1 WE CLOSE About 5:30 or 6 Occasionally About 4 or 5 But Sometimes As Late as 11 or 12. **SOME DAYS OR Afternoons,** We Aren't Here At All, and Lately I've Been Here Just About All The Time, **Except When I'm Someplace Else,** But I Should Be Here Then, Too.

Administrative

Following content is based on http://www.cubrid.org/blog/dev-platform/understanding-tcp-ip-network-stack/

Understand how data is transfered

Understanding TCP/IP Network Stack

- Understand how data is transfered
 - improve performance through tuning

Understanding TCP/IP Network Stack

- Understand how data is transfered
 - improve performance through tuning
 - improve performance through troubleshooting

Understanding TCP/IP Network Stack

- Understand how data is transfered
 - improve performance through tuning
 - improve performance through troubleshooting
 - introduction to a new technology

Objectives of TCP/IP

Objectives

- Transmit data quickly
- Keep data order
- Without any data loss

- Connection-Oriented
- Bidirectional Byte stream
- In-order Delivery
- Reliable through ACK
- Flow Control
- Congestion Control

Connection-Oriented

- First, a connection is made between two endpoints (local and remote)
- and then data is transferred.
- "TCP connection identifier" is a combination of addresses of the two endpoints, having

```
<local IP address, local port number,
remote IP address, remote port number>
```

Bidrectional Byte Stream

Bidirectional data communication is made by using byte stream.

In-order Delivery

In-order Delivery

 A receiver receives data in the order of sending data from a sender.

A receiver receives data in the order of sending data from a sender.

For that, the order of data is required.

in-order Delivery

- A receiver receives data in the order of sending data from a sender.
- For that, the order of data is required.
- To mark the order, 32-bit integer data type is used.

Reliability Through ACK

• When a sender did not receive ACK from a receiver after sending data, sender TCP re-sends the data.

Reliability Through ACK

- When a sender did not receive ACK from a receiver after sending data, sender TCP re-sends the data.
- Therefore, sender TCP buffers unacknowledged data from receiver.

Flow Control

• Sender sends as much data as a receiver can afford.

- Sender sends as much data as a receiver can afford.
- Receiver sends the maximum number of bytes that it can receive (unused buffer size, receive window) to sender.


- Sender sends as much data as a receiver can afford.
- Receiver sends the maximum number of bytes that it can receive (unused buffer size, receive window) to sender.
- Sender sends as much data as the size of bytes that receiver's receive window allows.

 Congestion Window: used separately from receive window to prevent network congestion by limiting the volume of data flowing in the network.

- Congestion Window: used separately from receive window to prevent network congestion by limiting the volume of data flowing in the network.
- Sender sends as much data as the size of bytes that the receiver's congestion windows allows by using a variety of algorithms, such as
 - TCP Vegas
 - Westwood
 - BIC
 - CUBIC

- Congestion Window: used separately from receive window to prevent network congestion by limiting the volume of data flowing in the network.
- Sender sends as much data as the size of bytes that the receiver's congestion windows allows by using a variety of algorithms, such as
 - TCP Vegas
 - Westwood
 - BIC
 - CUBIC
- Different from flow control, congestion control is implemented by the sender only.

Data Transmission



Operation Process by Each Layer of TCP/IP Network Stack for Data Transmission.

Data Transmission

Data Transmission

There are several layers that are briefly classified into three areas:

- User area
- Kernel area
- Device area

host vs. device

Data Transmission Data Transmission

Tasks at user area and kernel area are performed by CPU

Data Transmission

- Tasks at user area and kernel area are performed by CPU
- user area and kernel area are called "host" to distinguish them from device area

host vs. device

- Tasks at user area and kernel area are performed by CPU
- user area and kernel area are called "host" to distinguish them from device area
- here, device is NIC that sends and receives packets

Data Transmission

- Tasks at user area and kernel area are performed by CPU
- user area and kernel area are called "host" to distinguish them from device area
- here, device is NIC that sends and receives packets
- NIC is more accurate term than "LAN card"

Data Transmission 00•000000000000000 Data Transmission

• First, application creates data to send "User data"

- First, application creates data to send "User data"
- Then, calls the

write()

- First, application creates data to send "User data"
- Then, calls the

```
write()
```

system call to send the data.

- First, application creates data to send "User data"
- Then, calls the

```
write()
```

- system call to send the data.
- Assume fd has been created. When system call is called, the area is switched to kernel area.



POSIX

Data Transmission

• POSIX-series operating systems (*nix) exposes socket to application using file descriptor.

- POSIX-series operating systems (*nix) exposes socket to application using file descriptor.
- In POSIX, socket is a kind of file.

- POSIX-series operating systems (*nix) exposes socket to application using file descriptor.
- In POSIX, socket is a kind of file.
- File layer executes a simple examination and calls the socket function by using the socket structure connected to file structure.

- 1. One is the **send socket buffer** for sending
- 2. And the other is the **receive socket buffer** for receiving When the write system call is called:

Data Transmission

- 1. One is the **send socket buffer** for sending
- 2. And the other is the **receive socket buffer** for receiving When the write system call is called:
 - data in the user area is copied to the kernel memory

- 1. One is the **send socket buffer** for sending
- 2. And the other is the **receive socket buffer** for receiving When the write system call is called:
 - data in the user area is copied to the kernel memory
 - and then added to the end of the send socket buffer

- 1. One is the **send socket buffer** for sending
- 2. And the other is the **receive socket buffer** for receiving When the write system call is called:
 - data in the user area is copied to the kernel memory
 - and then added to the end of the send socket buffer
 - This is to send the data in order

- 1. One is the **send socket buffer** for sending
- 2. And the other is the **receive socket buffer** for receiving When the write system call is called:
 - data in the user area is copied to the kernel memory
 - and then added to the end of the send socket buffer
 - This is to send the data in order
 - Then, TCP is called

Administrative

Data Transmission

 There is the TCP Control Block (TCB) structure connected to the socket.

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are
 - connection state

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are
 - connection state
 - receive window

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are
 - connection state
 - receive window
 - congestion window

TCF CONTROL BIOCK

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are
 - connection state
 - receive window
 - congestion window
 - sequence number

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are
 - connection state
 - receive window
 - congestion window
 - sequence number
 - resending timer

- There is the TCP Control Block (TCB) structure connected to the socket.
- TCB includes data required for processing the TCP connection.
- Data in the TCB are
 - connection state
 - receive window
 - congestion window
 - sequence number
 - resending timer
 - etc

Connection States

- ESTABLISHED The socket has an established connection.
- **SYN_SENT** The socket is actively attempting to establish a connection.
- SYN_RECV A connection request has been received from the network.
- FIN_WAIT1 The socket is closed, and the connection is shutting down.
- **FIN_WAIT2** Connection is closed, and the socket is waiting for a shutdown from the remote end.
- TIME_WAIT The socket is waiting after close to handle packets still in the network.

- **CLOSE** The socket is not being used.
- CLOSE_WAIT The remote end has shut down, waiting for the socket to close.
- LAST_ACK The remote end has shut down, and the socket is closed. Waiting for acknowledgement.
- **LISTEN** The socket is listening for incoming connections. Such sockets are not included in the output unless you specify the –listening (-I) or –all (-a) option.
- CLOSING Both sockets are shut down but we still don't have all our data sent.
- UNKNOWN The state of the socket is unknown.

TCP State

Data Transmission Data Transmission

• If current TCP state allows for data transmission, a new

TCP segment is created.

TCP State


- If current TCP state allows for data transmission, a new TCP segment is created.
- If data transmission is impossible, due to flow control or such a reason, the system call is ended here and then mode is returned to user mode (control passed to the application)

There are two TCP segments:

- TCP header
- 2. Payload

TCP Frame Structure





Administrative

Payload

Data Transmission

 Payload includes data saved in the unacknowledged send socket buffer.

- Payload includes data saved in the unacknowledged send socket buffer.
- Maximum length of Payload is the maximum value among the receive window, congestion window, and maximum segment size (MSS).

TCP Checksum

Data Transmission Administrative

Data Transmission

• Then, TCP checksum is computed.

Data Transmission

- Then, TCP checksum is computed.
- Pseudo header information that are included are:
 - IP addresses
 - segment length
 - protocol number

- Then, TCP checksum is computed.
- Pseudo header information that are included are:
 - IP addresses
 - segment length
 - protocol number
- One or more packets can be transmitted according to the TCP state.

• TCP checksum is computed by NIC, not by the kernel.

• Why?

Data Transmission

The created TCP segment goes down to the IP layer, that does:

- Adds IP header to the TCP segment
- Performs IP routing

The created TCP segment goes down to the IP layer, that does:

- Adds IP header to the TCP segment
- Performs IP routing
- IP routing is a procedure of searching the next hop IP in order to go to the destination IP.

Ethernet Layer

Ethernet Layer

- Searches for the MAC address of the next hop IP by using the ARP.
- It then adds the Ethernet header to the packet.
- Host packet is completed by adding the Ethernet header.

- After IP routing is performed, the transmit interface (NIC) is knows as the result of IP routing.
- The interface is used for transmitting a packet to the next hop IP and the IP.
- Therefore, the transmit NIC driver is called.
- At this time, if a packet capture program such as tcpdump or wireshark is running, the kernel copies the packet data onto the memory buffer that the program uses.
- In that way, the receiving packet is directly captured on the driver.
- Generally, the traffic shaper function is implemented to run on this layer.

NIC Driver

- NIC driver requests packet transmission according to the driver-NIC communication protocol defined by the NIC manufacturer
- After receiving the packet transmission request, NIC copies the packets from the main memory to NIC **memory** and then sends it to the network line.
- At this time, by complying with the Ethernet standard, it adds the Inter-Frame Gap (IFG), preamble, and CRC to the packet.
 - IFG and preamble are used to distinguish the start of the packet (framing).
 - CRC is used to protect the data
- Packet transmission is started based on the physical speed of the Ethernet and the condition of Ethernet flow control.

NIC Interrupts

- When NIC sends a packets, NIC generates interrupts to the host CPU.
- Every interrupt has its own interrupt number, and the OS searches an adequate driver to handle the interrupt by using the number.
- The driver registers a function to handle the interrupt (an interrupt handler) when the driver is started.
- OS calls the interrupt handler and then the interrupt handler returns the transmitted packet to the OS.

However

- So far, we have discussed the procedure of data transmission through the kernel and the device when an application performs write.
- However, without a direct write request from the application, the kernel can transmit a packet directly calling TCP.
- For example ?!!

- So far, we have discussed the procedure of data transmission through the kernel and the device when an application performs write.
- However, without a direct write request from the application, the kernel can transmit a packet directly calling TCP.
- For example ?!!
- When an ACK is received and the receive window is expanded, the kernel creates a TCP segment including the data left in the socket buffer and sends the TCP segment to the receiver.

Next Week InchALLAH

Next Lecture

- Data Receiving
- Data Structure
- Following Code

Next Lab

- Review TCP/IP Suite (Solve selected Qs)
- Qs can be found at http://technologyeye.weebly. com/uploads/9/6/1/4/9614102/interview_ question_networkingrajkumar.pdf

- Study this lecture (very well)
- Prepare for the Next Lecture
- Check some Kernel code (mainly Networking Subsystem)



YOUGO NOW!