

Expose Pro

[Expose by Beyond Code](#)

Open main menu

[Docs](#) [Pricing](#) [Open Source](#) [Webhook Testing](#) [Sign in](#) [Create account](#)

Close main menu

[Docs](#) [Pricing](#) [Open Source](#) [Webhook Testing](#) [Sign in](#) [Create account](#)

Expose Documentation

- [Introduction](#)
- [Upgrade from Expose v1](#)
 - [Getting Started](#)
 - [Installation](#)
 - [Share your first site](#)
 - [Setup Your Token](#)
 - [Questions & Issues](#)
 - [Client](#)
 - [Sharing your local sites](#)
 - [Local Dashboard](#)
 - [Sharing TCP ports](#)
 - [Basic Authentication](#)
 - [Global Server Infrastructure](#)
 - [Server](#)
 - [Starting the server](#)
 - [SSL Support](#)
 - [Admin Interface](#)
 - [Server Configuration](#)
 - [Extending The Server](#)
 - [Subdomain Generator](#)
 - [User Repository](#)
 - [Custom Views](#)
 - [API](#)
 - [Authorization](#)
 - [Settings](#)
 - [Sites](#)
 - [Users](#)
 - [Release Notes](#)
 - [Expose 2.0](#)
- [Introduction](#)
- [Upgrade from Expose v1](#)
 - [Getting Started](#)
 - [Installation](#)
 - [Share your first site](#)
 - [Setup Your Token](#)
 - [Questions & Issues](#)
 - [Client](#)
 - [Sharing your local sites](#)
 - [Local Dashboard](#)
 - [Sharing TCP ports](#)
 - [Basic Authentication](#)
 - [Global Server Infrastructure](#)
 - [Server](#)
 - [Starting the server](#)
 - [SSL Support](#)
 - [Admin Interface](#)
 - [Server Configuration](#)
 - [Extending The Server](#)
 - [Subdomain Generator](#)
 - [User Repository](#)

- [Custom Views](#)

[API](#)

- [Authorization](#)
- [Settings](#)
- [Sites](#)
- [Users](#)

[Release Notes](#)

- [Expose 2.0](#)

Global Server Infrastructure ::pro

#

[Expose Pro](#) allows you to choose between multiple Expose servers around the world, so that you can use an endpoint closest to you.

To get a list of all the available Expose servers, you can run `expose servers`

```
$ expose servers
```

Key	Region	Type
eu-1	EU (Frankfurt)	Pro
us-1	US (New York)	Pro
us-2	US (San Francisco)	Pro
ap-1	Asia Pacific (Singapore)	Pro
in-1	India (Bangalore)	Pro
sa-1	South America (São Paulo)	Pro
au-1	Australia (Sydney)	Pro

Changing servers

#

When you share a local URL, or a local TCP port, you can specify the Expose server region, using the `--server` command line option. Pass the server key as the option to connect to this specific server.

```
expose share my-local-site.test --server=eu-1
```

Setting a default server

#

Most of the time you will want to always use the server location that is closest to you for all of your Expose commands. You can define the default server that Expose should use, by calling the `expose default-server` command:

```
expose default-server us-2
```

Now the next time that you will share a local URL or port, Expose is automatically going to connect to the `us-2` server for you.

[Imprint](#) [Privacy Policy](#) [Terms & Conditions](#) [Disclaimer](#) [Support](#)

[Beyond Code](#)