

The Way of Dockerize a Spring Boot and MySQL Application With Docker Compose.



[Amila Iroshan](#)

.

[Follow](#)

Published in

[The Fresh Writes](#)

.

6 min read

.

Jan 27, 2023

--

4

Listen

Share

Pre-requisite,

- Basic knowledge of docker and java with spring boot
- Setup Docker and Docker compose to local machine

Technology Stack

- + Spring Boot 3.0.0-RELEASE
- + Spring Data JPA
- + MySQL — 8.0
- + Docker — version 20.10.21
- + Docker-Compose — version v2.13.0

You can get instruction about docker installation from <https://docs.docker.com/desktop/install/windows-install/>. I have downloaded docker desktop to my local pc and It is wrapped up docker with docker compose. So no need to install docker compose separately.

Overview

My sample application provide GET api for display list of person's names. The sample data is fetching from MySql DB.

What is :

Docker : Docker is open source containerization platform used for building, packaging, and managing applications in an isolated environment.

Dockerfile : It is the place where we config the model of our docker container. By using dockerfile we can create docker image.

Docker Image: The blueprint for create docker containers.(According to oop concepts it is like a class)

Docker Container : It is runnable instance of image.(According to oop concepts it is like a object which is derived from class)

Docker Compose : Docker compose is a tool which helps us to easily handle multiple containers at once.

I'm going to following below steps:

- 1).Create spring boot application and connect it with MySql DB.
- 2).Create Dockerfile to Spring boot application.
- 3).Create docker compose configuration file
- 4).Run the system and inspect running containers

Step 1:

Create spring boot application and connect it with MySql DB.

- 1).Navigate to <https://start.spring.io>.
- 2).Choose

either Gradle or Maven as build tool. In here I'm using maven, Java 18 and .jar as packaging.

Create Spring boot application

3).Click Dependencies and select spring starter web, spring data jpa and mysql connector. This is my pom.xml file.

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 https://maven.apache.org/xsd/maven-4.0.0.xsd">
<modelVersion>4.0.0</modelVersion>
<parent>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-parent</artifactId>
<version>3.0.0</version>
<relativePath/> <!-- lookup parent from repository -->
</parent>
<groupId>com.example</groupId>
<artifactId>basic</artifactId>
<version>0.0.1-SNAPSHOT</version>
<name>basic</name>
<description>Demo project for Spring Boot</description>
<properties>
<maven.compiler.source>17</maven.compiler.source>
<maven.compiler.target>17</maven.compiler.target>
</properties>
<dependencies>
<dependency>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-web</artifactId>
</dependency>

<dependency>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-starter-data-jpa</artifactId>
</dependency>

<!-- MySQL -->
<dependency>
<groupId>mysql</groupId>
<artifactId>mysql-connector-java</artifactId>
</dependency>

</dependencies>

<build>
<plugins>
<plugin>
<groupId>org.springframework.boot</groupId>
<artifactId>spring-boot-maven-plugin</artifactId>
</plugin>
</plugins>
<finalName>spring_rest_docker</finalName>
</build>

</project>
```

4).Download the resulting ZIP file, which is an archive of a web application that is configured with your choices.

5).Create a GET endpoint to fetch data from db.

```
@RestController
public class BasicController {

@Autowired
private PersonService personService;

@GetMapping("/all")
public List<Persons> getAll() {
return personService.findAll();
}
```

```
}
```

6).Connect application with MySql db. Here is my application.properties file.

```
spring.jpa.hibernate.ddl-auto=update
spring.datasource.url=jdbc:mysql://localhost:3306/basics?allowPublicKeyRetrieval=true
spring.datasource.username=amila_one
spring.datasource.password=Amila_pw

spring.sql.init.mode=always
spring.datasource.initialization-mode=always
```

Step 2:

Create a Dockerfile to Spring boot application. The dockerfile should be in the class path.

```
#
# Build stage
#
FROM maven:3.8.3-openjdk-17 AS build
COPY src /home/app/src
COPY pom.xml /home/app
RUN mvn -f /home/app/pom.xml clean package
EXPOSE 8080
ENTRYPOINT [ "java", "-jar", "/home/app/target/spring_rest_docker.jar" ]
```

FROM : Fetching latest version of Java image with maven. This pre define docker image exists on docker hub.

COPY : Copying Project src folder to openjdk-17 container's root directory /home/app/src.Copy again pom.xml file to /home/app/.

RUN : Execute the mavean command to build the .jar file accoring to given pom.xml file.

EXPOSE : Specify that expose server port

ENTRYPOINT : Execute command for run the .jar file.We can use **CMD** instead of **ENTRYPOINT**.If we use **CMD** we can provide arguments to image when build it.

Step 3:

Create docker compose configuration file.The naming convention of this file should be docker-compose.yaml or .yml. This file should be on the class path. This docker compose file helps us to combine the spring boot app and MySql db setup.

```
version: "3.7"
services:
  api_service:
    build: .
    restart: always
    ports:
      - 8080:8080
    networks:
      - springapimysql-net
    environment:
      - spring.datasource.url=jdbc:mysql://mysqldb:3306/basics?allowPublicKeyRetrieval=true
    depends_on:
      - mysqldb

  volumes:
    - .m2:/root/.m2

mysqldb:
  image: "mysql:8.0"
  restart: always
  ports:
    - 3306:3306
  networks:
    - springapimysql-net
  environment:
    MYSQL_DATABASE: basics
    MYSQL_USER: amila_one
    MYSQL_PASSWORD: Amila_pw
    MYSQL_ROOT_PASSWORD: Amila_Rpw
networks:
  springapimysql-net:
```

version: Version of Docker Compose file format.

services: My application has two services: app (Spring Boot) and mysqldb (MySQL database image).

build: Configuration options that are applied at build time that we defined in the Dockerfile with relative path

image: Official Docker image from docker hub

volumes: Named volumes that keeps our data alive after restart.

network: The two services should be belong to one network.

depends_on: Dependency order, mysqldb is started before app

++Important : The data base host name should be replaced by data base service name. Ex : *jdbc:mysql://mysqldb:3306/basics?*

The project structure looks like below:

Project Structure

In here schema.sql (DDL queries) file added to create table structure and data.sql file added to load data (DML queries) while populate to spring application.

```
CREATE TABLE IF NOT EXISTS persons(  
    `id` bigint(20) NOT NULL AUTO_INCREMENT,  
    `name` varchar(255) DEFAULT NULL,  
    PRIMARY KEY (`id`)  
)ENGINE=InnoDB DEFAULT CHARSET=utf8mb4;  
  
INSERT INTO persons(name) VALUES('Amila');  
INSERT INTO persons(name) VALUES('Iroshan');
```

Step 4:

Run the system and inspect running containers. We can run our whole application using one docker command.

docker-compose up

You can check created docker images using : **docker images**

Show Docker Images

You can check created docker containers using : **docker ps**

Show Docker Containers

Login in to created containers using :

api_service container = **docker exec -it basic-api_service-1 bin/sh**

api_service container

mysqldb container = **docker exec -it basic-mysqldb-1 bash**

mysqldb container

Final Result

Navigate to this GET URL on you browser or any rest client.

<http://localhost:8080/all>

Final output

Source Code

The source code for this tutorial can be found at [Github](#).

Hope you find this helpful. Thank you for reading this article!.

Do support our publication by following it

[The Fresh Writes](#)

[We support small publishers to enhance their articles and increase their growth](#)

medium.com

Also refer to the following articles

[Threading and Multiprocessing in Python Explained](#)

[Threading and Multiprocessing are two popular methods used in Python for the parallel execution of tasks. Threading...](#)

medium.com

Make \$5000 a Month Tutoring from Home

My favorite platform. Make money from the comfort of your home.

medium.com

Nested Try Blocks In Java

In Java, a try statement can be inside the block of another try. It is called as nested try block.

medium.com

Are You Ready to Take the Plunge into the World of Blogging?

Do you have a passion for writing and creating content? Are you interested in sharing your thoughts and ideas with the...

medium.com

6 Passive Income Ideas for Making Money in 2023

Earn money while sleeping

medium.com